

## Cisco 12000 Series 8-Port Fast Ethernet Line Card

The Cisco® 12000 Series 8-port Fast Ethernet Line Card (Figure 1) offers high-density and low-cost intra-point of presence (POP) connectivity between the Cisco 12000 Series and other lower-end switches and routers (such as the Cisco Catalyst® 5000, Catalyst 6000, and Catalyst 7500 routers). Service providers benefit from this high-density Fast Ethernet line card by eliminating or reducing the need to implement and operate an intermediate layer of networking equipment between the Cisco 12000 Series and other switches and routers—and the results are significant cost savings, simplified network management, improved network availability, and increased savings in rack space.

Figure 1. Cisco 12000 Series 8-Port Fast Ethernet Line Card



### PRODUCT FEATURES

Table 1 describes the basic features on the Cisco 12000 Series Fast Ethernet line cards.

Table 1. Product Features

Feature	Description
<b>Packet Layer</b>	<ul style="list-style-type: none"> <li>Multiple virtual output queues, eliminating head-of-line blocking</li> <li>512-KB burst buffers, which smooth out the arriving packet bursts</li> <li>128-MB packet buffer on the transmit and receive directions</li> <li>A forwarding table that can accommodate up to one million forwarding entries</li> <li>Application-specific integrated circuit (ASIC)-based queuing</li> <li>Quality-of-service (QoS) support</li> <li>Configurable with up to 256 MB of code and route table memory</li> </ul>
<b>Ethernet Upper Layer</b>	<ul style="list-style-type: none"> <li>MAC with full-duplex (default) or half-duplex operation</li> <li>8B/10B encoding and decoding</li> <li>100BASE-TX copper interface, compliant with IEEE 802.3u specifications</li> <li>Optional 100BASE-FX multimode interface, compliant with IEEE 802.3u specifications</li> </ul>

Feature	Description
<b>Software Features</b>	<ul style="list-style-type: none"> <li>• Autonegotiation</li> <li>• Precedence setting and mapping</li> <li>• Access control list (ACL) and extended ACL</li> <li>• Cisco Group Management Protocol (GMP)</li> <li>• Hot-Standby Router Protocol (HSRP)</li> <li>• Multiprotocol Label Switching (MPLS) and Tag Switching</li> <li>• Committed access rate (CAR) on receive (Rx) side</li> <li>• NetFlow data export</li> <li>• VLAN trunking (802.1q)</li> <li>• Per-port address filtering (512 addresses per port)</li> </ul>

## PRODUCT SPECIFICATIONS

Table 2 provides specifications for the Cisco 12000 Series Fast Ethernet line cards.

**Table 2.** Product Specifications

Line-Card	Forwarding Engine	Cisco IOS® Software Release	Chassis Supported	Per-Chassis Port Densities
<b>8FE-FX-SC-B</b>	Engine 1	12.0(10)S or higher	<ul style="list-style-type: none"> <li>• Cisco 12404</li> <li>• Cisco 12006</li> <li>• Cisco 12406</li> <li>• Cisco 12010</li> <li>• Cisco 12410</li> <li>• Cisco 12810</li> <li>• Cisco 12016</li> <li>• Cisco 12416</li> <li>• Cisco 12816</li> </ul>	<ul style="list-style-type: none"> <li>• Cisco 12404: 24 ports</li> <li>• Cisco 12006 and 12406: 40 ports</li> <li>• Cisco 12010, 12410, and 12810: 72 ports</li> <li>• Cisco 12016, 12416, and 12816: 120 ports</li> </ul>
<b>8FE-TX-RJ45-B</b>	Engine 1	12.0(10)S or higher	<ul style="list-style-type: none"> <li>• Cisco 12404</li> <li>• Cisco 12006</li> <li>• Cisco 12406</li> <li>• Cisco 12010</li> <li>• Cisco 12410</li> <li>• Cisco 12810</li> <li>• Cisco 12016</li> <li>• Cisco 12416</li> <li>• Cisco 12816</li> </ul>	<ul style="list-style-type: none"> <li>• Cisco 12404: 24 ports</li> <li>• Cisco 12006 and 12406: 40 ports</li> <li>• Cisco 12010, 12410, and 12810: 72 ports</li> <li>• Cisco 12016, 12416, and 12816: 120 ports</li> </ul>

## PHYSICAL AND ELECTRICAL SPECIFICATIONS

Table 3 provides details about the physical and electrical specifications of the Cisco 12000 Series Fast Ethernet line cards.

**Table 3.** Physical and Electrical Specifications

Line-Card Part Number	Dimensions	Weight	Power	Connector	Route Memory	LEDs
<b>8FE-FX-SC-B</b>	<ul style="list-style-type: none"> <li>Height: 14.5 in. (36.8 cm)</li> <li>Depth: 18.5 in. (46.9 cm)</li> </ul>	6 lb (2.7 kg)	77 watts maximum	SC connector (1300-nm transceiver using multimode fiber)	<ul style="list-style-type: none"> <li>Default: 128 MB</li> <li>Maximum: 256 MB</li> </ul>	<ul style="list-style-type: none"> <li>Link status per port on front panel</li> <li>Power level</li> <li>Fabric clock</li> <li>Rx activity</li> <li>Tx activity</li> </ul>
<b>8FE-TX-RJ45-B</b>	<ul style="list-style-type: none"> <li>Height: 14.5 in. (36.8 cm)</li> <li>Depth: 18.5 in. (46.9 cm)</li> </ul>	6 lb (2.7 kg)	77 watts maximum	RJ-45 connector (UTP Category 5)	<ul style="list-style-type: none"> <li>Default: 128 MB</li> <li>Maximum: 256 MB</li> </ul>	<ul style="list-style-type: none"> <li>Link status per port on front panel</li> <li>Power level</li> <li>Fabric clock</li> <li>Rx activity</li> <li>Tx activity</li> </ul>

## ENVIRONMENTAL, APPROVALS AND COMPLIANCE

Table 4 gives standards-compliance information for the Cisco 12000 Series Fast Ethernet line cards.

**Table 4.** Compliance and Agency Approvals

Feature	Description
<b>Environmental</b>	<ul style="list-style-type: none"> <li>Operating temperature: 41 to 104°F (5 to 40°C)</li> <li>Operating temperature (short-term): 23 to 131°F (-5 to 55°C)</li> <li>Storage temperature: -4 to 149°F (-20 to 65°C)</li> <li>Relative humidity: <ul style="list-style-type: none"> <li>5 to 85%, noncondensing, operating conditions</li> <li>5 to 90%, noncondensing, operating conditions (short-term)</li> <li>Up to 95%, noncondensing, nonoperating conditions</li> </ul> </li> <li>Operating altitude: -60 to 4000m</li> </ul>
<b>Safety</b>	<ul style="list-style-type: none"> <li>UL 1950</li> <li>CSA 22.2-No. 950</li> <li>EN60950</li> <li>IEC 60950 CB Scheme</li> <li>ACA TS001</li> <li>AS/NZS 3260</li> </ul>

Feature	Description
<b>EMI</b>	<ul style="list-style-type: none"> <li>• FCC CFR 47-Part 15 1998 Class A</li> <li>• ICES 003 Class A</li> <li>• AS/NRZ 3548 Class A</li> <li>• EN55022 Class B</li> <li>• VCCI Class A</li> <li>• CISPR 22 Class B</li> <li>• BSMI/CNS 13438: 1997 Class A</li> <li>• IEC-1000-3-2 Power line harmonics</li> <li>• IEC 61000-3-3 Voltage fluctuations and flicker</li> </ul>
<b>Immunity (basic standards)</b>	<ul style="list-style-type: none"> <li>• IEC-1000-4-2 ESD (8-kV contact, 15-kV air)</li> <li>• IEC-1000-4-3 Radiated immunity (10 V/m)</li> <li>• IEC-1000-4-4 EFT (2-kV power port, 1-kV signal port)</li> <li>• IEC-1000-4-5 Surge AC port (4-kV CM, 2-kV DM)</li> <li>• IEC-1000-4-5 Surge Signal port (2-kV CM, 1-kV DM)</li> <li>• IEC-1000-4-5 Surge DC port (0.5-kV CM, 0.5-kV DM)</li> <li>• IEC-1000-4-6 Low Frequency Conductive Immunity, (10V)</li> <li>• IEC-1000-4-11 Voltage dips and sags</li> <li>• EN55024\CISPR24 ITE Immunity</li> </ul>
<b>ETSI and EN</b>	EN300 386
<b>Network Equipment Building Standards (NEBS)</b>	<p>This product is designed to meet the following requirements (some qualifications in progress):</p> <ul style="list-style-type: none"> <li>• SR-3580—NEBS criteria levels (Level 3-compliant)</li> <li>• GR-1089-Core—NEBS EMC and safety</li> <li>• GR-63-Core—NEBS Physical protection</li> </ul>

## ORDERING INFORMATION

To place an order, contact your local Cisco representative or visit the ordering page on the Cisco Website. Use the ordering information in Table 5.

**Table 5.** Ordering Information

Product Part Number	Product Name
<b>8FE-FX-SC-B</b>	8-port Fast Ethernet 100BASE-TX interface, SC connectors, with error correcting code (ECC) memory
<b>8FE-TX-RJ45-B</b>	8-port Fast Ethernet 100BASE-TX interface, RJ-45 connectors, with ECC memory
<b>MEM-GRP/LC-128 or MEM-GRP/LC-256</b>	Code and route table memory options for the 8-port Fast Ethernet line card

## SERVICE AND SUPPORT

Cisco Systems® delivers innovative services programs through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you protect your network investment, optimize network operations, and prepare your network for new applications to extend network intelligence and the power of your business. For more information about Cisco services, contact your local Cisco representative or visit the Cisco Website.

## FOR MORE INFORMATION

For more information about the Cisco 12000 Series Fast Ethernet line cards, contact your local Cisco representative or visit

<http://www.cisco.com/go/12000>.



### Corporate Headquarters

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
[www.cisco.com](http://www.cisco.com)  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

### European Headquarters

Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
[www-europe.cisco.com](http://www-europe.cisco.com)  
Tel: 31 0 20 357 1000  
Fax: 31 0 20 357 1100

### Americas Headquarters

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
[www.cisco.com](http://www.cisco.com)  
Tel: 408 526-7660  
Fax: 408 527-0883

### Asia Pacific Headquarters

Cisco Systems, Inc.  
168 Robinson Road  
#28-01 Capital Tower  
Singapore 068912  
[www.cisco.com](http://www.cisco.com)  
Tel: +65 6317 7777  
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus  
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel  
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal  
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan  
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)

