

Cisco MGX-XM60 Switching Module

Product Overview

The Cisco® MGX® 8000 Series Multiservice Switches are a scalable family of multiservice switches, scaling from 1.2 Gbps to 180 Gbps redundant switching capacity and from DS0 to OC-192/STM-64 interface capacity. This scalability provides exceptional savings and efficiency for network operations and services growth. The Cisco MGX 8000 family includes the Cisco MGX 8850, MGX 8850/B, MGX 8830/B and MGX 8950 Multiservice Switches.

The Cisco MGX-XM60 Switching Module is the switch fabric that powers the Cisco MGX 8950 Advanced ATM Multiservice Switch. The Cisco MGX-XM60 provides 60 Gbps of full-duplex nonblocking switching capacity. Each Cisco MGX 8950 can be configured with up to four Cisco XM-60s to provide 240 Gbps of switching capacity for the system.

The Cisco MGX-XM60 Switching Module meets service providers' demand for carrier-class availability by offering hot-standby, load-sharing redundancy. (Refer to Figure 1.)

Figure 1. Cisco MGX-XM60



Technical Specifications

The Cisco MGX-XM60 Switching Module has the following primary features:

- Single-height card
- 60-Gbps nonblocking crosspoint switch fabric
- Dynamic sharing of capacity across multiple Cisco XM-60s, allowing for N + 1 redundancy
- Four installed in each Cisco MGX 8950 for 240-Gbps total capacity, 180-Gbps redundant capacity
- Hot card insertion/removal
- Complete separation from control processor, allowing data forwarding in the event of control card failure

Table 1 provides product specifications.

Table 1. Product Specifications

Description	Specification
Chassis compatibility	MGX 8950
Software compatibility	MGX S/W Releases supporting MGX-XM60: <ul style="list-style-type: none"> • MGX RIs 4.0.15 and above
Network management	<ul style="list-style-type: none"> • Managed by Cisco WAN Manager Software suite • Based on Simple Network Management Protocol (SNMP)
Power	<ul style="list-style-type: none"> • Input power required: -48 VDC • Power consumption: 61 W
Physical dimensions	H x D: 7.25 x 16.5 in. (18.41 x 41.91 cm)
Weight	3.5 lb
Environmental conditions	<ul style="list-style-type: none"> • Storage Temperature: -40°C to 70°C (-40°F to 158°F) • Operating Temperature: <ul style="list-style-type: none"> ◦ Normal: 5°C to 40°C (41°F to 104°F) ◦ Short term: -5°C to 50°C (23°F to 122°F) • Relative Humidity: <ul style="list-style-type: none"> ◦ Normal: 5% to 85% ◦ Short-term: 5% to 90% but not to exceed 0.024 kg water/kg of dry air <p>Short-term refers to a period of not more than 96 consecutive hours and a total of not more than 15 days in 1 year. (This refers to a total of 360 hours in any given year, but no more than 15 occurrences during that 1 year period.)</p>

Approvals and Compliance

Table 2 lists compliance and agency approval details.

Table 2. Compliance and Agency Approvals

Compliance Type	Description
Safety standards	<ul style="list-style-type: none"> • UL/CSA/IEC/EN 60950-1 • IEC/EN 60825 Laser Safety • ACA TS001 • AS/NZS 60950 • FDA-Code of Federal Regulations Laser Safety
EMI	<ul style="list-style-type: none"> • FCC Class A • ICES 003 Class A • AS/NZS 3548 Class A • CISPR 22 (EN55022) Class A • VCCI Class A • BSMI Class A • IEC/EN 61000-3-2: Power Line Harmonics • IEC/EN 61000-3-3: Voltage Fluctuations and Flicker
Immunity (basic standards)	<ul style="list-style-type: none"> • IEC/EN-61000-4-2: Electrostatic Discharge Immunity (8kV Contact, 15kV Air) • IEC/EN-61000-4-3: Radiated Immunity (10V/m) • IEC/EN-61000-4-4: Electrical Fast Transient Immunity (2kV AC Power, 1kV DC Power) • IEC/EN-61000-4-5: Surge AC Port (2kV CM, 2kV DM) • IEC/EN-61000-4-5: Signal Ports (1kV) • IEC/EN-61000-4-5: Surge DC Port (1kV) • IEC/EN-61000-4-6: Immunity to Conducted Disturbances (10Vrms) • IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity (30A/m) • IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations
Network Equipment Building Systems (NEBS)	<p>This product is designed to meet the following requirements (qualification in progress):</p> <ul style="list-style-type: none"> • SR-3580: NEBS Criteria Levels (Level 3) • GR-1089-CORE: NEBS EMC and Safety • GR-63-CORE: NEBS Physical Protection

Compliance Type	Description
Telcordia CLEI	<ul style="list-style-type: none"> GR-485-CORE – CLEI coding GR-383-CORE – CLEI code product label GR-209-CORE – PCN Process

Ordering Information

To place an order, visit the [Cisco Ordering Homepage](#). Table 3 gives ordering information.

Table 3. Ordering Information

Product Part Number	Product Name
MGX-XM60	60G Switch Fabric Card

For More Information

For more information about Cisco service and support programs and benefits, go to:

<http://www.cisco.com>.



Americas Headquarters
 Cisco Systems, Inc.
 170 West Tasman Drive
 San Jose, CA 95134-1706
 USA
www.cisco.com
 Tel: 408 526-4000
 800 553-NETS (6387)
 Fax: 408 527-0883

Asia Pacific Headquarters
 Cisco Systems, Inc.
 168 Robinson Road
 #28-01 Capital Tower
 Singapore 068912
www.cisco.com
 Tel: +65 6317 7777
 Fax: +65 6317 7799

Europe Headquarters
 Cisco Systems International BV
 Haarlerbergpark
 Haarlerbergweg 13-19
 1101 CH Amsterdam
 The Netherlands
www-europe.cisco.com
 Tel: +31 0 800 020 0791
 Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

©2007 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, Packet, PIX, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0704R)