

Cisco LCD 110 PRO 52S

Product Overview

The Cisco® LCD 110 PRO 52S is a 52-inch professional display that complements the Cisco Digital Media Suite. It is certified as compatible with Cisco Digital Media Players; you can manage the application centrally from the Digital Media Manager platform, giving you a single-vendor solution for your DMS deployment. Using industry-best technology, the Cisco LCD 110 PRO 52S offers cutting-edge features along with visual appeal to emphasize your customer-facing communications.

Features

Features of the Cisco LCD 110 PRO 52S follow; Table 1 lists the benefits of this new product.

- Full-HD 1080p native resolution
- High brightness and high built-in contrast ratio
- Landscape and portrait modes support
- High-Definition Multimedia Interface (HDMI) inputs for real full-HD content rendering
- Built-in speakers for advanced audio applications
- Central management through the Cisco Digital Media Manager

Table 1. Benefits of Cisco LCD 110 PRO 52S

Benefit	
Integrated with DMS	Certified and tested to work with DMS suite of products
Low total cost of ownership (TCO)	Single vendor for all requirements to reduce costs and save time and long-term operating expenses
Cisco Services (Cisco SMARTnet® Next Business Day [NBD] replacement)	Exceptional, dependable, and proven service from industry-renowned Cisco support organization
Cisco CapitalSM leasing and financing options	Easy availability of financing options

Product Specifications

Table 2 lists the product specifications.

Table 2. Product Specifications

Feature	Specification
Diagonal size	52 inches
Native resolution	1080p (1920x1080)
Resolutions supported	1080p, 1080i, and 720p
Brightness (typical)	700 cd/m2
Contrast ratio (typical)	2000:1
Viewing angle (H/V)	178/178 degrees
Response time (G-to-G)	8 ms
Pixel pitch	0.6 x 0.6
Horizontal frequency	50–70 KHz
Vertical frequency	50–85 Hz

Inputs	CVBS, component, HDMI, VGA, DVI, and BNC
Speaker	Two 10W
Power consumption (maximum)	370W
Power consumption at standby (maximum)	2W
Power supply	100–240VAC – (+/– 10%), 50/60 Hz
VESA mount	800 x 400 mm
Weight (set/package)	36.8/47 kg
Dimensions (H x W x D)	713 x 1211 x 137.1
Bezel width	22 mm
Operating temperature	0–40°C
Humidity	10–80%
Mean time between failure (MTBF)	50,000 hours
Inbuilt TV Tuner	No
Special features	<ul style="list-style-type: none"> • Lamp error detection • Temperature sensor • Built-in fan • BNC in and out • RS-232C

System Requirements

The Cisco LCD 110 PRO 52s requires a corresponding mount (not sold through Cisco) for suitable installation, depending on your deployment location and situation.

Ordering Information

You can order the Cisco LCD 110 PRO 52s as part of the overall DMS product suite or independently. Table 3 gives ordering information.

Table 3. Ordering Information

Product Name	Part Number
Cisco LCD 52" Display, 1080p Bezel S, With Remote Control	LCD-110-PRO-52S

Service and Support

Using the Cisco Lifecycle Services approach, Cisco and our partners provide a broad portfolio of end-to-end services and support that can help increase the business value and return on investment of your Digital Media System. Specifically for Cisco LCD products, you can buy standard Cisco SMARTnet Next Business Day (NBD) replacement service and 24-hour phone support from Cisco Technical Assistance Center (TAC) worldwide.

For More Information

For more information about the Cisco LCD 110 PRO 52S, visit: <http://www.cisco.com/go/dms> or contact your local Cisco account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, CCSI, Cisco Eos, Cisco Explorer, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco TrustSec, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco.Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1002R)