



## **Release Notes for Cisco Smart PHY and Cisco Operations Hub 24.2**

**First Published:** 2024-10-30

### **Americas Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
<http://www.cisco.com>  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/c/en/us/about/legal/trademarks.html>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2024 Cisco Systems, Inc. All rights reserved.



# CONTENTS

## [Full Cisco Trademarks with Software License](#) ?

---

### CHAPTER 1

#### [What's New](#) 1

[New Features for Cisco Smart PHY and Cisco Operations Hub 24.2](#) 1

---

### CHAPTER 2

#### [Caveats](#) 3

[Open Caveats in Cisco Smart PHY 24.2](#) 3

[Resolved Caveats in Cisco Smart PHY 24.2](#) 3

[Cisco Bug Search](#) 4

---

### CHAPTER 3

#### [Other Important Information](#) 7

[Software Version Compatibility For Cisco Smart PHY 24.2](#) 7

[Cisco Smart PHY Documentation References](#) 8





# CHAPTER 1

## What's New



- Note** Explore the [Content Hub](#), the all new portal that offers an enhanced product documentation experience.
- Use faceted search to locate content that is most relevant to you.
  - Create customized PDFs for ready reference.
  - Benefit from context-based recommendations.

Get started with the Content Hub at [content.cisco.com](https://content.cisco.com) to craft a personalized documentation experience.

Do provide feedback about your experience with the Content Hub.

Cisco is continuously enhancing the product with every release and this section covers a brief description of key features and enhancements that were added. It also includes links to detailed documentation, where available.

- [New Features for Cisco Smart PHY and Cisco Operations Hub 24.2, on page 1](#)

## New Features for Cisco Smart PHY and Cisco Operations Hub 24.2

Feature	Description
<b>Infrastructure Enhancements</b>	
<a href="#">Modernized and Refreshed Smart PHY NSO Error Messages</a>	Smart PHY displays NSO-related errors in a user-friendly format, and only shows useful or relevant information regarding the NSO error.
<a href="#">Standardizing All 2/3 Sidebar Table Views</a>	Smart PHY has consistent standardized functionality across all its 2/3 sidebar tables.
<b>RPD Provisioning Enhancements</b>	

Feature	Description
<a href="#">Configure Maximum Retries for RPD SSD Operations</a>	With this release, you can configure the maximum number of Smart PHY's failed consecutive SSD operations and also configure the duration between the retry attempts. Enabling this feature allows you to manually configure and provide better control of the retry attempts and duration, instead of the default indefinite duration and retry attempts.
<a href="#">Support for 128 RPDs per Line Card</a>	Smart PHY's supports 128 RPDs per Line Card. A total of 32 DOCSIS Service Groups + 32 Video Service Groups can be configured on a Kobol-R line card (CBR-CCAP-LC-G2-R). This adds support for an additional 32 new Video Service Groups (downstream-video) in addition to the existing 32 Service Groups (downstream-cable).
<b>Other Enhancements</b>	
<a href="#">I15 Specifications - GCP Redirect Global Configuration</a>	With this release, if an RPD fails to be redirected using Smart PHY's I15 compliant GCP Redirect, then you can configure a redirect of the same RPD with its original pre-I15 redirect behavior.



## CHAPTER 2

# Caveats

This chapter describes open severity 1 and 2 caveats and select severity 3 caveats.

The *Open Caveats* section lists open caveats that apply to the current release and may apply to previous releases. A caveat that is open for a prior release and is still unresolved applies to all future releases until it is resolved.

The bug IDs are sorted alphanumerically.

The *Caveats* section includes the bug ID and a short description of the bug. For details on the symptoms, conditions, and workaround for a specific caveat you must use the Bug Search Tool.

- [Open Caveats in Cisco Smart PHY 24.2, on page 3](#)
- [Resolved Caveats in Cisco Smart PHY 24.2, on page 3](#)
- [Cisco Bug Search, on page 4](#)

## Open Caveats in Cisco Smart PHY 24.2

Identifier	Headline
<a href="#">CSCwk70443</a>	On Smart PHY 24.1.2 -> Fails to import of RPD Association CSV taken from Smart PHY-24.1 version [ Error: Data core IP Address is NULL]
<a href="#">CSCwk77923</a>	Newly added core after DB import won't come online when first csv import without a matching credential profile
<a href="#">CSCwm49811</a>	Sometime it needs to perform Save to SmartPHY twice to update correct peer rpds list in DB

## Resolved Caveats in Cisco Smart PHY 24.2

Identifier	Headline
<a href="#">CSCwj69664</a>	Ordering in aux core configuration can result in cosmetic reconciliation warnings
<a href="#">CSCwk70433</a>	Reconciliation panel does not update diff data
<a href="#">CSCwk70436</a>	SmartPHY should not change default cBR CLIs

Identifier	Headline
<a href="#">CSCwk70438</a>	RPD should not be reprovisioned when pilot tone profile is changed in Service Definition
<a href="#">CSCwk70440</a>	Reconciliation reports config deviation for 2x2 when none is present
<a href="#">CSCwk76743</a>	Multiple core reconciliation shows as deviation when two RPDs are configured in different cBR8s with same controller id
<a href="#">CSCwk80761</a>	Behavior change needed for RPD location description
<a href="#">CSCwk80766</a>	UI element overlaps text in drop down lists
<a href="#">CSCwm07936</a>	Reduce Smart PHY retries after hitting ConfigPushError
<a href="#">CSCwm14555</a>	If you select "x keep, 0 replace" option, csv import won't proceed
<a href="#">CSCwm49128</a>	Reconciliation is finding diffs for fiber-node configs that are the same CLIs
<a href="#">CSCwm56980</a>	Reconciliation incorrectly reports config deviation for 2x2 peerRpdS
<a href="#">CSCwm54113</a>	SmartPHY found deviation caused by extra space in same CLI
<a href="#">CSCwm65452</a>	base-power not Reconciled after Save to SmartPHY

## Cisco Bug Search

Use the [Cisco Bug Search Tool](#) to access open and resolved bugs for a release.

The tool allows you to search for a specific bug ID, or for all bugs specific to a product and a release.

Save Search Load Saved Search Clear Search Email Current Search

Search For:  Examples: CSCId10124, router crash, etc...

Product:  Select from list

Releases:  Enter release number

368025

You can filter the search results by last modified date, bug status (open, resolved), severity, rating, and support cases.

Save Search Load Saved Search Clear Search Email Current Search

Search For:  Examples: CSCId10124, router crash, etc...

Product:  Select from list

Releases:

Filter:       Customer Visible

Viewing 1 - 25 of 132 results Sort by  Export Results to Excel

368026



### **Obtaining Documentation and Submitting a Service Request**

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, see [What's New in Cisco Product Documentation](#).

To receive new and revised Cisco technical content directly to your desktop, you can subscribe to the [What's New in Cisco Product Documentation RSS feed](#). The RSS feeds are a free service.





## CHAPTER 3

### Other Important Information

- [Software Version Compatibility For Cisco Smart PHY 24.2, on page 7](#)
- [Cisco Smart PHY Documentation References, on page 8](#)

### Software Version Compatibility For Cisco Smart PHY 24.2

The following table shows the supported operating systems, web browsers, and the versions of Cisco cBR-8 router and RPD that are compatible with Cisco Smart PHY Application 24.2.

**Table 1: Software Version Compatibility For Cisco Smart PHY 24.2**

Software	Supported Versions
Operating System	<ul style="list-style-type: none"><li>• Mac OS 12 and later</li><li>• Windows 10 and later</li></ul>
Browser	<ul style="list-style-type: none"><li>• Mozilla Firefox Version 129 and later</li><li>• Google Chrome Version 129 and later</li><li>• Microsoft Edge Version 130 and later</li></ul>
Cisco cBR-8 Router	<ul style="list-style-type: none"><li>• Cisco IOS XE Dublin 17.15.1w</li><li>• Cisco IOS XE Dublin 17.12.1z1</li></ul>
Cisco RPD	Cisco RPD 10.8 (Compatible with Cisco IOS XE Dublin 17.15.1w & 17.12.1z1)
Smart PHY Upgrade	You cannot upgrade older versions of Cisco Smart PHY to Cisco Smart PHY, Release 24.2 using In-Place Software Upgrade.

# Cisco Smart PHY Documentation References

We recommend that you view the field notices for this release to see if your software or hardware platforms are affected. If you have an account at Cisco.com, you can find the field notices at [http://www.cisco.com/en/US/customer/support/tsd\\_products\\_field\\_notice\\_summary.html](http://www.cisco.com/en/US/customer/support/tsd_products_field_notice_summary.html).

If you do not have an account at Cisco.com, you can find the field notices at [http://www.cisco.com/en/US/support/tsd\\_products\\_field\\_notice\\_summary.html](http://www.cisco.com/en/US/support/tsd_products_field_notice_summary.html).



---

**Note** Cisco Smart PHY is generally available for field deployment. However, we recommend that you validate and qualify Cisco Smart PHY in a limited field trial with your specific network configuration requirements in order to ensure a smoother, faster, and successful field deployment.

---

For information on Cisco Smart PHY, go through the following links:

- [Cisco Smart PHY Install and Upgrade Guides](#)
- [Cisco Smart PHY User Guide](#)
- [Cisco Operations Hub and Smart PHY REST API Guide](#)
- [Cisco Smart PHY Other Product Documentation](#)