



Cisco Nexus 3000 Series NX-OS Release Notes

Release 10.4(3)F

Note: The documentation set for this product strives to use bias-free language. For the purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

Introduction

The Cisco Nexus 3000 Series NX-OS Release Notes document describes the features, issues, and exceptions of Cisco NX-OS Release 10.4(3)F software for use on Cisco Nexus 3500 and 3600 Series switches.

Changes to this document:

Date	Description
March 28, 2024	Cisco NX-OS Release 10.4(3)F became available.

New and Enhanced Software Features

New Software Features

Product Impact	Features	Description
Feature Set	Configuration Replace support for polymorphic commands	From Cisco NX-OS Release 10.4(3)F, you can also use polymorphic commands in candidate config to perform configuration replace. For more information, see the Cisco Nexus 9000 Series NX-OS System Management Configuration Guide.
	Partial difference support for polymorphic commands	From Cisco NX-OS Release 10.4(3)F, you can also use polymorphic commands in candidate config to perform partial diff. For more information, see the Cisco Nexus 9000 Series NX-OS System Management Configuration Guide.
	Unified Configuration Difference support	Beginning with Cisco NX-OS Release 10.4(3)F, the show diff running-config command on Cisco Nexus switches includes a 'merged' option, which allows merging of subcommand details, instead of replacing them. For more information, see Cisco Nexus 9000 Series NX-OS System Management Configuration Guide, Release 10.4(x).
Security	TLS v1.3	Beginning with Cisco NX-OS Release 10.4(3)F, support for TLS version 1.3 is added on Cisco Nexus 3000 Series Switches. For more information, see the Cisco Nexus 3000 Series NX-OS Security Configuration Guide, Release 10.4(x).
	X.509 certificate based SSH Authorization using TACACS	Beginning with Cisco NX-OS Release 10.4(3)F, authorization of X.509 certificates for SSH using a TACACS+ server can be configured using the aaa authorization ssh-certificate default group command.

New Enhanced Features

Cisco NX-OS Release 10.4(3)F does not include any new enhanced software features for the Cisco Nexus 3000 Series.

Hardware Features

Cisco NX-OS Release 10.4(3)F does not include any new hardware features for the Cisco Nexus 3000 Series.

Release Image

Cisco Nexus 3000 Series platforms support only 64-bit image. The 64-bit Cisco NX-OS image filename begins with "nxos64-msll" (for example, nxos64-msll.10.4.2.F.bin) and this image is supported on Cisco Nexus 3600 series fixed switches and Cisco Nexus 3500-XL series switches. 32-bit image is no longer supported.

Open Issues

Bug ID	Description
CSCwi34709	N3548: One Adjacency of ip routing not working in some failover scenario

Resolved Issues

Bug ID	Description
CSCwi41283	With Nexus 3000 MPLS Labels mismatch seen in label cnt - shMplsFwdSummary and shHwCapFwd

Device Hardware

The following tables list the Cisco Nexus 3500 and Cisco Nexus 3600 Series hardware that Cisco NX-OS Release 10.4(3)F supports. For additional information about the supported hardware, see the Hardware Installation Guide for your Cisco Nexus 3500 and Cisco Nexus 3600 Series devices.

Cisco Nexus 3500 Switches

Product ID	Description
N3K-C3524P-XL	Cisco Nexus 3524-XL switch
N3K-C3548P-XL	Cisco Nexus 3548-XL switch

Cisco Nexus 3500 Series Fans, Fan Trays, and Power Supplies

Product ID	Description
N2200-PAC-400W	Cisco Nexus 2000 or 3000 400W AC power supply, forward airflow (port side exhaust)
N2200-PAC-400W-B	Cisco Nexus 2000 or 3000 400W AC power supply, reverse airflow (port side intake)
N2200-PDC-400W	Cisco Nexus 2000 or 3000 400W DC power supply, forward airflow (port side exhaust)

Product ID	Description
N3K-PDC-350W-B	Cisco Nexus 2000 or 3000 350W DC power supply, reverse airflow (port side intake)
NXA-FAN-30CFM-B	Cisco Nexus 2000 or 3000 individual fan, reverse airflow (port side intake)
NXA-FAN-30CFM-F	Cisco Nexus 2000 or 3000 individual fan, forward airflow (port side exhaust)

Cisco Nexus 3600 Switches

Product ID	Description
N3K-C3636C-R	The Cisco Nexus 3636C-R is a 1 rack unit (RU) switch with 36 100-Gigabit QSFP28 ports, 40-Gigabit QSFP, 2 management ports, 1 console port, and 1 USB port. The switch supports both port-side exhaust and port-side intake airflow schemes. The switch has two power supplies, one for operations and the other for redundancy. Both power supplies must be either AC power supplies or DC power supplies.
N3K-C36180YC-R	<p>The Cisco Nexus 36180YC-R is a 1 rack unit (RU) switch with 48 1/10/25-Gigabit SFP ports and 6 40Gigabit QSFP/100-Gigabit QSFP28 ports, 1 management port, 1 console port, and 1 USB port. The switch supports both port-side exhaust and port-side intake airflow schemes. The switch has two power supplies, one for operations and the other for redundancy. Both power supplies must be either AC power supplies or DC power supplies.</p> <p>From Cisco NX-OS Release 10.3(3)F, the following AC ports are supported on Cisco Nexus 36180YC-R (N3K-C36180YC-R):</p> <ul style="list-style-type: none"> • AC port-side exhaust (NXA-PAC-750W-PE) • AC port-side intake (NXA-PAC-750W-PI) <p>The following table provides information about spares support:</p> <ul style="list-style-type: none"> • The Typical/Minimum port-side intake and fan speed percentage is 50% and the maximum port-side intake and fan speed percentage is 100%. • The Typical/Minimum port-side exhaust and fan speed percentage is 70% and the maximum port-side exhaust and fan speed percentage is 100%. <p>For information about N3K-C36180YC-R, see Cisco Nexus 3600 Hardware Installation Guide.</p>

Upgrade and Downgrade

To perform a software upgrade or downgrade, follow the instructions in the [Cisco Nexus 3500 Series NX-OS Software Upgrade and Downgrade Guide](#) and [Cisco Nexus 3600 Series NX-OS Software Upgrade and Downgrade Guide](#).

For information about an In Service Software Upgrade (ISSU), see the [Cisco NX-OS ISSU Support Matrix](#).

MIB Support

The Cisco Management Information Base (MIB) list includes Cisco proprietary MIBs and many other Internet Engineering Task Force (IETF) standard MIBs. These standard MIBs are defined in Requests for Comments (RFCs). To find specific MIB information, you must examine the Cisco proprietary MIB structure and related IETF-standard MIBs supported by the Cisco Nexus 3000 Series switch. The MIB Support List is available at the following FTP sites:

<https://cisco.github.io/cisco-mibs/supportlists/nexus3000/Nexus3000MIBSupportList.html>

Optics

To determine which transceivers and cables are supported by Cisco Nexus 3000 Series switches, see the [Transceiver Module \(TMG\) Compatibility Matrix](#).

To see the transceiver specifications and installation information, see [Install and Upgrade Guides](#).

Related Content

This document describes and provides links to the user documentation available for Cisco Nexus 3000 Series documentation. To find a document online, use one of the links in this section.

Document Title	Description
Cisco Nexus 3000 Series switch documentation	Cisco Nexus 3000 Series documentation
Cisco NX-OS Software Strategy and Lifecycle Guide	Cisco NX-OS Software Release and Image-naming Convention
Cisco Nexus 3000 and 9000 Series NXAPI REST SDK User Guide and API Reference	Cisco Nexus 3000 and 9000 Series NX-API REST SDK User Guide and API Reference
Cisco NX-OS Licensing Guide Cisco Nexus 9000 and 3000 Series NX-OS Switch License Navigator Cisco Nexus Smart Licensing Using Policy User Guide	Licensing Information

Documentation Feedback

To provide technical feedback on this document, or to report an error or omission, please send your comments to nexus9k-docfeedback@cisco.com. We appreciate your feedback.

Legal Information

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/c/en/us/about/legal/trademarks.html>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2024 Cisco Systems, Inc. All rights reserved.