

OSPF Limit on Number of Redistributed Routes

Open Shortest Path First (OSPF) supports a user-defined maximum number of prefixes (routes) that are allowed to be redistributed into OSPF from other protocols or other OSPF processes. Such a limit could help prevent the router from being flooded by too many redistributed routes.

- Finding Feature Information, on page 1
- Prerequisites for OSPF Limit on Number of Redistributed Routes, on page 1
- Information About OSPF Limit on Number of Redistributed Routes, on page 1
- How to Configure OSPF Limit the Number of OSPF Redistributed Routes, on page 2
- Configuration Examples for OSPF Limit on Number of Redistributed Routes, on page 5
- Additional References, on page 5
- Feature Information for OSPF Limit on Number of Redistributed Routes, on page 6

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see Bug Search Tooland the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Prerequisites for OSPF Limit on Number of Redistributed Routes

It is presumed that you have OSPF configured in your network, along with another protocol or another OSPF process you are redistributing.

Information About OSPF Limit on Number of Redistributed Routes

If large number of IP routes are sent into OSPF by redistributing Border Gateway Protocol (BGP) into OSPF, the network can be severely flooded. Limiting the number of redistributed routes prevents this potential problem.

OSPF can receive and accept packets from non-routable addresses (for example, 0.0.0.0/7) also.

How to Configure OSPF Limit the Number of OSPF Redistributed Routes

This section contains the following procedures, which are mutually exclusive. That is, you cannot both limit redistributed prefixes and also choose to be warned.

Limiting the Number of OSPF Redistributed Routes

This task describes how to limit the number of OSPF redistributed routes. If the number of redistributed routes reaches the maximum value configured, no more routes will be redistributed.

The redistribution limit applies to all IP redistributed prefixes, including summarized ones. The redistribution limit does not apply to default routes or prefixes that are generated as a result of Type-7 to Type-5 translation.

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- 3. router ospf process-id
- **4.** redistribute protocol [process-id][as-number] [metric metric-value] [metric-type type-value] [match{internal external 1| external 2}][tag tag-value] [route-map map-tag] [subnets]
- **5. redistribute maximum-prefix** *maximum* [threshold]
- end
- **7. show ip ospf** [process-id]

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.
	Example:	• Enter your password if prompted.
	Router> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example:	
	Router# configure terminal	
Step 3	router ospf process-id	Configures an OSPF routing process.
	Example:	
	Router(config)# router ospf 1	

	Command or Action	Purpose
Step 4	redistribute protocol [process-id][as-number] [metric metric-value] [metric-type type-value] [match{internal} external 1 external 2}][tag tag-value] [route-map map-tag] [subnets]	Redistributes routes from one routing domain into another routing domain.
	Example:	
	Router(config-router)# redistribute eigrp 10	
Step 5	redistribute maximum-prefix maximum [threshold] Example: Router(config-router) # redistribute maximum-prefix 100 80	Sets a maximum number of IP prefixes that are allowed to be redistributed into OSPF. • There is no default value for the <i>maximum</i> argument. • The <i>threshold</i> value defaults to 75 percent. Note If the warning-only keyword had been configured in this command, no limit would be enforced; a warning message is simply logged.
Step 6	<pre>end Example: Router(config-router)# end</pre>	Exits router configuration mode.
Step 7	<pre>show ip ospf [process-id] Example: Router# show ip ospf 1</pre>	(Optional) Displays general information about OSPF routing processes. • If a redistribution limit was configured, the output will include the maximum limit of redistributed prefixes and the threshold for warning messages.

Requesting a Warning About the Number of Routes Redistributed into OSPF

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- **3.** router ospf process-id
- **4. redistribute** protocol [process-id][as-number] [**metric** metric-value] [**metric-type** type-value] [**match**{internal | external 1| external 2}][tag tag-value] [**route-map** map-tag] [**subnets**]
- 5. redistribute maximum-prefix maximum [threshold] warning-only
- 6. end

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.

	Command or Action	Purpose
	Example:	Enter your password if prompted.
	Router> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example:	
	Router# configure terminal	
Step 3	router ospf process-id	Configures an OSPF routing process.
	Example:	
	Router(config) # router ospf 1	
Step 4	redistribute protocol [process-id][as-number] [metric metric-value] [metric-type type-value] [match {internal}]	Redistributes routes from one routing domain into another routing domain.
	external 1 external 2}][tag tag-value] [route-map map-tag] [subnets]	Note The redistribution count applies to external IP prefixes, including summarized routes. Default
	Example:	routes and prefixes that are generated as a result
	Router(config-router)# redistribute eigrp 10	of Type-7 to Type-5 translation are not considered.
Step 5	redistribute maximum-prefix maximum [threshold] warning-only	Causes a warning message to be logged when the maximum number of IP prefixes has been redistributed into OSPF.
	Example: Router(config-router) # redistribute maximum-prefix 1000 80 warning-only	 Because the warning-only keyword is included, no limit is imposed on the number of redistributed prefixes into OSPF.
		• There is no default value for the <i>maximum</i> argument.
		The threshold value defaults to 75 percent.
		This example causes two warnings: one at 80 percent
		of 1000 (800 routes redistributed) and another at 1000 routes redistributed.
Step 6	end	Exits router configuration mode.
	Example:	
	Router(config-router)# end	

Configuration Examples for OSPF Limit on Number of Redistributed Routes

Example OSPF Limit on Number of Redistributed Routes

This example sets a maximum of 1200 prefixes that can be redistributed into OSPF process 1. Prior to reaching the limit, when the number of prefixes redistributed reaches 80 percent of 1200 (960 prefixes), a warning message is logged. Another warning is logged when the limit is reached and no more routes are redistributed.

```
router ospf 1
router-id 10.0.0.1
domain-id 5.6.7.8
log-adjacency-changes
timers lsa-interval 2
network 10.0.0.1 0.0.0.0 area 0
network 10.1.5.1 0.0.0.0 area 0
network 10.2.2.1 0.0.0.0 area 0
redistribute static subnets
redistribute maximum-prefix 1200 80
```

Example Requesting a Warning About the Number of Redistributed Routes

This example allows two warning messages to be logged, the first if the number of prefixes redistributed reaches 85 percent of 600 (510 prefixes), and the second if the number of redistributed routes reaches 600. However, the number of redistributed routes is not limited.

```
router ospf 1
network 10.0.0.0 0.0.0.255 area 0
redistribute eigrp 10 subnets
redistribute maximum-prefix 600 85 warning-only
```

Additional References

Related Documents

Related Topic	Document Title	
OSPF commands	Cisco IOS IP Routing: OSPF Command Reference	

Standards

Standards	Title
No new or modified standards are supported by this feature, and support for existing standards has not been modified by this feature.	

MIBs

MIBs	MIBs Link	
None	To locate and download MIBs for selected platforms, Cisco software releases, and feature sets, use Cisco MIB Locator found at the following URL:	
	http://www.cisco.com/go/mibs	

RFCs

RFCs	Title
No new or modified RFCs are supported by this feature, and support for existing RFCs has not been modified by this feature.	

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	

Feature Information for OSPF Limit on Number of Redistributed Routes

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for OSPF Limit on Number of Redistributed Routes

Feature Name	Releases	Feature Information
OSPF Limit on Number of Redistributed Routes	12.0(25)S 12.3(2)T 12.2(18)S 12.2(27)SBC Cisco IOS XE 3.1.0 SG	OSPF supports a user-defined maximum number of prefixes (routes) that are allowed to be redistributed into OSPF from other protocols or other OSPF processes. Such a limit could help prevent the router from being flooded by too many redistributed routes. The following commands are introduced or modified in the feature documented in this module: • redistribute maximum-prefix • show ip ospf • show ip ospf database

Feature Information for OSPF Limit on Number of Redistributed Routes