



Release Notes for Cisco NCS 5500 Series Routers, IOS XR Release 7.11.21

[Network Convergence System 5500 Series Routers](#) 2

[What's New in Cisco IOS XR Release 7.11.21](#) 2

[Caveats](#) 2

[Release Package](#) 2

[Determine Software Version](#) 3

[Determine Firmware Support](#) 4

[Important Notes](#) 13

Revised: October 19, 2024

Network Convergence System 5500 Series Routers

What's New in Cisco IOS XR Release 7.11.21

Cisco IOS XR Release 7.11.21 is a service pack release for Cisco NCS 5500 Series routers. There are no new software features or hardware introduced in this release.

For more details on the Cisco IOS XR release model and associated support, see [Software Lifecycle Support Statement - IOS XR](#).

Caveats

There are no caveats in this release.

Release Package

This table lists the Cisco IOS XR Software feature set matrix (packages) with associated filenames.

Visit the [Cisco Software Download](#) page to download the Cisco IOS XR software images.

Table 1: Release 7.11.21 Packages for Cisco NCS 5500 Series Router

Composite Package		
Feature Set	Filename	Description
Cisco IOS XR IP Unicast Routing Core Bundle	ncs5500-mini-x.iso	Contains base image contents that includes: <ul style="list-style-type: none">• Host operating system• System Admin boot image• IOS XR boot image• BGP packages
Individually-Installable Optional Packages		
Feature Set	Filename	Description
Cisco IOS XR Manageability Package	ncs5500-mgbl-3.0.0.0-r71121.x86_64.rpm	Extensible Markup Language (XML) Parser, Telemetry, Netconf, gRPC and HTTP server packages.
Cisco IOS XR MPLS Package	ncs5500-mpls-2.1.0.0-r71121.x86_64.rpm ncs5500-mpls-te-rsvp-2.2.0.0-r71121.x86_64.rpm	MPLS and MPLS Traffic Engineering (MPLS-TE) RPM.

Cisco IOS XR Security Package	ncs5500-k9sec-3.1.0.0-r71121.x86_64.rpm	Support for Encryption, Decryption, Secure Shell (SSH), Secure Socket Layer (SSL), and Public-key infrastructure (PKI)
Cisco IOS XR ISIS package	ncs5500-isis-1.2.0.0-r71121.x86_64.rpm	Support ISIS
Cisco IOS XR OSPF package	ncs5500-ospf-2.0.0.0-r71121.x86_64.rpm	Support OSPF
Lawful Intercept (LI) Package	ncs5500-li-1.0.0.0-r71121.x86_64.rpm	Includes LI software images
Multicast Package	ncs5500-mcast-1.0.0.0-r71121.x86_64rpm	Support Multicast
EIGRP	ncs5500-eigrp-1.0.0.0-r71121.x86_64.rpm	Supports Enhanced Interior Gateway Routing Protocol
Lawful Intercept Control	ncs5500-lictrl-1.0.0.0-r71121x86_64.rpm	Supports Lawful Intercept Control
Healthcheck	ncs5500-healthcheck-1.0.0.0-r71121.x86_64.rpm	Supports System Health Check

Table 2: Release 7.11.21 TAR files for Cisco NCS 5500 Series Router

Feature Set	Filename
NCS 5500 IOS XR Software 3DES	NCS5500-iosxr-k9-7.11.21.tar
NCS 5500 IOS XR Software	NCS5500-iosxr-7.11.21.tar
NCS 5500 IOS XR Software	NCS5500-docs-7.11.21.tar

Table 3: Release 7.11.21 Packages for Cisco NCS 5700 Series Router

Feature Set	Filename
NCS 5700 IOS XR Software	ncs5700-x64-7.11.21.iso
NCS 5700 IOS XR Software (only k9 RPMs)	ncs5700-k9sec-rpms.7.11.21.tar
NCS 5700 IOS XR Software Optional Package	NCS5700-optional-rpms.7.11.21.tar This TAR file contains the following RPMS: <ul style="list-style-type: none"> • optional-rpms/cdp/* • optional-rpms/eigrp/* • optional-rpms/telnet/*

Determine Software Version

To verify the software version running on the router, use **show version** command in the EXEC mode.

```
Router# show version
Cisco IOS XR Software, Version 7.11.21
Copyright (c) 2013-2024 by Cisco Systems, Inc.
```

```

Build Information:
  Built By      : swtools
  Built On     : Thu Oct 17 00:14:00 PDT 2024
  Built Host   : iox-ucs-037
  Workspace    : /auto/srcarchive10/prod/7.11.21/ncs5500/ws
  Version      : 7.11.21
  Location     : /opt/cisco/XR/packages/
  Label       : 7.11.21

```

```

cisco NCS-5500 () processor
System uptime is 36 minutes

```

Determine Firmware Support

Use the **show hw-module fpd** command in EXEC and Admin mode to view the hardware components with their current FPD version and status. The status of the hardware must be CURRENT; Running and Programed version must be the same.]

You can also use the **show fpd package** command in Admin mode to check the fpd versions.

NCS 5500 Fixed Port Routers

```
Router# show fpd package
```

```

=====
                          Field Programmable Device Package
                          =====

```

Card Type	FPD Description	Req Reload	SW Ver	Min Req SW Ver	Min Req Board Ver
NC55-12X100G-SE-PR	Bootloader	YES	1.20	1.20	0.0
	IOFPGA	YES	0.12	0.12	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0
NC55-12X100GE-PROT	Bootloader	YES	1.22	1.22	0.0
	IOFPGA	YES	0.15	0.15	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0
NC55-18H18F	Bootloader	YES	1.20	1.20	0.0
	IOFPGA	YES	0.22	0.22	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
SATA-M500IT-MU-B	NO	4.00	4.00	0.0	

	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-24H12F-SE	Bootloader	YES	1.20	1.20	0.0
	IOFPGA	YES	0.09	0.09	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-24X100G-SE	Bootloader	YES	1.20	1.20	0.0
	IOFPGA	YES	0.13	0.13	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-32T16Q4H-A	Bootloader	YES	0.05	0.05	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.93	0.93	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-32T16Q4H-AT	Bootloader	YES	0.05	0.05	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.93	0.93	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-36X100G	Bootloader	YES	1.22	1.22	0.0
	IOFPGA	YES	0.15	0.15	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0

	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-36X100G-A-SE	Bootloader	YES	0.15	0.15	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.26	0.26	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-36X100G-S	Bootloader	YES	1.20	1.20	0.0
	IOFPGA	YES	0.12	0.12	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-5504-FC	Bootloader	YES	1.75	1.75	0.0
	IOFPGA	YES	0.10	0.10	0.0

NC55-5504-FC2	Bootloader	YES	1.13	1.13	0.0
	IOFPGA	YES	0.47	0.47	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-5508-FC	Bootloader	YES	1.74	1.74	0.0
	IOFPGA	YES	0.16	0.16	0.0

NC55-5508-FC2	Bootloader	YES	1.80	1.80	0.0
	IOFPGA	YES	0.19	0.19	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0

	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-5516-FC	Bootloader	YES	1.75	1.75	0.0
	IOFPGA	YES	0.27	0.27	0.0

NC55-5516-FC2	Bootloader	YES	1.80	1.80	0.0
	IOFPGA	YES	0.24	0.24	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-6X100GE-PROT	Bootloader	YES	1.22	1.22	0.0
	IOFPGA	YES	0.15	0.15	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-6X200-DWDM-S	Bootloader	YES	1.20	1.20	0.0
	IOFPGA	YES	0.14	0.14	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-MOD-A-S	Bootloader	YES	1.03	1.03	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.14	0.14	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-MOD-A-SE-S	Bootloader	YES	1.03	1.03	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.14	0.14	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0

	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-PWR-3KW-2HV	DT-LogicMCU	NO	3.01	3.01	0.2
	DT-PrimCU	NO	3.00	3.00	0.2
	DT-SecMCU	NO	3.01	3.01	0.2

NC55-PWR-3KW-DC	DT-SecMCU	NO	4.12	4.12	0.1

NC55-PWR-4.4KW-DC	QCS-LogicMCU	NO	3.00	3.00	0.1
	QCS-PrimCU	NO	3.00	3.00	0.1
	QCS-SecMCU	NO	3.00	3.00	0.1

NC55-RP	Bootloader	YES	9.31	9.31	0.0
	IOFPGA	YES	0.09	0.09	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-RP-E	Bootloader	YES	1.24	1.24	0.0
	IOFPGA	YES	0.23	0.23	0.0
	OMGFPGA	YES	0.61	0.61	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-RP-PROTO	Bootloader	YES	9.31	9.31	0.0
	IOFPGA	YES	0.06	0.06	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-RP2-E	Bootloader	YES	0.09	0.09	0.0
	IOFPGA	YES	0.50	0.50	0.0
	OMGFPGA	YES	0.52	0.52	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0

	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC55-SC	Bootloader	YES	1.74	1.74	0.0
	IOFPGA	YES	0.10	0.10	0.0

NC57-1600W-ACFW	PriMCU-ACFW	NO	1.02	1.02	0.0
	SecMCU-ACFW	NO	1.07	1.07	0.0

NC57-1600W-DCFV	PriMCU-DCFV	NO	1.07	1.00	0.0

NC57-18DD-SE	Bootloader	YES	1.03	1.03	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.22	0.22	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC57-24DD	Bootloader	YES	1.03	1.03	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.23	0.23	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC57-36H-SE	Bootloader	YES	1.03	1.03	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.07	0.07	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC57-36H6D-S	Bootloader	YES	0.02	0.02	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.47	0.47	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0

	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC57-48Q2D-S	ALDRINFPGA	YES	1.06	1.06	0.0
	Bootloader	YES	1.00	1.00	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.105	0.105	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC57-48Q2D-SE-S	ALDRINFPGA	YES	1.06	1.06	0.0
	Bootloader	YES	1.00	1.00	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.105	0.105	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC57-MOD-RP2-E	Bootloader	YES	0.13	0.13	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NC57-MOD-S	Bootloader	YES	2.03	2.03	0.0
	DBFPGA	YES	0.14	0.14	0.0
	IOFPGA	YES	0.42	0.42	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0

	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NCS-57C3-MOD-SYS	ALDRINFPGA	YES	1.04	1.04	0.0
	Bootloader	YES	0.14	0.14	0.0
	DBFPGA	YES	0.56	0.56	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NCS-57C3-MODS-SYS	ALDRINFPGA	YES	1.04	1.04	0.0
	Bootloader	YES	0.14	0.14	0.0
	DBFPGA	YES	0.56	0.56	0.0
	SATA-INTEL_240G	NO	1132.00	1132.00	0.0
	SATA-INTEL_480G	NO	1132.00	1132.00	0.0
	SATA-M500IT-MC	NO	3.00	3.00	0.0
	SATA-M500IT-MU-A	NO	5.00	5.00	0.0
	SATA-M500IT-MU-B	NO	4.00	4.00	0.0
	SATA-M5100	NO	75.00	75.00	0.0
	SATA-M600-MCT	NO	5.00	5.00	0.0
	SATA-M600-MU	NO	6.00	6.00	0.0
	SATA-Micron	NO	1.00	1.00	0.0
	SATA-SMART-128G	NO	1241.00	1241.00	0.0

NCS 5700 Fixed Port Routers

Router# show fpd package

```

=====
                          Field Programmable Device Package
=====

```

Card Type	FPD Description	Req Reload	SW Ver	Min Req SW Ver	Min Req Board Ver

NCS-57B1-5DSE-SYS	ADM1_Config	NO	0.50	0.50	0.0
	ADM2_Config	NO	0.50	0.50	0.0
	ADM3_Config	NO	0.50	0.50	0.0
	IoFpga	YES	0.09	0.09	0.0
	IoFpgaGolden	YES	0.09	0.08	0.0
	Primary-BIOS	YES	1.11	1.11	0.0
	StdbyFpga	YES	0.24	0.24	0.0
	StdbyFpgaGolden	YES	0.24	0.24	0.0
	TamFw	YES	6.05	6.05	0.0
	TamFwGolden	YES	6.05	6.05	0.0

NCS-57B1-6D24-SYS	ADM1_Config	NO	0.94	0.94	0.0
	ADM2_Config	NO	0.94	0.94	0.0
	ADM3_Config	NO	0.94	0.94	0.0
	IoFpga	YES	0.09	0.09	0.0
	IoFpgaGolden	YES	0.09	0.08	0.0
	Primary-BIOS	YES	1.11	1.11	0.0
	SsdIntelS4510	YES	11.20	11.20	0.0
	SsdMicron5300	YES	0.01	0.01	0.0
	StdbyFpga	YES	0.24	0.24	0.0
	StdbyFpgaGolden	YES	0.24	0.24	0.0
	TamFw	YES	6.05	6.05	0.0
	TamFwGolden	YES	6.05	6.05	0.0

NCS-57C1-48Q6-SYS	ADM1_Config	YES	0.07	0.07	0.0
	ADM2_Config	YES	0.07	0.07	0.0
	IoFpga	YES	0.47	0.47	0.0
	IoFpgaGolden	YES	0.47	0.47	0.0
	Primary-BIOS	YES	3.07	3.07	0.0
	SsdIntelS4510	YES	11.32	11.32	0.0
	SsdMicron5300	YES	0.01	0.01	0.0
	StdbyFpga	YES	0.31	0.31	0.0
	StdbyFpgaGolden	YES	0.31	0.31	0.0
	TamFw	YES	7.10	7.10	0.0
	TamFwGolden	YES	7.10	7.10	0.0

NCS-57D2-18DD-SYS	ADM1-DBConfig	YES	1.92	1.92	0.0
	ADM2-DBConfig	YES	1.92	1.92	0.0
	ADM3-DBConfig	YES	1.92	1.92	0.0
	ADM4-MBConfig	YES	1.92	1.92	0.0
	ADM5-MBConfig	YES	1.92	1.92	0.0
	ADM6-MBConfig	YES	1.92	1.92	0.0
	FtFpga	NO	0.20	0.20	0.0
	FtFpgaGolden	NO	0.20	0.00	0.0
	IoFpga	YES	0.06	0.06	0.0
	IoFpgaDB	YES	0.07	0.07	0.0
	IoFpgaGolden	YES	0.05	0.05	0.0
	IoFpgaGoldenDB	YES	0.05	0.05	0.0
	Primary-BIOS	YES	4.10	4.10	0.0
	SsdIntelS4510	YES	11.32	11.32	0.0
	SsdMicron5300	YES	0.01	0.01	0.0
	StdbyFpga	YES	0.96	0.96	0.0
	StdbyFpgaGolden	YES	0.83	0.83	0.0
	TamFw	YES	7.09	7.09	0.0
	TamFwGolden	YES	7.09	7.09	0.0

PSU1100W-ACPI	EM-PrimMCU	NO	1.01	1.01	0.0
	EM-SecMCU	NO	1.05	1.05	0.0

PSU2KW-ACPE	PO-PrimMCU	NO	1.03	1.03	0.0
	PO-SecMCU	NO	1.10	1.10	0.0

PSU2KW-ACPI	PO-PrimMCU	NO	1.03	1.03	0.0
	PO-SecMCU	NO	1.13	1.13	0.0

PSU2KW-DCPE	PO-PrimMCU	NO	1.11	1.11	0.0

PSU2KW-DCPI	PO-PrimMCU	NO	1.11	1.11	0.0

PSU950W-DCPI	EM-PrimMCU	NO	1.00	1.00	0.0

This sample output is for **show hw-module fpd** command from the Admin mode:

```
sysadmin-vm:0_RP0# show hw-module fpd
Auto-upgrade:Enabled
```

Location	Card type	FPD Versions		ATR Status	Run	Programd
		HWver	FPD device			
0/3	NC57-36H-SE	1.0	Bootloader	CURRENT	1.03	1.03
0/3	NC57-36H-SE	1.0	DBFPGA	CURRENT	0.14	0.14
0/3	NC57-36H-SE	1.0	IOFPGA	CURRENT	0.07	0.07
0/3	NC57-36H-SE	1.0	SATA-Micron	CURRENT	1.00	1.00
0/5	NC57-36H-SE	1.0	Bootloader	CURRENT	1.03	1.03
0/5	NC57-36H-SE	1.0	DBFPGA	CURRENT	0.14	0.14
0/5	NC57-36H-SE	1.0	IOFPGA	CURRENT	0.07	0.07
0/5	NC57-36H-SE	1.0	SATA-Micron	CURRENT	1.00	1.00
0/7	NC57-36H-SE	1.0	Bootloader	CURRENT	1.03	1.03
0/7	NC57-36H-SE	1.0	DBFPGA	CURRENT	0.14	0.14

0/7	NC57-36H-SE	1.0	IOFPGA	CURRENT	0.07	0.07
0/7	NC57-36H-SE	1.0	SATA-Micron	CURRENT	1.00	1.00
0/RP0	NC55-RP2-E	1.0	Bootloader	CURRENT	0.09	0.09
0/RP0	NC55-RP2-E	1.0	IOFPGA	CURRENT	0.50	0.50
0/RP0	NC55-RP2-E	1.0	OMGFPGA	CURRENT	0.52	0.52
0/RP0	NC55-RP2-E	1.0	SATA-Micron	CURRENT	1.00	1.00
0/RP1	NC55-RP2-E	1.0	Bootloader	CURRENT	0.09	0.09
0/RP1	NC55-RP2-E	1.0	IOFPGA	CURRENT	0.50	0.50
0/RP1	NC55-RP2-E	1.0	OMGFPGA	CURRENT	0.52	0.52
0/RP1	NC55-RP2-E	1.0	SATA-Micron	CURRENT	1.00	1.00
0/FC1	NC55-5508-FC2	1.0	Bootloader	CURRENT	1.80	1.80
0/FC1	NC55-5508-FC2	1.0	IOFPGA	CURRENT	0.20	0.20
0/FC1	NC55-5508-FC2	1.0	SATA-M5100	CURRENT	75.00	75.00
0/FC3	NC55-5508-FC2	1.0	Bootloader	CURRENT	1.80	1.80
0/FC3	NC55-5508-FC2	1.0	IOFPGA	CURRENT	0.20	0.20
0/FC3	NC55-5508-FC2	1.0	SATA-M5100	CURRENT	75.00	75.00
0/FC5	NC55-5508-FC2	1.0	Bootloader	CURRENT	1.80	1.80
0/FC5	NC55-5508-FC2	1.0	IOFPGA	CURRENT	0.20	0.20
0/FC5	NC55-5508-FC2	1.0	SATA-M5100	CURRENT	75.00	75.00
0/SC0	NC55-SC	1.6	Bootloader	CURRENT	1.74	1.74
0/SC0	NC55-SC	1.6	IOFPGA	CURRENT	0.11	0.11
0/SC1	NC55-SC	1.6	Bootloader	CURRENT	1.74	1.74
0/SC1	NC55-SC	1.6	IOFPGA	CURRENT	0.11	0.11

Important Notes

- The total number of bridge-domains (2*BDs) and GRE tunnels put together should not exceed 1518. Here the number 1518 represents the multi-dimensional scale value.
- The offline diagnostics functionality is not supported in NCS 5500 platform. Therefore, the **hw-module service offline location** command will not work. However, you can use the **(sysadmin)# hw-module shutdown location** command to bring down the LC.

Supported Transceiver Modules

To determine the transceivers that Cisco hardware device supports, refer to the [Transceiver Module Group \(TMG\) Compatibility Matrix](#) tool.

Upgrading Cisco IOS XR Software

Cisco IOS XR Software is installed and activated from modular packages, allowing specific features or software patches to be installed, upgraded, or downgraded without affecting unrelated processes. Software packages can be upgraded or downgraded on all supported card types, or on a single card (node).

Before starting the software upgrade, use the **show install health** command in the admin mode. This command validates if the statuses of all relevant parameters of the system are ready for the software upgrade without interrupting the system.



Note

- If you use a TAR package to upgrade from a Cisco IOS XR release prior to 7.x, the output of the **show install health** command in admin mode displays the following error messages:

```
sysadmin-vm:0_RSP0# show install health
. . .
ERROR /install_repo/gl/xr -rw-r--r--. 1 8413 floppy 3230320 Mar 14 05:45 <platform>-isis-2.2.0.0-r702.x86_64
ERROR /install_repo/gl/xr -rwxr-x---. 1 8413 165 1485781 Mar 14 06:02 <platform>-k9sec-3.1.0.0-r702.x86_64
ERROR /install_repo/gl/xr -rw-r--r--. 1 8413 floppy 345144 Mar 14 05:45 <platform>-li-1.0.0.0-r702.x86_64
```

You can ignore these messages and proceed with the installation operation.

- Quad configurations will be lost when you perform a software downgrade on a NCS-55A1-48Q6H device from IOS XR Release 7.5.1 onwards to a release prior to IOS XR Release 7.5.1 due to non-backward compatibility change. The lost configuration can be applied manually after the downgrade.



Note

A quad is a group of four ports with common speeds, 1G/10G or 25G. You can configure the ports speed for a quad by using the **hw-module quad** command.

Production Software Maintenance Updates (SMUs)

A production SMU is a SMU that is formally requested, developed, tested, and released. Production SMUs are intended for use in a live network environment and are formally supported by the Cisco TAC and the relevant development teams. Software bugs identified through software recommendations or Bug Search Tools are not a basis for production SMU requests.

For information on production SMU types, refer the [Production SMU Types](#) section of the *IOS XR Software Maintenance Updates (SMUs)* guide.

Cisco IOS XR Error messages

To view, search, compare, and download Cisco IOS XR Error Messages, refer to the [Cisco IOS XR Error messages](#) tool.

Cisco IOS XR MIBs

To determine the MIBs supported by platform and release, refer to the [Cisco IOS XR MIBs](#) tool.

Related Documentation

The most current Cisco NCS 5500 router documentation is located at the following URL:

<https://www.cisco.com/c/en/us/td/docs/iosxr/ios-xr.html>



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA 95134-1706
USA

Asia Pacific Headquarters
CiscoSystems(USA)Pte.Ltd.
Singapore

Europe Headquarters
CiscoSystemsInternationalBV
Amsterdam,TheNetherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.