**A P P E N D I X**  **B**

# Unsupported CLI Commands

This appendix lists some of the command-line interface (CLI) commands that are not supported in this release, either because they are not tested, or because of hardware limitations. These unsupported commands are displayed when you enter the question mark (?) at the CLI prompt. This is not a complete list. Unsupported commands are listed by command mode.

## Unsupported Privileged Exec Commands

clear ip accounting

show ip accounting

show ip cache

show ip tcp header-compression

show ip mcache

show ip mpacket

show controller pos pm

show controller pos [*variable*] pm

## Unsupported Global Configuration Commands

access-list aaa <1100-1199>

access-list aaa <200-299>

access-list aaa <700-799>

async-bootp

boot

bridge <num> acquire

bridge <num> address

bridge cmf

bridge <num> bitswap-layer3-addresses

bridge <num> circuit-group

bridge <num> domain

bridge <num> lat-service-filtering

bridge <num> protocol dec

bridge <num> protocol ibm

bridge <num> protocol vlan-bridge

chat-script

class-map match access-group

class-map match class-map

class-map match destination-address

class-map match mpls

class-map match protocol

class-map match qos-group

class-map match source-address

clns

define

dialer

dialer-list

downward-compatible-config

file

ip access-list log-update

ip access-list logging

ip address-pool

ip alias

ip bootp

ip gdp

ip local

ip reflexive-list

ip security

ip source-route

ip tcp

ipc

map-class

map-list

multilink

netbios

partition

policy-map class queue-limit

priority-list

queue-list

router iso-igrp

router mobile

service compress-config

service disable-ip-fast-frag

service exec-callback

service nagle

service old-slip-prompts

service pad

service slave-log

set privilege level

subscriber-policy

# Unsupported POS Interface Configuration Commands

access-expression

autodetect

bridge-group x circuit-group

bridge-group x input-*

bridge-group x lat-compression

bridge-group x output-*

bridge-group x subscriber-loop-control

clock

clns

custom-queue-list

down-when-looped

fair-queue

flowcontrol

full-duplex

half-duplex

hold-queue

ip accounting

ip broadcast-address

ip load-sharing per-packet

ip route-cache

ip security

ip tcp

ip verify

iso-igrp

loopback

multilink-group

netbios

pos flag c2

pos mode gfp

priority-group

pulse-time

random-detect

rate-limit

serial

service-policy history

source

timeout

transmit-interface

tx-ring-limit

# Unsupported FastEthernet or GigabitEthernet Interface Configuration Commands

access-expression

clns

custom-queue-list

fair-queue

hold-queue

ip accounting

ip broadcast-address

ip load-sharing per-packet

ip route-cache

ip security

ip tcp

ip verify

iso-igrp

keepalive

loopback

max-reserved-bandwidth

multilink-group

netbios

priority-group

random-detect

rate-limit

service-policy history

timeout

transmit-interface

tx-ring-limit

# Unsupported Port-Channel Interface Configuration Commands

access-expression

carrier-delay

cdp

clns

custom-queue-list

duplex

down-when-looped

encapsulation

fair-queue

flowcontrol

full-duplex

half-duplex

hold-queue

iso-igrp

keepalive

max-reserved-bandwidth

multilink-group

negotiation

netbios

ppp

priority-group

rate-limit

random-detect

timeout

tx-ring-limit

# Unsupported BVI Interface Configuration Commands

access-expression

carrier-delay

cdp

clns

flowcontrol

hold-queue

iso-igrp

keepalive

l2protocol-tunnel

load-interval

max-reserved-bandwidth

mode

multilink-group

netbios

ntp

mtu

rate-limit

timeout

transmit-interface

tx-ring-limit