



Command Reference



Note

The terms "Unidirectional Path Switched Ring" and "UPSR" may appear in Cisco literature. These terms do not refer to using Cisco ONS 15xxx products in a unidirectional path switched ring configuration. Rather, these terms, as well as "Path Protected Mesh Network" and "PPMN," refer generally to Cisco's path protection feature, which may be used in any topological network configuration. Cisco does not recommend using its path protection feature in any particular topological network configuration.

This appendix provides a command reference for those Cisco IOS commands or those aspects of Cisco IOS commands that are unique to ML-Series cards. For information about the standard Cisco IOS Release 12.4 commands, refer to the Cisco IOS documentation set available at <http://www.cisco.com/univercd/cc/td/doc/product/software/ios122/>.

■ [no] bridge *bridge-group-number* protocol {*drpri-rstp* | *ieee* | *rstp*}

[no] bridge *bridge-group-number* protocol {*drpri-rstp* | *ieee* | *rstp*}

To define the protocol employed by a bridge group, use the **bridge protocol** global configuration command. If no protocol will be employed by the bridge group, this command is not needed. To remove a protocol from the bridge group, use the no form of this command with the appropriate keywords and arguments.

Syntax Description	Parameter	Description
	drpri-rstp	The protocol that enables the Dual Resilient Packet Ring Interconnect (DRPRI) feature of the ML-Series cards. Note DRPRI is not supported in Release 7.2.
	ieee	IEEE 802.1D Spanning Tree Protocol.
	rstp	IEEE 802.1W Rapid Spanning Tree Protocol.
	<i>bridge-group-number</i>	The identifying number of the bridge group being assigned a protocol.

Defaults N/A

Command Modes Global configuration

Usage Guidelines The Rapid Spanning Tree Protocol (RSTP) or Spanning Tree Protocol (STP) can be implemented.

Examples The following example assigns the protocol to the bridge group with the bridge group number of 100.

```
Router(config)# bridge 100 protocol rstp
```

Related Commands bridge-group

[no] clock auto

Use the **clock auto** command to determine whether the system clock parameters are configured automatically from the TCC2/TCC2P card. When enabled, both daylight savings time and time zone are automatically configured, and the system clock is periodically synchronized to the TCC2/TCC2P card. Use the no form of the command to disable this feature.

Syntax Description This command has no arguments or keywords.

Defaults The default setting is clock auto.

Command Modes Global configuration

Usage Guidelines The no form of the command is required before any manual configuration of summertime, timezone, or clock. The no form of the command is required if Network Time Protocol (NTP) is configured in Cisco IOS. The ONS 15454 SONET/SDH is also configured through Cisco Transport Controller (CTC) to use a NTP or Simple Network Time Protocol (SNTP) server to set the date and time of the node.

Examples Router(config)# **no clock auto**

Related Commands clock timezone
clock set

interface spr 1

Use this command to create a shared packet ring (SPR) interface on an ML-Series card for a resilient packet ring (RPR) in Cisco proprietary RPR mode. If the interface has already been created, this command enters spr interface configuration mode. The only valid spr interface number is 1.

Defaults

N/A

Command Modes

Global configuration

Usage Guidelines

The command allows the user to create a virtual interface for the Cisco proprietary RPR/SPR. Commands such as **spr wrap** or **spr station-id** can then be applied to the proprietary RPR through SPR configuration command mode.

In this command, interface can be shortened to int.

Examples

The following example creates the shared packet ring interface:

```
Router(config)# interface spr 1
```

Related Commands

spr-intf-id
spr station-id
spr wrap

[no] ip radius nas-ip-address {*hostname* | *ip-address*}

The ML-Series card allows the user to configure a separate nas-ip-address for each ML-Series card. This allows the Remote Authentication Dial In User Services (RADIUS) server to distinguish among individual ML-Series card in the same ONS node. If there is only one ML-Series card in the ONS node, this command does not provide any advantage. The public IP address of the ONS node serves as the nas-ip-address in the RADIUS packet sent to the server.

Identifying the specific ML-Series card that sent the request to the server can be useful in debugging from the server. The nas-ip-address is primarily used for validation of the RADIUS authorization and accounting requests.

If this value is not configured, the nas-ip-address is filled in by the normal Cisco IOS mechanism using the value configured by the **ip radius-source** command. If no value is specified, then the best IP address that routes to the server is used. If no address routing to the server is available, the IP address of the server is used.

Syntax Description	Parameter	Description
	<i>hostname</i>	The host name of the ML card as defined by “hostname” command.
	<i>ip-address</i>	The IP address assigned to one of the ML interfaces, usually a front-end interface such as Fast Ethernet or Gigabit Ethernet.

Defaults N/A

Command Modes Global configuration

Usage Guidelines This command allows the user to specify the IP address or hostname of attribute 4 (nas-ip-address) in the radius packet.

Examples The following example creates an IP address for attribute 4 of the RADIUS packet:

```
Router# configure terminal
Router(config)# [no] ip radius nas-ip-address 10.92.92.92
```

Related Commands

- aaa new-model
- aaa authentication login

microcode fail system-reload

In the event of a microcode failure, use this command to configure the ML-Series card to save information to the flash memory and then reboot. The information is saved for use by the Cisco Technical Assistance Center (Cisco TAC). To contact TAC, see the [Obtaining Technical Assistance, page xxxiv](#).

Defaults N/A

Command Modes Global configuration

Usage Guidelines This command and feature is specific to ML-Series card.

Examples `router(config)# microcode fail system-reload`

Related Commands N/A

[no] pos pdi holdoff *time*

Use this command to specify the time, in milliseconds, to hold off sending the path defect indication (PDI) to the far end when a virtual concatenation (VCAT) member circuit is added to the virtual concatenation group (VCG). Use the no form of the command to use the default value.

Syntax Description	Parameter	Description
	<i>time</i>	Delay time in milliseconds, 100 to 1,000
Defaults	The default value is 100 milliseconds.	
Command Modes	Interface configuration mode (packet-over-SONET/SDH [POS] only)	
Usage Guidelines	This value is normally configured to match the setting on the peer terminal equipment (PTE). The time granularity for this command is 1 millisecond.	
Examples	<p>In this example, interface is shortened to int.</p> <pre>Gateway(config)# int pos0 Gateway(config-if)# pos pdi holdoff 500</pre>	
Related Commands	pos trigger defects	

[no] pos report *alarm*

Use this command to specify which alarms/signals are logged to the console. This command has no effect on whether alarms are reported to the TCC2/TCC2P and CTC. These conditions are soaked and cleared per Telcordia GR-253. Use the no form of the command to disable reporting of a specific alarm/signal.

Syntax Description	Parameter	Description
	<i>alarm</i>	The SONET/SDH alarm that is logged to the console. The alarms are as follows: all —All link down alarm failures ber_sd_b3 —PBIP BER in excess of signal degrade (SD) threshold failure ber_sf_b3 —PBIP BER in excess of signal fail (SF) threshold failure encap —Path signal label encapsulation mismatch failure pais —Path alarm indication signal failure plop —Path loss of pointer failure ppdi —Path payload defect indication failure pplm —Payload label mismatch path prdi —Path remote defect indication failure ptim —Path trace indicator mismatch failure puneq —Path label equivalent to zero failure

Defaults The default is to report all alarms.

Command Modes Interface configuration mode (POS only)

Usage Guidelines This value is normally configured to match the setting on the peer PTE.

Examples In this example, interface is shortened to int.

```
Gateway(config)# int pos0
Gateway(config-if)# pos report all
```

Related Commands pos trigger defects

[no] pos trigger defects *condition*

Use this command to specify which conditions cause the associated POS link state to change. Use the no form of the command to disable triggering on a specific condition.

Syntax Description	Parameter	Description
	<i>condition</i>	<p>The SONET/SDH condition that causes the link state change. The conditions are as follows:</p> <ul style="list-style-type: none"> all—All link down alarm failures ber_sd_b3—PBIP bit error rate (BER) in excess of SD threshold failure ber_sf_b3—PBIP BER in excess of SF threshold failure encap—Path Signal Label Encapsulation Mismatch failure pais—Path Alarm Indication Signal failure plop—Path Loss of Pointer failure ppdi—Path Payload Defect Indication failure pplm—Payload label mismatch path prdi—Path Remote Defect Indication failure ptim—Path Trace Indicator Mismatch failure puneq—Path Label Equivalent to Zero failure

Defaults The default is to report all conditions. For a list of all conditions, see the list in the Syntax Description.

Command Modes Interface configuration mode (POS only)

Usage Guidelines This value is normally configured to match the setting on the peer PTE.



Note

In previous Cisco IOS releases, the **pos trigger delay** command was used to modify the triggering interval. In Release 7.2, this command is not supported.

Examples In this example, interface is shortened to int.

```
Gateway(config)# int pos0
Gateway(config-if)# pos trigger defects all
```

Related Commands None

[no] pos scramble-spe

Use this command to enable scrambling.

Syntax Description This command has no arguments or keywords.

Defaults The default value depends on the encapsulation.

Encapsulation	Scrambling
LEX	pos scramble-spe
PPP/HDLC	no pos scramble-spe

Command Modes Interface configuration mode (POS only)

Usage Guidelines This value is normally configured to match the setting on the peer PTE. This command might change the pos flag c2 configuration.

Examples In this example, interface is shortened to int.

```
Gateway(config)# int pos0
Gateway(config-if)# pos scramble-spe
```

Related Commands None

rpr-ieee atd-timer *value*

Use this command to configure the attribute discovery (ATD) timer, which controls the frequency of ATD packet transmissions on the IEEE 802.17b based RPR interface.

Syntax Description	Parameter	Description
	<i>value</i>	Value expressed in seconds. Range is 1 through 10.
Defaults		Default is 1 second.
Command Modes		IEEE 802.17b based RPR interface configuration
Usage Guidelines		The ATD timer value is very rarely changed. This is usually done only if other equipment uses a different ATD value or has processor limitations and cannot handle frames at one per second.
Examples		In this example, interface is shortened to int. <pre>router(config)# int rpr-ieee 0 router(config-if)# rpr-ieee atd-timer 1</pre>
Related Commands		None

rpr-ieee fairness weight *value*

Use this command to configure the fairness weight of an IEEE 802.17b based RPR station.

Syntax Description	Parameter	Description
	<i>value</i>	Number, expressed as an exponent of two. Range is 0 through 7.

Defaults The default is 0.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines Weighted fairness is used to allow one card greater access (that is, transmission rate) to the ring than other cards have. This command sets the fairness weight of the particular IEEE 702.17b based RPR interface. By default when a ring is congested, fairness controls ring traffic to allow each station the same amount of added traffic (or transmission rate). A higher fairness weight value on one interface allows the station to add traffic at a higher rate during periods of congestion.

Examples In this example, interface is shortened to int.

```
router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee fairness weight 3
```

Related Commands rpr-ieee fairness active weights detect
rpr-ieee fairness mode

[no] rpr-ieee ri foreign

Use this command to control the secondary card laser states and the interface wait to restore (WTR) timer when changing from secondary mode to primary.

Foreign mode indicates that the secondary card's transmit laser(s) are turned off while in standby mode. In turn, the secondary card's partner card does not send traffic through the ring redundant interconnect (RI) interface. The time used to turn the lasers back up causes longer WTR during switchover to primary mode.

If foreign mode is turned off as in the default setting or by using the no form of this command, the secondary card's transmit laser(s) remain turned on while in standby mode, and the RI interface ucode is set to standby. In this case, the secondary card's partner card continues to send traffic through the ring RI interface, and the WTR time during switchover to primary mode is faster.

Syntax Description

This command has no arguments or keywords.

Defaults

The default form is no rpr-ieee ri foreign.

Command Modes

IEEE 802.17b based RPR interface configuration

Usage Guidelines

This command should be used if the ring is connected to a switch.

The no form of the command reduces a traffic outage if there is a switch from a secondary card to a primary. The secondary card stays in active mode during the WTR interval; the primary card is in active mode with the ucode set to standby during the WTR.

Examples

In this example, interface is shortened to int.

```
router(config)# int rpr-ieee 0
Router(config-if)# no rpr-ieee ri foreign
```

Related Commands

None

rpr-ieee keepalive-timer *interval* [east | west]

Use this command to configure the keepalive timer configuration on a specific IEEE 802.17b based RPR span (east or west).

Syntax Description	Parameter	Description
	east	Pertains to configuration for eastbound span traffic.
	west	Pertains to configuration for westbound span traffic.
	<i>interval</i>	Timer interval expressed in milliseconds. Protection switch keepalive range from 0 to 200 milliseconds.

Defaults The default is 1 second.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines If a station does not receive fairness frames from its neighboring stations in the ring, the keepalive timer value determines how much time will elapse before a protection event is triggered. The keepalive timer works in tandem with the SONET holdoff timer. You would lengthen both of these timer intervals to avoid double hits when IEEE 802.17b based RPR is running over a SONET-protected network.

Examples In this example, interface is shortened to int.

```
router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee keepalive-timer 100 east
```

Related Commands rpr-ieee protection sonet holdoff-timer

[no] rpr-ieee protection pref jumbo

Use this command to set the IEEE 802.17b based RPR station MTU preference to jumbo Ethernet frames. If all stations on the ring select jumbo preference, the ring MTU is 9,000 bytes; otherwise, it is 1,500 bytes. Use the no form of this command to select normal MTU preference.

Syntax Description This command has no arguments or keywords.

Defaults The default is jumbo preference: not set (that is, the ring does not support jumbo frames).

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines Jumbo frame support would be enabled to support frames larger than the standard Ethernet MTU of 1518 bytes across the IEEE 802.17b based RPR ring. In this command, protection can be shortened to prot.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee prot pref jumbo
```

Related Commands None

[no] rpr-ieee protection request forced-switch {east | west}

Use this command to trigger a forced-switch protection event on the specified IEEE 802.17b-based RPR span. Use the no form of this command to clear the switch.

Syntax Description	Parameter	Description
	east	Pertains to configuration for eastbound span traffic.
	west	Pertains to configuration for westbound span traffic.

Defaults N/A

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines If the IEEE 802.17b based RPR forced switch is initiated with this command at the command-line interface (CLI), traffic steers away from this span. To clear the force, use the no form of the command.



Note

The command is not cleared if you change the port service state in CTC from OOS,DSBLD (Locked,disabled) to IS/IS,AINS, or OOS,MT (Unlocked,enabled,automaticInService or outofservice Maintenance).

IEEE 802.17b based RPR switching options are similar to the path protection and bidirectional line switched ring (BLSR) protection switching options, but RPR-IEEE switching functions are only available at the CLI and not in CTC.

In this command, protection can be shortened to prot and request can be shortened to req.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee
Router(config-if)# rpr-ieee prot req forced-switch east
```

Related Commands rpr-ieee protection request manual-switch

[no] rpr-ieee protection request manual-switch {east | west}

Use this command to trigger a manual-switch protection event on the specified IEEE 802.17b based RPR span. Use the no form of this command to deactivate the switch.

Syntax Description	Parameter	Description
	east	Pertains to configuration for eastbound span traffic.
	west	Pertains to configuration for westbound span traffic.

Defaults N/A

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines IEEE 802.17b based RPR switching options are similar to the path protection and BLSR protection switching options, but RPR-IEEE switching is only available at the CLI and not in CTC.

In this command, protection can be shortened to prot and request can be shortened to req.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee prot req manual-switch east
```

Related Commands rpr-ieee protection request forced-switch

rpr-ieee protection sonet holdoff-timer *interval* {east | west}

Use this command to configure the SONET hold-off timer for a protection event on the specified IEEE 802.17b based RPR span. Use the no form of this command to turn off the SONET holdoff timer.



Note

This command replaces the **pos vcat defect {delayed | immediate}** command.

Syntax Description

Parameter	Description
east	Pertains to configuration for eastbound span traffic.
west	Pertains to configuration for westbound span traffic.
<i>interval</i>	Timer interval expressed in milliseconds. Value is a multiple of 10 milliseconds in the range of 0 to 200 milliseconds (for example, interval 2 sets the holdoff timer to 20 milliseconds).

Defaults

The default value is 0 milliseconds.

Command Modes

IEEE 802.17b based RPR interface configuration

Usage Guidelines

This command is used to allow the slower SONET protection mechanisms to take effect ahead of IEEE 802.17b based RPR protection. The SONET holdoff timer works in tandem with the keepalive timer. You could lengthen both of these interval values to avoid double hits when RPR-IEEE is running over a SONET-protected network.

In this command, protection can be shortened to prot.

Examples

In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee prot sonet holdoff-timer 2
```

Related Commands

rpr-ieee keepalive-timer

rpr-ieee protection timer fast *rate* {east | west}

Use this command to configure the fast protection timer value for the specified IEEE 802.17b based RPR span.

Syntax Description	Parameter	Description
	east	Pertains to configuration for eastbound span traffic.
	west	Pertains to configuration for westbound span traffic.
	<i>rate</i>	The rate, expressed in milliseconds, at which the fast protection timer sends a protection message. This occurs after a protection event on a particular (east or west) span. Range is 1 to 20 milliseconds.

Defaults N/A

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines This rate determines how quickly the fast protection timer sends a protection message after a protection event occurs.

In this command, protection can be shortened to prot.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee prot timer fast 5 east
```

Related Commands rpr-ieee protection timer slow

rpr-ieee protection timer slow *rate* {east | west}

Use this command to configure the slow protection timer value on the specified IEEE 802.17b based RPR span.

Syntax Description	Parameter	Description
	east	Pertains to configuration for eastbound span traffic.
	west	Pertains to configuration for westbound span traffic.
	<i>rate</i>	The rate, expressed in milliseconds, at which the slow protection timer sends a protection message. This occurs after a protection event on a particular (east or west) span. The rate is stated in 100-millisecond increments, with a value of 1 to 10. For example, a rate of 2 would be equivalent to 200 milliseconds.

Defaults N/A

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines This value determines the sending rate of protection messages between protection events. In this command, protection can be shortened to prot.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee prot timer slow 2 east
```

Related Commands rpr-ieee protection timer fast

rpr-ieee protection wtr-timer {interval | never}

Use this command to configure the amount of time that an IEEE 802.17b based RPR span stays in wait-to-restore (WTR) state before normal service is restored on a span. The never argument configures an RPR-IEEE span WTR timer to disallow the WTR function.

Syntax Description	Parameter	Description
	<i>interval</i>	The value, expressed in seconds, for the WTR timer to delay in restoring protection to the IEEE 802.17b based RPR span. Range is 0 to 1440 seconds.
	<i>never</i>	Never restore protection. Nonrevertive mode.

Defaults The default value is enabled, and the default interval is 10 seconds.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines This command can be used to moderate an IEEE 802.17 RPR span that repeatedly changes into and out of a protected state. It is provisioned similarly to the WTR timer used in SONET protection schemes. Use the no argument to configure a span not to go through a WTR period before restoring service during a protection event.

In this command, protection can be shortened to prot.b based

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee prot wtr-timer 50
```

Related Commands None

rpr-ieee flag c2 *value*

Use this command to specify the SONET C2 byte path overhead values for both IEEE 802.17b based RPR spans.

Syntax Description	Parameter	Description
	<i>value</i>	The bytes that the path signal uses to flag the IEEE 802.17b based RPR interface for faults. The numeric value range is 0 to 255, and the default is 0 (0x1b) for generic framing procedure (GFP) encapsulation.

Defaults The default is 0x1B, which indicates GFP encapsulation.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines This value would only be changed if you do not want to specify GFP encapsulation for the span. In practical terms, this term would almost never be changed.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee flag c2 0
```

Related Commands None

rpr-ieee pdi holdoff time *interval*

Use this command to configure the interval that occurs before a path defect indication (PDI) is raised on an IEEE 802.17b based RPR span.

Syntax Description	Parameter	Description
	<i>interval</i>	The period, expressed in milliseconds. The range is 100 to 1,000 milliseconds.

Defaults The default is 100 milliseconds.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines This command can be used to prevent holdoff timer switching if a PDI is raised on an IEEE 802.17b based RPR span. The PDI is an infrequent occurrence in this kind of span configuration.

Examples In this example, interface is shortened to int.

```
Router(config)# int prp-ieee 0
Router(config-if)# rpr-ieee pdi holdoff time 100
```

Related Commands None

[no] rpr-ieee report *alarm*

Use this command to specify which IEEE 802.17b based RPR alarms or signals are logged to the console. Use the no form of the command to disable a particular type of notification.

Syntax Description	Parameter	Description
	<i>alarm</i>	<p>The SONET/SDH object that is logged to the console. The alarms are as follows:</p> <ul style="list-style-type: none"> all—All link down alarm and signal failures encap—Path signal label encapsulation mismatch failure pais—Path alarm indication signal failure plop—Path loss of pointer failure ppdi—Path payload defect indication failure pplm—Payload label mismatch path prdi—Path remote defect indication failure ptim—Path trace indicator mismatch failure puneq—Path label equivalent to zero failure sd-ber-b3—PBIP BER in excess of SD threshold failure sf-ber-b3—PBIP BER in excess of SF threshold failure

Defaults N/A

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines This command does not determine whether alarms are reported to the TCC2P or whether they are shown in CTC. Conditions that are reported to the CLI console as a result of this command are soaked and cleared per Telcordia GR-253-CORE. Use the no form of the command to disable reporting of a specific alarm/signal.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee report all
```

Related Commands None

[no] rpr-ieee ri {primary | secondary} peer *peer-MAC-address*

Use this command to set the mode for the IEEE 802.17b based RPR interface and the peer address, or disables the feature. Use the no form to disable the feature.

Syntax Description	Parameter	Description
	primary	Single traffic queue mode.
	secondary	Dual traffic queue mode.
	<i>peer-MAC-address</i>	The MAC of the alternate station. For a primary station, this command enters the MAC address of the secondary station. For a secondary station, this command enters the primary station MAC address.

Command Default The default is disabled.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines The peer MAC address is in hexadecimal format. If you change the MAC address, you must repeat this command with the new address.

In this command, interface can be shortened to int. It is not necessary to use the RI term if you are specifically indicating a primary or secondary peer, as in the following example.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee ri mode primary peer 00.24.A4.0E.9A.68
```

Related Commands rpr-ieee ri {primary | secondary} delay interval

[no] rpr-ieee ri {primary | secondary} delay *interval*

Use this command to change the soak time for a primary card in active mode. Use the no form of this command to set the timer to default.

Syntax Description	Parameter	Description
	primary	Single traffic queue mode.
	secondary	Dual traffic queue mode.
	<i>interval</i>	Interval that the active mode timer waits before switching to the secondary card. Range is 1,000 to 20,000 milliseconds.

Command Default The default is 3,000 milliseconds.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines None.

Examples In this example, interface is shortened to int.

```
router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee ri primary delay 1000
```

Related Commands rpr-ieee ri mode {primary | secondary}

[no] rpr-ieee shutdown {east | west}

This command is similar to a **rpr-ieee protection request forced-switch {east | west}** command on the span. This command is essentially no different in function; it is an easier way to do the same thing.

Syntax Description	Parameter	Description
	east	Specifies a shutdown on the east span of the interface.
	west	Specifies a shutdown on the west span of the interface.

Defaults Default is no shutdown.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines Functionally, there is no difference between this command and the protection request commands. In this command, shutdown can be shortened to shut.



Note

This command cannot be cleared by transitioning the span state from OOS,DSBLD (Locked,disabled) to IS/IS,AINS/OOS,MT (Unlocked,enabled,automaticInService or Locked,maintenance).

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee shut east
```

Related Commands None

`rpr-ieee tx-traffic rate-limit high rate [east | west]`

Use this command to limit the rate at which Class A1 traffic is transmitted only on a specific (east or west) span.

Syntax Description	Parameter	Description
	<code>east</code>	Pertains to configuration for eastbound span traffic.
	<code>west</code>	Pertains to configuration for westbound span traffic.
	<code>rate</code>	Value, expressed in Mbps, of the maximum rate a station can use to transmit Class A1 traffic onto a particular (east or west) span. (Class A1 traffic is the Class A traffic in excess of A0.) The rate range is 0 to 1161 Mbps.

Defaults The default is 5 Mbps.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines Class A1 traffic is used for latency-sensitive traffic, such as voice traffic, that should run at a low rate. This command allows you to control the traffic on a specific span. It applies to only one span. Specifying the span might not be necessary in all cases.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee tx-traffic rate-limit high 10 east
```

Related Commands

- `rpr-ieee tx-traffic strict`
- `rpr-ieee tx-traffic rate-limit medium [east | west]`
- `rpr-ieee tx-traffic rate-limit low [east | west]`

rpr-ieee tx-traffic rate-limit medium *rate* [east | west]

Use this command to limit the rate that Class B-CIR traffic is transmitted on a specific (east or west) span.

Syntax Description	Parameter	Description
	east	Pertains to configuration for eastbound span traffic.
	west	Pertains to configuration for westbound span traffic.
	rate	Value, expressed in Mbps, of the maximum rate a station can use to transmit Class B-CIR traffic onto a particular (east or west) span. The rate range is 0 to 1161 Mbps.

Defaults The default is 5 Mbps.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines This command is used for adding Class B traffic to a specific span. Traffic added at or below the configured rate (for example, at or below 5 Mbps) is Class B-CIR traffic and is not fairness-eligible. Traffic added above the configured rate (for example, above 5 Mbps) is set as class B-EIR traffic and is fairness-eligible. This command is specific to one span and would only be used if necessary to make this distinction.

Examples In this example, interface is shortened to int.

```
router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee tx-traffic rate-limit medium 2 east
```

Related Commands

- rpr-ieee tx-traffic rate-limit low [rate] {east | west}
- rpr-ieee tx-traffic rate-limit high [rate] {east | west}
- rpr-ieee tx-traffic rate-limit reserved

`rpr-ieee tx-traffic rate-limit reserved rate [east | west]`

Use this command to limit the transmission rate of Class A0 reserved traffic on a specific (east or west) span.

Syntax Description	Parameter	Description
	<code>east</code>	Pertains to configuration for eastbound span traffic.
	<code>west</code>	Pertains to configuration for westbound span traffic.
	<code>rate</code>	Value, expressed in Mbps, of the total bandwidth a station can use to transmit Class A0 traffic onto a particular (east or west) span. Range is 0 to 1161 Mbps.

Defaults The default is 0 Mbps.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines A0 bandwidth is dedicated and cannot be reused for any other traffic, and thus should be assigned cautiously. This command is specific to one span and would only be used if necessary to make a distinction.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee tx-traffic rate-limit reserved 5 east
```

Related Commands

```
rpr-ieee tx-traffic rate-limit low [rate] {east | west}
rpr-ieee tx-traffic rate-limit medium [rate] {east | west}
rpr-ieee tx-traffic rate-limit high [rate] {east | west}
rpr-ieee tx-traffic rate-limit reserved [rate]
```

[no] rpr-ieee tx-traffic strict

Use this command to configure either all or none of the traffic added by the node to have the strict order (SO) bit set on or off in the IEEE 802.17b-based RPR header.

Syntax Description This command has no arguments or keywords.

Defaults The default is off.

Command Modes IEEE 802.17b based RPR interface configuration

Usage Guidelines By default, the SO bit is turned off. You can turn it on in the IEEE 802.17b based RPR interface with this command if you need to accommodate an application with high sensitivity to out-of-order packets, originating at this node. This command is seldom utilized.

Examples In this example, interface is shortened to int.

```
Router(config)# int rpr-ieee 0
Router(config-if)# rpr-ieee tx-traffic strict
```

Related Commands None

show controller pos *interface-number* [detail]

Use this command to display the status of the POS controller. Use the detail argument to obtain additional SONET and POS information for the interface.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the POS interface (0–1)

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command can be used to help diagnose and isolate POS or SONET problems.

Examples The following example is an example of POS continuous concatenation circuit (CCAT) show controller output.

```
Router(config)# show controller pos 0
Router# show controller pos 0
Interface POS0
Hardware is Packet/Ethernet over Sonet
Concatenation: CCAT
Circuit state: IS
PATH
    PAIS      = 0          PLOP      = 0          PRDI      = 0          PTIM = 0
    PPLM      = 0          PUNEQ    = 0          PPDI      = 0          PTIU = 0
    BER_SF_B3 = 0          BER_SD_B3 = 0          BIP(B3)  = 20         REI  = 2
    NEWPTR    = 0          PSE      = 0          NSE      = 0

Active Alarms : None
Demoted Alarms: None
Active Defects: None
Alarms reportable to CLI: PAIS PLOP PUNEQ PTIM PPLM PRDI PPDI BER_SF_B3 BER_SD_B3
VCAT_OOU_TPT LOM SQM
Link state change defects: PAIS PLOP PUNEQ PTIM PPLM PRDI PPDI BER_SF_B3
Link state change time   : 200 (msec)

DOS FPGA channel number : 0
Starting STS (0 based)  : 0
VT ID (if any) (0 based): 255
Circuit size            : VC4
RDI Mode                : 1 bit
C2 (tx / rx)           : 0x01 / 0x01
Framing                 : SDH

Path Trace
Mode                    : off
Transmit String         :
Expected String         :
Received String         :
Buffer                  : Stable
```



```

Remote hostname :
Remote interface:
Remote IP addr  :

B3 BER thresholds:
SFBER = 1e-4,   SDBER = 1e-7

5 total input packets, 73842 post-HDLC bytes
0 input short packets, 73842 pre-HDLC bytes
0 input long packets , 0 input runt packets
67 input CRCError packets , 0 input drop packets
0 input abort packets
0 input packets dropped by ucode

0 total output packets, 0 output pre-HDLC bytes
0 output post-HDLC bytes

Carrier delay is 200 msec

```

The following is an example of POS virtual concatenation (VCAT) show controller output.

```

Router# show controller pos 1
Interface POS1
Hardware is Packet/Ethernet over Sonet
Concatenation: VCAT
VCG State: VCG_NORMAL
LCAS Type:NO LCAS
Defect Processing Mode: IMMEDIATE
PDI Holdoff Time: 100 (msec)
Active Alarms : None
Demoted Alarms: None

***** Member 1 *****
ESM State: IS
VCG Member State: VCG_MEMBER_NORMAL
  PAIS      = 0          PLOP      = 0          PRDI      = 0          PTIM      = 0
  PPLM      = 0          PUNEQ     = 0          PPDI      = 0          PTIU      = 0
  BER_SF_B3 = 0          BER_SD_B3 = 0          BIP(B3)   = 16         REI       = 17
  NEWPTR    = 0          PSE       = 0          NSE       = 0

Active Alarms : None
Demoted Alarms: None
Active Defects: None
Alarms reportable to CLI: PAIS PLOP PUNEQ PTIM PPLM PRDI PPDI BER_SF_B3 BER_SD_B3
VCAT_OOU_TPT LOM SQM
Link state change defects: PAIS PLOP PUNEQ PTIM PPLM PRDI PPDI BER_SF_B3
Link state change time   : 200 (msec)

DOS FPGA channel number : 2
Starting STS (0 based)  : 3
VT ID (if any) (0 based): 255
Circuit size           : VC4
RDI Mode                : 1 bit
C2 (tx / rx)           : 0x01 / 0x01
Framing                 : SDH

Path Trace
Mode                    : off
Transmit String         :
Expected String         :
Received String         :
Buffer                  : Stable
Remote hostname         :

```

show controller pos interface-number [detail]

```

Remote interface:
Remote IP addr  :

B3 BER thresholds:
SFBER = 1e-4,   SDBER = 1e-7

***** Member 2 *****
ESM State: IS
VCG Member State: VCG_MEMBER_NORMAL
  PAIS      = 0          PLOP      = 0          PRDI      = 0          PTIM      = 0
  PPLM      = 0          PUNEQ     = 0          PPDI      = 0          PTIU      = 0
  BER_SF_B3 = 0          BER_SD_B3 = 0          BIP(B3)   = 15         REI       = 35
  NEWPTR    = 0          PSE       = 0          NSE       = 0

Active Alarms : None
Demoted Alarms: None
Active Defects: None
Alarms reportable to CLI: PAIS PLOP PUNEQ PTIM PPLM PRDI PPDI BER_SF_B3 BER_SD_B3
VCAT_OOU_TPT LOM SQM
Link state change defects: PAIS PLOP PUNEQ PTIM PPLM PRDI PPDI BER_SF_B3
Link state change time   : 200 (msec)

DOS FPGA channel number : 3
Starting STS (0 based)  : 24
VT ID (if any) (0 based): 255
Circuit size           : VC4
RDI Mode                : 1 bit
C2 (tx / rx)           : 0x01 / 0x01
Framing                 : SDH

Path Trace
Mode                    : off
Transmit String         :
Expected String         :
Received String         :
Buffer                  : Stable
Remote hostname         :
Remote interface        :
Remote IP addr         :

B3 BER thresholds:
SFBER = 1e-4,   SDBER = 1e-7

13 total input packets,  5031 post-HDLC bytes
0 input short packets,  5031 pre-HDLC bytes
0 input long packets , 0 input runt packets
0 input CRCerror packets , 0 input drop packets
0 input abort packets
0 input packets dropped by ucode

13 total output packets, 5031 output pre-HDLC bytes
5031 output post-HDLC bytes

Carrier delay is 200 msec

```

Related Commands

- show interface pos
- clear counters

show controller rpr-ieee *interface-number* [detail]

Use this command to display the status of the IEEE 802.17b based RPR controller. Use the detail argument to obtain additional SONET and RPR-IEEE information for the interface.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the IEEE 802.17b based RPR interface (0–1)
	detail	Greater detail per interface.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command can be used to help diagnose and isolate IEEE 802.17b based RPR or SONET problems.

Examples

```
router# show controller rpr-ieee 0 detail
Interface RPR-IEEE0
Hardware is RPR-IEEE channelized SONET
RPR Interface Defects:
  PROT ACTIVE = 0          MAX STATION = 0          MIS-CONF = 0          PASSTHRU = 1
  EXCEED A0 RESERVED RATE: RINGLET 0 = 0          RINGLET 1 = 0
Active Alarms : None
Demoted Alarms: None
East Span (Ringlet0 TX Ringlet1 RX)
Framing Mode: GFP
Concatenation: VCAT
East Span Defects:
  FS      = 0          SF      = 0          SD      = 0          MS      = 0
  WTR     = 0          MATCH   = 0          KEEPALIVE = 0
  LFD     = 0          CSF     = 0          UPI     = 0
Active Alarms : None
Demoted Alarms: None
Alarms reportable to CLI: PAIS PLOP PUNEQ PTIM PPLM ENCAP PRDI PPDI BER_SF_B3 BER_SD_B3
VCAT_OOU_TPT LOM SQM

***** VCG *****
VCG State: VCG_NORMAL
LCAS Type: SW-LCAS
Defect Processing Mode: IMMEDIATE
PDI Holdoff Time: 100 (msec)
Active Alarms : None
Demoted Alarms: None
  DEGRADED = 1          DOWN    = 1          LOA     = 1

***** Member 0 *****
ESM State: IS
VCG Member State: VCG_MEMBER_NORMAL
  PAIS     = 0          PLOP     = 0          PRDI     = 0          PTIM     = 0
  PPLM     = 0          PUNEQ    = 1          PPDI     = 0          PTIU     = 0
  BER_SF_B3 = 0          BER_SD_B3 = 0          BIP(B3) = 30          REI     = 0
```

show controller rpr-ieee interface-number [detail]

```

NEWPTR      = 3          PSE      = 0          NSE      = 0          ENCAP = 0
OOU-TPT     = 1          LOM      = 1          SQM      = 1          OOG     = 0
Active Alarms : None
Demoted Alarms: None
Active Defects: None
DOS FPGA channel number : 0
Starting STS (0 based) : 0
VT ID (if any) (0 based) : 255
Circuit size      : STS1
RDI Mode          : 1 bit
C2 (tx / rx)     : 0x1B / 0x1B
Framing          : SONET
Path Trace
Mode              : off
Transmit String :
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
Expected String :
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
Received String :
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
Buffer          : Stable
Remote hostname :
Remote interface:
Remote IP addr  :
B3 BER thresholds:
SFBER:1e-4, SDBER:1e-7, berMap:0x00, SFBER:0, SDBER:0
BER 1e-3:
  BIP Sum:0, setTh:2455, clrTh:1003, BurstMap:0x0003, BurstTh:1188
  Counts:0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-4:
  BIP Sum:0, setTh:870, clrTh:201, BurstMap:0x0003, BurstTh:405
  Counts:0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-5:
  BIP Sum:0, setTh:358, clrTh:81, BurstMap:0x000F, BurstTh:71
  Counts:0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-6:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x07FF, BurstTh:22
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-7:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-8:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-9:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-10:

```

```

BIP Sum:0, setTh:0, clrTh:0, BurstMap:0x0000, BurstTh:0
Counts:
  Over threshold:TRUE, Bursty:FALSE, Clear higher:FALSE, Set level:TRUE

***** Member 1 *****
ESM State: IS
VCG Member State: VCG_MEMBER_NORMAL
  PAIS      = 0          PLOP      = 0          PRDI      = 0          PTIM = 0
  PPLM      = 0          PUNEQ     = 1          PPDI      = 0          PTIU = 0
  BER_SF_B3 = 0          BER_SD_B3 = 0          BIP(B3)   = 22         REI  = 0
  NEWPTR    = 3          PSE       = 0          NSE       = 0          ENCAP = 0
  OOU-TPT   = 1          LOM       = 1          SQM       = 1          OOG  = 0
Active Alarms : None
Demoted Alarms: None
Active Defects: None
DOS FPGA channel number : 1
Starting STS (0 based)  : 1
VT ID (if any) (0 based) : 255
Circuit size           : STS1
RDI Mode                : 1 bit
C2 (tx / rx)           : 0x1B / 0x1B
Framing                 : SONET
Path Trace
  Mode                  : off
  Transmit String :
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
  Expected String :
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
  Received String :
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
  Buffer              : Stable
  Remote hostname :
  Remote interface:
  Remote IP addr  :
B3 BER thresholds:
  SFBER:1e-4, SDBER:1e-7, berMap:0x00, SFBER:0, SDBER:0
  BER 1e-3:
    BIP Sum:0, setTh:2455, clrTh:1003, BurstMap:0x0003, BurstTh:1188
    Counts:0, 0,
    Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
  BER 1e-4:
    BIP Sum:0, setTh:870, clrTh:201, BurstMap:0x0003, BurstTh:405
    Counts:0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
  BER 1e-5:
    BIP Sum:0, setTh:358, clrTh:81, BurstMap:0x000F, BurstTh:71
    Counts:0, 0, 0, 0,
    Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
  BER 1e-6:
    BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x07FF, BurstTh:22
    Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
  BER 1e-7:
    BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
    Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,

```

show controller rpr-ieee interface-number [detail]

```

    Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-8:
    BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
    Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-9:
    BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
    Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
    Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-10:
    BIP Sum:0, setTh:0, clrTh:0, BurstMap:0x0000, BurstTh:0
    Counts:
    Over threshold:TRUE, Bursty:FALSE, Clear higher:FALSE, Set level:TRUE
Input CMF Packets 0
Single bit errors   cHec: 0  tHec: 0  eHec: 0
Multiple bit errors cHec: 0  tHec: 0  eHec: 0
Out of sync counts: 0
1398002919 input packets dropped by ucode
West Span (Ringlet0 RX Ringlet1 TX)
Framing Mode: GFP
Concatenation: VCAT
West Span Defects:
    FS      = 0          SF      = 0          SD      = 0          MS      = 0
    WTR     = 0          MATCH   = 0          KEEPALIVE = 0
    LFD     = 0          CSF     = 0          UPI     = 0
Active Alarms : None
Demoted Alarms: None
Alarms reportable to CLI: PAIS PLOP PUNEQ PTIM PPLM ENCAP PRDI PPDI BER_SF_B3 BER_SD_B3
VCAT_OOU_TPT LOM SQM

***** VCG *****
VCG State: VCG_NORMAL
LCAS Type: SW-LCAS
Defect Processing Mode: IMMEDIATE
PDI Holdoff Time: 100 (msec)
Active Alarms : None
Demoted Alarms: None
    DEGRADED = 0          DOWN      = 1          LOA      = 0
***** Member 0 *****
ESM State: IS
VCG Member State: VCG_MEMBER_NORMAL
    PAIS     = 0          PLOP     = 0          PRDI     = 0          PTIM     = 0
    PPLM     = 0          PUNEQ    = 1          PPDI     = 0          PTIU     = 0
    BER_SF_B3 = 0          BER_SD_B3 = 0          BIP(B3) = 24          REI     = 0
    NEWPTR   = 3          PSE      = 0          NSE      = 0          ENCAP   = 0
    OOU-TPT  = 1          LOM      = 1          SQM      = 1          OOG     = 0
Active Alarms : None
Demoted Alarms: None
Active Defects: None
DOS FPGA channel number : 2
Starting STS (0 based)  : 24
VT ID (if any) (0 based): 255
Circuit size            : STS1
RDI Mode                 : 1 bit
C2 (tx / rx)            : 0x1B / 0x1B
Framing                  : SONET
Path Trace
Mode                     : off
Transmit String :
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
Expected String :

```

```

00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
Received String :
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
Buffer          : Stable
Remote hostname :
Remote interface:
Remote IP addr  :
B3 BER thresholds:
SFBER:1e-4, SDBER:1e-7, berMap:0x00, SFBER:0, SDBER:0
BER 1e-3:
  BIP Sum:0, setTh:2455, clrTh:1003, BurstMap:0x0003, BurstTh:1188
  Counts:0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-4:
  BIP Sum:0, setTh:870, clrTh:201, BurstMap:0x0003, BurstTh:405
  Counts:0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-5:
  BIP Sum:0, setTh:358, clrTh:81, BurstMap:0x000F, BurstTh:71
  Counts:0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-6:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x07FF, BurstTh:22
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-7:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-8:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-9:
  BIP Sum:0, setTh:399, clrTh:89, BurstMap:0x03FF, BurstTh:25
  Counts:0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
  Over threshold:FALSE, Bursty:TRUE, Clear higher:TRUE, Set level:FALSE
BER 1e-10:
  BIP Sum:0, setTh:0, clrTh:0, BurstMap:0x0000, BurstTh:0
  Counts:
  Over threshold:TRUE, Bursty:FALSE, Clear higher:FALSE, Set level:TRUE

***** Member 1 *****
ESM State: IS
VCG Member State: VCG_MEMBER_NORMAL
  PAIS      = 0          PLOP      = 0          PRDI      = 0          PTIM = 0
  PPLM      = 0          PUNEQ     = 1          PPDI      = 0          PTIU = 0
  BER_SF_B3 = 0          BER_SD_B3 = 0          BIP(B3)   = 24         REI  = 0
  NEWPTR     = 3          PSE       = 0          NSE       = 0          ENCAP = 0
  OOU-TPT    = 1          LOM       = 1          SQM       = 1          OOG  = 0
Active Alarms : None
Demoted Alarms: None
Active Defects: None
DOS FPGA channel number : 3
Starting STS (0 based)  : 25
VT ID (if any) (0 based) : 255
Circuit size           : STS1
RDI Mode                : 1 bit

```


Related Commands show interface rpr-ieee

show interface pos *interface-number*

Use this command to display the status of the POS.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the POS interface (0–1)

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command can be used to help diagnose and isolate POS or SONET/SDH problems. In this command, interface can be shortened to int.

Examples

```
Gateway# show interface pos 0
POS0 is up, line protocol is up
  Hardware is Packet/Ethernet over Sonet
  Description: foo bar
  MTU 4470 bytes, BW 155520 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation HDLC, crc 32, loopback not set
  Keepalive set (10 sec)
  Scramble enabled
  Last input 00:00:09, output never, output hang never
  Last clearing of "show interface" counters 05:17:30
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue :0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec

    2215 total input packets, 223743 post-HDLC bytes
    0 input short packets, 223951 pre-HDLC bytes
    0 input long packets , 0 input runt packets
    0 input CRCerror packets , 0 input drop packets
    0 input abort packets
    0 input packets dropped by ucode

    0 packets input, 0 bytes
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
      0 parity
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort

    2216 total output packets, 223807 output pre-HDLC bytes
    224003 output post-HDLC bytes

    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 applique, 8 interface resets
    0 output buffer failures, 0 output buffers swapped out
    0 carrier transitions
```

Related Commands

show controller pos
clear counters

show interface rpr-ieee *interface-number*

Use this command to display the status of chosen IEEE 802.17b based RPR interface.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the IEEE 802.17b based RPR interface (0–1)

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command can be used to help diagnose and isolate IEEE 802.17b based RPR interface or SONET/SDH problems.

In this command, interface can be shortened to int.

The rpr-ieee tx-traffic rate-limit high command shows the Class A1 rate range as 0 to 1161 Mbps



Note

If the Class A1 transmit rate is set to 5 Mbps, this command does not provide full interface information as it does for other typical values (3, 4, 6, 8, and 10 Mbps).

Examples

```
router# show interface rpr-ieee 0

RPR-IEEE0 is up, line protocol is up
  Hardware is RPR-IEEE Channelized SONET, address is 0005.9a3c.59c0 (bia 0005.9a3c.59c0)
  MTU 1500 bytes, BW 96768 Kbit, DLY 100 usec,
    reliability 255/255, txload 128/255, rxload 128/255
  Encapsulation: RPR-IEEE,
  West Span: loopback not set
  East Span: loopback not set
    MAC passthrough not set
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  West Span:5 minutes output rate 96361986 bits/sec, 76243 packets/sec
    5 minutes input rate 89824634 bits/sec, 71241 packets/sec
  East Span: 5 minutes output rate 71872254 bits/sec, 56867 packets/sec
    5 minutes input rate 95391157 bits/sec, 75475 packets/sec
  3402516571 packets input, 4038397818 bytes
  Received 0 broadcasts (0 IP multicast)
  0 runts, 0 giants, 0 throttles
  3 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast
  0 input packets with dribble condition detected
  1355393210 packets output, 4104587724 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
```

```
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier
0 output buffer failures, 0 output buffers swapped out
```

Related Commands

show int pos

show int spr

show ons alarm

Use this command to display all the active alarms on the ML-Series card running the Cisco IOS CLI session.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command can be used to help diagnose and isolate card problems.

Examples

```
router# show ons alarm
Equipment Alarms
Active: CONTBUS-IO-A CTNEQPT-PBWORK
```

```
Port Alarms
  POS0 Active: None
  POS1 Active: None
  FastEthernet0 Active: None
  FastEthernet1 Active: None
  FastEthernet2 Active: None
  FastEthernet3 Active: None
  FastEthernet4 Active: None
  FastEthernet5 Active: None
  FastEthernet6 Active: None
  FastEthernet7 Active: None
  FastEthernet8 Active: None
  FastEthernet9 Active: None
  FastEthernet10 Active: None
  FastEthernet11 Active: None
```

```
POS0
```

```
Active Alarms : None
Demoted Alarms: None
```

```
POS1 VCG State: VCG_NORMAL
VCAT Group
Active Alarms : None
Demoted Alarms: None
```

```
Member 0
Active Alarms : None
Demoted Alarms: None
```

```
Member 1
Active Alarms : None
Demoted Alarms: None
```

Related Commands

show controller pos
show ons alarm defect
show ons alarm failure

show ons alarm defect eqpt

Use this command to display the equipment-layer defects.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command displays the set of active defects for the equipment layer and the possible set of defects that can be set.

Examples

```
router# show ons alarm defect eqpt
Equipment Defects
Active: CONTBUS-IO-B
Reportable to TCC/CLI: CONTBUS-IO-A CONTBUS-IO-B CTNEQPT-PBWORK CTNEQPT-PBPROT EQPT
RUNCFG-SAVENEED ERROR-CONFIG
```

Related Commands show ons alarm failure

show ons alarm defect port

Use this command to display the port-layer defects.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command displays the set of active defects for the link layer and the possible set of defects that can be set. Note that the TPTFAIL defect can only occur on the POS ports and the CARLOSS defect can only occur on the Ethernet ports.

Examples

```
router# show ons alarm defect port
Port Defects
  POS0
  Active: TPTFAIL
  Reportable to TCC: CARLOSS TPTFAIL
  POS1
  Active: TPTFAIL
  Reportable to TCC: CARLOSS TPTFAIL
  GigabitEthernet0
  Active: None
  Reportable to TCC: CARLOSS TPTFAIL
  GigabitEthernet1
  Active: None
  Reportable to TCC: CARLOSS TPTFAIL
```

Related Commands show interface
show ons alarm failure

show ons alarm defect pos *interface-number*

Use this command to display the link-layer defects.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the interface (0–1)
Defaults	N/A	
Command Modes	Privileged executive	
Usage Guidelines	This command displays the set of active defects for the POS layer and the possible set of defects that can be set.	
Examples	<pre>router# show ons alarm defect pos 0 POS0 Active Defects: None Alarms reportable to TCC/CLI: PAIS PRDI PLOP PUNEQ PPLM PTIM PPDI BER_SF_B3 BER_SD_B3</pre>	
Related Commands	show controller pos show ons alarm failure	

show ons alarm defect rpr [interface-number]

Use this command to display the interface defects on the layer.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the interface (0-1)

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command displays the set of active defects for the IEEE 802.17b based RPR and the possible set of defects that can be set.

Examples

```
router# show ons alarm defect rpr

RPR-IEEE0
Active: None
Reportable to SC: RPR-PASSTHRU RPR-PROT_ACTIVE RPR-MAX_STATION RPR-MIS_CONF
RPR-RINGLETO_A0_EXCEED_BANDWIDTH RPR-RINGLET1_A0_EXCEED_BANDWIDTH RPR-RI_PEER_MISSING
RPR-RI_FAULT
```

Related Commands show ons alarm

show ons alarm failure eqpt

Use this command to display the equipment-layer failures.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command displays the active failures for the equipment layer. If an EQPT alarm is present, the board fail defect that was the source of the alarm is displayed.

Examples

```
router# show ons alarm failure eqpt
Equipment
Active Alarms: None
```

Related Commands show ons alarm defect

show ons alarm failure port

Use this command to display the port-layer failures.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command displays the set of active failures for the link layer.

Examples

```
router# show ons alarm failure port
Port Alarms
  POS0 Active: TPTFAIL
  POS1 Active: TPTFAIL
  GigabitEthernet0 Active: None
  GigabitEthernet1 Active: None
```

Related Commands

- show interface
- show ons alarm defect

show ons alarm failure pos *interface-number*

Use this command to display the link-layer failures.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the interface (0–1)
Defaults	N/A	
Command Modes	Privileged executive	
Usage Guidelines	This command displays the set of active failures for a specific interface at the POS layer. The display also specifies if an alarm has been demoted, as defined in Telcordia GR-253.	
Examples	<pre>router# show ons alarm failure pos 0 POS0 Active Alarms : None Demoted Alarms: None</pre>	
Related Commands	<pre>show controller pos show ons alarm defect</pre>	

show ons alarm failure rpr [interface-number]

Use this command to display failures on a specific IEEE 802.17b based RPR interface.

Syntax Description	Parameter	Description
	<i>interface-number</i>	Number of the interface (0-1)

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command displays the set of active failures for a specific IEEE 802.17b based RPR interface. The display also specifies if an alarm has been demoted, as defined in Telcordia GR-253-CORE.

Examples

```
router# show ons alarm failure rpr

RPR-IEEE0
Active: None
```

Related Commands show ons alarm

show rpr-ieee counters

Use this command to display the various packet/byte counters for each span of the IEEE 802.17b based RPR interface. For definitions of ML-Series card statistics, refer to the “Performance Monitoring” chapter in the *Cisco ONS 15454 SONET and DWDM Troubleshooting Guide* or the *Cisco ONS 15454 SDH Troubleshooting Guide*.

Syntax Description This command has no arguments or keywords.

Defaults Defaults can vary by each counter.

Command Modes Privileged executive

Usage Guidelines This command is primarily a troubleshooting tool. The same counter data is also available through Simple Network Management Protocol (SNMP) data, the Transaction Language 1 (TL1) interface, and CTC.

Examples

```
router# show rpr-ieee counters
Data Traffic Counters for Interface RPR-IEEEE0
WEST Span:
Transit
Total Low Priority          Packets          Bytes
1162649477                183697386417
Total Med EIR Priority      8936750          1412005236
Total Med CIR+EIR Priority  48436675         7653001286
Total High Priority         17567660         2775677008
Total Multicast            66039554         10435555023
Total Unicast              1162614609       183690629992

Host Receive
Unicast Low Priority        Packets          Bytes
16147390254                2550939336924
Unicast Med EIR Priority    0                0
Unicast Med CIR Priority    0                0
Unicast High Priority       0                0
Multicast Low Priority      1389170314       219486727447
Multicast Med EIR Priority  0                0
Multicast Med CIR Priority  0                0
Multicast High Priority     0                0
Broadcast                  0                N/A

Total Receive
Unicast Low Priority        Packets          Bytes
17319366142                2736075078618
Unicast Med EIR Priority    0                0
Unicast Med CIR Priority    0                0
Unicast High Priority       0                0
Multicast Low Priority      1389170314       219488627991
Multicast Med EIR Priority  0                0
Multicast Med CIR Priority  0                0
Multicast High Priority     0                0

Host Transmit
Packets          Bytes
```


Unicast Low Priority	18701060600	2954767575274
Unicast Med EIR Priority	0	0
Unicast Med CIR Priority	0	0
Unicast High Priority	0	0
Multicast Low Priority	233345	38183383
Multicast Med EIR Priority	456173838	72075466404
Multicast Med CIR Priority	48446005	7654468790
Multicast High Priority	192647108	30438243064
Broadcast	0	N/A
Total Transmit		
	Packets	Bytes
Unicast Low Priority	19863597488	3138448403894
Unicast Med EIR Priority	0	0
Unicast Med CIR Priority	0	0
Unicast High Priority	0	0
Multicast Low Priority	268795	45108717
Multicast Med EIR Priority	495672023	78316179634
Multicast Med CIR Priority	57382139	9066377962
Multicast High Priority	210212898	33213637884
Traffic Rate (5 Minutes)		
	packets/sec	bits/sec
Transit Low Priority	0	0
Transit Med EIR Priority	0	0
Transit Med CIR+EIR Priority	0	0
Transit High Priority	0	0
Transit Multicast	0	0
Transit Unicast	0	0
Host Receive	71269	90075869
Total Receive	71269	90076596
Host Transmit	76333	96478080
Total Transmit	76332	96478112
Control Frames:		
	Received	Transmitted
Control	26155194	8462107
OAM Echo	0	0
OAM Flush	0	0
OAM Org	0	0
OAM SAS Notify	0	0
Topology ATD	1946003	392352
Topology Checksum	4034923	4034891
Topology Protection	20174268	4034864
LRTT	0	0
FDD	0	0
Received Errors:		
0 input errors, 0 CRC, 0 ignored,		
0 framer runts, 0 framer giants, 0 framer aborts,		
0 mac runts, 0 mac giants, 0 mac ttl strips,		
0 non_we drop, 0 ltb_strict drop, 0 htb_strict drop		
0 scff errors, 0 bad addr frames, 0 self sourced frames		
EAST Span:		
	Packets	Bytes
Total Low Priority	2561406909	404771885533
Total Med EIR Priority	19279	3064252
Total Med CIR+EIR Priority	35591	5614688
Total High Priority	32164	5113038
Total Multicast	1389153110	219542479597
Total Unicast	1172313263	185238866568
Host Receive		
	Packets	Bytes
Unicast Low Priority	6599528894	1042960369924
Unicast Med EIR Priority	11972905593	1891155540262
Unicast Med CIR Priority	1826846617	288560828526

show rpr-ieee counters

Unicast High Priority	3693986118	583445203252
Multicast Low Priority	42456	9288351
Multicast Med EIR Priority	39498185	6240713230
Multicast Med CIR Priority	8936134	1411909172
Multicast High Priority	17565790	2775394820
Broadcast	0	N/A

Total Receive	Packets	Bytes
Unicast Low Priority	7761607024	1226426632416
Unicast Med EIR Priority	11972905600	1891010247740
Unicast Med CIR Priority	1826846617	288584487022
Unicast High Priority	3693986118	583547505106
Multicast Low Priority	42456	9288351
Multicast Med EIR Priority	39498185	6235011598
Multicast Med CIR Priority	8936134	1411909172
Multicast High Priority	17565790	2775394820

Host Transmit	Packets	Bytes
unicast Low Priority	6356990298	1004807678284
Unicast Med EIR Priority	7701766350	1216879083616
Unicast Med CIR Priority	1830175717	289167763286
Unicast High Priority	3695903572	583952764376
Multicast Low Priority	233345	38183383
Multicast Med EIR Priority	407714881	64418951198
Multicast Med CIR Priority	96890130	15308640540
Multicast High Priority	192646933	30438215414
Broadcast	0	N/A

Total Transmit	Packets	Bytes
Unicast Low Priority	7529228323	1190034710362
Unicast Med EIR Priority	7701766354	1216879084248
Unicast Med CIR Priority	1830175717	289167763286
Unicast High Priority	3695903572	583952764376
Multicast Low Priority	1389383752	219580264474
Multicast Med EIR Priority	407714881	64418951198
Multicast Med CIR Priority	96890130	15308640540
Multicast High Priority	192646933	30438215414

Traffic Rate (5 Minutes)	packets/sec	bits/sec
Transit Low Priority	6062	7654634
Transit Med EIR Priority	0	0
Transit Med CIR+EIR Priority	0	0
Transit High Priority	0	0
Transit Multicast	6062	7654634
Transit Unicast	0	0
Host Receive	75568	95494249
Total Receive	75568	95512522
Host Transmit	56933	71958410
Total Transmit	62992	79613030

Control Frames:	Received	Transmitted
Control	26155236	8462109
OAM Echo	0	0
OAM Flush	0	0
OAM Org	0	0
OAM SAS Notify	0	0
Topology ATD	1946019	392355
Topology Checksum	4034954	4034891
Topology Protection	20174268	4034864
LRTT	0	0
FDD	0	0

Received Errors:
3 input errors, 0 CRC, 0 ignored,

```
0 framer runts, 0 framer giants, 0 framer aborts,  
0 mac runts, 0 mac giants, 3 mac ttl strips,  
0 non_we drop, 0 ltb_strict drop, 0 htb_strict drop 0 scff errors, 0 bad addr frames, 0  
self sourced frames
```

Related Commands show int rpr-ieee interface-number

show rpr-ieee failure rpr-ieee *interface-number*

Use this command to display all inputs used to determine the failure state of each span on the IEEE 802.17b-based RPR interface.

Syntax Description

Parameter	Description
<i>interface-number</i>	IEEE 802.17b based RPR interface number. No space is included between rpr-ieee and the interface number (for example, rpr-ieee0).

Defaults

N/A

Command Modes

Privileged executive

Usage Guidelines

This command is primarily used for troubleshooting. Some of its information overlaps that obtained with **show rpr-ieee topology** and **show rpr-ieee protection** commands.

Examples

```
router# show rpr-ieee failure rpr-ieee0
Self Detected Failures Information for Interface RPR-IEEEE0
Span WEST:
Reported   Debounced   Current   Stable   Debounce
state      state         state     for(sec) delay(sec)
HW missing  IDLE          IDLE      IDLE     403628    0
Layer 1    IDLE          IDLE      IDLE     403628    0
MAC Keepalive IDLE          IDLE      IDLE     403628    0
Link quality IDLE          IDLE      IDLE     403628    0
Mate interface IDLE          IDLE      IDLE     403628    0
Span mismatch IDLE          IDLE      IDLE     403628    0
Result Self Detect = IDLE
Span EAST:
Reported   Debounced   Current   Stable   Debounce
state      state         state     for(sec) delay(sec)
HW missing  IDLE          IDLE      IDLE     403628    0
Layer 1    IDLE          IDLE      IDLE     403628    0
MAC Keepalive IDLE          IDLE      IDLE     403628    0
Link quality IDLE          IDLE      IDLE     403628    0
Mate interface IDLE          IDLE      IDLE     403628    0
Span mismatch IDLE          IDLE      IDLE     403628    0
Result Self Detect = IDLE
```

Related Commands

show int rpr-ieee

show rpr-ieee fairness detail

Use this command to display the state information of the fairness state machine for each span of the IEEE 802.17b based RPR interface.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines This command can be used for troubleshooting traffic issues related to fairness weighting or bandwidth usage. It provides deep detail for the fairness state of all IEEE 802.17b based RPR traffic on the interface.

Examples

```
router# show rpr-ieee fairness detail
IEEE 802.17 Fairness on RPR-IEEE0:
  Bandwidth: 96768 kilobits per second
  Station using aggressive rate adjustment.
Westbound Tx (Ringlet 1)
  Weighted Fairness:
    Local Weight: 0 (1)
  Single-Choke Fairness Status:
    Local Congestion:
      Congested? No
      Head? No
    Local Fair Rate:
      Approximate Bandwidth: 64892 Kbps
      25957 normalized bytes per aging interval
51914 bytes per ageCoef aging interval
  Downstream Congestion:
    Congested? No
    Tail? No
    Received Source Address: 0000.0000.0000
  Received Fair Rate:
    Approximate Bandwidth: FULL RATE
    65535 normalized bytes per aging interval

  Reserved Rate:
    0 Kbps
    0 bytes per aging interval
  Unreserved Rate:
    96768 Kbps
    4838 bytes per aging interval
  Allowed Rate:
    Approximate Bandwidth: 96000 Kbps
    4800 bytes per aging interval
  Allowed Rate Congested:
    Approximate Bandwidth: 96000 Kbps
    4800 bytes per aging interval
```

show rpr-ieee fairness detail

```

    TTL to Congestion: 255
    Total Hops Tx: 4
    Advertised Fair Rate:
    Approximate Bandwidth: FULL RATE
    65535 normalized bytes per aging interval
    8191 bytes per aging interval
    Eastbound Tx (Ringlet 0)
    Weighted Fairness:
    Local Weight: 0 (1)
    Single-Choke Fairness Status:
    Local Congestion:
    Congested? No
    Head? No
    Local Fair Rate:
    Approximate Bandwidth: 0 Kbps
    0 normalized bytes per aging interval
    0 bytes per ageCoef aging interval
    Downstream Congestion:
    Congested? No
    Tail? No
    Received Source Address: 0000.0000.0000
    Received Fair Rate:
    Approximate Bandwidth: FULL RATE
    65535 normalized bytes per aging interval

    Reserved Rate:
    0 Kbps
    0 bytes per aging interval
    Unreserved Rate:
    96768 Kbps
    4838 bytes per aging interval
    Allowed Rate:
    Approximate Bandwidth: 96000 Kbps
    4800 bytes per aging interval
    Allowed Rate Congested:
    Approximate Bandwidth: 96000 Kbps
    4800 bytes per aging interval
    TTL to Congestion: 255
    Total Hops Tx: 4
    Advertised Fair Rate:
    Approximate Bandwidth: FULL RATE
    65535 normalized bytes per aging interval
    8191 bytes per aging interval

```

Related Commands show rpr-ieee fairness history

show rpr-ieee fairness history

Use this command to retrieve performance monitoring information about local and downstream IEEE 802.17b based RPR congestion history over a period of up to 24 hours.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines Use this command to determine whether the local IEEE 802.17b based RPR station has been congested within the past 24 hr and, if so, what the time frame and degree of congestion is. Fairness history aids in managing traffic by allowing you to monitor or diagnose the ring.

Examples

```
router# show rpr-ieee fairness history
IEEE 802.17 Fairness History on RPR-IEEE0 for last 24 hours:
Congestion information gathered every 900 second(s)
Westbound Tx (Ringlet 1)
Local Congestion:
No.  Time:      Aging Intervals      Seconds      Percent
      Congested / Total      Congested / Total Congested
Instantaneous: 0 / 30
65  08:01:45: 0 / 2250000      0 / 900      0%
64  07:46:45:0 / 2250000      0 / 900      0%
63  07:31:45:0 / 2250000      0 / 900      0%
62  07:16:45:0 / 2250000      0 / 900      0%
61  07:01:45:0 / 2250000      0 / 900      0%
60  06:46:45:0 / 2250000      0 / 900      0%
59  06:31:45:0 / 2250010      0 / 900      0%
58  06:16:45:0 / 2250000      0 / 900      0%
57  06:01:45:0 / 2250000      0 / 900      0%
56  05:46:45:0 / 2250020      0 / 900      0%
55  05:31:45:0 / 2250000      0 / 900      0%
54  05:16:45:0 / 2250000      0 / 900      0%
53  05:01:45:0 / 2250000      0 / 900      0%
52  04:46:45:0 / 2250000      0 / 900      0%
51  04:31:45:0 / 2250000      0 / 900      0%
50  04:16:45:0 / 2250000      0 / 900      0%
49  04:01:45:0 / 2250000      0 / 900      0%
48  03:46:45:0 / 2250000      0 / 900      0%
47  03:31:45: 0 / 2250000      0 / 900      0%
46  03:16:45:0 / 2250000      0 / 900      0%
45  03:01:45:0 / 2250000      0 / 900      0%
44  02:46:45:0 / 2250000      0 / 900      0%
43  02:31:45: 0 / 2250000      0 / 900      0%
42  02:16:45:0 / 2250010      0 / 900      0%
41  02:01:45:0 / 2250000      0 / 900      0%
40  01:46:45:0 / 2250000      0 / 900      0%
39  01:31:45: 0 / 2250000      0 / 900      0%
38  01:16:45:0 / 2250000      0 / 900      0%
```

show rpr-ieee fairness history

```

37 01:01:45:0 / 2250000      0 / 900      0%
36 00:46:45:0 / 2250000      0 / 900      0%
35 00:31:45:0 / 2250000      0 / 900      0%
34 00:16:45:0 / 2250000      0 / 900      0%
33 00:01:45:0 / 2250000      0 / 900      0%
32 23:46:45:0 / 2250030      0 / 900      0%
31 23:31:45:0 / 2250000      0 / 900      0%
30 23:16:45:0 / 2250000      0 / 900      0%
29 23:01:45:0 / 2250090      0 / 900      0%
28 22:46:45:0 / 2250000      0 / 900      0%
27 22:31:45:0 / 2250000      0 / 900      0%
26 22:16:45:0 / 2250000      0 / 900      0%
25 22:01:45:0 / 2250000      0 / 900      0%
24 21:46:45:0 / 2250000      0 / 900      0%
23 21:31:45:0 / 2250000      0 / 900      0%
22 21:16:45:0 / 2250050      0 / 900      0%
21 21:01:45:0 / 2250000      0 / 900      0%
20 20:46:45:0 / 2250000      0 / 900      0%
19 20:31:45:0 / 2250000      0 / 900      0%
18 20:16:45:0 / 2250060      0 / 900      0%
17 20:01:45:0 / 2250000      0 / 900      0%
16 19:46:45:0 / 2250000      0 / 900      0%
15 19:31:45:0 / 2250000      0 / 900      0%
14 19:16:45:0 / 2250000      0 / 900      0%
13 19:01:45:0 / 2250000      0 / 900      0%
12 18:46:45:0 / 2250090      0 / 900      0%
11 18:31:45:0 / 2250000      0 / 900      0%
10 18:16:45:0 / 2250000      0 / 900      0%
9  18:01:45:0 / 2250000      0 / 900      0%
8  17:46:45:0 / 2250000      0 / 900      0%
7  17:31:45:0 / 2250000      0 / 900      0%
6  17:16:45:0 / 2250000      0 / 900      0%
5  17:01:45:0 / 2250000      0 / 900      0%
4  16:46:45:0 / 2250000      0 / 900      0%
3  16:31:45:0 / 2250000      0 / 900      0%
2  16:16:45:0 / 2250000      0 / 900      0%
1  16:01:45:0 / 2250000      0 / 900      0%
96 15:46:45:0 / 2250000      0 / 900      0%
95 15:31:45:0 / 2250000      0 / 900      0%
94 15:16:45:0 / 2250000      0 / 900      0%
93 15:01:45:0 / 2250000      0 / 900      0%
92 14:46:45:0 / 2250000      0 / 900      0%
91 14:31:45:0 / 2250000      0 / 900      0%
90 14:16:45:0 / 2250000      0 / 900      0%
89 14:01:45:0 / 2250000      0 / 900      0%
88 13:46:45:0 / 2250000      0 / 900      0%
87 13:31:45:0 / 2250000      0 / 900      0%
86 13:16:45:0 / 2250000      0 / 900      0%
85 13:01:45:0 / 2250000      0 / 900      0%
84 12:46:45:0 / 2250000      0 / 900      0%
83 12:31:45:0 / 2250100      0 / 900      0%
82 12:16:45:0 / 2250000      0 / 900      0%
81 12:01:45:0 / 2250000      0 / 900      0%
80 11:46:45:0 / 2250030      0 / 900      0%
79 11:31:45:0 / 2250000      0 / 900      0%
78 11:16:45:0 / 2250010      0 / 900      0%
77 11:01:45:0 / 2250000      0 / 900      0%
76 10:46:45:0 / 2250000      0 / 900      0%
75 10:31:45:0 / 2250000      0 / 900      0%
74 10:16:45:0 / 2250000      0 / 900      0%
73 10:01:45:0 / 2250000      0 / 900      0%
72 09:46:45:0 / 2250070      0 / 900      0%
71 09:31:45:0 / 2250000      0 / 900      0%
70 09:16:45:0 / 2250000      0 / 900      0%

```



```

        69 09:01:45:0 / 2250000          0 / 900          0%
        68 08:46:45:0 / 2250000          0 / 900          0%
        67 08:31:45:0 / 2250000          0 / 900          0%
Downstream Congestion:
No.  Time      : Aging Intervals      Seconds      Percent
      : Congested / Total      Congested / Total Congested
Instantaneous :      0 / 30          0 (ms) / 12 (ms) 0%
65 08:01:45 :      0 / 2250000          0 / 900          0%
64 07:46:45 :      0 / 2250000          0 / 900          0%
63 07:31:45 :      0 / 2250000          0 / 900          0%
62 07:16:45 :      0 / 2250000          0 / 900          0
61 07:01:45 :      0 / 2250000          0 / 900          0%
60 06:46:45 :      0 / 2250000          0 / 900          0%
59 06:31:45 :      0 / 2250010          0 / 900          0%
58 06:16:45 :      0 / 2250000          0 / 900          0%
57 06:01:45 :      0 / 2250000          0 / 900          0%
56 05:46:45 :      0 / 2250020          0 / 900          0%
55 05:31:45 :      0 / 2250000          0 / 900          0%
54 05:16:45 :      0 / 2250000          0 / 900          0%
53 05:01:45 :      0 / 2250000          0 / 900          0%
52 04:46:45 :      0 / 2250000          0 / 900          0%
51 04:31:45 :      0 / 2250000          0 / 900          0%
50 04:16:45 :      0 / 2250000          0 / 900          0%
49 04:01:45 :      0 / 2250000          0 / 900          0%
48 03:46:45 :      0 / 2250000          0 / 900          0%
47 03:31:45 :      0 / 2250000          0 / 900          0%
46 03:16:45 :      0 / 2250000          0 / 900          0%
45 03:01:45 :      0 / 2250000          0 / 900          0%
44 02:46:45 :      0 / 2250000          0 / 900          0%
43 02:31:45 :      0 / 2250000          0 / 900          0%
42 02:16:45 :      0 / 2250010          0 / 900          0%
41 02:01:45 :      0 / 2250000          0 / 900          0%
40 01:46:45 :      0 / 2250000          0 / 900          0%
39 01:31:45 :      0 / 2250000          0 / 900          0%
38 01:16:45 :      0 / 2250000          0 / 900          0%
37 01:01:45 :      0 / 2250000          0 / 900          0%
36 00:46:45 :      0 / 2250000          0 / 900          0%
35 00:31:45 :      0 / 2250000          0 / 900          0%
34 00:16:45 :      0 / 2250000          0 / 900          0%
33 00:01:45 :      0 / 2250000          0 / 900          0%
32 23:46:45 :      0 / 2250030          0 / 900          0%
31 23:31:45 :      0 / 2250000          0 / 900          0%
30 23:16:45 :      0 / 2250000          0 / 900          0%
29 23:01:45 :      0 / 2250090          0 / 900          0%
28 22:46:45 :      0 / 2250000          0 / 900          0%
27 22:31:45 :      0 / 2250000          0 / 900          0%
26 22:16:45 :      0 / 2250000          0 / 900          0%
25 22:01:45 :      0 / 2250000          0 / 900          0%
24 21:46:45 :      0 / 2250000          0 / 900          0%
23 21:31:45 :      0 / 2250000          0 / 900          0%
22 21:16:45 :      0 / 2250050          0 / 900          0%
21 21:01:45 :      0 / 2250000          0 / 900          0%
20 20:46:45 :      0 / 2250000          0 / 900          0%
19 20:31:45 :      0 / 2250000          0 / 900          0%
18 20:16:45 :      0 / 2250060          0 / 900          0%
17 20:01:45 :      0 / 2250000          0 / 900          0%
16 19:46:45 :      0 / 2250000          0 / 900          0%
15 19:31:45 :      0 / 2250000          0 / 900          0%
14 19:16:45 :      0 / 2250000          0 / 900          0%
13 19:01:45 :      0 / 2250000          0 / 900          0%
12 18:46:45 :      0 / 2250090          0 / 900          0%
11 18:31:45 :      0 / 2250000          0 / 900          0%
10 18:16:45 :      0 / 2250000          0 / 900          0%
 9 18:01:45 :      0 / 2250000          0 / 900          0%

```

show rpr-ieee fairness history

```

8 17:46:45 :      0 / 2250000          0 / 900      0%
7 17:31:45 :      0 / 2250000          0 / 900      0%
6 17:16:45 :      0 / 2250000          0 / 900      0%
5 17:01:45 :      0 / 2250000          0 / 900      0%
4 16:46:45 :      0 / 2250000          0 / 900      0%
3 16:31:45 :      0 / 2250000          0 / 900      0%
2 16:16:45 :      0 / 2250000          0 / 900      0%
1 16:01:45 :      0 / 2250000          0 / 900      0%
96 15:46:45 :      0 / 2250000          0 / 900      0%
95 15:31:45 :      0 / 2250000          0 / 900      0%
94 15:16:45 :      0 / 2250000          0 / 900      0%
93 15:01:45 :      0 / 2250000          0 / 900      0%
92 14:46:45 :      0 / 2250000          0 / 900      0%
91 14:31:45 :      0 / 2250000          0 / 900      0%
90 14:16:45 :      0 / 2250000          0 / 900      0%
89 14:01:45 :      0 / 2250000          0 / 900      0%
88 13:46:45 :      0 / 2250000          0 / 900      0%
87 13:31:45 :      0 / 2250000          0 / 900      0%
86 13:16:45 :      0 / 2250000          0 / 900      0%
85 13:01:45 :      0 / 2250000          0 / 900      0%
84 12:46:45 :      0 / 2250000          0 / 900      0%
83 12:31:45 :      0 / 2250100          0 / 900      0%
82 12:16:45 :      0 / 2250000          0 / 900      0%
81 12:01:45 :      0 / 2250000          0 / 900      0%
80 11:46:45 :      0 / 2250030          0 / 900      0%
79 11:31:45 :      0 / 2250000          0 / 900      0%
78 11:16:45 :      0 / 2250010          0 / 900      0%
77 11:01:45 :      0 / 2250000          0 / 900      0%
76 10:46:45 :      0 / 2250000          0 / 900      0%
75 10:31:45 :      0 / 2250000          0 / 900      0%
74 10:16:45 :      0 / 2250000          0 / 900      0%
73 10:01:45 :      0 / 2250000          0 / 900      0%
72 09:46:45 :      0 / 2250070          0 / 900      0%
71 09:31:45 :      0 / 2250000          0 / 900      0%
70 09:16:45 :      0 / 2250000          0 / 900      0%
69 09:01:45 :      0 / 2250000          0 / 900      0%
68 08:46:45 :      0 / 2250000          0 / 900      0%
67 08:31:45 :      0 / 2250000          0 / 900      0%

```

Eastbound Tx (Ringlet 0)

Local Congestion:

No.	Time	Aging Intervals Congested / Total	Seconds Congested / Total	Percent Congested
Instantaneous:		0 / 30	0 (ms) / 12 (ms)	0%
65	08:01:45 :	0 / 2250000	0 / 900	0%
64	07:46:45 :	0 / 2250000	0 / 900	0%
63	07:31:45 :	0 / 2250000	0 / 900	0%
62	07:16:45 :	0 / 2250000	0 / 900	0%
61	07:01:45 :	0 / 2250000	0 / 900	0%
60	06:46:45 :	0 / 2250000	0 / 900	0%
59	06:31:45 :	0 / 2250010	0 / 900	0%
58	06:16:45 :	0 / 2250000	0 / 900	0%
57	06:01:45 :	0 / 2250000	0 / 900	0%
56	05:46:45 :	0 / 2250020	0 / 900	0%
55	05:31:45 :	0 / 2250000	0 / 900	0%
54	05:16:45 :	0 / 2250000	0 / 900	0%
53	05:01:45 :	0 / 2250000	0 / 900	0%
52	04:46:45 :	0 / 2250000	0 / 900	0%
51	04:31:45 :	0 / 2250000	0 / 900	0%
50	04:16:45 :	0 / 2250000	0 / 900	0%
49	04:01:45 :	0 / 2250000	0 / 900	0%
48	03:46:45 :	0 / 2250000	0 / 900	0%
47	03:31:45 :	0 / 2250000	0 / 900	0%
46	03:16:45 :	0 / 2250000	0 / 900	0%
45	03:01:45 :	0 / 2250000	0 / 900	0%

```

44 02:46:45 :      0 / 2250000      0 / 900      0%
43 02:31:45 :      0 / 2250000      0 / 900      0%
42 02:16:45 :      0 / 2250010      0 / 900      0%
41 02:01:45 :      0 / 2250000      0 / 900      0%
40 01:46:45 :      0 / 2250000      0 / 900      0%
39 01:31:45 :      0 / 2250000      0 / 900      0%
38 01:16:45 :      0 / 2250000      0 / 900      0%
37 01:01:45 :      0 / 2250000      0 / 900      0%
36 00:46:45 :      0 / 2250000      0 / 900      0%
35 00:31:45 :      0 / 2250000      0 / 900      0%
34 00:16:45 :      0 / 2250000      0 / 900      0%
33 00:01:45 :      0 / 2250000      0 / 900      0%
32 23:46:45 :      0 / 2250030      0 / 900      0%
31 23:31:45 :      0 / 2250000      0 / 900      0%
30 23:16:45 :      0 / 2250000      0 / 900      0%
29 23:01:45 :      0 / 2250090      0 / 900      0%
28 22:46:45 :      0 / 2250000      0 / 900      0%
27 22:31:45 :      0 / 2250000      0 / 900      0%
26 22:16:45 :      0 / 2250000      0 / 900      0%
25 22:01:45 :      0 / 2250000      0 / 900      0%
24 21:46:45 :      0 / 2250000      0 / 900      0%
23 21:31:45 :      0 / 2250000      0 / 900      0%
22 21:16:45 :      0 / 2250050      0 / 900      0%
21 21:01:45 :      0 / 2250000      0 / 900      0%
20 20:46:45 :      0 / 2250000      0 / 900      0%
19 20:31:45 :      0 / 2250000      0 / 900      0%
18 20:16:45 :      0 / 2250060      0 / 900      0%
17 20:01:45 :      0 / 2250000      0 / 900      0%
16 19:46:45 :      0 / 2250000      0 / 900      0%
15 19:31:45 :      0 / 2250000      0 / 900      0%
14 19:16:45 :      0 / 2250000      0 / 900      0%
13 19:01:45 :      0 / 2250000      0 / 900      0%
12 18:46:45 :      0 / 2250090      0 / 900      0%
11 18:31:45 :      0 / 2250000      0 / 900      0%
10 18:16:45 :      0 / 2250000      0 / 900      0%
9  18:01:45 :      0 / 2250000      0 / 900      0%
8  17:46:45 :      0 / 2250000      0 / 900      0%
7  17:31:45 :      0 / 2250000      0 / 900      0%
6  17:16:45 :      0 / 2250000      0 / 900      0%
5  17:01:45 :      0 / 2250000      0 / 900      0%
4  16:46:45 :      0 / 2250000      0 / 900      0%
3  16:31:45 :      0 / 2250000      0 / 900      0%
2  16:16:45 :      0 / 2250000      0 / 900      0%
1  16:01:45 :      0 / 2250000      0 / 900      0%
96 15:46:45 :      0 / 2250000      0 / 900      0%
95 15:31:45 :      0 / 2250000      0 / 900      0%
94 15:16:45 :      0 / 2250000      0 / 900      0%
93 15:01:45 :      0 / 2250000      0 / 900      0%
92 14:46:45 :      0 / 2250000      0 / 900      0%
91 14:31:45 :      0 / 2250000      0 / 900      0%
90 14:16:45 :      0 / 2250000      0 / 900      0%
89 14:01:45 :      0 / 2250000      0 / 900      0%
88 13:46:45 :      0 / 2250000      0 / 900      0%
87 13:31:45 :      0 / 2250000      0 / 900      0%
86 13:16:45 :      0 / 2250000      0 / 900      0%
85 13:01:45 :      0 / 2250000      0 / 900      0%
84 12:46:45 :      0 / 2250000      0 / 900      0%
83 12:31:45 :      0 / 2250100      0 / 900      0%
82 12:16:45 :      0 / 2250000      0 / 900      0%
81 12:01:45 :      0 / 2250000      0 / 900      0%
80 11:46:45 :      0 / 2250030      0 / 900      0%
79 11:31:45 :      0 / 2250000      0 / 900      0%
78 11:16:45 :      0 / 2250010      0 / 900      0%
77 11:01:45 :      0 / 2250000      0 / 900      0%

```

show rpr-ieee fairness history

```

76 10:46:45 :    0 / 2250000    0 / 900          0%
75 10:31:45 :    0 / 2250000    0 / 900          0%
74 10:16:45 :    0 / 2250000    0 / 900          0%
73 10:01:45 :    0 / 2250000    0 / 900          0%
72 09:46:45 :    0 / 2250070    0 / 900          0%
71 09:31:45 :    0 / 2250000    0 / 900          0%
70 09:16:45 :    0 / 2250000    0 / 900          0%
69 09:01:45 :    0 / 2250000    0 / 900          0%
68 08:46:45 :    0 / 2250000    0 / 900          0%
67 08:31:45 :    0 / 2250000    0 / 900          0%

```

Downstream Congestion:

No.	Time	Aging Intervals		Seconds		Percent Congested
		Congested / Total		Congested / Total		
Instantaneous :		0 / 30		0 (ms) / 12 (ms)		0%
65	08:01:45 :	0 / 2250000		0 / 900		0%
64	07:46:45 :	0 / 2250000		0 / 900		0%
63	07:31:45 :	0 / 2250000		0 / 900		0%
62	07:16:45 :	0 / 2250000		0 / 900		0%
61	07:01:45 :	0 / 2250000		0 / 900		0%
60	06:46:45 :	0 / 2250000		0 / 900		0%
59	06:31:45 :	0 / 2250010		0 / 900		0%
58	06:16:45 :	0 / 2250000		0 / 900		0%
57	06:01:45 :	0 / 2250000		0 / 900		0%
56	05:46:45 :	0 / 2250020		0 / 900		0%
55	05:31:45 :	0 / 2250000		0 / 900		0%
54	05:16:45 :	0 / 2250000		0 / 900		0%
53	05:01:45 :	0 / 2250000		0 / 900		0%
52	04:46:45 :	0 / 2250000		0 / 900		0%
51	04:31:45 :	0 / 2250000		0 / 900		0%
50	04:16:45 :	0 / 2250000		0 / 900		0%
49	04:01:45 :	0 / 2250000		0 / 900		0%
48	03:46:45 :	0 / 2250000		0 / 900		0%
47	03:31:45 :	0 / 2250000		0 / 900		0%
46	03:16:45 :	0 / 2250000		0 / 900		0%
45	03:01:45 :	0 / 2250000		0 / 900		0%
44	02:46:45 :	0 / 2250000		0 / 900		0%
43	02:31:45 :	0 / 2250000		0 / 900		0%
42	02:16:45 :	0 / 2250010		0 / 900		0%
41	02:01:45 :	0 / 2250000		0 / 900		0%
40	01:46:45 :	0 / 2250000		0 / 900		0%
39	01:31:45 :	0 / 2250000		0 / 900		0%
38	01:16:45 :	0 / 2250000		0 / 900		0%
37	01:01:45 :	0 / 2250000		0 / 900		0%
36	00:46:45 :	0 / 2250000		0 / 900		0%
35	00:31:45 :	0 / 2250000		0 / 900		0%
34	00:16:45 :	0 / 2250000		0 / 900		0%
33	00:01:45 :	0 / 2250000		0 / 900		0%
32	23:46:45 :	0 / 2250030		0 / 900		0%
31	23:31:45 :	0 / 2250000		0 / 900		0%
30	23:16:45 :	0 / 2250000		0 / 900		0%
29	23:01:45 :	0 / 2250090		0 / 900		0%
28	22:46:45 :	0 / 2250000		0 / 900		0%
27	22:31:45 :	0 / 2250000		0 / 900		0%
26	22:16:45 :	0 / 2250000		0 / 900		0%
25	22:01:45 :	0 / 2250000		0 / 900		0%
24	21:46:45 :	0 / 2250000		0 / 900		0%
23	21:31:45 :	0 / 2250000		0 / 900		0%
22	21:16:45 :	0 / 2250050		0 / 900		0%
21	21:01:45 :	0 / 2250000		0 / 900		0%
20	20:46:45 :	0 / 2250000		0 / 900		0%
19	20:31:45 :	0 / 2250000		0 / 900		0%
18	20:16:45 :	0 / 2250060		0 / 900		0%
17	20:01:45 :	0 / 2250000		0 / 900		0%

```

16 19:46:45 :      0 / 2250000      0 / 900      0%
15 19:31:45 :      0 / 2250000      0 / 900      0%
14 19:16:45 :      0 / 2250000      0 / 900      0%
13 19:01:45 :      0 / 2250000      0 / 900      0%
12 18:46:45 :      0 / 2250090      0 / 900      0%
11 18:31:45 :      0 / 2250000      0 / 900      0%
10 18:16:45 :      0 / 2250000      0 / 900      0%
 9 18:01:45 :      0 / 2250000      0 / 900      0%
 8 17:46:45 :      0 / 2250000      0 / 900      0%
 7 17:31:45 :      0 / 2250000      0 / 900      0%
 6 17:16:45 :      0 / 2250000      0 / 900      0%
 5 17:01:45 :      0 / 2250000      0 / 900      0%
 4 16:46:45 :      0 / 2250000      0 / 900      0%
 3 16:31:45 :      0 / 2250000      0 / 900      0%
 2 16:16:45 :      0 / 2250000      0 / 900      0%
 1 16:01:45 :      0 / 2250000      0 / 900      0%
96 15:46:45 :      0 / 2250000      0 / 900      0%
95 15:31:45 :      0 / 2250000      0 / 900      0%
94 15:16:45 :      0 / 2250000      0 / 900      0%
93 15:01:45 :      0 / 2250000      0 / 900      0%
92 14:46:45 :      0 / 2250000      0 / 900      0%
91 14:31:45 :      0 / 2250000      0 / 900      0%
90 14:16:45 :      0 / 2250000      0 / 900      0%
89 14:01:45 :      0 / 2250000      0 / 900      0%
88 13:46:45 :      0 / 2250000      0 / 900      0%
87 13:31:45 :      0 / 2250000      0 / 900      0%
86 13:16:45 :      0 / 2250000      0 / 900      0%
85 13:01:45 :      0 / 2250000      0 / 900      0%
84 12:46:45 :      0 / 2250000      0 / 900      0%
83 12:31:45 :      0 / 2250100      0 / 900      0%
82 12:16:45 :      0 / 2250000      0 / 900      0%
81 12:01:45 :      0 / 2250000      0 / 900      0%
80 11:46:45 :      0 / 2250030      0 / 900      0%
79 11:31:45 :      0 / 2250000      0 / 900      0%
78 11:16:45 :      0 / 2250010      0 / 900      0%
77 11:01:45 :      0 / 2250000      0 / 900      0%
76 10:46:45 :      0 / 2250000      0 / 900      0%
75 10:31:45 :      0 / 2250000      0 / 900      0%
74 10:16:45 :      0 / 2250000      0 / 900      0%
73 10:01:45 :      0 / 2250000      0 / 900      0%
72 09:46:45 :      0 / 2250070      0 / 900      0%
71 09:31:45 :      0 / 2250000      0 / 900      0%
70 09:16:45 :      0 / 2250000      0 / 900      0%
 69 09:01:45 :      0 / 2250000      0 / 900      0%
68 08:46:45 :      0 / 2250000      0 / 900      0%
67 08:31:45 :      0 / 2250000      0 / 900      0%

```

Related Commands show rpr-ieee fairness

show rpr-ieee protection

Use this command to display the protection state of the local station, along with brief overview of the station's neighbors, timer configuration, and self-detected failures that might contribute to the current state.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines Use this command to show the current protection status on the ring.
In this command, protection can be shortened to prot.

Examples

```
router# show rpr-ieee protection

Protection Information for Interface RPR-IEEEE0
MAC Addresses
  West Span (Ringlet 0 RX) neighbor 000b.fcff.9d34
  East Span (Ringlet 1 RX) neighbor 0013.1991.1fc0
  Station MAC address 0005.9a3c.59c0
TP frame sending timers:
fast timer: 10 msec
  slow timer: 1x100 msec (100 msec)
Protection holdoff timers:
  L1 Holdoff                               Keepalive Detection
  West Span 0x10 msec ( 0 msec)             West Span 5 msec
  East Span 0x10 msec ( 0 msec)             East Span 5 msec
Configured protection mode: STEERING
Protection Status
Ring is IDLE
Protection WTR period is 10 sec. (timer is inactive)
  Self Detected Requests                     Remote Requests
  West Span IDLE                             West Span IDLE
  East Span IDLE                             East Span IDLE
  Distant Requests
  East Span IDLE                             West Span IDLE
West Span Failures: none
East Span Failures: none
```

Related Commands None

show rpr-ieee rate detail

Use this command to display the configured rate limits for each service class of traffic.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines Use this command to show the configured rates for Class A1, B-EIR, B-CIR, and reserved traffic.

Examples

```
router# show rpr-ieee rate detail
Rate Limit Information for Interface RPR-IEEEE0
West Span:
  Reserved Bandwidth (Class A0): 0 Mbps
  Rate Limiter High (Class A1): 20 Mbps
  Rate Limiter Medium (Class B-CIR): 10 Mbps
  Rate Limiter Low (Class B-EIR, C): full
East Span:
  Reserved Bandwidth (Class A0): 0 Mbps
  Rate Limiter High (Class A1): 20 Mbps
  Rate Limiter Medium (Class B-CIR): 10 Mbps
  Rate Limiter Low (Class B-EIR, C): full
Service Type: Relaxed
Idle Shaper is Enabled
  Transmit at 500 packets per million when PTQ vacancy above 18432 bytes
  Transmit at 250 packets per million when PTQ vacancy below 18432 bytes
```

Related Commands None

show rpr-ieee topology detail

Use this command to display topology information gathered by the station from the protection and ATD messages received on either span of an IEEE 802.17b based RPR ring.

Syntax Description This command has no arguments or keywords.

Defaults N/A

Command Modes Privileged executive

Usage Guidelines Use this command to obtain an extremely detailed status of the ring, including details about each station's configuration.

Examples

```
router# show rpr-ieee topology detail
802.17 Topology Display
  RX ringlet0->West spanRX ringlet1->East span
Number of nodes on
  ringlet0: 5ringlet1: 5
=====
Local Station Topology Info
=====
Topology entry:
  Station MAC address: 0005.9a3c.59c0
  West Span (Outer ringlet RX) neighbor 000b.fcff.9d34
  East Span (Inner ringlet RX) neighbor 0013.1991.1fc0
  Ring Topology: CLOSED (STABLE)
  Containment Active: NO
  A0 class reserved rate:
    ringlet0: 0 (mbps)ringlet1: 0 (mbps)
  Ringlet reserved rate:
    ringlet0: 0 (mbps)ringlet1: 0 (mbps)
  Ringlet unreserved rate:
    ringlet0: 96 (mbps)ringlet1: 96 (mbps)
  Ringlet effective unreserved rate:
    ringlet0: 95.9 (mbps)ringlet1: 95.9 (mbps)
  Advertised Protection requests:
    ringlet0: IDLERinglet1: IDLE
  Active Edges:
    ringlet0: NO ringlet1: NO
  Configured protection mode: STEERING
  Jumbo preference: NOT SET (ring doesn't support JUMBOS)
  Is revertive: YES
  Measured LRTT: 0
  Sequence Number: 3
ATD INFO:
  ATD timer: 1 sec
  Station Name: ML100T-481
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
```



```

Weight:
  ringlet0: 1ringlet1: 1
Secondary Mac Addresses:
  MAC 1: 0000.0000.0000 (UNUSED)
  MAC 2: 0000.0000.0000 (UNUSED)

=====
Topology Map for Outer ringlet
=====

=====
Topology entry at Index 1 on ringlet 0:
Station MAC address: 000b.fcff.9d34
Valid on ringlet0: YES
Entry reachable: YES
Advertised Protection requests:
  ringlet0: IDLERinglet1: IDLE
Active Edges:
  ringlet0: NO ringlet1: NO
Preferred protection mode: STEERING
Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
Measured LRTT: 0
Sequence Number: 3
ATD INFO:
  Station Name: ML100X-491
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
  Weight:
    ringlet0: 1ringlet1: 1
  Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)

=====

Topology entry at Index 2 on ringlet 0:
Station MAC address: 0011.2130.b568
Valid on ringlet0: YES
Entry reachable: YES
Advertised Protection requests:
  ringlet0: IDLERinglet1: IDLE
Active Edges:
  ringlet0: NO ringlet1: NO
Preferred protection mode: STEERING
Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
Measured LRTT: 0
Sequence Number: 3
ATD INFO:
  Station Name: ML1000-491
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
  Weight:
    ringlet0: 1ringlet1: 1
  Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)

=====

Topology entry at Index 3 on ringlet 0:
Station MAC address: 0005.9a39.7630
Valid on ringlet0: YES
Entry reachable: YES
Advertised Protection requests:

```

show rpr-ieee topology detail

```

    ringlet0: IDLERinglet1: IDLE
Active Edges:
    ringlet0: NO ringlet1: NO
Preferred protection mode: STEERING
Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
Measured LRTT: 0
Sequence Number: 3
ATD INFO:
Station Name: ML1000-492
A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
SAS enabled: YES
Weight:
    ringlet0: 1ringlet1: 1
Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)
=====

Topology entry at Index 4 on ringlet 0:
Station MAC address: 0013.1991.1fc0
Valid on ringlet0: YES
Entry reachable: YES
Advertised Protection requests:
    ringlet0: IDLERinglet1: IDLE
Active Edges:
    ringlet0: NO ringlet1: NO
Preferred protection mode: STEERING
Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
Measured LRTT: 0
Sequence Number: 3
ATD INFO:
Station Name: ML100T-482
A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
SAS enabled: YES
Weight:
    ringlet0: 1ringlet1: 1
Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)
=====

Topology entry at Index 5 on ringlet 0:
Station MAC address: 0005.9a3c.59c0
Valid on ringlet0: YES
Entry reachable: YES
Advertised Protection requests:
    ringlet0: IDLERinglet1: IDLE
Active Edges:
    ringlet0: NO ringlet1: NO
Preferred protection mode: STEERING
Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
Measured LRTT: 0
Sequence Number: 3
ATD INFO:
Station Name: ML100T-481
A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
SAS enabled: YES
Weight:
    ringlet0: 1ringlet1: 1
Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)

```

```

MAC 2: 0000.0000.0000 (UNUSED)
=====
Topology Map for Inner ringlet
=====

Topology entry at Index 1 on ringlet 1:
  Station MAC address: 0013.1991.1fc0
  Valid on ringlet1: YES
  Entry reachable: YES
  Advertised Protection requests:
    ringlet0: IDLERinglet1: IDLE
  Active Edges:
    ringlet0: NO ringlet1: NO
  Preferred protection mode: STEERING
  Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
  Measured LRTT: 0
  Sequence Number: 3
ATD INFO:
  Station Name: ML100T-482
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
  Weight:
    ringlet0: 1ringlet1: 1
  Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)
=====

Topology entry at Index 2 on ringlet 1:
  Station MAC address: 0005.9a39.7630
  Valid on ringlet1: YES
  Entry reachable: YES
  Advertised Protection requests:
    ringlet0: IDLERinglet1: IDLE
  Active Edges:
    ringlet0: NO ringlet1: NO
  Preferred protection mode: STEERING
  Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
  Measured LRTT: 0
  Sequence Number: 3
ATD INFO:
  Station Name: ML1000-492
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
  Weight:
    ringlet0: 1ringlet1: 1
  Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)
=====

Topology entry at Index 3 on ringlet 1:
  Station MAC address: 0011.2130.b568
  Valid on ringlet1: YES
  Entry reachable: YES
  Advertised Protection requests:
    ringlet0: IDLERinglet1: IDLE
  Active Edges:
    ringlet0: NO ringlet1: NO
  Preferred protection mode: STEERING
  Jumbo preference: NOT SET (ring doesn't supports JUMBOS)

```

show rpr-ieee topology detail

```

Measured LRTT: 0
Sequence Number: 3
ATD INFO:
  Station Name: ML1000-491
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
  Weight:
    ringlet0: 1ringlet1: 1
  Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)
=====

Topology entry at Index 4 on ringlet 1:
  Station MAC address: 000b.fcff.9d34
  Valid on ringlet1: YES
  Entry reachable: YES
  Advertised Protection requests:
    ringlet0: IDLEringlet1: IDLE
  Active Edges:
    ringlet0: NO ringlet1: NO
  Preferred protection mode: STEERING
  Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
  Measured LRTT: 0
  Sequence Number: 3
ATD INFO:
  Station Name: ML100X-491
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
  Weight:
    ringlet0: 1ringlet1: 1
  Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)
=====

Topology entry at Index 5 on ringlet 1:
  Station MAC address: 0005.9a3c.59c0
  Valid on ringlet1: YES
  Entry reachable: YES
  Advertised Protection requests:
    ringlet0: IDLEringlet1: IDLE
  Active Edges:
    ringlet0: NO ringlet1: NO
  Preferred protection mode: STEERING
  Jumbo preference: NOT SET (ring doesn't supports JUMBOS)
  Measured LRTT: 0
  Sequence Number: 3
ATD INFO:
  Station Name: ML100T-481
  A0 reserved Bandwidth:
    ringlet0: 0 mbpsringlet1: 0 mbps
  SAS enabled: YES
  Weight:
    ringlet0: 1ringlet1: 1
  Secondary Mac Addresses:
    MAC 1: 0000.0000.0000 (UNUSED)
    MAC 2: 0000.0000.0000 (UNUSED)

```

Related Commands None

[no] shutdown

Use this command to place a POS or IEEE 802.17b based RPR interface in pass-through mode. This command has no arguments or keywords. Use the no form of this command to reverse the shutdown.

Defaults

The default is not shut down.

Command Modes

POS or IEEE 802.17b based RPR interface configuration

Usage Guidelines

For GFP and high-level data link control (HDLC) modes, the POS shutdown causes a path alarm indication signal (AIS-P) to be sent to the peer. In RPR-IEEE mode, AIS-P is not inserted toward the peer.

In this command, shutdown can be shortened to shut.

Examples

In this example, interface is shortened to int.

```
Router(config)# int pos 0  
Router(config-if)# shut
```

Related Commands

None

spr-intf-id *shared-packet-ring-number*

Use this command to assign the POS interface to the SPR interface.

Syntax Description	Parameter	Description
	<i>shared-packet-ring-number</i>	The only valid shared-packet-ring-number (SPR number) is 1.

Defaults N/A

Command Modes POS interface configuration

Usage Guidelines

- The SPR number must be 1, which is the same SPR number assigned to the SPR interface.
- The members of the SPR interface must be POS interfaces.
- An SPR interface is configured similarly to a EtherChannel (port-channel) interface. Instead of using the **channel-group** command to define the members, you use the **spr-intf-ID** command. Like port-channel, you then configure the SPR interfaces instead of the POS interface.



Note A similar command, the **spr drpri-id [0 | 1]** command, is not supported in R7.2.

Examples

In this example, interface is shortened to int. An ML-Series card POS interface is being assigned to an SPR interface with a shared-packet-ring-number of 1:

```
Router(config)# interface pos 0
Router(config-if)# spr-intf-id 1
```

Related Commands

```
interface spr 1
spr station-id
spr wrap
```

[no] spr load-balance {auto | port-based}

Use this command to specify the Cisco proprietary RPR load-balancing scheme for unicast packets.

Syntax Description	Parameter	Description
	auto	The default auto option balances the load based on the MAC addresses or source and destination addresses of the IP packet.
	port-based	The port-based load balancing option maps even ports to the POS 0 interface and odd ports to the POS 1 interface.

Defaults The default setting is auto.

Command Modes SPR interface configuration

Examples The following example configures an SPR interface to use port-based load balancing:

```
Router(config)# interface spr 1
Router(config-if)# spr load-balance port-based
```

Related Commands interface spr 1

spr station-id *station-id-number*

Use this command to configure a station ID.

Syntax Description	Parameter	Description
	<i>station-id-number</i>	The user must configure a different number for each SPR interface that attaches to the Cisco proprietary RPR. Valid station ID numbers range from 1 to 254.
Defaults	N/A	
Command Modes	SPR interface configuration	
Usage Guidelines		The different ML-Series cards attached to the RPR all have the same interface type and number, spr1. The station ID helps to differentiate the SPR interfaces.
Examples		The following example sets an ML-Series card SPR station ID to 100: <pre>Router(config)# interface spr 1 Router(config-if)# spr station-id 100</pre>
Related Commands	interface spr 1 spr-intf-id spr wrap	

spr wrap {immediate | delayed}

Use this command to set the Cisco proprietary RPR wrap mode to either wrap traffic the instant it detects a link state change or to wrap traffic after the carrier delay, which gives the SONET protection time to register the defect and declare the link down.

Syntax Description	Parameter	Description
	immediate	Wraps Cisco proprietary RPR traffic the instant it detects a link state change.
	delayed	Wraps Cisco proprietary RPR traffic after the carrier delay time expires.

Defaults The default setting is immediate.

Command Modes SPR interface configuration

Usage Guidelines Immediate should be used if Cisco proprietary RPR is running over unprotected SONET/SDH circuits. Delayed should be run for SONET protected circuits, such as BLSR or path protection, or SDH protected circuits, such as subnetwork connection protection (SNCP) or multiplex section-shared protection ring (MS-SPRing).

Examples The following example sets an ML-Series card to delayed:

```
Router(config)# interface spr 1
Router(config-if)# spr wrap delayed
```

Related Commands

- interface spr 1
- spr-intf-id
- spr station-id

[no] xconnect [*destination*] [*vc-id*] [encapsulation mpls]

Use this command at customer-edge (CE) or service provider-edge customer-located equipment (PE-CLE) ingress and egress Ethernet ports, or at dot1Q VLAN subinterfaces with a destination and virtual connection identifier (VC ID) to route Layer 2 packets over a specified point-to-point VC by using Ethernet over multiprotocol label switching (EoMPLS). Use the no form of this command on both edge devices to delete the VC.



Note

This command replaces the **mpls l2transport route** command.

Syntax Description

<i>destination</i>	The <i>destination</i> label distribution protocol (LDP) IP address of the remote provider edge device. The IP address cannot be an IP address on the route on which the command is entered. The <i>destination</i> is required for the standard form of the command. It cannot be used with the no form of the command.
<i>vc-id</i>	Assign a <i>vc-id</i> for the virtual connection between the two peer provider edge devices. The range is 1 to 4294967295. The <i>vc-id</i> is required for the standard form of the command. It cannot be used with the no form of the command.
encapsulation mpls	Specify the MPLS data encapsulation method.



Note

Though visible in the command-line help strings, the **pw-class** keyword is not supported.

Defaults

No point-to-point connections are configured by default.

Command Modes

Interface configuration

Usage Guidelines

An MPLS VC runs across an MPLS cloud to connect Ethernet interfaces on two PE-CLE devices at each edge of the service provider network. You must enter the command at the PE device at each edge of the service provider network to establish a bidirectional virtual connection, which consists of two unidirectional label-switched paths (LSPs). A VC is not established if it is not properly defined from both ends.

For the *destination* parameter, specify the LDP IP address of the other PE-CLE device; do not specify the IP address of the device on which you are entering the command.

The *vc-id* must be unique for each pair of provider edge devices. Therefore, in large networks, you should keep track of the VC ID assignments to ensure that a VC ID is not assigned more than once.

Examples

This example shows how to establish an EoMPLS tunnel between the PE1 VLAN 3 interfaces and the PE2 VLAN 4 interface. PE1 has IP address 10.0.0.1/32 that PE2 discovers through routing and PE2 has IP address 20.0.0.1/32 that PE1 discovers through routing.

■ [no] xconnect [destination] [vc-id] [encapsulation mpls]

At the PE1 interface:

```
Switch(config)# interface vlan 3  
Switch(config-if)# xconnect 20.0.0.1 123 encapsulation mpls
```

At the PE2 interface:

```
Switch(config)# interface vlan 4  
Switch(config-if)# xconnect 10.0.0.1 123 encapsulation mpls
```

Related Commands show mpls l2transport route