



## Supported Optical Sources

- [Supported Optical Sources, on page 1](#)

## Supported Optical Sources

*Table 1: Feature History*

Feature Name	Release Information	Feature Description
New Optical Source and Pluggable Support	Cisco ONP Release 4.2	<p>Optical Sources enable you to simulate the optical feasibility of the network with the 400G and other interfaces that are not natively modeled in Cisco ONP. The following Optical Sources are introduced in this release:</p> <ul style="list-style-type: none"> <li>• ONS-CFP2D-400G-C-OpticalSources-V 2.mxd</li> <li>• QDD-400G-ZRP-S-OpticalSources-V2.mxd</li> </ul>

Cisco ONP supports the following optical sources:

- OpticalSources\_NCS2K\_400GXP-LC\_NCS4K-4H-OPW-QC2 DWDM Line Card
  - 400GXP\_100G\_25%\_DE
  - 400GXP\_200G\_15%\_DE
  - 100G-SD-FEC
  - 400GXP\_100G\_15%\_DE
  - 200G-SD-FEC
  - 400GXP\_100G\_15%
  - 400GXP\_200G\_15%
  - 400GXP\_200G\_25%DE
- NCS1004\_OpticalSources\_V3
  - NCS1004\_QPSK\_SP\_16QAM\_200G\_27%SDFEC\_60GBd

- NCS1004\_SP\_16QAM\_300G\_27%SDFEC\_69GBd
- NCS1004\_QPSK\_200G\_27%SDFEC\_69GBd
- NCS1004\_16QAM\_32QAM\_400G\_27%SDFEC\_62GBd
- NCS1004\_16QAM\_400G\_27%SDFEC\_69GBd
- NCS1004\_SP\_16QAM\_16QAM\_300G\_27%SDFEC\_60GBd
- NCS1004\_32QAM\_500G\_27%SDFEC\_69GBd
- QDD and CFP2-DCO variants
  - **ONS-CFP2D-400G-C-OpticalSources-V2.mxd**<sup>1</sup>
    - CFP2\_200OR\_TXP\_FOIC2\_OFEC\_15\_DE\_ON\_4Q\_1S\_BR63\_1
    - CFP2\_300OR\_TXP\_FOIC3\_OFEC\_15\_DE\_ON\_8Q\_1S\_BR63\_1
    - CFP2\_400OR\_TXP\_FOIC4\_OFEC\_15\_DE\_ON\_16Q\_1S\_BR63\_1
  - **ONS-CFP2D-400G-C-OpticalSources-V2.mxd**<sup>2</sup>
    - CFP2\_300ZR+\_MXP\_GAUI8\_OFEC\_15\_DE\_ON\_8Q\_0S\_BR60\_1
    - CFP2\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_8Q\_1E\_BR40\_1
    - CFP2\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_16Q\_1E\_BR30\_1
    - CFP2\_400ZR\_TXP\_GAUI8\_CFEC\_15\_DE\_ON\_16Q\_0S\_BR59\_8
    - CFP2\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_4Q\_0S\_BR60\_1
    - CFP2\_100ZR+\_TXP\_GAUI2\_OFEC\_15\_DE\_ON\_4Q\_1S\_BR30\_1
    - CFP2\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_4Q\_1S\_BR60\_1
    - CFP2\_400ZR+\_TXP\_GAUI8\_OFEC\_15\_DE\_ON\_16Q\_1E\_BR60\_1
    - CFP2\_300ZR+\_MXP\_GAUI8\_OFEC\_15\_DE\_ON\_8Q\_1E\_BR60\_1
    - CFP2\_400ZR+\_TXP\_GAUI8\_OFEC\_15\_DE\_ON\_16Q\_0S\_BR60\_1
    - CFP2\_100OR\_TXP\_FOIC1\_OFEC\_15\_DE\_ON\_4Q\_1S\_BR31\_6
    - CFP2\_200OR\_TXP\_FOIC2\_OFEC\_15\_DE\_ON\_8Q\_1S\_BR42\_1
    - CFP2\_200OR\_TXP\_FOIC2\_OFEC\_15\_DE\_ON\_16Q\_1E\_BR31\_6
  - **QDD-400G-ZRP-S-OpticalSources-V2.mxd**<sup>2</sup>
    - QDD\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_4Q\_1S\_BR60\_1
    - QDD\_400ZR\_TXP\_GAUI8\_CFEC\_15\_DE\_ON\_16Q\_0S\_BR59\_8
    - QDD\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_4Q\_0S\_BR60\_1
    - QDD\_400ZR+\_TXP\_GAUI8\_OFEC\_15\_DE\_ON\_16Q\_1E\_BR60\_1

<sup>1</sup> The optical source interfaces are supported for SSON networks.

<sup>2</sup> The optical source interfaces are supported for SSON and non-SSON networks.

- QDD\_400ZR+\_TXP\_GAUI8\_OFEC\_15\_DE\_ON\_16Q\_0S\_BR60\_1
- QDD\_300ZR+\_MXP\_GAUI8\_OFEC\_15\_DE\_ON\_8Q\_1E\_BR60\_1
- QDD\_400ZR+\_TXP\_GAUI8\_OFEC\_15\_DE\_ON\_16Q\_0E\_BR60\_1
- QDD\_300ZR+\_MXP\_GAUI8\_OFEC\_15\_DE\_ON\_8Q\_0E\_BR60\_1
- QDD\_100ZR+\_TXP\_GAUI2\_OFEC\_15\_DE\_ON\_4Q\_1S\_BR30\_1
- QDD\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_16Q\_1E\_BR30\_1
- QDD\_300ZR+\_MXP\_GAUI8\_OFEC\_15\_DE\_ON\_8Q\_0S\_BR60\_1
- QDD\_200ZR+\_MXP\_GAUI2\_OFEC\_15\_DE\_ON\_8Q\_1E\_BR40\_1



---

**Note** NCS 1004 is supported as an optical source.

---



---

**Note** The following optical source files are not supported in NCS 2000 Release 11.0:

- NCS1004\_16QAM\_32QAM\_400G\_27%SDFEC\_62GBd
- NCS1004\_QPSK\_SP\_16QAM\_200G\_27%SDFEC\_60GB

Hence, we recommend you to upgrade the system release of the network to Release 11.1, or force the optical source files that are supported for the Release 11.0.

---

