

# Release Notes for Cisco Catalyst IR1101 and Cisco ESR 6300 Routers - (Cisco IOS XE 17.3.5)

**First Published:** 2022-01-20 **Last Modified:** 2023-04-02

## **Introduction to this Document**

This Release Notes document provides information about the Cisco Catalyst IR1101 Rugged Series Routers and Cisco ESR6300 Embedded Series Routers running Cisco IOS XE 17.3.5.

This document describes the new features, limitations, troubleshooting, besides providing recommended configurations, caveats, and information on how to obtain support and documentation.



Note

The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

#### Cisco Catalyst IR1101 Rugged Series Router



The Cisco Catalyst IR1101 Rugged Series Router is a next-generation modular industrial router, which has a base platform with additional pluggable modules that can be added. The pluggable modules provide the flexibility of adding different interfaces to the IR1101 platform, for example, a cellular module, which provides Fourth-Generation Long-Term Evolution (4G LTE) cellular networks and Third-Generation (3G) cellular networks.

The IR1101 also has an expansion module that adds key capabilities to the IR1101, such as mSATA SSD FRU, Ethernet SFP port, and digital GPIO connections. The expansion module also makes the IR1101 dual LTE capable, with one LTE module in the base and the other LTE module in the expansion module.



Note

The IR-1100-SP expansion module is the same as the IR-1100-SPMI module, without the digital I/O and mSATA components.

#### Cisco ESR6300 Embedded Series Router



The ESR6300 is a small form factor embedded router module with a board size of 3.0 in. x 3.775 in. (76.2 mm x 95.885 mm).

The more compact design simplifies integration, and offers system integrators the ability to use the Cisco ESR6300 in a wide variety of embedded applications. The ESR module is available with a Cisco-designed cooling plate customized to the ESR, as well as without the cooling plate for system integrators who want to design their own custom thermal solution.

There are two ESR6300 SKUs:

- ESR-6300-NCP-K9: Embedded Router Board without a cooling plate (NCP = No Cooling Plate)
- ESR-6300-CON-K9: Embedded Router Board without a cooling plate (NCP = No Cooling Plate)

Both of the SKUs offer the following port and module interfaces:

- Four GE LAN ports
- Two combo GE WAN ports
- One USB 3.0 port
- One mSATA module interface

## **Interface Naming Conventions**

#### Cisco Catalyst IR1101 Rugged Series Router

| Port  | Naming Convention                 |
|---|-----------------------------------|
| Gigabit Ethernet combo port                   | GigabitEthernet0/0/0              |
| Gigabit Ethernet SFP port on Expansion Module | GigabitEthernet0/0/5              |
| Fast Ethernet ports                           | FastEthernet0/0/1-0/0/4           |
| Cellular Interface on IR1101 Base             | Cellular 0/1/0 and Cellular 0/1/1 |
| Cellular Interface on Expansion Module        | Cellular 0/3/0 and Cellular 0/3/1 |
| Asynchronous Serial Interface                 | Async0/2/0                        |
| USB   | usbflash0:                        |
| mSATA   | msata                             |

| Port                         | Naming Convention |
|------------------------------|-------------------|
| IR1101 Base Unit Alarm input | alarm contact 0   |
| GPIO on Expansion Module     | alarm contact 1-4 |

#### **Cisco ESR6300 Embedded Series Router**

| Port                                   | Naming Convention           |  |
|--|-----------------------------|--|
| Gigabit Ethernet combo port WAN Layer3 | GigabitEthernet0/0/0        |  |
|  | GigabitEthernet0/0/1        |  |
| Gigabit Ethernet LAN Layer 2 ports     | GigabitEthernet0/1/0        |  |
|  | GigabitEthernet0/1/1        |  |
|  | GigabitEthernet0/1/2        |  |
|  | GigabitEthernet0/1/3        |  |
| USB Port                               | usbflash0: (IOS and rommon) |  |
| Console Port                           | Line console 0              |  |

# **Software Images for Cisco IOS XE Release 17.3.5**



Note

You must have a Cisco.com account to download the software.

Table 1: Software Images for Cisco IOS-XE, Release 17.3.5

| Router             | Image Type | Filename                               |  |
|--------------------|------------|--|--|
| R1101 Universal ir |            | ir1101-universalk9.17.03.05.SPA.bin    |  |
|                    | NPE        | ir1101-universal9_npe.17.03.05.SPA.bin |  |
| ESR6300            | Universal  | c6300-universalk9.17.03.05.SPA.bin     |  |

The latest software downloads for the routers can be found at:

https://software.cisco.com/download/home/286323433

Click the link corresponding to your device to take you to the specific software you are looking for.

## **New Features in Cisco IOS XE 17.3.5**

There are no new features with this release.

### **Related Documentation**

#### Cisco Catalyst IR1101 Rugged Series Router

IR1101 documentation landing page

#### Cisco ESR6300 Embedded Series Router

ESR6300 documentation landing page

#### **Product Independent Documentation**

Cisco Industrial Routers and Industrial Wireless Access Points Antenna Guide

Cisco IOS XE 17.x

Cisco SD-WAN

Cisco IoT Field Network Director

Cisco Industrial Network Director

## **Known Limitations**

This release has the following limitations or deviations from expected behavior. These limitations are listed below by router type.

#### **Smart Licensing**

Starting with Cisco IOS XE 17.6.1, with the introduction of Smart Licensing Using Policy, even if you configure a hostname for a product instance or device, only the Unique Device Identifier (UDI) is displayed. This change in the display can be observed in all licensing utilities and user interfaces where the hostname was displayed in earlier releases. It does not affect any licensing functionality. There is no workaround for this limitation

The licensing utilities and user interfaces that are affected by this limitation include only the following: Cisco Smart Software Manager (CSSM), Cisco Smart License Utility (CSLU), and Smart Software Manager On-Prem (SSM On-Prem).

## **Caveats**

Caveats describe unexpected behavior in Cisco IOS XE releases. Caveats listed as open in a prior release are carried forward to the next release as either open or resolved.

The Cisco Bug Search Tool (BST) is a gateway to the Cisco bug-tracking system, which maintains a comprehensive list of defects and vulnerabilities in Cisco products and software. The BST provides you with detailed defect information about your products and software.

## Open Caveats in Cisco IOS XE 17.3.5

There are no open caveats to report in this release.

#### **Resolved Caveats in Cisco IOS XE 17.3.5**

To view the details of a caveat, click on the identifier.

| Identifier                  | Description  | Platform |
|-----------------------------|--|----------|
| CSCwa33567                  | No radius packets sent from the router while using | IR1101   |
| type 6 password encrytption | ESR6300  |          |

## **Communications, Services, and Additional Information**

- To receive timely, relevant information from Cisco, sign up at Cisco Profile Manager.
- To get the business impact you're looking for with the technologies that matter, visit Cisco Services.
- To submit a service request, visit Cisco Support.
- To discover and browse secure, validated enterprise-class apps, products, solutions, and services, visit Cisco DevNet.
- To obtain general networking, training, and certification titles, visit Cisco Press.
- To find warranty information for a specific product or product family, access Cisco Warranty Finder.

#### **Documentation Feedback**

To provide feedback about Cisco technical documentation, use the feedback form available in the right pane of every online document.

## **Abbreviated Cisco Trademarks**

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/c/en/us/about/legal/trademarks.html. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)