



# NetFlow Commands

---

To use commands of this module, you must be in a user group associated with a task group that includes appropriate task IDs. If the user group assignment is preventing you from using any command, contact your AAA administrator for assistance.

This module provides command line interface (CLI) commands for configuring NetFlow on the Cisco ASR 9000 Series Router.

- [cache entries](#), on page 3
- [cache permanent](#), on page 4
- [cache immediate](#), on page 5
- [cache timeout](#), on page 6
- [clear flow exporter](#), on page 7
- [clear flow monitor](#), on page 8
- [clear flow platform producer statistics location](#), on page 9
- [destination](#), on page 10
- [dscp](#), on page 11
- [exporter](#), on page 12
- [flow](#), on page 13
- [flow datalinkframesection monitor](#), on page 15
- [flow exporter-map](#), on page 16
- [flow monitor-map](#), on page 18
- [options](#), on page 20
- [option filtered](#), on page 23
- [random 1 out-of](#), on page 24
- [record ipv4](#), on page 25
- [record ipv6](#), on page 28
- [record mpls](#), on page 30
- [record datalinksection](#), on page 32
- [sampler-map](#), on page 33
- [show flow exporter](#), on page 35
- [show flow exporter-map](#), on page 37
- [show flow monitor](#), on page 40
- [show flow monitor-map](#), on page 61
- [show flow platform producer statistics location](#), on page 64
- [show flow platform nfea sampler](#), on page 66

- [show flow platform nfea interface](#), on page 67
- [show flow platform nfea sp location](#), on page 68
- [show flow platform nfea policer np](#), on page 69
- [show flow platform nfea bundle](#), on page 70
- [show flow platform nfea chkp](#), on page 71
- [show flow platform pal-cpp chkpt object](#), on page 72
- [show flow platform pal-cpp object](#), on page 73
- [show controllers pse qfp feature fnf datapath](#), on page 74
- [show flow trace platform producer location](#), on page 76
- [show flow trace ea location](#), on page 77
- [source \(NetFlow\)](#), on page 78
- [template \(NetFlow\)](#), on page 80
- [transport udp](#), on page 82
- [version v9](#), on page 83
- [version ipfix](#), on page 85

## cache entries

To configure the number of entries in the monitor map flow cache, enter the **cache entries** command in flow monitor map configuration mode. To remove a configured number of entries and return the cache to the default configuration, use the **no** form of this command.

**cache entries** *number*

|                           |  |
|---------------------------|--|
| <b>Syntax Description</b> | <i>number</i> Number of entries in the flow cache. Replace the <i>number</i> argument with the number of flow entries allowed in the flow cache. Range is from 4096 through 1000000. |
|---------------------------|--|

|                        |                       |
|------------------------|-----------------------|
| <b>Command Default</b> | <i>number</i> : 65535 |
|------------------------|-----------------------|

|                      |                                |
|----------------------|--------------------------------|
| <b>Command Modes</b> | Flow monitor map configuration |
|----------------------|--------------------------------|

|                        |                |                              |
|------------------------|----------------|------------------------------|
| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|                        | Release 3.9.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | No specific guidelines impact the use of this command. |
|-------------------------|--|

| Task ID | Task    | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

|                 |  |
|-----------------|--|
| <b>Examples</b> | This example shows how to configure the number of entries in the monitor map flow cache to be 10000: |
|-----------------|--|

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# cache entries 10000
```

# cache permanent

To disable the removal of entries from the monitor map flow cache, enter the **cache permanent** command in flow monitor map configuration mode. To re-enable the removal of entries from the flow cache, use the **no** form of this command.

**cache permanent**

| <b>Syntax Description</b> | This command has no keywords or arguments.  |         |              |               |                              |
|---------------------------|---|---------|--------------|---------------|------------------------------|
| <b>Command Default</b>    | The removal of entries from the monitor map flow cache is enabled.  |         |              |               |                              |
| <b>Command Modes</b>      | Flow monitor map configuration  |         |              |               |                              |
| <b>Command History</b>    | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> </tbody> </table> | Release | Modification | Release 3.9.1 | This command was introduced. |
| Release                   | Modification  |         |              |               |                              |
| Release 3.9.1             | This command was introduced.  |         |              |               |                              |
| <b>Usage Guidelines</b>   | No specific guidelines impact the use of this command.  |         |              |               |                              |

| Task ID | Task    | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

## Examples

This example shows how to disable the removal of entries from the monitor map flow cache:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)#flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# cache permanent
```

This example shows how to re-enable the removal of entries from the monitor map flow cache:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# no cache permanent
```

# cache immediate

To enable immediate aging cache type, use the **cache immediate** command in flow monitor map configuration mode. To disable, use **no** form of the command.

## cache immediate

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** Flow monitor map configuration

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 6.5.1 | This command was introduced. |

**Usage Guidelines** Immediate Aging is a special cache type that ensures that the flows are exported as soon as they are added to the cache.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

This example shows how to enable immediate aging cache type:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)#flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# cache immediate
```

## cache timeout

To configure the active, inactive, and update flow cache timeout, enter the **cache timeout** command in flow monitor map configuration mode. To remove the configured timeout value and return the cache to its default timeout value, use the **no** form of this command.

**cache timeout** {**active** | **inactive** | **update**} *timeout\_value*

| Syntax Description |                      |   |
|--------------------|----------------------|---|
|                    | <b>active</b>        | Specifies the active flow timeout.  |
|                    | <b>inactive</b>      | Specifies the inactive flow timeout.  |
|                    | <b>update</b>        | Specifies the update timeout.   |
|                    | <i>timeout_value</i> | Timeout value for the specified keyword ( <b>active</b> , <b>inactive</b> , or <b>update</b> ), in seconds. Range is from 1 through 604800. |

| Command Default |  |
|-----------------|--|
|                 | For active timeout, the default value is 1800 seconds. |
|                 | For inactive timeout, the default value is 15 seconds. |
|                 | For update timeout, the default value is 1800 seconds. |

| Command Modes |                                |
|---------------|--------------------------------|
|               | Flow monitor map configuration |

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

### Usage Guidelines



**Note** The **inactive** timeout value should be smaller than the **active** timeout value. The **update** keyword is used for permanent caches only. It specifies the timeout value that is used to export entries from permanent caches. In this case, the entries are exported but remain the cache.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

### Examples

This example shows how to set the active timeout for the monitor map cache to 200,000 seconds:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# cache timeout active 200000
```

# clear flow exporter

To export flow exporter templates to the collector or restart the flow exporter statistics collector, enter the **clear flow exporter** command in EXEC mode.

```
clear flow exporter [fem-name] {restart | statistics} location node-id
```

| Syntax Description             |  |
|--------------------------------|--|
| <i>fem-name</i>                | (Optional) Flow exporter name.   |
| <b>restart</b>                 | Exports all of the current templates to the collector.   |
| <b>statistics</b>              | Clears the exporter statistics.  |
| <b>location</b> <i>node-id</i> | Identifies the node whose flow exporter statistics you want to clear, or whose flow exporter statistics collector you want to restart. The <i>node-id</i> argument is expressed in the <i>rack/slot/module</i> notation. |

**Command Default** No default behavior or values

**Command Modes** EXEC mode

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID        | Operations     |
|---------|----------------|----------------|
|         | basic-services | read,<br>write |
|         | netflow        | read,<br>write |

## Examples

This example exports all templates to the collector:

```
RP/0/RSP0/CPU0:router# clear flow exporter restart location 0/0/SP  
Restart exporter all locations. Continue? [confirm]
```

This example shows how to clear flow exporter statistics on a specific node:

```
RP/0/RSP0/CPU0:router# clear flow exporter statistics location 0/0/CPU0  
Clear statistics for all exporters on the location. Continue? [confirm]
```

# clear flow monitor

To clear the flow monitor data, enter the **clear flow monitor** command in EXEC mode.

**clear flow monitor** [*name*] **cache** [**force-export** | **statistics**] **location** *node-id*

| Syntax Description             |  |
|--------------------------------|--|
| <i>name</i>                    | (Optional) Identifies a specific cache you want to clear.  |
| <b>cache</b>                   | Clears all cache related information.  |
| <b>force-export</b>            | (Optional) Forces the export of flow records on flushing the cache on the specified node.                                    |
| <b>statistics</b>              | (Optional) Clears cache statistics on a specific node.   |
| <b>location</b> <i>node-id</i> | Node whose flow monitor you want to clear. The <i>node-id</i> argument is expressed in the <i>rack/slot/module</i> notation. |

**Command Default** None

**Command Modes** EXEC mode

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task    | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

## Examples

This example shows how to clear the cache-related flow records on a specific node:

```
RP/0/RSP0/CPU0:router# clear flow monitor cache force-export location 0/0/CPU0
```

```
Clear cache entries for this monitor on this location. Continue? [confirm]
```



# clear flow platform producer statistics location

To clear statistics collected by the NetFlow producer, use the **clear flow platform producer statistics location** command in EXEC mode.

**clear flow platform producer statistics location** *node-id*

| <b>Syntax Description</b> | <p><i>node-id</i> Node on which to clear statistics collected by the NetFlow producer. The <i>node-id</i> is expressed in the <i>rack/slot/module</i> notation.</p> <p><b>Note</b> Enter the <b>show platform</b> command to see the location of all nodes installed in the router.</p> |         |              |               |                              |
|---------------------------|---|---------|--------------|---------------|------------------------------|
| <b>Command Default</b>    | None  |         |              |               |                              |
| <b>Command Modes</b>      | EXEC mode   |         |              |               |                              |
| <b>Command History</b>    | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> </tbody> </table>   | Release | Modification | Release 3.9.1 | This command was introduced. |
| Release                   | Modification  |         |              |               |                              |
| Release 3.9.1             | This command was introduced.  |         |              |               |                              |
| <b>Usage Guidelines</b>   | No specific guidelines impact the use of this command.  |         |              |               |                              |
| <b>Task ID</b>            | <table border="1"> <thead> <tr> <th>Task ID</th> <th>Operations</th> </tr> </thead> <tbody> <tr> <td>netflow</td> <td>read,<br/>write</td> </tr> </tbody> </table>  | Task ID | Operations   | netflow       | read,<br>write               |
| Task ID                   | Operations  |         |              |               |                              |
| netflow                   | read,<br>write  |         |              |               |                              |
| <b>Examples</b>           | <p>This example shows how to clear statistics collected by the NetFlow producer:</p> <pre>RP/0/RSP0/CPU0:router# clear flow platform producer statistics location 0/0/CPU0</pre>  |         |              |               |                              |

## destination

To configure the collector export destination, enter the **destination** command in flow exporter map configuration mode. To remove a configured export destination, use the **no** form of this command.

**destination** *hostname\_or\_IP\_address* [**vrf** *vrf\_name*]

| Syntax Description            |   |
|-------------------------------|---|
| <i>hostname_or_IP_address</i> | Specify the export destination for the current flow exporter map. Enter the hostname or destination IP address in the <i>A.B.C.D</i> format.  |
| <b>vrf</b> <i>vrf_name</i>    | (Optional) Specify the name of the VRF that is used to reach export destination. This is an optional keyword. If the <b>vrf</b> keyword is specified, then the destination is searched in the VRF that is specified ( <i>vrf_name</i> ). If the <b>vrf</b> keyword is not specified then, the destination is searched in the default routing table. |

**Command Default** None

**Command Modes** Flow exporter map configuration

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task    | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

**Examples** This example shows how to configure the flow exporter map export destination to be a specific IP address:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1
RP/0/RSP0/CPU0:router(config-fem)# destination 172.18.189.38
```

# dscp

To configure the differentiated services codepoint (DSCP) value for export packets, enter the **dscp** command in flow exporter map configuration mode. To remove a configured DSCP value, use the **no** form of this command.

**dscp** *dscp\_value*

| <b>Syntax Description</b> | <i>dscp_value</i> Specifies the DSCP value for export packets. Replace <i>dscp_value</i> with a number. Range is from 0 through 63.   |         |              |               |                              |
|---------------------------|---|---------|--------------|---------------|------------------------------|
| <b>Command Default</b>    | None  |         |              |               |                              |
| <b>Command Modes</b>      | Flow exporter map configuration   |         |              |               |                              |
| <b>Command History</b>    | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> </tbody> </table> | Release | Modification | Release 3.9.1 | This command was introduced. |
| Release                   | Modification  |         |              |               |                              |
| Release 3.9.1             | This command was introduced.  |         |              |               |                              |
| <b>Usage Guidelines</b>   | No specific guidelines impact the use of this command.  |         |              |               |                              |
| <b>Task ID</b>            | <table border="1"> <thead> <tr> <th>Task ID</th> <th>Operations</th> </tr> </thead> <tbody> <tr> <td>netflow</td> <td>read,<br/>write</td> </tr> </tbody> </table>                      | Task ID | Operations   | netflow       | read,<br>write               |
| Task ID                   | Operations  |         |              |               |                              |
| netflow                   | read,<br>write  |         |              |               |                              |

## Examples

This example shows how to configure the DSCP value for export packets to be 30:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1
RP/0/RSP0/CPU0:router(config-fem)# dscp 30
```

# exporter

To associate a flow exporter map with the current flow monitor map, enter the **exporter** command in flow monitor map configuration mode. To remove an associated flow exporter map from a flow monitor map, use the **no** form of this command.

**exporter** *map\_name*

## Syntax Description

*map\_name* Name of the flow exporter map you want to associate with the current flow monitor map. The exporter map name can be a maximum of 32 characters.

**Note** A single flow monitor map supports up to 8 exporters. Only the first five will be used.

## Command Default

None

## Command Modes

Flow monitor map configuration

## Command History

| Release       | Modification                 |
|---------------|------------------------------|
| Release 3.9.1 | This command was introduced. |

## Usage Guidelines

No specific guidelines impact the use of this command.

## Task ID

| Task ID | Operations     |
|---------|----------------|
| netflow | read,<br>write |

## Examples

This example shows how to associate a flow exporter map called “fem\_1” with the current flow monitor map:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# exporter fem_1
```

# flow

To specify a flow monitor map and a sampler map for the packets on an interface, use the **flow** command in interface configuration mode. To remove a configured flow monitor map, use the **no** form of this command.

**flow** [**ipv4** | **ipv6** | **mpls**] **monitor** *name* **sampler** *name* {**egress** | **ingress**}

| Syntax Description         |  |   |
|----------------------------|--|---|
| <b>ipv4</b>                |  | Enables IPV4 NetFlow on the specified interface.  |
| <b>ipv6</b>                |  | Enables IPV6 NetFlow on the specified interface.  |
| <b>mpls</b>                |  | Enables Multiprotocol Label Switching (MPLS)-aware NetFlow on the specified interface.          |
| <b>monitor</b> <i>name</i> |  | Specifies the name of the flow monitor map you want to specify for IPv4, IPv6, or MPLS packets. |
| <b>sampler</b> <i>name</i> |  | Name of the sampler map you want to apply to the flow monitor map.                              |
| <b>egress</b>              |  | Applies the flow monitor map on outgoing packets.   |
| <b>ingress</b>             |  | Applies the flow monitor map on incoming packets.   |

**Command Default** None

**Command Modes** Interface configuration

| Command History | Release       | Modification  |
|-----------------|---------------|---|
|                 | Release 3.9.1 | This command was introduced.  |
|                 | Release 4.3.1 | The support for NetFlow over Bridge-group Virtual Interface was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

## Examples

This example shows how to enable IPV4 NetFlow on a GigabitEthernet interface, and then apply the flow monitor map, named "map1," on outgoing IPv4 packets:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# interface GigabitEthernet 0/4/0/0
RP/0/RSP0/CPU0:router(config-if)# flow ipv4 monitor map1 sampler smap1 ingress
RP/0/RSP0/CPU0:router(config-if)# flow ipv4 monitor NMS sampler NMS egress
```

This example shows how to enable MPLS NetFlow on a GigabitEthernet interface, and apply the flow monitor map, named "map\_mpls1," on outgoing MPLS packets:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# interface gigabit Ethernet 0/0/0/0
RP/0/RSP0/CPU0:router(config-if)# flow mpls monitor map_mpls1 sampler smap1 egress
```

This example shows how to enable IPv4 NetFlow on a Bridge-group virtual interface, and then apply the flow monitor map on incoming and outgoing IPv4 packets:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# interface BVI 1
RP/0/RSP0/CPU0:router(config-if)# flow ipv4 monitor NMS sampler NMS ingress
RP/0/RSP0/CPU0:router(config-if)# flow ipv4 monitor NMS sampler NMS egress
```

This example shows how to enable IPv6 NetFlow on a Bridge-group virtual interface, and then apply the flow monitor map on incoming and outgoing IPv6 packets:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# interface BVI 1
RP/0/RSP0/CPU0:router(config-if)# flow ipv6 monitor NMS sampler NMS ingress
RP/0/RSP0/CPU0:router(config-if)# flow ipv6 monitor NMS sampler NMS egress
```

## flow datalinkframesection monitor

To monitor and capture information element that carries  $n$  octets from the data link frame (IPFIX 315) of a selected frame in the ingress direction of an interface, use **flow datalinkframesection monitor** command in interface configuration mode.

**flow datalinkframesection monitor** *monitor-map* **sampler** *sampler-map* **ingress**

|                           |   |   |
|---------------------------|---|---|
| <b>Syntax Description</b> | <b>monitor</b> <i>monitor-map</i>   | Specify flow monitor map name.  |
|                           | <b>sampler</b> <i>sampler-map</i>   | Specify flow sampler map name.  |
|                           | <b>ingress</b>  | Specify ingress direction. The IPFIX 315 info is captured from incoming traffic on specified interface. |
| <b>Command Default</b>    | None.   |   |
| <b>Command Modes</b>      | Interface configuration mode  |   |
| <b>Command History</b>    | <b>Release</b>  | <b>Modification</b>   |
|                           | Release 6.5.1   | This command was introduced.  |
| <b>Usage Guidelines</b>   | When datalinkframesection flow type is enabled on an interface, other flows like IPv4, IPv6 and MPLS are not allowed. The option field in the frame indicates the IPFIX 315 info. |   |
| <b>Task ID</b>            | <b>Task ID</b>  | <b>Operation</b>  |
|                           | netflow   | read,<br>write  |

This sample shows how to enable flow datalinkframesection monitor on hundredGigE interface:

```
RP/0/RSP0/CPU0:router(config)#interface hundredGigE 0/0/0/18
RP/0/RSP0/CPU0:router(config-if)#flow datalinkframesection monitor ipfix-mon sampler ipfix-sam
ingress
```

## flow exporter-map

To create a flow exporter map and enter flow exporter map configuration mode, use the **flow exporter-map** command in Global Configuration mode. To remove a configured flow exporter map, use the **no** form of this command.

**flow exporter-map** *fem-name*

|                           |   |
|---------------------------|---|
| <b>Syntax Description</b> | <i>fem-name</i> Creates a new exporter map name, or specifies the name of an existing exporter map. |
|---------------------------|---|

|                        |      |
|------------------------|------|
| <b>Command Default</b> | None |
|------------------------|------|

|                      |                           |
|----------------------|---------------------------|
| <b>Command Modes</b> | Global Configuration mode |
|----------------------|---------------------------|

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|------------------------|----------------|------------------------------|
|                        | Release 3.9.1  | This command was introduced. |

|                         |   |
|-------------------------|---|
| <b>Usage Guidelines</b> | When you issue the <b>flow exporter-map</b> <i>fem-name</i> command in global configuration mode, the CLI prompt changes to “config-fem,” indicating that you have entered the flow exporter map configuration submenu. |
|-------------------------|---|

In this sample output, the question mark ( ? ) online help function displays all the commands available under flow exporter map configuration submenu:

```
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1
RP/0/RSP0/CPU0:router(config-fem)# ?

RP/0/RSP0/CPU0:routerconfig-fem)#?
  clear          Clear the uncommitted configuration
  commit         Commit the configuration changes to running
  describe       Describe a command without taking real actions
  destination     Export destination configuration
  do             Run an exec command
  dscp           Specify DSCP value for export packets
  exit           Exit from this submenu
  no            Negate a command or set its defaults
  pwd           Commands used to reach current submenu
  root          Exit to the global configuration mode
  show          Show contents of configuration
  source        Source interface
  transport     Specify the transport protocol for export packets
  version       Specify export version parameters
```

| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|----------------|----------------|-------------------|
|                | netflow        | read,<br>write    |

|                 |  |
|-----------------|--|
| <b>Examples</b> | This example shows how to create a flow exporter map called “map1,” and then enter the flow exporter map configuration submenu for that map: |
|-----------------|--|



```
RP/0/RSP0/CPU0:router# configure  
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1  
RP/0/RSP0/CPU0:router(config-fem)#
```

## flow monitor-map

To create and configure a flow monitor map and enter flow monitor map configuration submode, use the **flow monitor-map** command in Global Configuration mode. To remove a configured flow monitor map, use the **no** form of this command:

```
flow monitor-map map_name
```

|                           |  |
|---------------------------|--|
| <b>Syntax Description</b> | <i>map_name</i> New monitor map name, or specifies the name of an existing monitor map. The monitor map name can be a maximum 32 characters. |
|---------------------------|--|

|                        |      |
|------------------------|------|
| <b>Command Default</b> | None |
|------------------------|------|

|                      |                           |
|----------------------|---------------------------|
| <b>Command Modes</b> | Global Configuration mode |
|----------------------|---------------------------|

|                        |                |                              |
|------------------------|----------------|------------------------------|
| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|                        | Release 3.9.1  | This command was introduced. |

**Usage Guidelines** When you issue the **flow monitor-map** *map\_name* command in Global Configuration mode, the CLI prompt changes to “config-fmm,” indicating that you have entered the flow monitor map configuration submode. In the following sample output, the question mark ( ? ) online help function displays all the commands available under flow monitor map configuration submode:

```
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)#?

cache      Specify flow cache attributes
clear      Clear the uncommitted configuration
commit     Commit the configuration changes to running
describe   Describe a command without taking real actions
do         Run an exec command
exit       Exit from this submode
exporter   Specify flow exporter map name
no         Negate a command or set its defaults
pwd        Commands used to reach current submode
record     Specify a flow record map name
record ipv4 Encapsulates PE L2-L3 record for ipv4
record ipv6 Encapsulates PE L2-L3 record for ipv6
root       Exit to the global configuration mode
show       Show contents of configuration
```

|                |                |                   |
|----------------|----------------|-------------------|
| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|                | netflow        | read,<br>write    |

**Examples** This example shows how to enter flow monitor map configuration mode for a monitor map called “map1:”

```
RP/0/RSP0/CPU0:router# configure  
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1  
RP/0/RSP0/CPU0:router(config-fmm)#
```

# options

To export the tables in the options template and specify export timeout values, enter the **options** command in flow exporter map version configuration mode. To return the options template to its default configuration values, use the **no** form of this command.

**options** {**interface-table** | **sampler-table** | **vrf-table**} [**timeout** *seconds*]

## Syntax Description

**interface-table** Export the interface table.

**sampler-table** Exports the sampler table.

Use **options sampler-table timeout** command to send IE 305. This command configures the timeout value for the sampler table. This timeout value can be in the range 1–604800 seconds and the default value is 1800 seconds.

You can also use **options sampler-table** command to export the following IEs:

- IE 302—to export selector ID.
- IE 304—to export sampling algorithm.
- IE 309—to export sampling size.
- IE 310—to export sampling population.
- IE 84—to export sampler name.
- IE 335—to export selector name.

IE 309, IE 310, and IE 335 are supported starting from Release 7.8.2

**vrf-table** Exports the VRF to VRF-Name table.

**timeout** *seconds* Specifies the export timeout value. Replace *seconds* with the export timeout value. Range is from 1 through 604800 seconds.

## Command Default

Without options command, the default value for timeout is 0 seconds, which means that the template options are not exported by default. Where as when options command is used without mentioning any timeout, default timeout is 1800 seconds.

## Command Modes

Flow exporter map version configuration

## Command History

| Release       | Modification                          |
|---------------|---------------------------------------|
| Release 3.9.1 | This command was introduced.          |
| Release 5.2.0 | The keyword vrf-table was introduced. |

## Usage Guidelines

No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

### Examples

This example shows how to export the timeout in the interface table to the options template.

```
RP/0/RSP0/CPU0:router(config)# flow exporter-map f1
RP/0/RSP0/CPU0:router(config-fem)# version v9
RP/0/RSP0/CPU0:router(config-fem)# options interface-table timeout 45
```

### Examples

This is the sample output after setting to export the interface table and configure the export timeout value:

```
RP/0/RSP0/CPU0:router(config-fem-ver)# show running-config flow exporter-map f1
flow exporter-map f1
  version v9
  options vrf-table 50
  !
  transport udp 9321
  source HundredGigE 0/4/3/0
  destination 10.64.81.237
  !

RP/0/RSP0/CPU0:router(config-fem-ver)# do show flow exporter-map f1

Flow Exporter Map : f1
-----
Id                : 21
DestinationIpAddr : 10.64.81.237
SourceIfName      : HundredGigE 0/4/3/0
SourceIpAddr      : 0.0.0.0
DSCP              : 0
TransportProtocol : UDP
TransportDestPort : 9321

Export Version: 9
  Common Template Timeout : 1800 seconds
  Options Template Timeout : 1800 seconds
  Data Template Timeout   : 1800 seconds
  Interface-Table Export Timeout : 0 seconds
  Sampler-Table Export Timeout : 0 seconds
  VRF-Table Export Timeout  : 50 seconds

RP/0/RSP0/CPU0:router(config-fem-ver)# do show running-config flow exporter-map f1
flow exporter-map f1
  version v9
  options interface-table
  options sampler-table
  options vrf-table
  !
  transport udp 9321
  source HundredGigE 0/4/3/0
  destination 10.64.81.237
  !
RP/0/RSP0/CPU0:router(config-fem-ver)# show flow exporter-map f1
```

Flow Exporter Map : f1

```
-----  
Id : 21  
DestinationIpAddr : 10.64.81.237  
SourceIfName : HundredGigE 0/4/3/0  
SourceIpAddr : 0.0.0.0  
DSCP : 0  
TransportProtocol : UDP  
TransportDestPort : 9321
```

Export Version: 9

```
Common Template Timeout : 1800 seconds  
Options Template Timeout : 1800 seconds  
Data Template Timeout : 1800 seconds  
Interface-Table Export Timeout : 1800 seconds  
Sampler-Table Export Timeout : 1800 seconds  
VRF-Table Export Timeout : 1800 seconds
```

# option filtered

To enable filtering of the Netflow records, use **option filtered** command in flow monitor map configuration mode.

## option filtered

|                           |  |
|---------------------------|--|
| <b>Syntax Description</b> | <b>filtered</b> Enables filtering of records |
|---------------------------|--|

|                        |                             |
|------------------------|-----------------------------|
| <b>Command Default</b> | Flow filtering is disabled. |
|------------------------|-----------------------------|

|                      |                                |
|----------------------|--------------------------------|
| <b>Command Modes</b> | Flow monitor map configuration |
|----------------------|--------------------------------|

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|------------------------|----------------|------------------------------|
|                        | Release 6.0.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | MPLS netflow filtering is not supported. |
|-------------------------|--|

Since the filtering of packets is based on the ACL, you must define ACL configuration before using **option filtered** command. Use the **capture** keyword while defining ACL. For example:

```
ipv4 access-list nf_ex
 10 permit ipv4 10.1.1.1/24 any capture
```

| <b>Task ID</b> | <b>Task ID</b> | <b>Operation</b> |
|----------------|----------------|------------------|
|                | netflow        | read,<br>write   |

This example shows how to create flow monitor map that filters Netflow records with cache entries upto 10000:

```
RP/0/RSP0/CPU0:router# config
RP/0/RSP0/CPU0:router(config)# flow monitor-map fmm1
RP/0/RSP0/CPU0:router(config-fmm)# record ipv4
RP/0/RSP0/CPU0:router(config-fmm)# option filtered
RP/0/RSP0/CPU0:router(config-fmm)# exporter fem1
RP/0/RSP0/CPU0:router(config-fmm)# cache entries 10000
RP/0/RSP0/CPU0:router(config-fmm)# cache timeout active 1800
RP/0/RSP0/CPU0:router(config-fmm)# cache timeout inactive 15
RP/0/RSP0/CPU0:router(config-fmm)# exit
```

# random 1 out-of

To configure the packet sampling interval for a sampler map, use the **random 1 out-of** command in sampler map configuration submenu. To remove a configured sampling interval and return to the default sampling interval, use the **no** form of this command. The limit of sampling rate values per line card per direction is 4, and limit of total samplers per line card per direction is 16.

**random 1 out-of** *number\_of\_packets*

| <b>Syntax Description</b> | <i>number_of_packets</i> Sampling interval in units of packets. Replace the <i>number_of_packets</i> argument with a number. Range is from 1 through 65535 units.  |         |              |               |                              |
|---------------------------|--|---------|--------------|---------------|------------------------------|
| <b>Command Default</b>    | There is no default value to <i>number_of_packets</i> . However, for optimal performance, the recommended value for <i>number_of_packets</i> is 10000.   |         |              |               |                              |
| <b>Command Modes</b>      | Sampler map configuration  |         |              |               |                              |
| <b>Command History</b>    | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> </tbody> </table>  | Release | Modification | Release 3.9.1 | This command was introduced. |
| Release                   | Modification   |         |              |               |                              |
| Release 3.9.1             | This command was introduced.   |         |              |               |                              |
| <b>Usage Guidelines</b>   | <p>On Cisco ASR 9000 High Density 100GE Ethernet line cards, when the configured sampling rate is one of the following values, the sampling behavior is random with a deviation of more than 10 percent:</p> <ul style="list-style-type: none"> <li>• 2048</li> <li>• 4096</li> <li>• 8192</li> <li>• 16384</li> <li>• 32768</li> <li>• 65535</li> </ul> |         |              |               |                              |

| Task ID | Task    | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

## Examples

This example shows how to configure the sampler map to randomly sample 1 out of every 10 packets:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# sampler map1
RP/0/RSP0/CPU0:router(config-sm)# random 1 out-of 10
```



# record ipv4

To activate an IPv4 flow record, use the **record ipv4** command in flow monitor map configuration mode. To deactivate the flow record, use the **no** form of this command.

```
record ipv4 [ peer-as || destination-tos | |[srv6][12-13] ]
```

| Syntax Description | peer-as                | (Optional) Records peer AS.   |
|--------------------|------------------------|---|
|                    | <b>Note</b>            | The Border Gateway Protocol (BGP) AS is not collected unless the <b>bgp attribute download</b> command is configured. |
|                    | <b>destination-tos</b> | (Optional) Records IPv4 destination based NetFlow accounting.   |
|                    | <b>srv6</b>            | Records SRv6 based NetFlow data.  |
|                    | <b>12-13</b>           | Records L2 and L3 specific NetFlow data.  |

**Command Default** The default is that no IPv4 flow record is enabled.

**Command Modes** Flow monitor map configuration

| Command History | Release        | Modification   |
|-----------------|----------------|--|
|                 | Release 3.9.1  | This command was introduced.   |
|                 | Release 4.2.0  | The <b>destination-tos</b> keyword was added to support destination-based Netflow accounting.  |
|                 | Release 7.10.1 | This command was modified and the following optional keywords were introduced for the <code>record ipv4</code> option: <ul style="list-style-type: none"> <li>• <code>srv6</code></li> <li>• <code>12-13</code></li> </ul> <p>This keywords are supported on 4th generation and later ASR 9000 line cards.</p> |

- Usage Guidelines**
- The BGP AS is not collected unless the **bgp attribute download** command is configured.
  - The **record ipv4** command exports the BGP AS information in the following format:
 

```
bgpSourceAsNumber
bgpDestinationAsNumber
```
  - The **record ipv4 peer-as** command exports the adjacent BGP AS information in the following format:
 

```
bgpPrevAdjacentAsNumber
bgpNextAdjacentAsNumber
```

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

## Examples

This example shows how to configure an IPv4 flow record:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# record ipv4
```

This example shows how to configure an IPv4 flow record for destination-based NetFlow accounting:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# record ipv4 destination-tos
RP/0/RSP0/CPU0:router(config-fmm)# exit
RP/0/RSP0/CPU0:router(config)# interface Gigabit Ethernet 0/0/0/0
RP/0/RSP0/CPU0:router(config-if)# flow ipv4 monitor monitor1 ingress
RP/0/RSP0/CPU0:router(config-if)# end
```

This example shows how to configure the srv6 flow record map name for the record ipv4 option:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config-fem)# flow monitor-map MON-MAP-v6
RP/0/RSP0/CPU0:router(config-fmm)# record ipv6 srv6
RP/0/RSP0/CPU0:router(config-fmm)# exporter EXP
RP/0/RSP0/CPU0:router(config-fmm)# cache timeout inactive 5
RP/0/RSP0/CPU0:router(config-fmm)# !
RP/0/RSP0/CPU0:router(config-fmm)# sampler-map SAMP
RP/0/RSP0/CPU0:router(config-fmm)# random 1 out-of 1000
RP/0/RSP0/CPU0:router(config-fmm)# !
RP/0/RSP0/CPU0:router(config-fmm)# interface GigabitEthernet0/1/0/0
RP/0/RSP0/CPU0:router(config-fmm)# ipv4 address 1.1.1.1 255.255.255.0
RP/0/RSP0/CPU0:router(config-fmm)# flow ipv6 monitor M1 sampler SAMP ingres
```

This example shows how to configure the 12-13 flow record map name for the record ipv4 option:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config-fem)# flow monitor-map M-IPv4
RP/0/RSP0/CPU0:router(config-fmm)# record ipv4 12-13
RP/0/RSP0/CPU0:router(config-fmm)# exporter EXP-ipfix
RP/0/RSP0/CPU0:router(config-fmm)# !
RP/0/RSP0/CPU0:router(config-fmm)# flow monitor-map M-IPv6
RP/0/RSP0/CPU0:router(config-fmm)# record ipv6 12-13
RP/0/RSP0/CPU0:router(config-fmm)# exporter EXP-ipfix
RP/0/RSP0/CPU0:router(config-fmm)# !
RP/0/RSP0/CPU0:router(config-fmm)# sampler-map SAMP
RP/0/RSP0/CPU0:router(config-fmm)# random 1 out-of 1000
RP/0/RSP0/CPU0:router(config-fmm)# !
RP/0/RSP0/CPU0:router(config-fmm)# interface GigabitEthernet0/1/0/0
```

```
RP/0/RSP0/CPU0:router(config-fmm) # description CE-PE Interface  
RP/0/RSP0/CPU0:router(config-fmm) # ipv4 address<>  
RP/0/RSP0/CPU0:router(config-fmm) # ipv6 address<>  
RP/0/RSP0/CPU0:router(config-fmm) # flow ipv4 monitor M-IPv4 sampler SAMP ingres  
RP/0/RSP0/CPU0:router(config-fmm) # flow ipv6 monitor M-IPv6 sampler SAMP ingress  
RP/0/RSP0/CPU0:router(config-fmm) # !  
RP/0/RSP0/CPU0:router
```

# record ipv6

To configure the flow record map name for IPv6, use the **record ipv6** command in flow monitor map configuration mode. To remove the configured name from a flow record, use the **no** form of this command.

```
record ipv6 { | [srv6][l2-l3] }
```

| Syntax Description |  |  |
|--------------------|--|--|
| <b>peer-as</b>     |  | Records peer AS.                         |
| <b>srv6</b>        |  | Records SRv6 based NetFlow data.         |
| <b>l2-l3</b>       |  | Records L2 and L3 specific NetFlow data. |

**Command Default** The default is that originating AS numbers are recorded.

**Command Modes** Flow monitor map configuration

| Command History | Release        | Modification  |
|-----------------|----------------|---|
|                 | Release 3.9.1  | This command was introduced.  |
|                 | Release 7.10.1 | This command was modified and the following optional keywords were introduced for the <code>record ipv6</code> option: <ul style="list-style-type: none"> <li>• <code>srv6</code></li> <li>• <code>l2-l3</code></li> </ul> This keywords are supported on 4th generation and later ASR 9000 line cards. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

## Examples

This example shows how to configure the flow record map name for IPv6:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# record ipv6
```

This example shows how to configure the `srv6` flow record map name for the `record ipv6` option:

```
RP/0/RSP0/CPU0:router# configure
```

```

RP/0/RSP0/CPU0:router(config-fem) # flow monitor-map MON-MAP-v6
RP/0/RSP0/CPU0:router(config-fmm) # record ipv6 srv6
RP/0/RSP0/CPU0:router(config-fmm) # exporter EXP
RP/0/RSP0/CPU0:router(config-fmm) # cache timeout inactive 5
RP/0/RSP0/CPU0:router(config-fmm) # !
RP/0/RSP0/CPU0:router(config-fmm) # sampler-map SAMP
RP/0/RSP0/CPU0:router(config-fmm) # random 1 out-of 1000
RP/0/RSP0/CPU0:router(config-fmm) # !
RP/0/RSP0/CPU0:router(config-fmm) # interface GigabitEthernet0/1/0/0
RP/0/RSP0/CPU0:router(config-fmm) # ipv6 address 2001:DB8:c18:1::/64
RP/0/RSP0/CPU0:router(config-fmm) # flow ipv6 monitor M1 sampler SAMP ingres

```

This example shows how to configure the 12-13 flow record map name for the record ipv6 option:

```

RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config-fem) # flow monitor-map M-IPv4
RP/0/RSP0/CPU0:router(config-fmm) # record ipv4 12-13
RP/0/RSP0/CPU0:router(config-fmm) # exporter EXP-ipfix
RP/0/RSP0/CPU0:router(config-fmm) # !
RP/0/RSP0/CPU0:router(config-fmm) # flow monitor-map M-IPv6
RP/0/RSP0/CPU0:router(config-fmm) # record ipv6 12-13
RP/0/RSP0/CPU0:router(config-fmm) # exporter EXP-ipfix
RP/0/RSP0/CPU0:router(config-fmm) # !
RP/0/RSP0/CPU0:router(config-fmm) # sampler-map SAMP
RP/0/RSP0/CPU0:router(config-fmm) # random 1 out-of 1000
RP/0/RSP0/CPU0:router(config-fmm) # !
RP/0/RSP0/CPU0:router(config-fmm) # interface GigabitEthernet0/1/0/0
RP/0/RSP0/CPU0:router(config-fmm) # description CE-PE Interface
RP/0/RSP0/CPU0:router(config-fmm) # ipv4 address<>
RP/0/RSP0/CPU0:router(config-fmm) # ipv6 address<>
RP/0/RSP0/CPU0:router(config-fmm) # flow ipv4 monitor M-IPv4 sampler SAMP ingres
RP/0/RSP0/CPU0:router(config-fmm) # flow ipv6 monitor M-IPv6 sampler SAMP ingress
RP/0/RSP0/CPU0:router(config-fmm) # !
RP/0/RSP0/CPU0:router

```

# record mpls

To configure the flow record map name for MPLS, use the **record mpls** command in flow monitor map configuration mode. To remove the configured name from a flow record, use the **no** form of this command.

**record mpls** [**ipv4-fields**] [**ipv6-fields**] [**ipv4-ipv6-fields**] [**labels** *number*]

| Syntax Description          |   |
|-----------------------------|---|
| <b>ipv4-fields</b>          | (Optional) Collects IPv4 fields in the MPLS-aware Netflow when the payload of the MPLS packet has IPv4 fields. It also collects MPLS traffic with no IPv4 payload, but the IPv4 fields are set to zero.                                     |
| <b>ipv6-fields</b>          | (Optional) Collects IPv6 fields in the MPLS-aware Netflow when the payload of the MPLS packet has IPv6 fields. It also collects MPLS traffic with no IPv6 payload, but the IPv6 fields are set to zero.                                     |
| <b>ipv4-ipv6-fields</b>     | (Optional) Collects IPv4 and IPv6 fields in the MPLS-aware Netflow when the payload of the MPLS packet has either IPv4 fields or IPv6 fields. It also collects MPLS traffic with no IPv4 or IPv6 payload, but those fields are set to zero. |
| <b>labels</b> <i>number</i> | (Optional) Configures the number of labels that are used in hashing. The <i>number</i> argument is the number of labels that are used in hashing. The range is from 1 to 6.   |

**Command Default** The default is no IPV4 fields and six labels.

**Command Modes** Flow monitor map configuration

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** In Cisco IOS XR software, you can have only one MPLS flow monitor running on an interface at a time. If you apply an additional MPLS flow monitor to the interface, the new flow monitor overwrites the existing one.

You can configure the MPLS flow monitor to collect IPv4 fields, IPv6 fields, or both types of fields.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

**Examples** This configuration allows you to collect only MPLS fields. No payload information is collected.

```
RP/0/RSP0/CPU0:router(config)# flow monitor-map MPLS-fmm
RP/0/RSP0/CPU0:router(config-fmm)# record mpls labels 3
RP/0/RSP0/CPU0:router(config-fmm)# cache permanent
RP/0/RSP0/CPU0:router(config)# exit
```

```
RP/0/RSP0/CPU0:router(config)# interface Gigabit Ethernet 0/0/0/0
RP/0/RSP0/CPU0:router(config-if)# flow mpls monitor MPLS-fmm sampler fsm ingress
```

This configuration allows you to collect MPLS traffic with IPv4 fields. It also collects MPLS traffic with no IPv4 payload, but the IPv4 fields are set to zero.

```
RP/0/RSP0/CPU0:router(config)# flow monitor-map MPLS-IPv4-fmm
RP/0/RSP0/CPU0:router(config-fmm)# record mpls IPv4-fields labels 3
RP/0/RSP0/CPU0:router(config-fmm)# cache permanent
RP/0/RSP0/CPU0:router(config-fmm)# exit
RP/0/RSP0/CPU0:router(config)# interface gigabitEthernet 0/0/0/0
RP/0/RSP0/CPU0:router(config-if)# flow mpls monitor MPLS-IPv4-fmm sampler fsm ingress
```

This configuration allows you to collect MPLS traffic with IPv6 fields. It also collects MPLS traffic with no IPv6 payload, but the IPv6 fields are set to zero.

```
RP/0/RSP0/CPU0:router(config)# flow monitor-map MPLS-IPv6-fmm
RP/0/RSP0/CPU0:router(config-fmm)# record mpls IPv6-fields labels 3
RP/0/RSP0/CPU0:router(config-fmm)# cache permanent
RP/0/RSP0/CPU0:router(config-fmm)# exit
RP/0/RSP0/CPU0:router(config)# interface gigabitEthernet 0/0/0/0
RP/0/RSP0/CPU0:router(config-if)# flow mpls monitor MPLS-IPv6-fmm sampler fsm ingress
```

This configuration allows you to collect MPLS traffic with both IPv6 and IPv4 fields. It also collects MPLS traffic with no IPv4 or IPv6 payload, but those fields are set to zero.

```
RP/0/RSP0/CPU0:router(config)# flow monitor-map MPLS-IPv4-IPv6-fmm
RP/0/RSP0/CPU0:router(config-fmm)# record mpls IPv4-IPv6-fields labels 3
RP/0/RSP0/CPU0:router(config-fmm)# cache permanent
RP/0/RSP0/CPU0:router(config-fmm)# exit
RP/0/RSP0/CPU0:router(config)# interface gigabitEthernet 0/0/0/0
RP/0/RSP0/CPU0:router(config-if)# flow mpls monitor MPLS-IPv4-IPv6-fmm sampler fsm ingress
```

This example shows how to configure three labels for hashing:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow monitor-map map1
RP/0/RSP0/CPU0:router(config-fmm)# record mpls labels 3
```

## record datalinksection

To record the information element that carries  $n$  octets from the data link frame (IPFIX 315), use the **record datalinksection** command in flow monitor map configuration mode. To disable recording, use the **no** form of this command.

**record datalinksection**

**Syntax Description** This command has no keywords or arguments.

**Command Default** None

**Command Modes** Flow monitor map configuration

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 6.5.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

### Examples

This configuration allows you to collect IPFIX 315 element information:

```
RP/0/RSP0/CPU0:router(config)# flow monitor-map ipfix-mon
RP/0/RSP0/CPU0:router(config-fmm)# record datalinkframesection
RP/0/RSP0/CPU0:router(config-fmm)# cache immediate
RP/0/RSP0/CPU0:router(config)# exit
RP/0/RSP0/CPU0:router(config)# interface Gigabit Ethernet 0/0/0/1
RP/0/RSP0/CPU0:router(config-if)# flow datalinkframesection monitor ipfix-mon sampler
ipfix-sm ingress
```



# sampler-map

To enter sampler map configuration submode for a specific monitor map, use the **sampler-map** command in Global Configuration mode. To remove a configured sampler map, use the **no** form of this command.

**sampler-map** *map\_name*

| <b>Syntax Description</b> | <i>map_name</i> Name of the sampler map you want to configure. The sampler map name can be a maximum 32 characters.  |         |              |               |                              |
|---------------------------|--|---------|--------------|---------------|------------------------------|
| <b>Command Default</b>    | None   |         |              |               |                              |
| <b>Command Modes</b>      | Global Configuration mode  |         |              |               |                              |
| <b>Command History</b>    | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> </tbody> </table>  | Release | Modification | Release 3.9.1 | This command was introduced. |
| Release                   | Modification   |         |              |               |                              |
| Release 3.9.1             | This command was introduced.   |         |              |               |                              |
| <b>Usage Guidelines</b>   | <p>When you issue the <b>sampler-map</b> <i>map_name</i> command in Global Configuration mode, the CLI prompt changes to “config-sm,” indicating that you have entered the sampler map configuration submode. In this sample output, the question mark ( ? ) online help function displays all the commands available under sampler map configuration submode:</p> <pre>RP/0/RSP0/CPU0:router(config)# <b>sampler-map test</b> RP/0/RSP0/CPU0:router(config-sm)# ?  clear      Clear the uncommitted configuration commit     Commit the configuration changes to running describe   Describe a command without taking real actions do         Run an exec command exit       Exit from this submode no         Negate a command or set its defaults pwd        Commands used to reach current submode random     Use random mode for sampling packets root       Exit to the global configuration mode show       Show contents of configuration</pre> <p>These restrictions prevent the NetFlow processes from using up all of the available CPU:</p> <ul style="list-style-type: none"> <li>• NetFlow supports a policer rate of 35,000 packets per second per direction for each individual line card.</li> <li>• NetFlow supports a policer rate of 50,000 packets per second per direction for each individual line card if Sampled NetFlow (SNF) is enabled in one direction (ingress or egress). Note that this limit does not apply if SNF is enabled in both directions. If SNF is enabled in both directions, then NetFlow supports 25,000 packets per second per direction for each individual line card.</li> </ul> |         |              |               |                              |

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

---

**Examples**

This example shows how to use the **sampler-map** command to enter sampler map configuration submode for the monitor map called “map1:”

```
RP/0/RSP0/CPU0:router# configure  
RP/0/RSP0/CPU0:router(config)# sampler-map map1  
RP/0/RSP0/CPU0:router(config-sm)#
```

# show flow exporter

To display flow exporter data, enter the **show flow exporter** command in EXEC mode.

```
show flow exporter [exporter_name] location node-id
```

## Syntax Description

*exporter\_name* Identifies the flow exporter whose data you want to display.

**location** *node-id* Location where the cache resides. The *node-id* argument is expressed in the *rack/slot/module* notation.

**Note** Enter the **show platform** command to see the location of all nodes installed in the router.

## Command Default

None

## Command Modes

EXEC mode

## Command History

| Release       | Modification                 |
|---------------|------------------------------|
| Release 3.9.1 | This command was introduced. |

## Usage Guidelines

No specific guidelines impact the use of this command.

## Task ID

| Task ID      | Operations |
|--------------|------------|
| netflow read |            |

## Examples

This example shows how to display flow exporter map data:

```
RP/0/RSP0/CPU0:router# show flow exporter fem1 location 0/0/CPU0
```

```
Flow Exporter: NFC
```

```
Used by flow monitors: fmm4
```

```
Status: Normal
```

```
Transport UDP
```

```
Destination 12.24.39.0 (50001)
```

```
Source 12.25.54.3 (5956)
```

```
Flows exported: 0 (0 bytes)
```

```
Flows dropped: 0 (0 bytes)
```

```
Templates exported: 1 (88 bytes)
```

```
Templates dropped: 0 (0 bytes)
```

```
Option data exported: 0 (0 bytes)
```

```
Option data dropped: 0 (0 bytes)
```

```
Option templates exported: 2 (56 bytes)
```

```
Option templates dropped: 0 (0 bytes)
```

```

Packets exported:          3 (144 bytes)
Packets dropped:          0 (0 bytes)

Total export over last interval of:
  1 hour:                  0 pkts
                           0 bytes
                           0 flows
  1 minute:                3 pkts
                           144 bytes
                           0 flows
  1 second:                0 pkts
                           0 bytes
                           0 flows

```

**Table 1: show flow exporter Field Descriptions**

| Field                                      | Description   |
|--|---|
| Id   | Identifies the flow exporter map.   |
| Used by flow monitors                      | Name of the flow monitors associated with the specified flow exporter map.  |
| Status                                     | Status of the exporter. <ul style="list-style-type: none"> <li>• Normal—Exporter is active and can export packets.</li> <li>• Disabled—Exporter cannot send out packets because the collector is unreachable or the configuration is incomplete.</li> </ul> |
| Destination                                | Export destination address the current flow exporter map.   |
| Flows exported                             | Flows exported, in bytes.   |
| Flows dropped                              | Flows dropped, in bytes.  |
| Templates exported                         | Templates exported, in bytes.   |
| Templates dropped                          | Templates dropped, in bytes.  |
| Option data exported                       | Option data exported, in bytes.   |
| Option data dropped                        | Option data dropped, in bytes.  |
| Option templates exported                  | Option templates exported, in bytes.  |
| Option templates dropped                   | Option templates dropped, in bytes.   |
| Packets exported:                          | Packets exported, in bytes.   |
| Packets dropped                            | Packets dropped, in bytes.  |
| Average export rate over interval of last: | Average export rate, in bytes/pkts. Information is displayed for intervals of the last hour, minute, and second.  |

# show flow exporter-map

To display flow exporter map information for a specific node, enter the **show flow exporter-map** command in EXEC mode.

```
show flow exporter-map [name]
```

| <b>Syntax Description</b> | <i>name</i> Name of the exporter map whose information you want to display.  |         |              |               |                              |               |  |                |  |
|---------------------------|--|---------|--------------|---------------|------------------------------|---------------|--|----------------|--|
| <b>Command Default</b>    | None   |         |              |               |                              |               |  |                |  |
| <b>Command Modes</b>      | EXEC mode  |         |              |               |                              |               |  |                |  |
| <b>Command History</b>    | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> <tr> <td>Release 6.0.1</td> <td>This command was updated to display exporter version type IPFIX information.</td> </tr> <tr> <td>Release 7.10.1</td> <td>The show command output was updated to display <b>router-id</b> information.</td> </tr> </tbody> </table> | Release | Modification | Release 3.9.1 | This command was introduced. | Release 6.0.1 | This command was updated to display exporter version type IPFIX information. | Release 7.10.1 | The show command output was updated to display <b>router-id</b> information. |
| Release                   | Modification   |         |              |               |                              |               |  |                |  |
| Release 3.9.1             | This command was introduced.   |         |              |               |                              |               |  |                |  |
| Release 6.0.1             | This command was updated to display exporter version type IPFIX information.   |         |              |               |                              |               |  |                |  |
| Release 7.10.1            | The show command output was updated to display <b>router-id</b> information.   |         |              |               |                              |               |  |                |  |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations |
|---------|---------|------------|
|         | netflow | read       |

## Examples

This example shows how to configure IPFIX as an exporter version in the exporter-map **fem\_ipfix**:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map fem_ipfix

RP/0/RSP0/CPU0:router(config-fem)# destination 10.17.7.24
RP/0/RSP0/CPU0:router(config-fem)# transport udp 1025
RP/0/RSP0/CPU0:router(config-fem)# version ipfix
RP/0/RSP0/CPU0:router(config-fem-ver)# options sampler-table timeout 1800
RP/0/RSP0/CPU0:router(config-fem-ver)# exit
RP/0/RSP0/CPU0:router(config-fem)# exit
RP/0/RSP0/CPU0:router(config)# exit
```

The **show flow exporter-map** command output shows IPFIX as an exporter version that we configured earlier in flow exporter map **fem\_ipfix**:

```
RP/0/RSP0/CPU0:router# show flow exporter-map fem_ipfix

Flow Exporter Map : fem_ipfix
-----
Id                : 2
DestinationIpAddr : 10.17.7.24
```

## show flow exporter-map

```

VRFName          : default
SourceIfName     :
SourceIpAddr     :
DSCP             : 0
TransportProtocol : UDP
TransportDestPort : 1025

```

```

Export Version: IPFIX
  Common Template Timeout : 1800 seconds
  Options Template Timeout : 1800 seconds
  Data Template Timeout : 1800 seconds
  Interface-Table Export Timeout : 0 seconds
  Sampler-Table Export Timeout : 1800 seconds
  VRF-Table Export Timeout : 0 seconds

```

This example shows how to display flow exporter map information:

```
RP/0/RSP0/CPU0:router# show flow exporter-map map1
```

```

Flow Exporter Map : map1
-----
Id                : 2
DestinationIpAddr : 10.1.1.1
SourceIfName     : Loopback0
SourceIpAddr     : 10.1.1.1
DSCP             : 10
TransportProtocol : UDP
TransportDestPort : 1024

```

```

Export Version: 9
  Common Template Timeout : 1800 seconds
  Options Template Timeout : 1800 seconds
  Data Template Timeout : 600 seconds
  Interface-Table Export Timeout : 1800 seconds
  Sampler-Table Export Timeout : 0 seconds

```

This example shows how to display flow exporter map with **router-id** information:

```
Router# show flow exporter-map E
Fri Mar 24 13:28:13.617 IST
```

```

Flow Exporter Map : E
-----
Id                : 6
Packet-Length    : 1468
DestinationIpAddr :
VRFName         :
SourceIfName     :
SourceIpAddr     : Unsupported family type (0)
DSCP             : 0
TransportProtocol :
TransportDestPort :
TransportSourcePortSelectionMethod :
Do Not Fragment  : Not Enabled
Router-Id       : 209.165.201.1

```

```

Export Version: 9
  Common Template Timeout : 1800 seconds
  Options Template Timeout : 1800 seconds
  Data Template Timeout : 1800 seconds
  Interface-Table Export Timeout : 0 seconds
  Sampler-Table Export Timeout : 0 seconds
  VRF-Table Export Timeout : 0 seconds

```

This table describes the significant fields shown in the display.

**Table 2: show flow exporter-map Field Descriptions**

| Field                          | Description   |
|--------------------------------|---|
| Id                             | Identifies the flow exporter map.   |
| DestinationIpAddr              | Exports destination configuration.  |
| SourceIfName                   | Source interface for this exporter map. You can specify the source interface with the <b>flow exporter-map</b> command.   |
| SourceIpAddr                   | IP address of the source interface (SourceIfName).  |
| DSCP                           | Differentiated services codepoint (DSCP) value for export packets.<br><b>Note</b> You can specify the DSCP with the <b>flow exporter-map</b> command.   |
| TransportProtocol              | Displays the configured transport protocol.<br><b>Note</b> Cisco IOS XR software supports the UDP transport protocol only.<br><b>Note</b> You can specify the transport protocol with the <b>flow exporter-map</b> command. |
| TransportDestPort              | Displays the configured destination port for UDP packets.   |
| Router-Id                      | Displays the configured router-id or agent-id.  |
| Export Version                 | Displays the configured export format.<br><b>Note</b> Cisco IOS XR software supports export format version 9 only.  |
| Common Template Timeout        | Displays the configured common template timeout.  |
| Options Template Timeout       | Displays the configured options template timeout.<br><b>Note</b> You can specify the options template timeout with the <b>flow exporter-map</b> command.  |
| Data Template Timeout          | Displays the configured data template timeout.<br><b>Note</b> You can specify the data template timeout with the <b>flow exporter-map</b> command.  |
| Interface-Table Export Timeout | Displays the export timeout value for the interface table.<br><b>Note</b> You can specify the export timeout for the interface table with the <b>flow exporter-map</b> command.   |
| Sampler-Table Export Timeout   | Displays the export timeout value for the sampler table.<br><b>Note</b> You can specify the export timeout for the sampler table with the <b>flow exporter-map</b> command.   |

## show flow monitor

To display flow monitor cache data in various formats, enter the **show flow monitor** command in EXEC mode.

To match on Access Control Lists (ACLs) and one or more fields:

```
show flow monitor monitor-name cache match {ipv4 {acl name | source-address match-options | destination-address match-options | protocol match-options | tos match-options} | ipv6 {acl name | source-address match-options | destination-address match-options | protocol match-options | tc match-options} | layer4 {source-port-overloaded match-options | destination-port-overloaded match-options | tcp-flags match-flags-options} | bgp {source-as match-options | destination-as match-options} | interface {ingress match-if-options | egress match-if-options} | timestamp {first match-options | last match-options} | counters {byte match-options | packets match-options} | misc {forwarding-status match-options | direction match-dir-options}}
```

To sort flow record information according to a particular field:

```
show flow monitor monitor-name cache sort {ipv4 {source-address | destination-address | tos | protocol} | ipv6 {source-address | destination-address | tc | protocol} | mpls {label-2 | label-3 | label-4 | label-5 | label-6 | label-type | prefix | top-label} | layer4 {source-port-overloaded | destination-port-overloaded} | bgp {source-as | destination-as} | timestamp {first | last} | counters {bytes | packets} | misc {forwarding-status | direction} {top | bottom} [entries]}
```

To include or exclude one or more fields in the **show flow monitor** command output:

```
show flow monitor monitor-name cache {include | exclude} {ipv4 {source-address | destination-address | tos | protocol} | ipv6 {source-address | destination-address | tc | flow-label | option-headers | protocol} | mpls {label-2 | label-3 | label-4 | label-5 | label-6 | top-label} | layer4 {source-port-overloaded | destination-port-overloaded} | bgp {source-as | destination-as} | timestamp {first | last} | counters {bytes | packets} | misc {forwarding-status match-options | direction match-dir-options}}
```

To display summarized flow record statistics:

```
show flow monitor monitor-name cache summary location node-id
```

To display only key field, packet, and byte information for the flow records:

```
show flow monitor monitor-name cache brief location node-id
```

To display flow record information for a particular node only:

```
show flow monitor monitor-name cache location node-id
```

### Syntax Description

If you specified the **show flow monitor monitor-name cache match** command to match on ACL and one or more fields:

|                     |   |
|---------------------|---|
| <i>monitor-name</i> | Flow monitor map whose details you want to display. |
| <b>cache</b>        | Displays details about the flow monitor cache.      |



|                                     |  |
|-------------------------------------|--|
| <b>match</b>                        | Specifies match criteria for the display.<br>Enter the <b>match</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.  |
| <b>ipv4</b>                         | Specifies IPv4 fields.   |
| <b>ipv6</b>                         | Specifies IPv6 fields.   |
| <b>acl name</b>                     | Specifies an access list. Replace name with the <i>name</i> of the access whose information you want to display.   |
| <b>source-address match-options</b> | Specifies source IP address match options. Possible match options are: <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>source-address</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>   |
| <b>destination-address</b>          | Specifies IPV4 or IPV6 destination address match options. Possible match options are: <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>destination-address</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>                         |
| <b>tos match-options</b>            | Compares fields and matches them based on the type of service value. Range is from 0 through 255. Possible match options are: <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>tos</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p> |

|                                      |   |
|--------------------------------------|---|
| <b>protocol</b> <i>match-options</i> | <p>Compares fields and matches them based on the protocol value. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>protocol</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>  |
| <b>layer4</b>                        | <p>Compares Layer 4 fields and matches them based on specific criteria. You can specify match criteria for any of the following Layer 4 fields:</p> <ul style="list-style-type: none"> <li>• <b>destination-port-overloaded</b></li> <li>• <b>source-port-overloaded</b></li> <li>• <b>tcp-flags</b></li> </ul> <p><b>Note</b> Enter the <b>layer4</b> keyword followed by the <b>?</b> command to see a complete list of possible Layer 4 fields to compare and match.</p>   |
| <b>destination-port-overloaded</b>   | <p>Compares fields and matches them based on the <b>destination-port-overloaded</b> value. The destination port is matched if the protocol specified for that port is TCP or UDP.</p> <p>Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>destination-port-overloaded</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p> |

|  |  |
|--|--|
| <p><b>source-port-overloaded</b></p>               | <p>Compares fields and matches them based on the <b>source-port-overloaded</b> value.</p> <p>The source port is matched if the protocol specified for that port is one of the following:</p> <ul style="list-style-type: none"> <li>• TCP—Range is from 0 through 65535.</li> <li>• UDP—Range is from 0 through 65535.</li> <li>• ICMP—Type or code is in range from 0 through 255.</li> <li>• IGMP—Type is in range from 0 through 255.</li> </ul> <p>Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> NoteEnter the <b>source-port-overloaded</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p> |
| <p><b>tcp-flags</b> <i>match-flags-options</i></p> | <p>Specifies TCP flags, as follows:</p> <ul style="list-style-type: none"> <li>• <b>all</b> —Match all of the fields</li> <li>• <b>any</b> —Match any of the fields</li> <li>• <b>none</b> —Match none of the fields.</li> </ul> <p><b>Note</b> Enter the <b>tcp-flags</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>   |
| <p><b>bgp</b></p>                                  | <p>Compares BGP fields and matches them based on specific criteria. You can specify match criteria for any of the following BGP fields:</p> <ul style="list-style-type: none"> <li>• <b>destination-as</b> —Destination as.</li> <li>• <b>source-as</b> —Source as.</li> </ul>   |

|  |  |
|--|--|
| <b>source-as</b> <i>match-options</i>      | <p>Compares and matches the BGP autonomous system number of the destination address.</p> <p>Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>source-as</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p> |
| <b>destination-as</b> <i>match-options</i> | <p>Compares and matches the BGP autonomous system number of the source address. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>destination-as</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>        |
| <b>timestamp</b>                           | <p>Specifies the time stamp for which to compare and match the specified criteria. Enter the <b>first</b> keyword or the <b>last</b> keyword to specify the time stamp whose criteria you want to compare.</p>   |
| <b>first</b> <i>match-options</i>          | <p>Compares fields from the first time stamp and matches them based on the match-options value. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>first</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p> |

|                                     |   |
|-------------------------------------|---|
| <b>last</b> <i>match-options</i>    | <p>Compares fields from the last time stamp and matches them based on the match-if-options value. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>last</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p> |
| <b>counters</b>                     | <p>Specifies the counters for which to compare and match the specified criteria. Enter the <b>byte</b> keyword or the <b>packets</b> keyword to specify the counters whose criteria you want to compare.</p>  |
| <b>byte</b> <i>match-options</i>    | <p>Compares bytes counter fields and matches them based on the match-options value. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>byte</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>               |
| <b>packets</b> <i>match-options</i> | <p>Compares packets counter fields and matches them based on the match-options value. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p><b>Note</b> Enter the <b>byte</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>             |
| <b>misc</b>                         | <p>Specifies miscellaneous fields for which to compare and match the specified criteria. Enter the <b>forwarding-status</b> keyword or the <b>direction</b> keyword to specify the field whose criteria you want to compare.</p>  |

|  |  |
|--|--|
| <b>forwarding-status</b> <i>match-options</i>                    | <p>Compares forwarding status fields and matches them based on the match-options value. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>gt</b> —Match if greater than field value.</li> <li>• <b>lt</b> —Match if less than field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> <li>• <b>range</b> —Match if within the range of field values.</li> </ul> <p>Enter the <b>forwarding-status</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p> |
| <b>direction</b> <i>match-dir-options</i>                        | <p>Compares information about the direction of the flow and matches it based on the match-options value. Possible match options are:</p> <ul style="list-style-type: none"> <li>• <b>eq</b> —Match if equal to field value.</li> <li>• <b>neq</b> —Match if not equal to field value.</li> </ul> <p><b>Note</b> Enter the <b>direction</b> keyword followed by the <b>?</b> command to see a complete list of possible match criteria.</p>   |
| To sort flow record information according to a particular field: |  |
| <i>monitor-name</i>  | Flow monitor map whose details you want to display.  |
| <b>cache</b>   | Displays details about the flow monitor cache.   |
| <b>sort</b>  | Determines sorting criteria for the <b>show flow monitor</b> command display.  |
| <b>ipv4</b>  | <p>Specifies sorting criteria for one of the following IPv4 fields:</p> <ul style="list-style-type: none"> <li>• <b>destination-address</b></li> <li>• <b>source-address</b></li> <li>• <b>protocol</b></li> <li>• <b>tos</b></li> </ul> <p><b>Note</b> Enter the <b>ipv4</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>  |

|                            |  |
|----------------------------|--|
| <b>ipv6</b>                | <p>Specifies sorting criteria for one of the following IPv6 fields:</p> <ul style="list-style-type: none"> <li>• <b>destination-address</b></li> <li>• <b>source-address</b></li> <li>• <b>protocol</b></li> <li>• <b>tos</b></li> </ul> <p><b>Note</b> Enter the <b>ipv6</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>  |
| <b>source-address</b>      | <p>Displays IPv4 or IPv6 information for the source address according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>source-address</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>           |
| <b>destination-address</b> | <p>Displays IPv4 or IPv6 information for the destination address according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>destination-address</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>tos</b>                 | <p>Displays IPv4 type of service information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>tos</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>                                     |

|                 |   |
|-----------------|---|
| <b>tc</b>       | <p>Displays IPv6 traffic class information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>tc</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>   |
| <b>protocol</b> | <p>Displays IPv4 or IPv6 protocol information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>tos</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>   |
| <b>mpls</b>     | <p>Specifies sorting criteria for one of the following MPLS fields:</p> <ul style="list-style-type: none"> <li>• <b>label-2</b></li> <li>• <b>label-3</b></li> <li>• <b>label-4</b></li> <li>• <b>label-5</b></li> <li>• <b>label-6</b></li> <li>• <b>label-type</b></li> <li>• <b>prefix</b></li> <li>• <b>top-label</b></li> </ul> <p><b>Note</b> Enter the <b>mpls</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>label-2</b>  | <p>Displays MPLS information for the second label in the MPLS label stack. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>   |



|                   |   |
|-------------------|---|
| <b>label-3</b>    | Displays MPLS information for the third label in the MPLS label stack. Possible sorting options are: <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>             |
| <b>label-4</b>    | Displays MPLS information for the fourth label in the MPLS label stack. Possible sorting options are: <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>            |
| <b>label-5</b>    | Displays MPLS information for the fifth label in the MPLS label stack. Possible sorting options are: <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>             |
| <b>label-6</b>    | Displays MPLS information for the sixth label in the MPLS label stack. Possible sorting options are: <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>             |
| <b>label-type</b> | Displays MPLS information for the specified type of label in the MPLS label stack. Possible sorting options are: <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> |
| <b>prefix</b>     | Displays MPLS information for the destination address. Possible sorting options are: <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>                             |
| <b>top-label</b>  | Displays MPLS information for the top label in the MPLS label stack. Possible sorting options are: <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>               |

|                                    |   |
|------------------------------------|---|
| <b>layer4</b>                      | <p>Specifies sorting criteria for one of the following Layer 4 fields:</p> <ul style="list-style-type: none"> <li>• <b>source-port-overloaded</b></li> <li>• <b>destination-port-overloaded</b></li> </ul> <p><b>Note</b> Enter the <b>layer4</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>   |
| <b>source-port-overloaded</b>      | <p>Displays source port overload information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>source-port-overloaded</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>           |
| <b>destination-port-overloaded</b> | <p>Displays destination port overload information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>destination-port-overloaded</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>bgp</b>                         | <p>Specifies sorting criteria for one of the following BGP fields:</p> <ul style="list-style-type: none"> <li>• <b>source-as</b></li> <li>• <b>destination-as</b></li> </ul> <p><b>Note</b> Enter the <b>layer4</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>   |

|                       |   |
|-----------------------|---|
| <b>source-as</b>      | <p>Displays information about the BGP source address autonomous system number according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>source-as</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>           |
| <b>destination-as</b> | <p>Displays information about the BGP destination address autonomous system number according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>destination-as</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>timestamp</b>      | <p>Specifies sorting criteria for the first or last time stamp. Enter the <b>first</b> keyword or the <b>last</b> keyword to specify the time stamp whose criteria you want to specify.</p> <p><b>Note</b> Enter the <b>timestamp</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>   |
| <b>first</b>          | <p>Displays information for the first time stamp according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>first</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>  |

|                 |  |
|-----------------|--|
| <b>last</b>     | <p>Displays information for the last time stamp according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>last</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>counters</b> | <p>Specifies sorting criteria for the bytes or packets counters. Follow the <b>counters</b> keyword with the <b>byte</b> keyword or the <b>packets</b> keyword to specify the counters whose criteria you want to compare.</p>   |
| <b>bytes</b>    | <p>Displays bytes counter information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>bytes</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>          |
| <b>packets</b>  | <p>Displays packets counter information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>packets</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>      |
| <b>misc</b>     | <p>Specifies sorting criteria for miscellaneous fields. Follow the <b>misc</b> keyword with the <b>forwarding-status</b> keyword or the <b>direction</b> keyword to specify the counters whose criteria you want to compare.</p>   |

|   |   |
|---|---|
| <b>forwarding-status</b>  | <p>Displays forwarding status information according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>forwarding-status</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>       |
| <b>direction</b>  | <p>Displays information about the direction of the flow according to the specified sorting criteria. Possible sorting options are:</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul> <p><b>Note</b> Enter the <b>direction</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>top</b>  | <p>Displays top cache entries. Replace records with the number of records you want to display.</p> <p><b>Note</b> You can follow the <b>top</b> keyword with the optional entries argument to specify the number of records to display.</p>   |
| <b>bottom</b>   | <p>Displays bottom cache entries. Replace records with the number of records you want to display.</p> <p><b>Note</b> You can follow the <b>bottom</b> keyword with the optional entries argument to specify the number of records to display.</p>   |
| <i>entries</i>  | Number of records to display. Range is from 1 through 1000.   |
| To include or exclude one or more fields in the show flow monitor command output: |   |
| <i>monitor-name</i>   | Flow monitor map whose details you want to display.   |
| <b>cache</b>  | Displays details about the flow monitor cache.  |
| <b>include</b>  | <p>Includes the specified fields in the display output. Enter the <b>include</b> keyword, followed by the keyword or keywords that specify the fields to include.</p> <p><b>Note</b> To see a list of fields that can be included, enter the <b>include</b> keyword, followed by the <b>?</b> command.</p>  |

|                            |  |
|----------------------------|--|
| <b>exclude</b>             | Excludes the specified fields in the display output. Enter the <b>exclude</b> keyword, followed by the keyword or keywords that specify the fields to exclude.<br><br><b>Note</b> To see a list of fields that can be excluded, enter the <b>exclude</b> keyword, followed by the ? command.   |
| <b>ipv4</b>                | Includes or excludes one of the following IPv4 fields in the command output:<br><br><ul style="list-style-type: none"> <li>• <b>destination-address</b></li> <li>• <b>source-address</b></li> <li>• <b>protocol</b></li> <li>• <b>tos</b></li> </ul><br><b>Note</b> Enter the <b>ipv4</b> keyword followed by the ? command to see a complete list of possible sorting criteria.   |
| <b>ipv6</b>                | Includes or excludes one of the following IPv6 fields in the command output:<br><br><ul style="list-style-type: none"> <li>• <b>destination-address</b></li> <li>• <b>flow-label</b></li> <li>• <b>option-headers</b></li> <li>• <b>source-address</b></li> <li>• <b>protocol</b></li> <li>• <b>tos</b></li> </ul><br><b>Note</b> Enter the <b>ipv6</b> keyword followed by the ? command to see a complete list of possible sorting criteria. |
| <b>source-address</b>      | Includes or excludes IPV4 or IPV6 information for the source address in the command output.  |
| <b>destination-address</b> | Includes or excludes IPV4 or IPV6 information for the destination address in the command output.   |
| <b>flow-label</b>          | Includes or excludes information about the IPv6 flow label in the command output. The flow label is the 20-bit flow label id present in every IPv6 packet header.  |

|                       |  |
|-----------------------|--|
| <b>option-headers</b> | Includes or excludes IPV6 information for the option headers in the command output. The option header is a bit mask that indicates which options headers are present in the IPv6 header.   |
| <b>tos</b>            | Includes or excludes IPV4 type of service information in the command output.   |
| <b>tc</b>             | Includes or excludes IPV6 traffic class information in the command output.   |
| <b>protocol</b>       | Includes or excludes IPV4 or IPV6 protocol information in the command output.  |
| <b>mpls</b>           | Includes or excludes one of the following MPLS fields in the command output: <ul style="list-style-type: none"> <li>• <b>label-2</b></li> <li>• <b>label-3</b></li> <li>• <b>label-4</b></li> <li>• <b>label-5</b></li> <li>• <b>label-6</b></li> <li>• <b>top-label</b></li> </ul> <p><b>Note</b> Enter the <b>mpls</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>label-2</b>        | Includes or excludes MPLS information for the second label in the MPLS label stack.  |
| <b>label-3</b>        | Includes or excludes MPLS information for the third label in the MPLS label stack.   |
| <b>label-4</b>        | Includes or excludes MPLS information for the fourth label in the MPLS label stack.  |
| <b>label-5</b>        | Includes or excludes MPLS information for the fifth label in the MPLS label stack.   |
| <b>label-6</b>        | Includes or excludes MPLS information for the sixth label in the MPLS label stack.   |
| <b>top-label</b>      | Includes or excludes MPLS information for the top label in the MPLS label stack.   |

|                                    |   |
|------------------------------------|---|
| <b>layer4</b>                      | <p>Includes or excludes one of the following the following Layer 4 fields in the command output:</p> <ul style="list-style-type: none"> <li>• <b>source-port-overloaded</b></li> <li>• <b>destination-port-overloaded</b></li> </ul> <p><b>Note</b> Enter the <b>layer4</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p> |
| <b>source-port-overloaded</b>      | Includes or excludes source port overload information in the command output.  |
| <b>destination-port-overloaded</b> | <p>Includes or excludes destination port overload information in the command output.</p> <ul style="list-style-type: none"> <li>• <b>top</b> —Displays top cache entries.</li> <li>• <b>bottom</b> —Displays bottom cache entries.</li> </ul>   |
| <b>bgp</b>                         | <p>Includes or excludes the following BGP fields in the command output:</p> <ul style="list-style-type: none"> <li>• <b>source-as</b></li> <li>• <b>destination-as</b></li> </ul> <p><b>Note</b> Enter the <b>bgp</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>   |
| <b>source-as</b>                   | Includes or excludes information about the BGP source address autonomous system number in the command output.   |
| <b>destination-as</b>              | Includes or excludes information about the BGP destination address autonomous system number in the command output.  |
| <b>timestamp</b>                   | <p>Includes or excludes information from the first or last time stamp in the command output. Enter the <b>first</b> keyword or the <b>last</b> keyword to include or exclude information about a specific time stamp.</p> <p><b>Note</b> Enter the <b>timestamp</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.</p>         |
| <b>first</b>                       | Includes or excludes information for the first time stamp in the command output.  |
| <b>last</b>                        | Includes or excludes information for the first time stamp in the command output.  |



|   |   |
|---|---|
| <b>counters</b>                               | Includes or excludes bytes or packets counters in the command output. Follow the <b>counters</b> keyword with the <b>byte</b> keyword or the <b>packets</b> keyword to include or exclude particular counters.<br><br><b>Note</b> Enter the <b>counters</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria.                             |
| <b>bytes</b>                                  | Includes or excludes bytes counter information in the command output.   |
| <b>packets</b>                                | Includes or excludes packets counter information in the command output.   |
| <b>misc</b>                                   | Includes or excludes information for miscellaneous fields in the command output. Follow the <b>misc</b> keyword with the <b>forwarding-status</b> keyword or the <b>direction</b> keyword to specify the field you want to include or exclude.<br><br><b>Note</b> Enter the <b>misc</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria. |
| <b>forwarding-status</b>                      | Includes or excludes forwarding status information in the command output.   |
| <b>direction</b>                              | Includes or excludes information about the direction of the flow in the command output.   |
| <b>top</b>                                    | Includes or excludes top cache entries in the command output. Replace records with the number of <i>records</i> you want to display.  |
| <b>bottom</b>                                 | Includes or excludes bottom cache entries. Replace records with the number of <i>records</i> you want to display  |
| <i>entries</i>                                | Number of records to display. Range is from 1 through 1000.   |
| To display summarized flow record statistics: |   |
| <i>monitor-name</i>                           | Flow monitor map whose details you want to display.   |
| <b>cache</b>                                  | Displays details about the flow monitor cache.  |
| <b>summary</b>                                | Displays summarized flow monitor information only.  |
| <i>monitor-name</i>                           | Flow monitor map whose details you want to display.   |
| <b>cache</b>                                  | Displays details about the flow monitor cache.  |

|  |   |
|--|---|
| <b>brief</b>   | Abbreviates the <b>show flow monitor</b> command output.  |
| To display flow record information for a particular node only: |   |
| <i>monitor-name</i>  | Flow monitor map whose details you want to display.   |
| <b>cache</b>   | Displays details about the flow monitor cache.  |
| <b>location</b> <i>node-id</i>                                 | Identifies the node whose flow exporter statistics you want to clear, or whose flow exporter statistics collector you want to restart. The <i>node-id</i> argument is expressed in the <i>rack/slot/module</i> notation.<br><br><b>Note</b> Enter the <b>location</b> keyword followed by the <b>?</b> command to see a complete list of possible sorting criteria. |

**Command Default** None

**Command Modes** EXEC mode

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>                         |
|------------------------|----------------|---|
|                        | Release 4.0.0  | The interface keyword options were removed. |

### Usage Guidelines



**Note** To collect source and destination AS information, you must enable BGP on the relevant BGP AFI/SAFI. Unless this is done, all AS numbers in the flow records are displayed as 0.

Keep these information in mind when using the **show flow monitor** command:

- The **show flow monitor** command can include combinations of these options:

- **format**
- **match**
- **include**
- **exclude**
- **sort**
- **summary**
- **location**

- We do not recommend including the **summary** option with the **sort** and **format** options.
- The mutually exclusive options are **summary**, **brief**, **include**, and **exclude**.
- To see a list of fields that can be included after a keyword, enter the **?** command, as shown in this example:

```
RP/0/RSP0/CPU0:router# show flow monitor map1 cache summary ?
```

```
brief      Show just the key fields
exclude    Exclude field
format     Display format
include    Include field
location   Specify a location
match     Match criteria
sort      Sorting criteria
```

| Task ID | Task ID | Operations |
|---------|---------|------------|
|         | netflow | read       |

**Examples**

This example shows how to display flow monitor data for a specific monitor map cache in the location 0/0/CPU0 :

```
RP/0/RSP0/CPU0:router# show flow monitor fmm2 cache loc 0/0/CPU0
```

Cache summary for Flow Monitor fmm2:

```
Cache size:          65535
Current entries:     4
High Watermark:     62258
Flows added:        4
Flows not added:    0
Ager Polls:         60
- Active timeout    0
- Inactive timeout  0
- TCP FIN flag      0
- Watermark aged   0
- Emergency aged   0
- Counter wrap aged 0
- Total             0
Periodic export:
- Counter wrap     0
- TCP FIN flag     0
Flows exported      0
Matching entries:   4
```

| IPV4SrcAddr     | IPV4DstAddr        | L4SrcPort            | L4DestPort  | BGPDstOrigAS | BGPSrcOrigAS | IPV4SrcPrfxLen | IPV4Prot | IPV4TOS | InputInterface | OutputInterface | L4TCPFlags | ForwardStatus |
|-----------------|--------------------|----------------------|-------------|--------------|--------------|----------------|----------|---------|----------------|-----------------|------------|---------------|
| ForwardReason   | FirstSwitched      | LastSwitched         | ByteCount   | PacketCount  | Dir          | Sampler ID     |          |         |                |                 |            |               |
| 17.17.17.2      | 18.18.18.2         | 0                    | 0           | 0            | 0            | 24             |          |         |                |                 |            | 24            |
| 61              | normal             | HundredGigE /0/0/8   | HundredGigE | 0/0/0/12     | 0            | Fwd            |          |         |                |                 |            |               |
| 00:02:43:800 00 | 00:02:49:980 37200 | 620                  | In          | 0            |              |                |          |         |                |                 |            |               |
| 18.18.18.2      | 17.17.17.2         | 0                    | 0           | 0            | 0            | 24             |          |         |                |                 |            | 24            |
| 61              | normal             | HundredGigE 0/0/0/12 | HundredGigE | 0/0/0/8      | 0            | Fwd            |          |         |                |                 |            |               |
| 00:02:43:791 00 | 00:02:49:980 37200 | 620                  | In          | 0            |              |                |          |         |                |                 |            |               |
| 17.17.17.2      | 18.18.18.2         | 0                    | 0           | 0            | 0            | 24             |          |         |                |                 |            | 24            |
| 61              | normal             | HundredGigE 0/0/0/8  | HundredGigE | 0/0/0/12     | 0            | Fwd            |          |         |                |                 |            |               |

```

00:02:43:798 00 00:02:49:980 34720          620          Out 0
18.18.18.2      17.17.17.2      0            0            0            0            24
0
$
61      normal    HundredGigE 0/0/0/12    HundredGigE 0/0/0/8    0            Fwd
0
00
00:02:43:797 00 00:02:49:980 34720          620          Out 0
L4SrcPort  L4DestPort BGPDstOrigAS BGPsrcOrigAS IPV4DstPrfxLen

```

This table describes the significant fields shown in the display.

**Table 3: show flow monitor Field Descriptions**

| Field                               | Description   |
|-------------------------------------|---|
| Cache summary for Flow Monitor fmm2 | <p>Displays general cache information for the specified flow monitor. The following information is displayed</p> <ul style="list-style-type: none"> <li>• Cache size for the specified flow monitor map</li> <li>• Current number of entries in the cache</li> <li>• High watermark for this cache</li> <li>• Number of flows added to the cache</li> <li>• Number of flows not added to the cache</li> </ul> |
| Ager Polls                          | <p>Displays the following ager statistics:</p> <ul style="list-style-type: none"> <li>• Active timeout</li> <li>• Inactive timeout</li> <li>• TCP FIN flag</li> <li>• Watermark aged</li> <li>• Emergency aged</li> <li>• Counter wrap aged</li> <li>• Total</li> </ul>   |
| Periodic export                     | <ul style="list-style-type: none"> <li>• Counter wrap</li> <li>• TCP FIN flag</li> </ul>  |
| Cache summary for Flow Monitor fmm2 | <p>Displays general cache information for the specified flow monitor. The following information is displayed</p> <ul style="list-style-type: none"> <li>• Cache size for the specified flow monitor map</li> <li>• Current number of entries in the cache</li> <li>• High watermark for this cache</li> <li>• Number of flows added to the cache</li> <li>• Number of flows not added to the cache</li> </ul> |
| FirstSwitched                       | <p>Displays the system uptime at which the first packet of this flow was switched. The display format is days hours:minutes:seconds:milliseconds</p>  |
| LastSwitched                        | <p>Displays the system uptime at which the last packet of this flow was switched. The display format is days hours:minutes:seconds:milliseconds</p>   |

# show flow monitor-map

To display flow monitor map data, enter the **show flow monitor-map** command in EXEC mode.

**show flow monitor-map** *map-name* **Optional:** [srv6]

| <b>Syntax Description</b> | <i>map-name</i> Name of the monitor map whose data you want to display.  |         |              |               |   |               |                              |               |  |
|---------------------------|--|---------|--------------|---------------|---|---------------|------------------------------|---------------|--|
| <b>Command Default</b>    | None   |         |              |               |   |               |                              |               |  |
| <b>Command Modes</b>      | EXEC mode  |         |              |               |   |               |                              |               |  |
| <b>Command History</b>    | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 7.8.1</td> <td>The show flow monitor-map command output was modified to display the monitor-map data for ipv6 srv6 subtypes.</td> </tr> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> <tr> <td>Release 3.4.1</td> <td>The ipv4-raw record map name was replaced with ipv4.</td> </tr> </tbody> </table> | Release | Modification | Release 7.8.1 | The show flow monitor-map command output was modified to display the monitor-map data for ipv6 srv6 subtypes. | Release 3.9.1 | This command was introduced. | Release 3.4.1 | The ipv4-raw record map name was replaced with ipv4. |
| Release                   | Modification   |         |              |               |   |               |                              |               |  |
| Release 7.8.1             | The show flow monitor-map command output was modified to display the monitor-map data for ipv6 srv6 subtypes.  |         |              |               |   |               |                              |               |  |
| Release 3.9.1             | This command was introduced.   |         |              |               |   |               |                              |               |  |
| Release 3.4.1             | The ipv4-raw record map name was replaced with ipv4.   |         |              |               |   |               |                              |               |  |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations |
|---------|---------|------------|
|         | netflow | read       |

## Examples

This example shows how to display IPv4 monitor-map data for a specific flow:

```
RP/0/RSP0/CPU0:router# show flow monitor-map map1

Flow Monitor Map : map1
-----
Id:                1
RecordMapName:    ipv4
ExportMapName:    NFC
CacheAgingMode:   Permanent
CacheMaxEntries:  10000
CacheActiveTout:  N/A
CacheInactiveTout: N/A
CacheUpdateTout:  60 seconds
```

This example shows how to display SRv6 monitor-map data for a specific flow:

```
RP/0/RSP0/CPU0:router# show flow monitor-map MON-MAP-1

Flow Monitor Map : MON
-----
Id:                1
```

```

RecordMapName:      srv6
ExportMapName:      EXP
CacheAgingMode:     Normal
CacheMaxEntries:    65535
CacheActiveTout:    101 seconds
CacheInactiveTout:  15 seconds
CacheUpdateTout:    N/A
CacheRateLimit:     2000
HwCacheExists:      False
HwCacheInactTout:   50

```

This table describes the significant fields shown in the display.

**Table 4: show flow monitor-map Field Descriptions**

| Field             | Description   |
|-------------------|---|
| Flow Monitor Map  | Name of the flow monitor map whose information is display in the <b>show flow monitor-map</b> command output.   |
| Id                | Number that identifies the flow monitor map.  |
| RecordMapName     | Name of the flow record map that is associated with this monitor map. The RecordMapName indicates the type of packets NetFlow captures as they leave the router.  |
| ExportMapName     | Name of the export map that is associated with this monitor map.  |
| CacheAgingMode    | Current aging mode configured on this cache. “Permanent” indicates that the removal of entries from the monitor map flow cache is disabled.<br><br><b>Note</b> To configure the number of entries allowed in the monitor map flow cache, enter the <b>cache entries</b> command in flow monitor map configuration mode. To disable the removal of entries from the monitor map flow cache, enter the <b>cache permanent</b> command in flow monitor map configuration mode. |
| CacheMaxEntries   | Number of flow entries currently allowed in the flow cache before the oldest entry is removed.<br><br><b>Note</b> To modify the number of entries in the monitor map flow cache, enter the <b>cache entries</b> command in flow monitor map configuration mode  |
| CacheActiveTout   | Active flow timeout configured for this cache, in seconds.<br><br><b>Note</b> To modify the configured active flow timeout, use the <b>cache timeout</b> command in flow monitor map configuration mode.  |
| CacheInactiveTout | Inactive flow timeout configured for this cache, in seconds.<br><br><b>Note</b> To modify the configured inactive flow timeout, use the <b>cache timeout</b> command in flow monitor map configuration mode.  |
| CacheUpdateTout   | Update timeout configured for this cache, in seconds.<br><br><b>Note</b> To modify the configured update timeout, use the <b>cache timeout</b> command in flow monitor map configuration mode.  |

This example shows how to display monitor-map data for a specific IPv6 flow:

```
RP/0/RSP0/CPU0:router# show flow monitor-map map2
```

```
Tue Jan 22 00:15:53.424 PST  
Flow Monitor Map : map2
```

```
-----  
Id: 1  
RecordMapName: ipv6-destination  
CacheAgingMode: Normal  
CacheMaxEntries: 65535  
CacheActiveTout: 1800 seconds  
CacheInactiveTout: 15 seconds  
CacheUpdateTout: N/A
```

# show flow platform producer statistics location

To display statistics collected by the NetFlow producer, use the **show flow platform producer statistics location** command in EXEC mode.

**show flow platform producer statistics location** *node-id*

## Syntax Description

*node-id* Location of the node whose NetFlow producer statistics you want to display. The *node-id* is expressed in the *rack/slot/module* notation.

**Note** Enter the **show platform** command to see the location of all nodes installed in the router.

## Command Default

None

## Command Modes

EXEC mode

## Command History

| Release       | Modification                 |
|---------------|------------------------------|
| Release 3.9.1 | This command was introduced. |

## Usage Guidelines

No specific guidelines impact the use of this command.

## Task ID

| Task ID | Operations |
|---------|------------|
| netflow | read       |

## Examples

This example shows how to display statistics collected by the NetFlow producer for the CPU card in slot 0:

```
# show flow platform producer statistics location 0/0/CPU0
Thu Oct 29 09:49:35.771 UTC
Netflow Platform Producer Counters:
IPv4 Ingress Packets:          41447246
IPv4 Egress Packets:          41447242
IPv6 Ingress Packets:          0
IPv6 Egress Packets:          0
MPLS Ingress Packets:         0
MPLS Egress Packets:          0
Drops (no space):             0
Drops (other):                0
Unknown Ingress Packets:      0
Unknown Egress Packets:       0
Worker waiting:                4677
SPP Packets:                   2032602
Flow Packets:                  82894488
Flow Packets per SPP Frame:    40
```



This table describes the significant fields shown in the display.

**Table 5: show flow platform producer statistics Field Descriptions**

| Field                      | Description  |
|----------------------------|--|
| IPv4 Ingress Packets       | Number of IPV4 packets that were received from the remote end.   |
| IPv4 Egress Packets        | Number of transmitted IPV4 packets.  |
| MPLS Ingress Packets       | Number of MPLS packets that were received from the remote end.   |
| MPLS Egress Packets        | Number of transmitted MPLS packets.  |
| Drops (no space)           | Number of packets that the producer could not enqueue to the NetFlow server because the server input ring was full.                              |
| Drops (other)              | Number of packets that the producer could not enqueue to the NetFlow server due to errors other than the server input ring being full.           |
| Unknown Ingress Packets    | Number of unrecognized packets received from the remote end that were dropped.   |
| Unknown Egress Packets     | Number of packets transmitted to the remote end that were dropped because they were not recognized by the remote end.                            |
| Worker waiting             | Number of times that the producer needed to use the server.<br><b>Note</b> This field is strictly informational and does not indicate any error. |
| SPP Packets                | Number of sequenced packet protocol (SPP) packets transmitted to the remote end.   |
| Flow Packets               | Number of flow packets transmitted to the remote end.  |
| Flow Packets per SPP Frame | Number of flow packets per SPP frame transmitted to the remote end.  |

# show flow platform nfea sampler

To display sampler map information, enter the **show sampler-map** command in EXEC mode.

**show flow platform nfea sampler** [*detaillocation*]

| Syntax Description |  |
|--------------------|--|
| <i>detail</i>      | Displays flow platform nfea sampler detail information |
| <i>location</i>    | Displays the node number                               |

**Command Default** None

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task Operations ID |
|---------|--------------------|
|         | netflow read       |

## Examples

The following example shows how to display flow platform nfea samp detail :

```
RP/0/RSP0/CPU0:router# show flow platform nfea samp
RP/0/RSP0/CPU0:router#show flow pla nfea samp detail loc 0/1/cpu0
Fri Sep 18 16:30:08.435 UTC
Sampler Name:    nf_samp
id: 1,  sp_id: 0,  interval: 1,  ref_count: 2
Attached Interface List Info
Interface Name: GigabitEthernet0/1/0/1,  Direction:  Ingress,    NP ID: 3
Flow Type(s) Configured: IPv4,
Checkpoint Record ID: 12184
Interface Name: GigabitEthernet0/1/0/31,  Direction:  Ingress,    NP ID: 0
Flow Type(s) Configured: IPv4,
Checkpoint Record ID: 12088
Sampler Name:    nf_samp1
id: 2,  sp_id: 1,  interval: 2,  ref_count: 1
Attached Interface List Info
Interface Name: GigabitEthernet0/1/0/1,  Direction:  Egress,    NP ID: 3
Flow Type(s) Configured: IPv4,
Checkpoint Record ID: 12248
```

# show flow platform nfea interface

To display flow map platform information, enter the **show flow platform nfea interface** command in EXEC mode.

**show flow platform nfea interface** *type interface-path-id* {*ingress*|*egress*} **location** *location node id*

| Syntax Description       |  |
|--------------------------|--|
| <i>interface-path-id</i> | Physical interface or virtual interface. |
| <i>egress</i>            | Egress direction                         |
| <i>ingress</i>           | Ingress direction                        |
| <i>location</i>          | Specifies the location                   |

**Command Default** None

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations |
|---------|---------|------------|
|         | netflow | read       |

## Examples

The following example shows how to display flow map platform information:

```
RP/0/RSP0/CPU0:router# show flow platform nfea interface bundle-ether1 ingress location 0/1/CPU0
```

# show flow platform nfea sp location

To display sampling profile information, enter the **show flow platform nfea sp location** command in EXEC mode.

```
show flow platform nfea sp location node-id
```

|                           |  |
|---------------------------|--|
| <b>Syntax Description</b> | <b>location</b> <i>node-id</i> Specifies the location node number. The <i>node-id</i> argument is expressed in the <i>rack/slot/module</i> notation. |
|---------------------------|--|

|                        |   |
|------------------------|---|
| <b>Command Default</b> | Default value for the output when monitor is not configured is all zeros. |
|------------------------|---|

|                      |           |
|----------------------|-----------|
| <b>Command Modes</b> | EXEC mode |
|----------------------|-----------|

|                        |                |                              |
|------------------------|----------------|------------------------------|
| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|                        | Release 3.9.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | No specific guidelines impact the use of this command. |
|-------------------------|--|

|                |             |                   |
|----------------|-------------|-------------------|
| <b>Task ID</b> | <b>Task</b> | <b>Operations</b> |
|                | netflow     | read              |

**Examples** The following example shows how to display sampling profile information:

```
RP/0/RSP0/CPU0:router# show flow platform nfea sp location 0/1/CPU0
```

# show flow platform nfea policer np

To display policer rate information, enter the **show flow platform nfea policer np** command in EXEC mode.

```
show flow platform nfea policer np node-id
```

|                           |   |
|---------------------------|---|
| <b>Syntax Description</b> | <i>node-id</i> Identifies the location node number. |
|---------------------------|---|

|                        |   |
|------------------------|---|
| <b>Command Default</b> | The Default values depends on how many NPs are programmed with the netflow, for example, if the interface is configured on only one NP with netflow, the output will be 100,000; if more NPs are configured, the output will be divided by the number of NPs; if no netflow is configured on a particular NP, the output is 0 |
|------------------------|---|

|                      |           |
|----------------------|-----------|
| <b>Command Modes</b> | EXEC mode |
|----------------------|-----------|

|                        |                |                              |
|------------------------|----------------|------------------------------|
| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|                        | Release 3.9.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | When Netflow is applied on PWHE interfaces, the <i>ing_lns</i> and <i>egr_lns</i> fields in the <b>show flow platform nfea policer np</b> command are not updated. |
|-------------------------|--|

This issue is observed in the third and fourth generation of ASR 9000 Enhanced Ethernet line cards.



|             |  |
|-------------|--|
| <b>Note</b> | The <i>ing_lns</i> field indicates that the Netflow is configured in ingress direction for a particular interface corresponding to the NP. Similarly, <i>eng_lns</i> indicates that the Netflow is configured in egress direction. |
|-------------|--|

|                |                |                   |
|----------------|----------------|-------------------|
| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|                | netflow        | read              |

|                 |  |
|-----------------|--|
| <b>Examples</b> | The following example shows how to display sampler map information for a router: |
|-----------------|--|

```
RP/0/RSP0/CPU0:router# show flow platform nfea policer np 3 location 0/0/CPU0
```

# show flow platform nfea bundle

To display bundle ether interface location information, enter the **show flow platform nfea bundle** command in EXEC mode.

```
show flow platform nfea bundle bundle-ether 100 location node-id
```

|                           |   |
|---------------------------|---|
| <b>Syntax Description</b> | <b>location</b> <i>node-id</i> The node-id is expressed in the rack/slot/module notation. |
|---------------------------|---|

|                        |      |
|------------------------|------|
| <b>Command Default</b> | None |
|------------------------|------|

|                      |           |
|----------------------|-----------|
| <b>Command Modes</b> | EXEC mode |
|----------------------|-----------|

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|------------------------|----------------|------------------------------|
|                        | Release 3.9.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | No specific guidelines impact the use of this command. |
|-------------------------|--|

| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|----------------|----------------|-------------------|
|                | netflow        | read              |

## Examples

The following example shows how to display bundle ether interface location information:

```
RP/0/RSP0/CPU0:router# show flow platform nfea bundle bundle-ether 100 location 0/$
```

# show flow platform nfea chkp

To display checkpoint information, enter the **show flow platform nfea chkp** command in EXEC mode.

**show flow platform nfea chkp** [*checkpoint table number*intf*policersp*] [*checkpoint record number*all]  
**location** *node-id*

| Syntax         | Description                            |
|----------------|--|
| <0-2>          | Displays checkpoint table number.      |
| <i>intf</i>    | Displays interface checkpoint table.   |
| <i>policer</i> | Displays policer checkpoint table.     |
| <i>sp</i>      | Displays sp checkpoint table.          |
| <1-4294967295> | Displays the checkpoint record number. |

**Command Default** Default values should be all zeros, when no interface is configured with monitor in the location.

**Command Modes** EXEC mode

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations |
|---------|---------|------------|
|         | netflow | read       |

**Examples** The following example shows how to display checkpoint information:

```
RP/0/RSP0/CPU0:router# show flow platform nfea chkpt policer all location 0/0/CPU0
RP/0/RSP0/CPU0:router# show flow platform nfea chkpt intf all location 0/0/CPU0
RP/0/RSP0/CPU0:router# show flow platform nfea chkpt sp all location 0/0/CPU0
```

# show flow platform pal-cpp chkpt object

To display Netflow CPP platform checkpoint information, use the **show flow platform pal-cpp chkpt object** command in EXEC mode.

**show flow platform pal-cpp chkpt object** [*number*] **location** *node-id*

|                           |                                |  |
|---------------------------|--------------------------------|--|
| <b>Syntax Description</b> | <i>number</i>                  | Displays checkpoint record number. Range is 1-4294967295.  |
|                           | <b>location</b> <i>node-id</i> | Specifies the location node number. The <i>node-id</i> argument is expressed in the <i>rack/slot/module</i> notation |

**Command Default** None

**Command Modes** EXEC mode

|                        |                |                              |
|------------------------|----------------|------------------------------|
| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|                        | Release 4.0.0  | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

|                |                |                   |
|----------------|----------------|-------------------|
| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|                | netflow        | read              |

## Examples

The following example shows how to display the checkpoint information for 0/1/CPU0:

```
RP/0/RSP0/CPU0:router# show flow platform pal-cpp chkpt object location 0/1/CPU0
```



# show flow platform pal-cpp object

To display Netflow CPP platform layer object information, use the **show flow platform pal-cpp object** command in EXEC mode.

```
show flow platform pal-cpp object {all | fmm name | fem name | fsm name} location node-id
```

| Syntax Description             |  |  |
|--------------------------------|--|--|
| <b>all</b>                     |  | Displays all flow object information.  |
| <b>fmm</b>                     |  | Displays flow monitor information.   |
| <b>fem</b>                     |  | Displays flow exporter information.  |
| <b>fsm</b>                     |  | Displays flow sampler information.   |
| <i>name</i>                    |  | Flow name.   |
| <b>location</b> <i>node-id</i> |  | Specifies the location node number. The node-id argument is expressed in the rack/slot/module notation |

**Command Default** None

**Command Modes** EXEC mode

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 4.0.0 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task    | Operations |
|---------|---------|------------|
|         | netflow | read       |

## Examples

The following example shows how to display all flow object information for location 0/1/CPU0:

```
RP/0/RSP0/CPU0:router# show flow platform pal-cpp object all location 0/1/CPU0
```

## show controllers pse qfp feature fnf datapath

To display QFP Netflow Datapath information on interfaces, use the **show controllers pse qfp feature fnf datapath** command in EXEC mode.

**show controllers pse qfp feature fnf datapath** {**all** | **all-detail** | **builder-program** | **cache** | **cache-state** | **exporter** | **monitor** | **monitor-state** | **sampler** | **sampler-state**} *type interface-path-id*

| Syntax Description       |             |  |
|--------------------------|-------------|--|
| <b>all</b>               |             | Displays netflow information.  |
| <b>all-detail</b>        |             | Displays detailed netflow information.   |
| <b>builder-program</b>   |             | Displays builder program.  |
| <b>cache</b>             |             | Displays cache structure.  |
| <b>cache-state</b>       |             | Displays cache_state structure.  |
| <b>exporter</b>          |             | Displays exporter.   |
| <b>monitor</b>           |             | Displays monitor structure.  |
| <b>monitor-state</b>     |             | Displays monitor_state structure   |
| <b>sampler</b>           |             | Displays sampler structure.  |
| <b>sampler-state</b>     |             | Displays sampler_state structure.  |
| <i>type</i>              |             | Interface type. For more information, use the question mark ( ? ) online help function.                    |
| <i>interface-path-id</i> |             | Physical interface or virtual interface.   |
|                          | <b>Note</b> | Use the <b>show interfaces</b> command to see a list of all interfaces currently configured on the router. |
|                          |             | For more information about the syntax for the router, use the question mark ( ? ) online help function.    |

**Command Default** None

**Command Modes** EXEC mode

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 4.0.0 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task Operations ID |
|---------|--------------------|
|         | netflow read       |

### Examples

The following example shows how to display datapath information for all interfaces:

```
RP/0/RSP0/CPU0:router# show controllers pse qfp feature fnf datapath all ?
ATM                ATM Network Interface(s)
Bundle-Ether       Aggregated Ethernet interface(s)
Bundle-POS         Aggregated POS interface(s)
GigabitEthernet    GigabitEthernet/IEEE 802.3 interface(s)
Loopback           Loopback interface(s)
MgmtEth            Ethernet/IEEE 802.3 interface(s)
Multilink          Multilink network interface(s)
Null               Null interface
POS                Packet over SONET/SDH network interface(s)
Serial             Serial network interface(s)
TenGigE            TenGigabitEthernet/IEEE 802.3 interface(s)
WORD              Other interface
tunnel-gte         MPLS Traffic Engineering GMPLS Tunnel interface
tunnel-ip          GRE/IPinIP Tunnel Interface(s)
tunnel-ipsec       IPsec Tunnel interface(s)
tunnel-mte         MPLS Traffic Engineering P2MP Tunnel interface(s)
tunnel-te         MPLS Traffic Engineering Tunnel interface(s)
```

# show flow trace platform producer location

To trace the information for all or specified netflow processes on all or specified location.

**show flow trace platform producer** *location-id*

|                           |  |
|---------------------------|--|
| <b>Syntax Description</b> | <i>location-id</i> Displays the location |
|---------------------------|--|

|                      |           |
|----------------------|-----------|
| <b>Command Modes</b> | EXEC mode |
|----------------------|-----------|

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|------------------------|----------------|------------------------------|
|                        | Release 3.9.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | No specific guidelines impact the use of this command. |
|-------------------------|--|

| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|----------------|----------------|-------------------|
|                | netflow        | read              |

**Examples** The following example shows how to display sampler map information for a router:

```
RP/0/RSP0/CPU0:router# show flow trace platform producer location 0/0/CPU0
```

# show flow trace ea location

**show flow trace platform producer location node-id**

|                           |   |
|---------------------------|---|
| <b>Syntax Description</b> | <i>node-id</i> The <i>node-id</i> is expressed in the <i>rack/slot/module</i> notation. |
|---------------------------|---|

|                      |           |
|----------------------|-----------|
| <b>Command Modes</b> | EXEC mode |
|----------------------|-----------|

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|------------------------|----------------|------------------------------|
|                        | Release 3.9.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | No specific guidelines impact the use of this command. |
|-------------------------|--|

| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|----------------|----------------|-------------------|
|                | netflow        | read              |

**Examples** The following example shows how to display sampler map information for a router:

```
RP/0/RSP0/CPU0:router# show flow trace ea location 0/0/CPU0
```

## source (NetFlow)

To configure a source interface for the current collector, use the **source** command in flow exporter map configuration mode. To remove a configured source interface, use the **no** form of this command.

**source** *type interface-path-id*

|                           |                          |   |
|---------------------------|--------------------------|---|
| <b>Syntax Description</b> | <i>type</i>              | Interface type. For more information, use the question mark ( ? ) online help function. |
|                           | <i>interface-path-id</i> | Physical interface or virtual interface.  |

**Note** Use the **show interfaces** command to see a list of all interfaces currently configured on the router.

For more information about the syntax for the router, use the question mark ( ? ) online help function.

**Command Default** None

**Command Modes** Flow exporter map configuration

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|------------------------|----------------|------------------------------|
|                        | Release 3.9.1  | This command was introduced. |

**Usage Guidelines** For the *interface-path-id* argument, use the following guidelines:

- If specifying T1/E1/DS0 physical interfaces, the naming notation is *rack/slot/module/port/t1-num:channel-group-number*. If specifying other physical interface types, the naming notation is *rack/slot/module/port*. The slash between values is required as part of the notation. An explanation of each component of the naming notation is as follows:
  - *rack*: Chassis number of the rack.
  - *slot*: Physical slot number of the modular services card or line card.
  - *module*: Module number. A physical layer interface module (PLIM) is always 0. Shared port adapters (SPAs) are referenced by their subslot number.
  - *port*: Physical port number of the T3 controller.
  - *t1-num* : T1 or E1 channel number. T1 channels range from 1 to 24; E1 channels range from 1 to 31.
  - *channel-group-number* : Time slot number. T1 time slots range from 1 to 24; E1 time slots range from 1 to 31. The *channel-group-number* is preceded by a colon and not a slash.
- If specifying a virtual interface, the number range varies, depending on interface type.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

### Examples

This example shows how to configure a physical interface as a source for the current collector:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1
RP/0/RSP0/CPU0:router(config-fem)# source GigabitEthernet 0/1/0/0
```

This example shows how to configure a virtual interface as a source for the current collector. In this example, the source is an Ethernet bundle:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1
RP/0/RSP0/CPU0:router(config-fem)# source Bundle-Ether 1
```

### Related Commands

| Command  | Description   |
|--|---|
| <a href="#">flow exporter-map, on page 16</a>      | Creates a flow exporter map                                 |
| <a href="#">flow monitor-map, on page 18</a>       | Creates and configures a flow monitor map                   |
| <a href="#">show flow exporter, on page 35</a>     | Displays flow exporter data                                 |
| <a href="#">show flow exporter-map, on page 37</a> | Displays flow exporter map information for a specific node. |

## template (NetFlow)

To configure the export timeout value for the data and options templates, enter the **template** command in flow exporter map version configuration mode. To remove a configured template export timeout value, use the **no** form of this command.

**template** [**data** | **options**] **timeout** *seconds*

| Syntax Description | data                          | (Optional) Specifies the data template.  |
|--------------------|-------------------------------|--|
|                    | <b>options</b>                | (Optional) Specifies the options template.   |
|                    | <b>timeout</b> <i>seconds</i> | Configures the timeout value for the specified template, or for both the data and options templates. Replace <i>seconds</i> with the export timeout value. Range is from 1 through 604800 seconds. |

**Command Default** Default timeout value for data and options template is 1800 seconds.

**Command Modes** Flow exporter map version configuration

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 3.9.1 | This command was introduced. |

**Usage Guidelines** No specific guidelines impact the use of this command.

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

**Examples** This example shows how to configure the export timeout value for the data template to be 300 seconds:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map fem1
RP/0/RSP0/CPU0:router(config-fem)# version v9
RP/0/RSP0/CPU0:router(config-fem-ver)# template data timeout 300
```

| Related Commands | Command  | Description                               |
|------------------|--|---|
|                  | <a href="#">flow exporter-map, on page 16</a>  | Creates a flow exporter map               |
|                  | <a href="#">flow monitor-map, on page 18</a>   | Creates and configures a flow monitor map |
|                  | <a href="#">show flow exporter, on page 35</a> | Displays flow exporter data               |



| Command  | Description   |
|--|---|
| <a href="#">show flow exporter-map, on page 37</a> | Displays flow exporter map information for a specific node. |

## transport udp

To configure the destination port for User Datagram Protocol (UDP) packets, enter the **transport udp** command in flow exporter map configuration mode. To remove a configured destination port, use the **no** form of this command.

**transport udp** *port\_value*

| <b>Syntax Description</b>                          | <i>port_value</i> Destination port for UDP packets. Replace <i>port</i> with the destination port value. Range is from 1024 through 65535.  |         |              |   |                              |  |   |  |                             |  |   |
|--|---|---------|--------------|---|------------------------------|--|---|--|-----------------------------|--|---|
| <b>Command Default</b>                             | None  |         |              |   |                              |  |   |  |                             |  |   |
| <b>Command Modes</b>                               | Flow exporter map configuration   |         |              |   |                              |  |   |  |                             |  |   |
| <b>Command History</b>                             | <table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>Release 3.9.1</td> <td>This command was introduced.</td> </tr> </tbody> </table>   | Release | Modification | Release 3.9.1                                 | This command was introduced. |  |   |  |                             |  |   |
| Release  | Modification  |         |              |   |                              |  |   |  |                             |  |   |
| Release 3.9.1                                      | This command was introduced.  |         |              |   |                              |  |   |  |                             |  |   |
| <b>Usage Guidelines</b>                            | No specific guidelines impact the use of this command.  |         |              |   |                              |  |   |  |                             |  |   |
| <b>Task ID</b>                                     | <table border="1"> <thead> <tr> <th>Task ID</th> <th>Operations</th> </tr> </thead> <tbody> <tr> <td>netflow</td> <td>read,<br/>write</td> </tr> </tbody> </table>  | Task ID | Operations   | netflow                                       | read,<br>write               |  |   |  |                             |  |   |
| Task ID  | Operations  |         |              |   |                              |  |   |  |                             |  |   |
| netflow  | read,<br>write  |         |              |   |                              |  |   |  |                             |  |   |
| <b>Examples</b>                                    | <p>This example shows how to configure the destination port for UDP packets:</p> <pre>RP/0/RSP0/CPU0:router# configure RP/0/RSP0/CPU0:router(config)# flow exporter-map map1 RP/0/RSP0/CPU0:router(config-fem)# transport udp 1030</pre>  |         |              |   |                              |  |   |  |                             |  |   |
| <b>Related Commands</b>                            | <table border="1"> <thead> <tr> <th>Command</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td><a href="#">flow exporter-map, on page 16</a></td> <td>Creates a flow exporter map</td> </tr> <tr> <td><a href="#">flow monitor-map, on page 18</a></td> <td>Creates and configures a flow monitor map</td> </tr> <tr> <td><a href="#">show flow exporter, on page 35</a></td> <td>Displays flow exporter data</td> </tr> <tr> <td><a href="#">show flow exporter-map, on page 37</a></td> <td>Displays flow exporter map information for a specific node.</td> </tr> </tbody> </table> | Command | Description  | <a href="#">flow exporter-map, on page 16</a> | Creates a flow exporter map  | <a href="#">flow monitor-map, on page 18</a> | Creates and configures a flow monitor map | <a href="#">show flow exporter, on page 35</a> | Displays flow exporter data | <a href="#">show flow exporter-map, on page 37</a> | Displays flow exporter map information for a specific node. |
| Command  | Description   |         |              |   |                              |  |   |  |                             |  |   |
| <a href="#">flow exporter-map, on page 16</a>      | Creates a flow exporter map   |         |              |   |                              |  |   |  |                             |  |   |
| <a href="#">flow monitor-map, on page 18</a>       | Creates and configures a flow monitor map   |         |              |   |                              |  |   |  |                             |  |   |
| <a href="#">show flow exporter, on page 35</a>     | Displays flow exporter data   |         |              |   |                              |  |   |  |                             |  |   |
| <a href="#">show flow exporter-map, on page 37</a> | Displays flow exporter map information for a specific node.   |         |              |   |                              |  |   |  |                             |  |   |

## version v9

To enter flow exporter map version configuration submode so that you can configure export version parameters, enter the **version v9** command in flow exporter map configuration mode. To remove the current export version configuration and return to the default configuration, use the **no** form of this command.

**version v9**

|                           |  |
|---------------------------|--|
| <b>Syntax Description</b> | This command has no keywords or arguments. |
|---------------------------|--|

|                        |      |
|------------------------|------|
| <b>Command Default</b> | None |
|------------------------|------|

|                      |                                 |
|----------------------|---------------------------------|
| <b>Command Modes</b> | Flow exporter map configuration |
|----------------------|---------------------------------|

| <b>Command History</b> | <b>Release</b> | <b>Modification</b>          |
|------------------------|----------------|------------------------------|
|                        | Release 3.9.1  | This command was introduced. |

|                         |  |
|-------------------------|--|
| <b>Usage Guidelines</b> | When you issue the <b>version v9</b> command, the CLI prompt changes to “config-fem-ver,” indicating that you have entered flow exporter map version configuration submode. In this sample output, the question mark ( ? ) online help function displays all the commands available under flow exporter map version configuration submode: |
|-------------------------|--|

```
RP/0/RSP0/CPU0:router(config-fem)# version v9
RP/0/RSP0/CPU0:router(config-fem-ver)#?

clear      Clear the uncommitted configuration
commit     Commit the configuration changes to running
describe   Describe a command without taking real actions
do         Run an exec command
exit       Exit from this submode
no         Negate a command or set its defaults
options    Specify export of options template
pwd        Commands used to reach current submode
root       Exit to the global configuration mode
show       Show contents of configuration
template   Specify template export parameters
```

| <b>Task ID</b> | <b>Task ID</b> | <b>Operations</b> |
|----------------|----------------|-------------------|
|                | netflow        | read,<br>write    |

### Examples

This example shows how to enter flow exporter map version configuration submode:

```
RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1
```

```
RP/0/RSP0/CPU0:router(config-fem)# version v9  
RP/0/RSP0/CPU0:router(config-fem-ver)#
```

**Related Commands**

| <b>Command</b>                                     | <b>Description</b>  |
|--|---|
| <a href="#">flow exporter-map, on page 16</a>      | Creates a flow exporter map                                 |
| <a href="#">flow monitor-map, on page 18</a>       | Creates and configures a flow monitor map                   |
| <a href="#">show flow exporter, on page 35</a>     | Displays flow exporter data                                 |
| <a href="#">show flow exporter-map, on page 37</a> | Displays flow exporter map information for a specific node. |

## version ipfix

To configure Internet Protocol Flow Information Export (IPFIX) as an export version and configure export version parameters, enter the **version ipfix** command in flow exporter map configuration mode. To remove the current export version configuration and return to the default configuration, use the **no** form of this command.

**version ipfix** [**options** {**interface-table** | **sampler-table** | **vrf-table**} **timeout** *timeout-value* | **template** {**data** | **options**} **timeout** *timeout-value*]

| Syntax Description | options                 | (Optional) Specifies export of options template. Options template provide extra information about the flow records. The options template include these options:         |
|--------------------|-------------------------|---|
|                    |                         | <ul style="list-style-type: none"> <li>• interface-table</li> <li>• sampler-table</li> <li>• vrf-table</li> </ul>   |
|                    |                         | For each options template specify timeout value (in seconds) during which the exporter has to retransmit each active options template.                                  |
|                    | template                | (Optional) Specifies template export parameters such as data template and options template timeout configurations.  |
|                    | timeout                 | Specifies custom timeout value (in seconds) during which the exporter has to retransmit each active template. The range of <i>timeout-value</i> is 1 to 604800 seconds. |
|                    | <i>timeoutout-value</i> |   |

**Command Default** None

**Command Modes** Flow exporter map configuration

| Command History | Release       | Modification                 |
|-----------------|---------------|------------------------------|
|                 | Release 6.0.1 | This command was introduced. |

**Usage Guidelines** When you issue the **version ipfix** command, the CLI prompt changes to “config-fem-ver,” indicating that you have entered flow exporter map version configuration submenu. In this sample output, the question mark ( ? ) online help function displays all the commands available under flow exporter map version configuration submenu:

```
RP/0/RSP0/CPU0:router(config-fem)# version ipfix
RP/0/RSP0/CPU0:router(config-fem-ver)#?

clear      Clear the uncommitted configuration
commit     Commit the configuration changes to running
describe   Describe a command without taking real actions
do         Run an exec command
exit       Exit from this submenu
no         Negate a command or set its defaults
options    Specify export of options template
```

```

pwd          Commands used to reach current submode
root         Exit to the global configuration mode
show        Show contents of configuration
template    Specify template export parameters

```

| Task ID | Task ID | Operations     |
|---------|---------|----------------|
|         | netflow | read,<br>write |

## Examples

This example shows how to configure IPFIX as an exporter in an flow exporter map configuration submode:

```

RP/0/RSP0/CPU0:router# configure
RP/0/RSP0/CPU0:router(config)# flow exporter-map map1
RP/0/RSP0/CPU0:router(config-fem)# version ipfix
RP/0/RSP0/CPU0:router(config-fem-ver)#

```