Caveats

This chapter describes open and resolved severity 1 and 2 caveats and select severity 3 caveats:

- The "Open Caveats" sections list open caveats that apply to the current release and may apply to previous releases. A caveat that is open for a prior release and is still unresolved applies to all future releases until it is resolved.

- The "Resolved Caveats" sections list caveats resolved in a specific release, but open in previous releases.

The bug IDs are sorted alphanumerically.

Note The Caveats section includes the bug ID and a short description of the bug. For details on the symptoms, conditions, and workaround for a specific caveat you must use the Bug Search Tool.

Resolved Caveats – Cisco IOS XE 17.13.1

Identifier	Headline
CSCwh88274	Unable to remove service-policy from from standby member link.
CSCwi75499	Lost CEM circuit configuration after reboot.
CSCwh84408	The process pubd is not running in ASR920 and RSP2 device.
CSCwh68394	Unable to remove the service instance under interface.
CSCwj01024	ISIS: Counter for the number of redistributed routes does not get decremented.

Open Caveats–Cisco IOS XE 17.13.1

Identifier	Headline
CSCwh17987	Traffic drop seen when BW on the Gig interface is changed to 100 Mb with MTU beyond 5000
CSCwj05647	3GMS Serial interface protocol down with specific modem.
CSCwj06370	Serial cease traffic when configuring module other port.
CSCwi64206	Port LED status glows in green color even after the peer end connection is removed and same other wise too.
CSCwh75614	Increased CPU after upgrading router to 17.6.3 from 16.9.4 when 1000 SLM/DMM sessions are configured.
CSCwh66210	Netconf RPC failed to apply if increase mpls MTU limit to 9644 bytes.

Cisco Bug Search Tool

Cisco Bug Search Tool (BST), the online successor to Bug Toolkit, is designed to improve effectiveness in network risk management and device troubleshooting. You can search for bugs based on product, release, and keyword, and aggregates key data such as bug details, product, and version. For more details on the tool, see the help page located at http://www.cisco.com/web/applicat/cbsshelp/help.html