



Release Notes for Cisco Connected Grid Device Manager, Version 2.0

Part Number: OL-28024-01

Last Published: September 2012

Cisco 1000 Series Connected Grid Routers (Cisco CG-OS routers or CGR 1000) are multi-service communications platforms designed for use in field area networks.

The portfolio consists of two models - Cisco CGR 1240 and Cisco CGR 1120 - both ruggedized to varying degrees for outdoor and indoor deployments. Both models are modular and support a wide-range of communications interfaces such as 2G/3G, Ethernet, and WiFi.

The Cisco Connected Grid Device Manager (Device Manager) is a Windows-based application that field technicians can use to manage the Cisco CG-OS Router remotely. For some activities, the Device Manager retrieves information from the Cisco Connected Grid Network Management System (Cisco CG-NMS).

The Device Manager connects to the Cisco CG-OS Router by using a secure Ethernet or WiFi link.

Tell Us What You Think



Send your feedback about this document directly to the Connected Energy Documentation Team.

[Connected Energy Documentation Feedback Form](#)



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Contents

This document contains the following sections:

- [New Features, page 2](#)
- [System Requirements, page 4](#)
- [Important Notes, page 4](#)
- [Caveats, page 4](#)
- [Related Documentation, page 5](#)
- [Related Documentation, page 5](#)
- [Obtaining Documentation and Submitting a Service Request, page 5](#)

New Features

[Table 1](#) lists the new features added in Cisco Connected Grid Device Manager, Version 2.0(0.221).

For configuration details for the features highlighted in [Table 1](#), refer to the [Cisco Connected Grid Device Manager Installation and User Guide, Release 2.0](#).



Note

Please refer to the [“Important Notes” section on page 4](#) before installing this software.

Table 1 **New Feature Summary for CG-DM Version 2.0**

Feature	Description
Add and remove modules	<p>The Manage Modules page provides a wizard that guides you through the process of adding or removing 3G and WiMAX modules.</p> <p>Manage Modules is a new option on the At a Glance page.</p>
Certificate import enhancement	<p>You can now import certificates through the Device Manager by employing the Setup wizard or by command line. The application launches the Setup wizard when either the user clicks the Setup icon or when the certificate is not detected.</p>
Non-admin Privilege	<p>You no longer need to have administrator privileges on your Microsoft Windows user account to perform tasks with the Device Manager.</p>
Role-based Access Control (RBAC)	<p>As a user, you can be assigned up to four different types of roles that manage your access to operational and management functions on the Device Manager.</p> <ul style="list-style-type: none"> • When the Device Manager is operating in non-NMS mode, user access is managed by the assigned certificate extension OID. • When the Device Manager is operating in NMS mode, user access is managed by the role assigned in the Work Authorization. <p>The Device Manager displays or restricts features based on your assigned role.</p>
Work Authorization	<p>You can view Work Authorization requests and their status on the Device Manager when you are connected to a Cisco CG-NMS.</p> <p>The Work Authorization screen is the opening page of the Device Manager. On this page, you can synchronize with the Cisco CG-NMS to download work authorizations.</p> <p>At the Cisco CG-NMS, an admin assigns a user role for each of these work authorizations.</p> <p>You must enable Work Authorization on the Cisco CG-OS router to support this functionality on the Device Manager.</p>

System Requirements

Microsoft Windows 7 Enterprise
2 GHz or faster processor recommended
1 GB RAM minimum (for potential large log file processing)
WiFi or Ethernet interface
4 GB disk storage space
Windows login enabled
PFX file containing Utility-signed Certificate Authority (CA) and Client Certificate for router authentication (obtained from your IT department)

Important Notes

Data Reentry Required After Upgrade From Version 1.1 and 2.0

You will need to reenter data after upgrading from Device Manager 1.1 to 2.0 due to changes made for new feature support and the structure of data for enhanced security.

Specifically, data related to Test Connectivity, Change Configuration, and Update Image requires reentry after you upgrade from version 1.1 to 2.0.

Caveats

Open Caveats

- **CSCub00167**

Symptom: When an Update Image attempt on a CGR 1000 failed, the CGR 1000 returned an improper error message that was unknown to the Device Manager user.

Conditions: All conditions.

Workaround: There is no workaround.

- **CSCub16913**

Symptom: In rare circumstances, when a Device Manager cannot access a specified CGR 1000 over Ethernet due to repeated failures and retry attempts by the user, the Device Manager might attempt to connect to a different, known CGR 1000 with cached WiFi credentials.

Conditions: The following conditions exist:

- Work Authorization is not in use
- Another CGR 1000 that had a previous successful connection over WiFi, was still in range
- Ethernet connection experienced repeated failures and retry attempts by the user

Workaround: There is no workaround.

- **CSCuc32604**

Symptom: After a successful connection to the CGR 1000 router, the status bar might incorrectly indicate a certificate error.

Conditions: Issue occurs when the Device Manager starts up with an invalid certificate although the user has imported the correct certificate. The Device Manager connects successfully; however, a stale certificate error message persists.

Workaround: Close and relaunch the Device Manager.

- **CSCuc37232**

Symptom: The Device Manager might indicate a connection error when switching from a WiFi to Ethernet connection right after the Ethernet interface is brought up.

Conditions: The connection error might occur during an application-intensive operation such as performing an interface refresh.

Workaround: If the connection error persists, then close and relaunch the Device Manager.

Related Documentation

See all support documentation for Cisco 1000 Series Connected Grid Routers at:

www.cisco.com/go/cgr1000-docs

See all support documentation for Cisco Connected Grid Modules at:

www.cisco.com/go/cg-modules

Obtaining Documentation and Submitting a Service Request

For information on obtaining documentation, submitting a service request, and gathering additional information, see the monthly *What's New in Cisco Product Documentation*, which also lists all new and revised Cisco technical documentation, at:

<http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html>

Subscribe to the What's New in Cisco Product Documentation as an RSS feed and set content to be delivered directly to your desktop using a reader application. The RSS feeds are a free service. Cisco currently supports RSS Version 2.0.

This document is to be used in conjunction with the documents listed in the “[Related Documentation](#)” section.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2012 Cisco Systems, Inc. All rights reserved.

♻️ Printed in the USA on recycled paper containing 10% postconsumer waste.

