



Caveats

This chapter describes open and resolved severity 1 and 2 caveats and select severity 3 caveats:

- The “Open Caveats” sections list open caveats that apply to the current release and may apply to previous releases. A caveat that is open for a prior release and is still unresolved applies to all future releases until it is resolved.
- The “Resolved Caveats” sections list caveats resolved in a specific release, but open in previous releases.

The bug IDs are sorted alphanumerically.



Note The Caveats section includes the bug ID and a short description of the bug. For details on the symptoms, conditions, and workaround for a specific caveat you must use the Bug Search Tool.

- [Resolved Caveats – Cisco IOS XE Cupertino 17.9.6, on page 1](#)
- [Open Caveats – Cisco IOS XE Cupertino 17.9.6, on page 2](#)
- [Resolved Caveats – Cisco IOS XE Cupertino 17.9.5a, on page 2](#)
- [Open Caveats – Cisco IOS XE Cupertino 17.9.5a, on page 2](#)
- [Resolved Caveats – Cisco IOS XE Cupertino 17.9.4, on page 2](#)
- [Open Caveats – Cisco IOS XE Cupertino 17.9.4, on page 2](#)
- [Resolved Caveats - Cisco IOS XE Cupertino 17.9.3, on page 2](#)
- [Open Caveats – Cisco IOS XE Cupertino 17.9.3, on page 3](#)
- [Resolved Caveats – Cisco IOS XE Cupertino 17.9.2a, on page 3](#)
- [Open Caveats – Cisco IOS XE Cupertino 17.9.2a, on page 3](#)
- [Resolved Caveats – Cisco IOS XE Cupertino 17.9.1, on page 3](#)
- [Open Caveats – Cisco IOS XE Cupertino 17.9.1, on page 4](#)
- [Cisco Bug Search Tool, on page 4](#)

Resolved Caveats – Cisco IOS XE Cupertino 17.9.6

There are no resolved caveats for this release.

Open Caveats – Cisco IOS XE Cupertino 17.9.6

| Identifier | Headline |
|----------------------------|--|
| CSCwc56918 | IPv6 host functionality config fails after upgrade to latest image |

Resolved Caveats – Cisco IOS XE Cupertino 17.9.5a

There are no resolved caveats for this release.

Open Caveats – Cisco IOS XE Cupertino 17.9.5a

| Identifier | Headline |
|----------------------------|---|
| CSCwc56918 | NCS520:: ipv6 host functionality config fails after upgrade to latest image |

Resolved Caveats – Cisco IOS XE Cupertino 17.9.4

| Identifier | Headline |
|----------------------------|---|
| CSCwe53050 | Misreporting Output Drops as Errors in Interface counters |

Open Caveats – Cisco IOS XE Cupertino 17.9.4

There are no open caveats for this release.

Resolved Caveats - Cisco IOS XE Cupertino 17.9.3

| Identifier | Headline |
|----------------------------|--|
| CSCwb77093 | next hop self does changes automatically on VRF lite and ipv4 |
| CSCwc55520 | Traceback and IDB leak noticed when a RSP3 setup performs a switchover |
| CSCwd06972 | IOS-XE 17.x - user password not saved if user attribute list is configured |
| CSCwd57471 | Change in BGP ORF prefix-filter not being advertised from XE to XR node |
| CSCwd58396 | NETCONF: Failed sync between Running configs and Candidate database |
| CSCwd66936 | RSP2 UDP pseudowire stuck in Activating |

| Identifier | Headline |
|----------------------------|--|
| CSCwe07340 | Static route not programmed in CEF when more than six static routes use the same next hop ip address |

Open Caveats – Cisco IOS XE Cupertino 17.9.3

| Identifier | Headline |
|----------------------------|---|
| CSCwd76589 | BGP On Change Notification not sent for BGP Dynamic Peers |
| CSCwc03907 | ISIS SRLG to BGPLS export problems |
| CSCwd90908 | NTP packets are sent from global VRF with a source IP configured on service VRF interface |

Resolved Caveats – Cisco IOS XE Cupertino 17.9.2a

| Identifier | Headline |
|----------------------------|--|
| CSCwb77396 | G.8032: Ring brief output doesnt display the Block port flag in Idle state |
| CSCwc21402 | Invalid BGP update when add-paths negotiated only for label (SAFI 4) and not unicast (SAFI1) |
| CSCwc67367 | Seeing traffic issues after clearing isis with SRTE_ODN_ISIS_Flex_Algo configs |

Open Caveats – Cisco IOS XE Cupertino 17.9.2a

| Identifier | Headline |
|----------------------------|--|
| CSCwc54860 | EIGRP down authentication issues after upgrading from 17.3 to 17.6 |
| CSCwc03907 | ISIS SRLG to BGPLS export problems |
| CSCwc23316 | Command show snmp mib ifmib ifindex detail [IntName] truncated when it is more than 32 characters |

Resolved Caveats – Cisco IOS XE Cupertino 17.9.1

| Identifier | Headline |
|----------------------------|--|
| CSCwb25703 | NCS520 may experience an unexpected reset when defaulting a port-channel interface |

| Identifier | Headline |
|----------------------------|--|
| CSCwc38933 | change "no negotiation auto" to "negotiation auto" after multiple power cycles |

Open Caveats – Cisco IOS XE Cupertino 17.9.1

| Identifier | Headline |
|----------------------------|--|
| CSCwb78907 | DS3_RX_RAI is shown in both facility-alarm and facility-condition status cli |

Cisco Bug Search Tool

[Cisco Bug Search Tool](#) (BST), the online successor to Bug Toolkit, is designed to improve effectiveness in network risk management and device troubleshooting. You can search for bugs based on product, release, and keyword, and aggregates key data such as bug details, product, and version. For more details on the tool, see the help page located at <http://www.cisco.com/web/applicat/cbsshelp/help.html>