



# Recommended Computing Resources for Cisco SD-WAN Controller Release 20.7.x (On-Prem Deployment)

## Single Tenant

The supported hardware specifications for the Cisco vBond Orchestrator, Cisco vManage, and the Cisco vSmart Controller are as follows:



**Note** For cloud deployments, the Cisco operation teams actively monitor the customer deployment and add resource in collaboration with the customer. This topic does not include recommendations for Cisco cloud deployments.



**Note** The controller and the device version should be the same, to achieve the below scale.

*Table 1: Cisco SD-WAN Manager Recommended Computing Resources*

Devices	Aggregated Statistics from Edge Devices	Nodes and Deployment Models	vCPUs *	RAM*	Storage Size*	Deployment Type
<b>On-Prem</b>						
<b>** SD-WAN Application Intelligence Engine (SAIE) Disabled</b>						
<250	Disabled	One Node vManage (All Services)	16 vCPUs	32 GB RAM	500 GB	UCS
250-1000	Disabled	One Node vManage (All Services)	32 vCPUs	64 GB RAM	1 TB	UCS
1000-1500	Disabled	One Node vManage (All Services)	32 vCPUs	128 GB RAM	1 TB	UCS
1500-2000	Disabled	Three Node vManage Cluster (All Services)	32 vCPUs	64 GB RAM	1 TB	UCS

Devices	Aggregated Statistics from Edge Devices	Nodes and Deployment Models	vCPUs *	RAM*	Storage Size*	Deployment Type
2000-5000	Disabled	Three Node vManage Cluster (All Services)	32 vCPUs	128 GB RAM	1 TB	UCS
5000-7000	Disabled	Six Node vManage Cluster (3 Node with ConfigDB) and all nodes messaging server,Stats, and AppServer	32 vCPUs	128 GB RAM	1 TB	UCS
0-2000	Disabled	Three Node vManage Cluster (All Services)	32 vCPUs	64 GB RAM	1 TB	HX
2000-5000	Disabled	Three Node vManage Cluster (All Services)	32 vCPUs	128 GB RAM	1 TB	HX
<b>** SD-WAN Application Intelligence Engine (SAIE) Enabled</b>						
<500	50 GB/Day	One Node vManage (All Services)	32 vCPUs	128 GB RAM	10 TB	UCS
500-2000	100 GB/Day	Three Node vManage Cluster (All Services)	32 vCPUs	128 GB RAM	10 TB	UCS
2000-7000	2.0 TB/Day**	Six Node vManage Cluster (3 Node with ConfigDB) and all nodes messaging server,Stats, and AppServer	32 vCPUs	128 GB RAM	10 TB	UCS

**Note**

- \*For a larger dataset per day, run Stats on all the servers.
- \*\* Along with the SAIE, the Aproute statistics are also considered in the recommendations.
- \* vCPU, RAM, and Storage Size numbers are on per Cisco vManage basis. The Storage Size numbers are the maximum tested values by Cisco, you can allocate smaller storage sizes.

To achieve scale beyond the above mentioned numbers, deploy multiple overlays.

**Note**

In Cisco vManage Release 20.5.1 and earlier releases, You can modify the **DPI** size to the desired value to achieve the above mentioned storage size numbers.



**Note** Starting from Cisco vManage Release 20.6.1, you can achieve the above mentioned storage size numbers by modifying the aggregated DPI size. The aggregated DPI size is unidimensional and varies when the deployment includes edge devices that run on a mix of releases (Cisco SD-WAN Release 20.6.x and earlier releases). The aggregated DPI also varies when on-demand troubleshooting is enabled for the devices.

Ensure that both the DPI and aggregated DPI index sizes are configured to enable on-demand troubleshooting.

To modify the aggregated DPI value,

1. From the **Cisco vManage** menu, choose **Administration > Settings**.
2. Click **Edit** next to **Statistics Database Configuration**.
3. Modify the **Aggregated DPI** size to the desired value based on your DPI traffic, the default disk size allocation is 5 GB.



**Note** When DPI is enabled, you must set the Statistics Collection timer to 30 minutes or higher.

To set the Statistics Collection timer,

1. From the **Cisco vManage** menu, choose **Administration > Settings**.
2. Click **Edit** next to **Statistics Configuration**.
3. Modify the **Collection Interval** minutes to the desired value based on your DPI traffic, the default collection interval is 30 minutes.
4. Click **Save**.

**Table 2: Cisco Catalyst SD-WAN Validator Recommended Computing Resources for HX/UCS**

Devices	vCPUs	RAM	OS Volume	vNICs
1-50	2	4 GB	10 GB	2 (one for tunnel interface, one for management)
51-250	2	4 GB	10 GB	2 (one for tunnel interface, one for management)
251-1000	2	4 GB	10 GB	2 (one for tunnel interface, one for management)
1001 or more	4	8 GB	10 GB	2 (one for tunnel interface, one for management)



**Note** The tested and recommended limit of supported Cisco vBond Orchestrator instances in a single Cisco SD-WAN overlay is eight.

**Table 3: Cisco Catalyst SD-WAN Controller Recommended Computing Resources for HX/UCS**

Devices	vCPUs	RAM	OS Volume	vNICs
---------	-------	-----	-----------	-------

1-50	2	4 GB	16 GB	2 (one for tunnel interface, one for management)
51-250	4	8 GB	16 GB	2 (one for tunnel interface, one for management)
251-1000	4	16 GB	16 GB	2 (one for tunnel interface, one for management)
1001 or more	8	16 GB	16 GB	2 (one for tunnel interface, one for management)

### Testbed Specifications

**Table 4: Testbed specifications for UCS Platforms**

Hardware SKU	Specifications
UCSC-C240-M5SX	UCS C240 M5 24 SFF + 2 rear drives without CPU, memory cards, hard disk, PCIe, PS
UCS-MR-X16G1RT-H	16GB DDR4-2933-MHz RDIMM/1Rx4/1.2v
UCS-CPU-I6248R	Intel 6248R 3GHz/205W 24C/35.75MB DDR4 2933MHz
UCS-SD16T123X-EP	1.6TB 2.5in Enterprise Performance 12G SAS SSD (3X endurance)



**Note** Any UCS Platform (Fifth generation and above) with the same or higher hardware specifications mentioned in the above table supports Cisco SD-WAN Controllers with similar scale numbers mentioned in this document.

Drive specifications:

- Interface Speed— 12.0 Gbit per second
- Read speed (64KB) —1800 MB per second
- Write speed (64KB)—850 MB per second



**Note**

- The recommended numbers are based on the test setup specifications. Systems below these requirements may have challenges processing high volume of statistics data like SAIE.
- Tested with 10 TB Volume (8 X 1.6 TB SSD Drives Raid 0).
- Default hyperthreading is enabled.
- Slower disks can impact processing speed.

**Table 5: Testbed specifications for HX Platforms**

Hardware SKU	Specifications
HXAF240-M5SX	Cisco HyperFlex HX240c M5 All Flash Node
HX-MR-X32G2RT-H	32GB DDR4-2933-MHz RDIMM/2Rx4/1.2v
HX-CPU-I6248	Intel 6248 2.5GHz/150W 20C/24.75MB 3DX DDR4 2933 MHz
HX-SD38T61X-EV	3.8TB 2.5 inch Enterprise Value 6G SATA SSD
HX-NVMEXPB-I375	375GB 2.5 inch Intel Optane NVMe Extreme Performance SSD

Drive specifications:

- The tested replication factor is 3.
- The default compression on the HX system is applicable to all cases. This compression is automatically determined by the system and cannot be configured.

**Multitenant**

The supported hardware specifications for the Cisco vBond Orchestrator, Cisco vManage, and the Cisco vSmart Controllers are as follows:

**Table 6: Hardware Specifications to Support 50 Tenants and 1000 Devices**

Server	Cisco vManage	Cisco vBond Orchestrator	Cisco vSmart Controller
<b>Deployment Model</b>	On-premises Cluster	On-premises deployment	On-premises deployment
<b>Number of Instances</b>	3 Compute+Data nodes	2 instances	2 instances per 24 tenants To support 50 tenants and 1000 devices across all tenants, deploy 6 Cisco vSmart Controller instances.
<b>CPU</b>	32 vCPU	4 vCPU	8 vCPU
<b>DRAM</b>	128 GB	4 GB	16 GB
<b>Hard Disk</b>	Minimum: 1 TB; Recommended: 10 TB	10 GB	10 GB
<b>Bandwidth</b>	1 Gbps	10 Mbps	100 Mbps

Table 7: Hardware Specifications to Support 100 Tenants and 5000 Devices

Server	Cisco vManage	Cisco vBond Orchestrator	Cisco vSmart Controller
<b>Deployment Model</b>	On-premises Cluster	On-premises deployment	On-premises deployment
<b>Number of Instances</b>	6 nodes: 3 Compute+Data nodes and 3 Data nodes	2 instances	2 instances per 24 tenants To support 100 tenants and 5000 devices across all tenants, deploy 10 Cisco vSmart Controllers.
<b>CPU</b>	64 vCPU	4 vCPU	8 vCPU
<b>DRAM</b>	128 GB	4 GB	16 GB
<b>Hard Disk</b>	Minimum: 2 TB; Recommended: 10 TB	10 GB	10 GB
<b>Bandwidth</b>	1 Gbps	10 Mbps	100 Mbps

**Note**

- If DPI is enabled, we recommend that the aggregated DPI data (across all Cisco vManage nodes and all tenants in the multitenant system) does not exceed 350 GB per day. If the DPI data exceeds 350 GB per day, increase the Hard Disk capacity of each Cisco vManage node up to 10 TB.
- A pair of Cisco vSmart Controllers supports 24 tenants and 1000 devices across all tenants.
- A tenant can add a maximum of 1000 devices.
- The tested and recommended limit of supported Cisco vBond Orchestrator instances in a single Cisco SD-WAN overlay is eight.