



Technical Specifications

This chapter contains the following sections:

- [Device Specifications, on page 1](#)
- [MIB Information, on page 2](#)

Device Specifications

This section provides device, port, cabling specifications, and power adapters for the Cisco ISA 3000.



Warning Ultimate disposal of this product should be handled according to all national laws and regulations. Statement 1040

Table 1: Cisco ISA 3000 Specifications

Description	Technical Specification
Dimensions (H x W x D)	(height x width x depth x) are 5.13 x 4.42 x 6.31 in. (13 cm x 11.2 x 16 cm).
Weight	4.75 lbs
Operating Temperature	-40C to 60C (0 LFM) -40C to 70C (40 LFM) -34C to 75C (200 LFM)
Humidity	0 to 95% RH, non condensing
Ingress Protection Rating	IP30
Transportation/Storage Conditions	15K ft. altitude; -40C to 85C temperature

Description	Technical Specification
Shock/Vibration	<ul style="list-style-type: none"> • IEC60068-2-6 and IEC60068-2-27 MIL-STD-810, Method 514.4 Marine EN60945 Industrial EN61131-2/IEC61131-2 Railway EN50155 Smart Grid EN61850-3 IEEE 1613
DC input voltage	<ul style="list-style-type: none"> • Maximum operating range: 9.6 to 60 VDC • Rated: +/- 12 to 48 VDC • The DC-input power supply is an SELV circuit, and it can only be connected to another
Maximum DC input current	<ul style="list-style-type: none"> • 0.5A @ 48VDC • 1.0A @ 24VDC • 2.0A @ 12VDC
Power consumption	24 Watts

MIB Information

MIBs supported for the device can be seen in the network management MIBS
 URL: <https://snmp.cloudapps.cisco.com/Support/SNMP/do/BrowseMIB.do?local=en>