



Security Exchange Protocol

See SXP

Numerics

10/100 autonegotiation feature, forced [25](#)

10-Gigabit Ethernet or Gigabit Ethernet ports

deploy on WS-X4606-10GE-E and Sup 6-E [13](#)

10-Gigabit Ethernet port

deploy with Gigabit Ethernet SFP ports [12](#), [13](#)

10-slot chassis, support for WS-X46490-CSFP-E [17](#)

1400 W DC Power supply

special considerations [21](#)

1400 W DC SP Triple Input power supply

special considerations [22](#)

802.10 SAID (default) [4](#)

802.1AE

standard [2](#)

802.1Q

trunks [6](#)

tunnel ports with other features [5](#)

tunneling

compatibility with other features [5](#)

defaults [3](#)

described [2](#)

802.1Q VLANs

trunk restrictions [4](#)

802.1s

See MST

802.1w

See MST

802.1X

See port-based authentication

802.1X authentication

Authentication Failed VLAN assignment [17](#)

for Critical Authentication [14](#)

for guest VLANs [11](#)

for MAC Authentication Bypass [12](#)

for Unidirectional Controlled Port [15](#)

VLAN User Distribution [16](#)

web-based authentication [14](#)

with port security [19](#)

with VLAN assignment [10](#)

with voice VLAN ports [22](#)

802.1X Host Mode [6](#)

multiauthentication mode [8](#)

multidomain authentication mode [7](#)

single-host [7](#)

802.1x-REV [2](#)

802.3ad

See LACP

9000W AC, displaying OBFL [4](#)

A

AAA [1](#)

AAA (authentication, authorization, and accounting). See also port-based authentication. [1](#)

abbreviating commands [5](#)

about Wireshark [5](#)

access control entries

See ACEs

access control entries and lists [1](#)

access list filtering, SPAN enhancement [13](#)

access lists

using with WCCP [8](#)

- access ports
 - and Layer 2 protocol tunneling [15](#)
 - configure port security [7](#), [22](#)
 - configuring [7](#)
- access VLANs [5](#)
- access-group mode, configuring on Layer 2 interface [33](#)
- access-group mode, using PACL with [32](#)
- accounting
 - with RADIUS [113](#)
 - with TACACS+ [16](#), [21](#)
- ACEs
 - ACLs [2](#)
 - IP [41](#), [2](#)
 - Layer 4 operation restrictions [11](#)
- ACEs and ACLs [1](#)
- ACL assignments and redirect URLs, configure [40](#)
- ACL assignments, port-based authentication [20](#)
- ACL configuration, displaying a Layer 2 interface [34](#)
- ACLs
 - ACEs [2](#)
 - and SPAN [5](#)
 - and TCAM programming for Sup 6-E [10](#)
 - and TCAM programming for Sup II-Plus thru V-10GE [7](#)
 - applying IPv6 ACLs to a Layer 3 interface [18](#)
 - applying on routed packets [28](#)
 - applying on switched packets [27](#)
 - compatibility on the same switch [3](#)
 - configuring with VLAN maps [27](#)
 - CPU impact [13](#)
 - downloadable [7](#)
 - hardware and software support [6](#)
 - IP, matching criteria for port ACLs [5](#)
 - MAC extended [14](#)
 - matching criteria for router ACLs [4](#)
 - port
 - and voice VLAN [5](#)
 - defined [3](#)
 - processing [13](#)
 - selecting mode of capturing control packets [7](#)
 - troubleshooting high CPU [7](#)
 - types supported [3](#)
 - understanding [2](#)
 - VLAN maps [5](#)
- ACLs and VLAN maps, examples [21](#)
- ACLs, applying to a Layer 2 interface [33](#)
- acronyms, list of [1](#)
- action drivers, marking [21](#), [55](#)
- activating and deactivating a capture point, Wireshark [14](#)
- activating and deactivating Wireshark capture points, conceptual, Wireshark [10](#)
- active queue management [9](#)
- active queue management via DBL, QoS on Sup 6-E [34](#), [68](#)
- active traffic monitoring, IP SLAs [1](#)
- adding members to a community [9](#)
- address resolution [44](#)
- addresses
 - displaying the MAC table [44](#)
 - dynamic
 - changing the aging time [30](#)
 - defined [28](#)
 - learning [29](#)
 - removing [31](#)
 - IPv6 [2](#)
 - MAC, discovering [44](#)
 - See MAC addresses
 - static
 - adding and removing [36](#)
 - defined [28](#)
- adjacency tables
 - description [2](#)
 - displaying statistics [10](#)
- administrative VLAN
 - REP, configuring [9](#)
- administrative VLAN per segment [9](#)
- administrative VLAN, REP [8](#)
- advertisements
 - LLDP [7](#), [2](#)

- advertisements, VTP
 - See VTP advertisements
- aggregation switch, enabling DHCP snooping [9](#)
- aging time
 - MAC address table [30](#)
- All Auth manager sessions on the switch authorized for a specified authentication method [128](#)
- All Auth manager sessions, displaying summary [128](#)
- ANCP client
 - enabling and configuring [2](#)
 - guidelines and restrictions [5](#)
 - identify a port with DHCP option 82 [4](#)
 - identify a port with protocol [2](#)
 - overview [1](#)
- ANCP protocol
 - identifying a port with [2](#)
- applying IPv6 ACLs to a Layer 3 interface [18](#)
- AQM via DBL, QoS on Sup 6-E [34](#), [68](#)
- archiving crashfiles information [8](#)
- ARP
 - defined [44](#)
 - table
 - address resolution [44](#)
 - managing [44](#)
- asymmetrical links, and 802.1Q tunneling [3](#)
- attachment points, Wireshark [6](#)
- attributes, RADIUS
 - vendor-proprietary [116](#)
 - vendor-specific [114](#)
- Auth manager session for an interface, verifying [128](#)
- Auth manager summary, displaying [128](#)
- authentication
 - NTP associations [4](#)
 - RADIUS
 - key [106](#)
 - login [108](#)
 - See also port-based authentication
 - TACACS+
 - defined [16](#)
 - key [18](#)
 - login [19](#)
- Authentication Failed, configuring 80.1X [73](#)
- Authentication methods registered with the Auth manager, determining [127](#)
- authentication open comand [8](#)
- authentication proxy web pages [4](#)
- authentication server
 - defined [3](#)
 - RADIUS server [3](#)
- Authentication, Authorization, and Accounting (AAA) [1](#)
- authoritative time source, described [2](#)
- authorization
 - with RADIUS [112](#)
 - with TACACS+ [16](#), [21](#)
- authorized and unauthorized ports [5](#)
- authorized ports with 802.1X [5](#)
- Auto Identity
 - Built-in Policies [4](#)
 - Class Map Templates [4](#)
 - Global Template [2](#)
 - Interface Templates [3](#)
 - Overview [2](#)
 - Parameter Maps [5](#)
 - Service Templates [5](#)
- Auto SmartPorts built-in macros
 - configuring parameters [6](#)
- Auto SmartPorts macros
 - built-in macros [4](#)
 - configuration guidelines [5](#)
 - default configuration [4](#)
 - defined [1](#)
 - displaying [13](#)
 - enabling [3](#)
 - IOS shell [2](#), [10](#)
- Auto Smartports macros
 - defined [2](#)
- Auto SmartPorts user-defined macros
 - configuring [10](#)

- autoconfiguration [2](#)
 - automatic discovery
 - considerations [7](#)
 - Auto-MDIX on a port
 - configuring [37](#)
 - displaying the configuration [37](#)
 - overview [36](#)
 - autonegotiation feature
 - forced 10/100Mbps [25](#)
 - auto-sync command [8, 7](#)
 - Auto SmartPorts macros
 - See also SmartPorts macros
 - Auto Smartports macros
 - See also Smartports macros
-
- B**
- b command [3](#)
 - b flash command [3](#)
 - Baby Giants
 - interacting with [35](#)
 - BackboneFast
 - adding a switch (figure) [3](#)
 - and MST [23](#)
 - configuring [23](#)
 - link failure (figure) [22, 23](#)
 - not supported MST [23](#)
 - understanding [21](#)
 - See also STP
 - banners
 - configuring
 - login [27](#)
 - message-of-the-day login [24](#)
 - default configuration [24](#)
 - when displayed [24](#)
 - BFD
 - and hardware support [7](#)
 - configuration example
 - BFD in a BGP network [25](#)
 - BFD in an EIGRP network with echo mode enabled by default [17](#)
 - BFD in an OSPF network [22](#)
 - support for static routing [27](#)
 - configuring
 - Echo mode [15](#)
 - session parameters on the interface [8](#)
 - Slow timer [16](#)
 - support for BGP [9](#)
 - support for dynamic routing protocols [9](#)
 - support for EIGRP [10](#)
 - support for OSPF [11](#)
 - support for static routing [13](#)
 - disabling echo mode without asymmetry [16](#)
 - monitoring and troubleshooting [17](#)
 - neighbor relationships [3](#)
 - operation [3](#)
 - prerequisites [2](#)
 - restrictions [2](#)
 - BGP [17](#)
 - routing session with multi-VRF CE [9](#)
 - blocking packets [1](#)
 - blocking state (STP)
 - RSTP comparisons (table) [24](#)
 - Boolean expressions in tracked lists [4](#)
 - boot bootldr command [32](#)
 - boot command [28](#)
 - boot commands [3](#)
 - boot fields
 - See configuration register boot fields
 - boot system command [26, 32](#)
 - boot system flash command [28](#)
 - bootstrap program
 - See ROM monitor
 - Border Gateway Protocol
 - See BGP
 - boundary ports
 - description [27](#)
 - BPDU Guard

- and MST [23](#)
- configuring [23](#)
- overview [15](#)

BPDUs

- and media speed [2](#)
- pseudobridges and [25](#)
- what they contain [3](#)

Bridge Assurance [8](#), [11](#)

bridge ID

- See STP bridge ID

bridge priority (STP) [17](#)

bridge protocol data units

- See BPDUs

bridging loop [40](#)

Broadcast Storm Control

- disabling [5](#)
- enabling [3](#)

Built-in macros and user-defined triggers, configuring mapping [9](#)

C

- cache engine clusters [1](#)
- cache engines [1](#)
- cache farms
 - See cache engine clusters
- Call Home
 - description [24](#), [1](#)
 - message format options [2](#)
 - messages
 - format options [2](#)
- call home [1](#)
 - alert groups [6](#)
 - configuring e-mail options [9](#)
 - contact information [4](#)
 - default settings [18](#)
 - destination profiles [5](#)
 - displaying information [13](#)
 - mail-server priority [10](#)
 - pattern matching [8](#)
 - periodic notification [8](#)
 - rate limit messages [9](#)
 - severity threshold [8](#)
 - smart call home feature [2](#)
 - SMTP server [9](#)
 - testing communications [10](#)
- call home alert groups
 - configuring [6](#)
 - description [6](#)
 - subscribing [7](#)
- call home contacts
 - assigning information [4](#)
- call home destination profiles
 - attributes [5](#)
 - configuring [5](#)
 - description [5](#)
 - displaying [16](#)
- call home notifications
 - full-txt format for syslog [25](#)
 - XML format for syslog [28](#)
- candidate switch, cluster
 - defined [12](#)
- candidates
 - automatic discovery [7](#)
- capture filter, Wireshark [7](#)
- capture points, Wireshark [6](#)
- Capturing control packets
 - selecting mode [7](#)
- cautions
 - Unicast RPF
 - BGP optional attributes [4](#)
- cautions for passwords
 - encrypting [22](#)
- CDP
 - automatic discovery in communities [7](#)
 - configuration [2](#)
 - defined with LLDP [1](#)
 - displaying configuration [3](#)

- enabling on interfaces **3**
- host presence detection **8**
- Layer 2 protocol tunneling **13**
- maintaining **3**
- monitoring **3**
- overview **2, 1**
- cdp enable command **3**
- CEF
 - adjacency tables **2**
 - and NSF with SSO **5**
 - configuring load balancing **7**
 - displaying statistics **8**
 - enabling **7, 2**
 - hardware switching **4**
 - load balancing **6**
 - overview **1**
 - software switching **4**
- certificate authority (CA) **3**
- CFM
 - and Ethernet OAM interaction **51**
 - and Ethernet OAM, configuring **51**
 - clearing **31**
 - configuration guidelines **7, 4**
 - configuring crosscheck for VLANs **11**
 - configuring fault alarms **16**
 - configuring port MEP **14**
 - configuring static remote MEP **13, 16, 18**
 - crosscheck **5**
 - defined **2**
 - EtherChannel support **7, 4**
 - fault alarms
 - configuring **16**
 - IP SLAs support for **6**
 - IP SLAs with endpoint discovers **21**
 - maintenance domain **3**
 - manually configuring IP SLAs ping or jitter **19**
 - measuring network performance **6**
 - monitoring **32, 33**
 - port MEP, configuring **14**
 - remote MEPs **5**
 - static RMEP check **5**
 - static RMEP, configuring **13, 16, 18**
 - Y.1731
 - described **27**
- CGMP
 - overview **2**
- Change of Authorization, RADIUS **100**
- channel-group group command **49, 9, 11**
- Cisco 7600 series Internet router
 - enabling SNMP **4, 5**
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco IOS IP SLAs **2**
- Cisco IOS NSF-aware
 - support **2**
- Cisco IOS NSF-capable support **2**
- Cisco IP Phones
 - configuring **2**
 - sound quality **1**
- Cisco TrustSec
 - credentials **10**
 - switch-to-switch security
 - 802.1x mode **11**
 - configuration example **14**
 - manual mode **12**
- Cisco TrustSec Network Device Admission Control
 - See NDAC
- CiscoWorks 2000 **4**
- CIST
 - description **22**
- civic location **3**
- class level, configure in a service policy **31, 65**
- class of service
 - See CoS

- clear cdp counters command [4](#)
- clear cdp table command [3](#)
- clear counters command [42](#)
- clear ip eigrp neighbors command [19](#)
- clearing
 - Ethernet CFM [31](#)
 - IP multicast table entries [28](#)
- CLI
 - accessing [2](#)
 - backing out one level [5](#)
 - getting commands [5](#)
 - history substitution [4](#)
 - managing clusters [13](#)
 - modes [5](#)
 - monitoring environments [1](#)
 - ROM monitor [7](#)
 - software basics [4](#)
- client processes, tracking [1](#)
- clients
 - in 802.1X authentication [3](#)
- clock
 - See system clock
- clustering switches
 - command switch characteristics and VTY [12](#)
 - convert to a community [10](#)
 - managing
 - through CLI [13](#)
 - overview [2](#)
 - planning considerations
 - CLI [13](#)
 - passwords [8](#)
- CoA Request Commands [102](#)
- command modes [5](#)
- command switch, cluster
 - requirements [11](#)
- command-line processing [3](#)
- commands
 - b [3](#)
 - b flash [3](#)
 - boot [3](#)
 - confreg [3](#)
 - dev [3](#)
 - dir device [3](#)
 - frame [5](#)
 - i [3](#)
 - listing [5](#)
 - meminfo [6](#)
 - reset [3](#)
 - ROM monitor [2–3](#)
 - ROM monitor debugging [5–6](#)
 - SNMP [4](#)
 - sysret [5](#)
- common and internal spanning tree
 - See CIST
- common spanning tree
 - See CST
- community of switches
 - access modes in Network Assistant [9](#)
 - adding devices [9](#)
 - communication protocols [8](#)
 - community name [8](#)
 - configuration information [9](#)
 - converting from a cluster [10](#)
 - host name [8](#)
 - passwords [8](#)
- community ports [3](#)
- community strings
 - configuring [7](#)
 - overview [4](#)
- community VLANs [2, 3](#)
 - configure as a PVLAN [15](#)
- compiling MIBs [4](#)
- config terminal command [9](#)
- config-register command [29](#)
- configurable leave timer,IGMP [4](#)
- configuration examples
 - SNMP [15](#)

- configuration files
 - limiting TFTP server access [15](#)
 - obtaining with DHCP [6](#)
 - saving [10](#)
 - system contact and location information [14](#)
- configuration guidelines
 - CFM [7](#), [4](#)
 - Ethernet OAM [35](#)
 - REP [7](#)
 - SNMP [6](#)
 - VLAN mapping [9](#)
- configuration register
 - boot fields
 - listing value [29](#)
 - modifying [28](#)
 - changing from ROM monitor [3](#)
 - changing settings [28–29](#)
 - configuring [26](#)
 - settings at startup [27](#)
- configure class-level queue-limit in a service policy [31](#), [65](#)
- configure terminal command [29](#), [2](#)
- configuring access-group mode on Layer 2 interface [33](#)
- configuring flow control [29](#)
- configuring interface link and trunk status events [43](#)
- configuring named IPv6 ACLs [16](#)
- configuring named MAC extended ACLs [14](#), [15](#)
- configuring unicast MAC address filtering [14](#)
- configuring VLAN maps [19](#)
- confreg command [3](#)
- Connectivity Fault Management
 - See CFM
- console configuration mode [5](#)
- console download [4–5](#)
- console port
 - disconnecting user sessions [7](#)
 - monitoring user sessions [6](#)
- contact information
 - assigning for call home [4](#)
- Control Plane Policing
 - and Layer 2 Control packet QoS, configuration example [18](#)
 - configuration guidelines and restrictions [9](#)
 - configuring for control plane traffic [4](#)
 - configuring for data plane and management plan traffic [6](#)
 - defaults [4](#)
 - general guidelines [4](#)
 - monitoring [10](#)
 - understanding [2](#)
- control protocol, IP SLAs [4](#)
- controlling switch access with RADIUS [98](#)
- convergence
 - REP [4](#)
- copy running-config startup-config command [10](#)
- copy system:running-config nvram:startup-config command [32](#)
- core system filter, Wireshark [7](#)
- CoS
 - definition [3](#)
 - figure [2](#)
 - overriding on Cisco IP Phones [4](#)
 - priority [4](#)
- counters
 - clearing MFIB [29](#)
 - clearing on interfaces [42](#)
- CPU port sniffing [10](#)
- CPU, impact of ACL processing [13](#)
- crashfiles information, archiving [8](#)
- Critical Authentication
 - configure with 802.1X [65](#)
- crosscheck, CFM [5](#), [11](#)
- CST
 - description [25](#)
 - IST and [22](#)
 - MST and [22](#)
- CTS Fields [6](#)
- customer edge devices [2](#)
- C-VLAN [2](#), [7](#)

D

database agent

configuration examples [15](#)

enabling the DHCP Snooping [13](#)

daylight saving time [13](#)

debug commands, ROM monitor [5–6](#)

decoding and displaying packets, Wireshark [9](#)

default configuration

802.1X [29](#)

banners [24](#)

DNS [23](#)

Ethernet OAM [35](#)

IGMP filtering [30](#)

IGMP snooping [5, 6](#)

IP SLAs [6](#)

IPv6 [7](#)

Layer 2 protocol tunneling [16](#)

LLDP [5](#)

MAC address table [30](#)

MVR [23](#)

NTP [4](#)

private VLANs [12](#)

RADIUS [105](#)

REP [7](#)

resetting the interface [45](#)

RMON [3](#)

SNMP [5](#)

SPAN and RSPAN [6](#)

system message logging [3](#)

TACACS+ [18](#)

VLAN mapping [9](#)

Y.1731 [29](#)

default gateway

configuring [11](#)

verifying configuration [11](#)

default settings, erase command [33](#)

default web-based authentication configuration

802.1X [6](#)

defining/modifying/deleting a capture point, Wireshark [12](#)

denial-of-service attacks

IP address spoofing, mitigating [5](#)

Unicast RPF, deploying [5](#)

denying access to a server on another VLAN [25](#)

deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports [12, 13](#)

deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports on WS-X4606-10GE-E and Sup 6-E [13](#)

description command [29](#)

dev command [3](#)

device discovery protocol [1](#)

device IDs

call home format [21, 22](#)

device sensor

configuring [120](#)

DHCP

configuring

rate limit for incoming packets [13](#)

denial-of-service attacks, preventing [13](#)

rate limiting of packets

configuring [13](#)

DHCP option 82

identifying a port with [4](#)

overview [3](#)

DHCP Snooping

enabling, and Option 82 [10](#)

DHCP snooping

accepting untrusted packets from edge switch [10](#)

configuring [6](#)

default configuration [7](#)

displaying binding tables [19](#)

displaying configuration [19](#)

displaying information [18](#)

enabling [7](#)

enabling on private VLAN [12](#)

enabling on the aggregation switch [9](#)

enabling the database agent [13](#)

message exchange process [4](#)

- monitoring [23](#)
- option 82 data insertion [3](#)
- overview [1](#)
- Snooping database agent [2](#)
- DHCP Snooping Database Agent
 - adding to the database (example) [18](#)
 - enabling (example) [15](#)
 - overview [2](#)
 - reading from a TFTP file (example) [17](#)
- DHCP-based autoconfiguration
 - client request message exchange [3](#)
 - configuring
 - client side [3](#)
 - DNS [5](#)
 - relay device [5](#)
 - server-side [4](#)
 - TFTP server [4](#)
 - example [7](#)
 - lease options
 - for IP address information [4](#)
 - for receiving the configuration file [4](#)
 - overview [2](#)
 - relationship to BOOTP [3](#)
- Diagnostics
 - online [1](#)
 - Power-On-Self-Test
 - causes of failure [19](#)
 - how it works [10](#)
 - overview [10](#)
 - Power-On-Self-Test for Supervisor Engine V-10GE [12](#)
- Differentiated Services Code Point values
 - See DSCP values
- DiffServ architecture, QoS [2](#)
- Digital optical monitoring transceiver support [23](#)
- dir device command [3](#)
- disabled state
 - RSTP comparisons (table) [24](#)
- disabling
 - broadcast storm control [5](#)
 - disabling multicast storm control [6](#)
 - disconnect command [7](#)
 - discovery, clusters
 - See automatic discovery
 - discovery, Ethernet OAM [34](#)
 - display dection and removal events [7](#)
 - display filter, Wireshark [7](#)
 - display PoE consumed by a module [8](#)
 - display PoE detection and removal events [7](#)
 - displaying
 - Auth Manager summary for an interface [128](#)
 - MAB details [130](#)
 - summary of all Auth manager sessions [128](#)
 - summary of all Auth manager sessions on the switch authorized for a specified authentication method [128](#)
 - displaying EtherChannel to a Virtual Switch System [20](#)
 - displaying storm control [6](#)
 - displaying Wireshark information [14](#)
 - dispute mechanism [40](#)
 - DNS
 - and DHCP-based autoconfiguration [5](#)
 - default configuration [23](#)
 - displaying the configuration [24](#)
 - overview [22](#)
 - setting up [23](#)
 - Domain Name System
 - See DNS
 - domain names
 - DNS [22](#)
 - double-tagged packets
 - 802.1Q tunneling [2](#)
 - Layer 2 protocol tunneling [15](#)
 - downloading MIBs [3, 4](#)
 - drop threshold for Layer 2 protocol packets [16](#)
 - DSCP values
 - definition [4](#)
 - IP precedence [2](#)
 - Dual_Active Detection
 - using Enhanced PAgP [23](#)

- Dual-Active Detection, using Fast-Hello [24](#)
 - duplex command [27](#)
 - duplex mode
 - configuring interface [24](#)
 - dynamic ARP inspection
 - ARP cache poisoning [2](#)
 - configuring
 - ACLs for non-DHCP environments [11](#)
 - in DHCP environments [5](#)
 - log buffer [14](#)
 - rate limit for incoming ARP packets [16](#)
 - denial-of-service attacks, preventing [16](#)
 - interface trust state, security coverage [3](#)
 - log buffer
 - configuring [14](#)
 - logging of dropped packets [4](#)
 - overview [1](#)
 - port channels, their behavior [5](#)
 - priority of static bindings [4](#)
 - purpose of [2](#)
 - rate limiting of ARP packets [4](#)
 - configuring [16](#)
 - validation checks, performing [19](#)
 - Dynamic Host Configuration Protocol snooping
 - See DHCP snooping
 - dynamic port VLAN membership
 - example [28](#)
 - limit on hosts [28](#)
 - reconfirming [25](#), [26](#)
 - troubleshooting [28](#)
- E**
-
- EAP frames
 - changing retransmission time [88](#)
 - exchanging (figure) [4](#), [6](#), [13](#)
 - request/identity [4](#)
 - response/identity [4](#)
 - setting retransmission number [89](#)
 - EAPOL frames
 - 802.1X authentication and [3](#)
 - OTP authentication, example (figure) [4](#), [13](#)
 - start [4](#)
 - Echo mode,configuring BFD [15](#)
 - edge ports
 - description [27](#)
 - EGP
 - overview [17](#)
 - EIGRP
 - configuration examples [20](#)
 - monitoring and maintaining [19](#)
 - EIGRP (Enhanced IGRP)
 - stub routing
 - benefits [18](#)
 - configuration tasks [18](#)
 - configuring [14](#)
 - overview [14](#)
 - restrictions [18](#)
 - verifying [19](#)
 - EIGRP (enhanced IGRP)
 - overview [18](#)
 - eigrp stub command [19](#)
 - EIGRP stub routing, configuring [13](#)
 - ELIN location [3](#)
 - e-mail addresses
 - assigning for call home [4](#)
 - e-mail notifications
 - Call Home [24](#), [1](#)
 - Embedded CiscoView
 - displaying information [48](#)
 - installing and configuring [45](#)
 - overview [45](#)
 - emergency alarms on Sup Engine 6-E systems [5](#)
 - enable command [9](#), [28](#)
 - enable mode [5](#)
 - enabling SNMP [4](#), [5](#)
 - encryption keying [2](#)
 - encryption keys, MKA [2](#)

- Enhanced Interior Gateway Routing Protocol
 - See EIGRP
- enhanced object tracking
 - defined [1](#)
 - IP routing state [2](#)
 - line-protocol state [2](#)
 - tracked lists [3](#)
- Enhanced PoE support on E-series [15](#)
- Enhanced PoE support on E-series, configuring Universal PoE [16](#)
- environmental monitoring
 - using CLI commands [1](#)
- EPM logging [131](#)
- errdisable recovery
 - configuring [14](#)
- ERSPAN
 - Overview [3](#)
- EtherChannel
 - channel-group group command [49, 9, 11](#)
 - configuration guidelines [32, 6](#)
 - configuring [7–20](#)
 - configuring (tasks) [30](#)
 - configuring Layer 2 [11](#)
 - configuring Layer 3 [8](#)
 - DFC restriction, see CSCdt27074 in the Release Notes
 - displaying to a virtual switch system [20](#)
 - interface port-channel command [8](#)
 - lACP system-priority
 - command example [16](#)
 - modes [3](#)
 - overview [2](#)
 - PAgP
 - Understanding [4](#)
 - physical interface configuration [49, 8](#)
 - port-channel interfaces [2](#)
 - port-channel load-balance command [19](#)
 - removing [20](#)
 - removing interfaces [19](#)
 - understanding [1](#)
- EtherChannel guard
 - disabling [7](#)
 - enabling [6](#)
 - overview [6](#)
- Ethernet management port
 - and routing [6](#)
 - and routing protocols [6](#)
 - configuring [11](#)
 - default setting [6](#)
 - described [29, 6](#)
 - for network management [29, 6](#)
 - specifying [11](#)
 - supported features [10](#)
 - unsupported features [11](#)
- Ethernet management port, internal
 - and routing protocols [6](#)
- Ethernet Management Port, using [6](#)
- Ethernet OAM [34](#)
 - and CFM interaction [51](#)
 - configuration guidelines [35](#)
 - configuring with CFM [51](#)
 - default configuration [35](#)
 - discovery [34](#)
 - enabling [36, 52](#)
 - link monitoring [34, 38](#)
 - messages [34](#)
 - protocol
 - defined [33](#)
 - monitoring [49](#)
 - remote failure indications [34](#)
 - remote loopback [34, 37](#)
 - templates [45](#)
- Ethernet OAM protocol CFM notifications [51](#)
- Ethernet Remote Defect Indication (ETH-RDI) [28](#)
- event triggers, user-defined
 - configuring, 802.1X-based [8](#)
 - configuring, MAC address-based [9](#)
- explicit host tracking
 - enabling [11](#)

extended range VLANs

See VLANs

Extensible Authentication Protocol over LAN [2](#)

Exterior Gateway Protocol

See EGP

F

Fa0 port

See Ethernet management port

Failure detection, using BFD [7](#)

Fallback Authentication

configure with 802.1X [80](#)

fast link notification

on VSL failure [13](#)

Fast UDLD

configuring probe message interval [8](#)

default configuration [3](#)

displaying link status [9](#)

enabling globally [5](#)

enabling on individual interface [7](#)

enabling per-interface [6](#)

modes of operation [3](#)

resetting disabled LAN interfaces [8](#)

use case [2](#)

Fast UDLD, overview [1](#)

FastDrop

overview [11](#)

fastethernet0 port

See Ethernet management port

Fast-Hello

dual-active detection [24](#)

Fast-Hello dual-active detection, configuring [53](#)

feature interactions, Wireshark [10](#)

FIB

description [2](#)

See also MFIB

fiber-optics interfaces

disabling UDLD [7](#)

Filter-ID ACL and Per-User ACL, configure port-based authentication

configure Per-User ACL and Filter-ID ACL [48](#)

filtering

in a VLAN [19](#)

non-IP traffic [14, 15](#)

filters, Wireshark [6](#)

flags [12](#)

Flash memory

configuring router to boot from [31](#)

loading system images from [30](#)

security precautions [31](#)

Flex Links

configuration guidelines [5](#)

configuring [6](#)

configuring preferred VLAN [9](#)

configuring VLAN load balancing [8](#)

monitoring [12](#)

Flexible NetFlow

caveats [8](#)

defined [4, 1](#)

flooded traffic, blocking [2](#)

flow control, configuring [29](#)

flowchart, traffic marking procedure [21, 55](#)

For [13](#)

forward-delay time (STP)

configuring [19](#)

forwarding information base

See FIB

frame command [5](#)

G

gateway

See default gateway

get-bulk-request operation [3](#)

get-next-request operation [3, 4](#)

get-request operation [3, 4](#)

get-response operation [3](#)
 Gigabit Ethernet SFP ports
 deploy with 10-Gigabit Ethernet [12, 13](#)
 GLBP, introduction [15](#)
 global configuration mode [5](#)
 Guest-VLANs
 configure with 802.1X [60](#)

H

hardware and software ACL support [6](#)
 hardware switching [5](#)
 hello time (STP)
 configuring [17](#)
 high CPU due to ACLs, troubleshooting [7](#)
 history
 CLI [4](#)
 history table, level and number of syslog messages [9](#)
 hop counts
 configuring MST bridges [28](#)
 host
 limit on dynamic port [28](#)
 host modes, MACsec [3](#)
 host ports
 kinds of [4](#)
 host presence CDP message [8](#)
 Hot Standby Routing Protocol
 See HSRP
 HSRP
 description [15](#)
 HSRP, introduction [15](#)
 hw-module module num power command [22](#)

i command [3](#)
 ICMP
 enabling [12](#)
 ping [7](#)

 running IP traceroute [9](#)
 time exceeded messages [9](#)
 ICMP Echo operation
 configuring [11](#)
 IP SLAs [11](#)
 IDS
 using with SPAN and RSPAN [2](#)
 IEEE 802.1ag [2](#)
 IEEE 802.1s
 See MST
 IEEE 802.1w
 See MST
 IEEE 802.3ad
 See LACP
 IGMP
 configurable-leave timer [4](#)
 description [3](#)
 enabling [15](#)
 explicit host tracking [4](#)
 immediate-leave processing [3](#)
 leave processing, enabling [8](#)
 overview [2](#)
 report suppression
 disabling [10](#)
 IGMP filtering
 configuring [31](#)
 default configuration [30](#)
 described [30](#)
 monitoring [34](#)
 IGMP groups
 setting the maximum number [33](#)
 IGMP Immediate Leave
 configuration guidelines [9](#)
 IGMP profile
 applying [32](#)
 configuration mode [31](#)
 configuring [31](#)
 IGMP Snooping
 configure

- leave timer [9](#)
- configuring
 - Learning Methods [7](#)
 - static connection to a multicast router [8](#)
- configuring host statically [11](#)
- enabling
 - Immediate-Leave processing
 - explicit host tracking [11](#)
 - suppressing multicast flooding [12](#)
- IGMP snooping
 - configuration guidelines [5](#)
 - default configuration [5](#), [6](#)
 - enabling
 - globally [6](#)
 - on a VLAN [6](#)
 - enabling and disabling [6](#)
 - IP multicast and [4](#)
 - monitoring [14](#), [10](#)
 - overview [2](#)
- IGMP Snooping, displaying
 - group [16](#)
 - hot membership [15](#)
 - how to [15](#)
 - MAC address entries [18](#)
 - multicast router interfaces [17](#)
 - on a VLAN interface [18](#)
 - Querier information [19](#)
- IGMPSnooping Querier, configuring [10](#)
- Immediate Leave, IGMP
 - enabling [8](#)
- immediate-leave processing
 - enabling [8](#)
- IGMP
 - See fast-leave processing
- ingress packets, SPAN enhancement [12](#)
- inline power
 - configuring on Cisco IP phones [5](#)
- insufficient inline power handling for Supervisor Engine II-TS [22](#)
- Intelligent Power Management [4](#)
- interacting with Baby Giants [35](#)
- interface
 - displaying operational status [6](#)
- interface command [9](#), [2](#)
- interface configuration
 - REP [10](#)
- interface link and trunk status events
 - configuring [43](#)
- interface port-channel command [48](#), [8](#)
- interface range command [4](#)
- interface range macro command [11](#)
- interfaces
 - adding descriptive name [29](#)
 - clearing counters [42](#)
 - configuring [2](#)
 - configuring ranges [4](#)
 - displaying information about [41](#)
 - Layer 2 modes [3](#)
 - maintaining [41](#)
 - monitoring [41](#)
 - naming [29](#)
 - numbers [2](#)
 - overview [2](#)
 - restarting [42](#), [43](#)
 - See also Layer 2 interfaces
 - using the Ethernet Management Port [6](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- introduction
 - 802.1X Identity-Based Network Security, list of supported features [34](#)
 - Bidirectional Forwarding Detection [13](#)
 - Cisco Call Home [24](#)
 - Cisco Energy Wise [24](#)

- Cisco Express Forwarding [14](#)
- Cisco IOS IP Service Level Agreements [24](#)
- Cisco IOS Mediatrace and Performance Monitor [26](#)
- Cisco Media Services Proxy [25](#)
- Cisco Medianet AutoQoS [25](#)
- Cisco Medianet Flow Metadata [26](#)
- Cisco TrustSec MACsec Encryption [36](#)
- Cisco TrustSec Security Architecture [36](#)
- Debugging Features (platform and debug platform) [43](#)
- Device Sensor [14](#)
- Dynamic Host Control Protocol [28](#)
- Easy Virtual Network [28](#)
- EIGRP Stub routing [14](#)
- Embedded Event Manager [29](#)
- Enhanced Object Tracking [14](#)
- EtherChannel bundles [3](#)
- Ethernet CFM [3](#)
- Ethernet Management Port [29](#)
- Ethernet OAM Protocol [3](#)
- FAT File Management System (Sup 60-E, 6L-E, 4948E, and 4900M) [30](#)
- File System Management (Sup 7-E and 7L-E) [29](#)
- Flex Link and MAC Address-Table Move Update [3](#)
- Flexible Netflow (Sup 7-E and 7L-E) [4](#)
- GLBP [15](#)
- hard-based Control Plane Policing [37](#)
- HSRP [15](#)
- In Service Software Upgrade [19](#)
- Intelligent Power Management [30](#)
- Internet Group Management Protocol (IGMP) Snooping [4](#)
- IP Routing protocols [17](#)
- IP Source Guard [38](#)
- IP Source Guard or Static Hosts [38](#)
- IPv6 [19](#)
- IPv6 First Hop Security [38](#)
- IPv6 Multicast BSR and BSR Scoped Zone Support, introduction [5](#)
- IPv6 Multicast Listen Discovery (MLD) and Multicast Listen Discovery Snooping [6](#)
- IS-IS [18](#)
- Jumbo Frame [6](#)
- Layer 2 traceroute [43](#)
- Link Aggregation Control Protocol [7](#)
- MAC Address Notification [30](#)
- NAC
 - Layer 2 802.1X authentication [40](#)
 - Layer 2 IP validation [40](#)
- NetFlow-lite [31](#)
- Network Security with ACLs (IP ACLs, MAC ACLs, Port ACLs, Router, ACLs, and VLAN ACLs) [41](#)
- NSF with SSO [21](#)
- OSPF [18](#)
- OSPF for Routed Access [21](#)
- Port Security [41](#)
- Power over Ethernet [31](#)
- RIP [19](#)
- Simple Network Management Protocol [31](#)
- SPAN and RSPAN [32](#)
- Time Domain Reflectometry [43](#)
- Unicast Reverse Path Forwarding [22](#)
- Universal Power over Ethernet [32](#)
- Virtual Router Redundancy Protocol [23](#)
- VRF-lite [22](#)
- Web Content Coordination Protocol [32](#)
- Web-based Authentication [43](#)
- Wireshark [33](#)
- XML-PI [33](#)
- Intrusion Detection System
 - See IDS
- inventory management TLV [3, 9](#)
- IOS shell
 - See Auto SmartPorts macros
- IP
 - configuring default gateway [11](#)
 - configuring static routes [11](#)
 - displaying statistics [8](#)
- IP addresses
 - 128-bit [2](#)

- cluster candidate or member [12](#)
 - cluster command switch [11](#)
 - discovering [44](#)
 - IPv6 [2](#)
- ip cef command [7, 2](#)
- IP Enhanced IGRP
 - interfaces, displaying [20](#)
- ip icmp rate-limit unreachable command [12](#)
- ip igmp profile command [31](#)
- ip igmp snooping tcn flood command [13](#)
- ip igmp snooping tcn flood query count command [14](#)
- ip igmp snooping tcn query solicit command [14](#)
- IP information
 - assigned
 - through DHCP-based autoconfiguration [2](#)
- ip load-sharing per-destination command [8](#)
- ip local policy route-map command [12](#)
- ip mask-reply command [13](#)
- IP MTU sizes, configuring [9](#)
- IP multicast
 - clearing table entries [28](#)
 - configuring [13](#)
 - default configuration [14](#)
 - displaying PIM information [24](#)
 - displaying the routing table information [24](#)
 - enabling dense-mode PIM [15](#)
 - enabling sparse-mode [15](#)
 - features not supported [13](#)
 - hardware forwarding [9](#)
 - IGMP snooping and [5, 4](#)
 - overview [1](#)
 - routing protocols [2](#)
 - software forwarding [9](#)
 - See also Auto-RP; IGMP; PIM; RP; RPF
- IP multicast routing
 - enabling [14](#)
 - monitoring and maintaining [23](#)
- IP multicast traffic, load splitting [22](#)
- ip multicast-routing command [14](#)
- IP phones
 - configuring voice ports [3](#)
 - See Cisco IP Phones [1](#)
- ip pim command [15](#)
- ip pim dense-mode command [15](#)
- ip pim sparse-dense-mode command [16, 17](#)
- ip policy route-map command [9, 11, 14](#)
- IP Port Security for Static Hosts
 - on a Layer 2 access port [25](#)
 - on a PVLAN host port [28](#)
 - overview [24](#)
- ip redirects command [13](#)
- IP routing tables
 - deleting entries [28](#)
- IP Service Level Agreements
 - See IP SLAs
- IP service levels, analyzing [1](#)
- IP SLAs
 - benefits [2](#)
 - CFM endpoint discovery [21](#)
 - configuration guidelines [6](#)
 - Control Protocol [4](#)
 - default configuration [6](#)
 - definition [1](#)
 - ICMP echo operation [11](#)
 - manually configuring CFM ping or jitter [19](#)
 - measuring network performance [3](#)
 - multioperations scheduling [5](#)
 - operation [3](#)
 - reachability tracking [9](#)
 - responder
 - described [4](#)
 - enabling [7](#)
 - response time [4](#)
 - scheduling [5](#)
 - SNMP support [2](#)
 - supported metrics [2](#)
 - threshold monitoring [6](#)
 - track state [9](#)

- UDP jitter operation [8](#)
 - IP Source Guard
 - configuring [20](#)
 - configuring on private VLANs [22](#)
 - displaying [22](#), [23](#)
 - overview [23](#)
 - IP statistics
 - displaying [8](#)
 - IP traceroute
 - executing [9](#)
 - overview [8](#)
 - IP unicast
 - displaying statistics [8](#)
 - IP Unnumbered support
 - configuring on a range of Ethernet VLANs [5](#)
 - configuring on LAN and VLAN interfaces [4](#)
 - configuring with connected host polling [6](#)
 - DHCP Option 82 [2](#)
 - displaying settings [7](#)
 - format of agent remote ID suboptions [2](#)
 - troubleshooting [8](#)
 - with connected host polling [3](#)
 - with DHCP server and Relay agent [2](#)
 - ip unreachable command [12](#)
 - IPsec VPN, introduction [40](#)
 - IPv4, IPv6, and MAC ACLs, configuring on a Layer 2 interface [31](#)
 - IPv6
 - addresses [2](#)
 - default configuration [7](#)
 - defined [19](#), [1](#)
 - Enhanced Interior Gateway Routing Protocol (EIGRP) IPv6 [6](#)
 - Router ID [6](#)
 - OSPF [6](#)
 - IPv6 control traffic, policing [20](#)
 - IPv6 First Hop Security, introduction [38](#)
 - IPX
 - redistribution of route information with EIGRP [18](#)
 - is [23](#)
 - IS-IS, introduction [18](#)
 - ISL
 - trunking with 802.1Q tunneling [4](#)
 - isolated port [4](#)
 - isolated VLANs [2](#), [3](#), [4](#)
 - ISSU
 - compatibility matrix [63](#), [14](#)
 - compatibility verification using Cisco Feature Navigator [64](#), [15](#)
 - NSF overview [3](#), [4](#)
 - perform the process
 - aborting a software upgrade [79](#), [34](#)
 - configuring the rollback timer as a safeguard [81](#), [35](#), [36](#)
 - displaying a compatibility matrix [82](#), [36](#), [40](#), [37](#)
 - loading the new software on the new standby [72](#), [27](#)
 - stopping the rollback timer [72](#), [26](#)
 - switching to the standby [70](#), [24](#)
 - verify the ISSU state [67](#), [20](#), [21](#)
 - verify the redundancy mode [65](#), [19](#)
 - verify the software installation [65](#), [18](#), [19](#)
 - vload the new software on standby [68](#), [21](#)
 - prerequisites [58](#), [1](#), [2](#)
 - process overview [6](#), [7](#)
 - restrictions [58](#), [1](#), [2](#)
 - SNMP support [15](#)
 - SSO overview [3](#), [4](#)
 - versioning capability in software to support [13](#)
 - IST
 - and MST regions [22](#)
 - description [22](#)
 - master [27](#)
 - ITU-T Y.1731
 - See Y.1731
-
- J**
- jumbo frames

- and ethernet ports [33](#)
- configuring MTU sizes for [34](#)
- ports and linecards that support [31](#)
- understanding MTUs [32](#)
- understanding support [32](#)
- VLAN interfaces [33](#)

K

keyboard shortcuts [3](#)

L

l2protocol-tunnel command [17](#), [19](#)

labels, definition [3](#)

LACP

- system ID [5](#)

Layer 2 access ports [7](#)

Layer 2 Control Packet QoS

- and CoPP configuration example [18](#)
- default configuration [15](#)
- disabling [17](#)
- enabling [15](#)
- guideline and restrictions [20](#)
- understanding [15](#)

Layer 2 frames

- classification with CoS [2](#)

Layer 2 interface

- applying ACLs [33](#)
- configuring access-mode mode on [33](#)
- configuring IPv4, IPv6, and MAC ACLs [31](#)
- displaying an ACL configuration [34](#)

Layer 2 interface type

- resetting [24](#)
- setting [24](#)

Layer 2 interfaces

- assigning VLANs [7](#)
- configuring [5](#)
- configuring as PVLAN host ports [18](#)

- configuring as PVLAN promiscuous ports [17](#)
- configuring as PVLAN trunk ports [19](#)
- defaults [4](#)
- disabling configuration [8](#)
- modes [3](#)
- show interfaces command [6](#)

Layer 2 protocol tunneling

- default configuration [16](#)
- guidelines [16](#)

Layer 2 switching

- overview [1](#)

Layer 2 Traceroute

- and ARP [10](#)
- and CDP [10](#)
- host-to-host paths [10](#)
- IP addresses and subnets [10](#)
- MAC addresses and VLANs [10](#)
- multicast traffic [10](#)
- multiple devices on a port [10](#)
- unicast traffic [43](#), [9](#)
- usage guidelines [10](#)

Layer 2 trunks

- configuring [5](#)
- overview [3](#)

Layer 3 interface counters,configuring [11](#)

Layer 3 interface counters,understanding [3](#)

Layer 3 interface, applying IPv6 ACLs [18](#)

Layer 3 interfaces

- changing from Layer 2 mode [16](#)
- configuration guidelines [5](#)
- configuring VLANs as interfaces [8](#)
- overview [1](#)
 - counters [3](#)
 - logical [2](#)
 - physical [2](#)
 - SVI autostate exclude [3](#)

Layer 3 packets

- classification methods [2](#)

Layer 4 port operations

- configuration guidelines [11](#)
 - restrictions [11](#)
 - Leave timer, enabling [9](#)
 - licenses, managing with PRTU [14](#)
 - limitations on using a TwinGig Convertor [14](#)
 - Link Aggregation Control Protocol, introduction [7](#)
 - link and trunk status events
 - configuring interface [43](#)
 - link integrity, verifying with REP [4](#)
 - Link Layer Discovery Protocol
 - See CDP
 - link monitoring, Ethernet OAM [34](#), [38](#)
 - link status, displaying UDLD [9](#)
 - link-state tracking
 - configuration guidelines [26](#)
 - default configuration [26](#)
 - described [23](#)
 - displaying status [27](#)
 - generic configuration procedure [26](#)
 - listening state (STP)
 - RSTP comparisons (table) [24](#)
 - LLDP
 - configuring [4](#)
 - characteristics [5](#)
 - default configuration [5](#)
 - disabling and enabling
 - globally [6](#)
 - on an interface [7](#)
 - monitoring and maintaining [14](#)
 - overview [1](#)
 - transmission timer and holdtime, setting [5](#)
 - LLDP Media Endpoint Discovery
 - See LLDP-MED
 - LLDP-MED
 - configuring
 - procedures [4](#)
 - TLVs [9](#), [11](#)
 - monitoring and maintaining [14](#)
 - overview [1](#)
 - supported TLVs [2](#)
 - load balancing
 - configuring for CEF [7](#)
 - configuring for EtherChannel [18](#)
 - overview [6](#)
 - per-destination [7](#)
 - load splitting IP multicast traffic [22](#)
 - Location Service
 - overview [1](#)
 - location service
 - configuring [12](#)
 - understanding [3](#)
 - location TLV [3](#), [9](#)
 - logging, EPM [131](#)
 - Logical Layer 3 interfaces
 - configuring [6](#)
 - logical layer 3 VLAN interfaces [2](#)
 - login authentication
 - with RADIUS [108](#)
 - with TACACS+ [19](#)
 - login banners [24](#)
 - login timer
 - changing [6](#)
 - logoutwarning command [6](#)
 - loop guard
 - and MST [23](#)
 - configuring [5](#)
 - overview [3](#)
- ## M
-
- MAC address learning, disabling on a VLAN [39](#)
 - configuring [39](#)
 - deployment scenarios [40](#)
 - feature compatibility [42](#)
 - feature incompatibility [43](#)
 - feature inompatibility [43](#)
 - usage guidelines [40](#)
 - MAC address table

- displaying [44](#)
- MAC addresses
 - aging time [30](#)
 - allocating [6](#)
 - and VLAN association [29](#)
 - building tables [28, 2](#)
 - convert dynamic to sticky secure [5](#)
 - default configuration [30](#)
 - disabling learning on a VLAN [39](#)
 - discovering [44](#)
 - displaying [3](#)
 - displaying in DHCP snooping binding table [19](#)
 - dynamic
 - learning [29](#)
 - removing [31](#)
 - in ACLs [14](#)
 - static
 - adding [37](#)
 - allowing [38](#)
 - characteristics of [36](#)
 - dropping [38](#)
 - removing [37](#)
 - sticky [4](#)
 - sticky secure, adding [5](#)
- MAC address-table move update
 - configuration guidelines [9](#)
 - configuring [10](#)
 - monitoring [12](#)
- MAC Authentication Bypass
 - configure with 802.1X [63](#)
- MAC details, displaying [130](#)
- MAC extended access lists [14](#)
- MAC/PHY configuration status TLV [2](#)
- macl [15](#)
- macros
 - See Auto SmartPorts macros
 - See Auto Smartports macros
 - See Smartports macros
- MACSec
 - 802.1AE Tagging [9](#)
 - MACsec [2](#)
 - configuring on an interface [7](#)
 - defined [1, 2](#)
 - switch-to-switch security [1](#)
 - MACsec Key Agreement Protocol
 - See MKA
 - main-cpu command [8, 7](#)
 - management address TLV [2](#)
 - management options
 - SNMP [1](#)
 - Management Port, Ethernet [6](#)
 - managing software licenses, using PRTU [14](#)
 - manual preemption, REP, configuring [13](#)
 - marking
 - hardware capabilities [23, 57](#)
 - marking action drivers [21, 55](#)
 - marking network traffic [18, 52](#)
 - marking support, multi-attribute [22, 56](#)
 - match ip address command [8, 10, 12, 13](#)
 - maximum aging time (STP)
 - configuring [18](#)
 - MDA
 - configuration guidelines [23–??](#)
 - described [23](#)
 - MEC
 - configuration [48](#)
 - described [13](#)
 - failure [14](#)
 - Media Access Control Security
 - See MACsec
 - member switch
 - managing [13](#)
 - member switch, cluster
 - defined [2](#)
 - members
 - automatic discovery [7](#)
 - meminfo command [6](#)
 - messages, Ethernet OAM [34](#)

- messages, to users through banners [24](#)
- Metro features
 - Y.1731 (AIS and RDI), introduction [12](#)
- metro tags [2](#)
- MFIB
 - CEF [6](#)
 - overview [12](#)
- MFIB, IP
 - displaying [26](#)
- MIBs
 - compiling [4](#)
 - downloading [3](#), [4](#)
 - overview [1](#)
 - related information [3](#)
 - SNMP interaction with [4](#)
- MKA
 - configuring policies [6](#)
 - defined [2](#)
 - policies [2](#)
 - replay protection [3](#)
 - statistics [4](#)
 - virtual ports [3](#)
- MLD Done messages and Immediate-leave [4](#)
- MLD messages [2](#)
- MLD queries [3](#)
- MLD reports [4](#)
- MLD Snooping
 - MLD Done messages and Immediate-leave [4](#)
 - MLD messages [2](#)
 - MLD queries [3](#)
 - MLD reports [4](#)
 - Multicast client aging robustness [3](#)
 - Multicast router discovery [3](#)
 - overview [1](#)
- Mode of capturing control packets, selecting [7](#)
- modules
 - checking status [1](#)
 - powering down [22](#)
- monitoring
 - 802.1Q tunneling [23](#)
 - ACL information [37](#)
 - Ethernet CFM [32](#), [33](#)
 - Ethernet OAM [49](#)
 - Ethernet OAM protocol [49](#)
 - Flex Links [12](#)
 - IGMP
 - snooping [10](#)
 - IGMP filters [34](#)
 - IGMP snooping [14](#)
 - Layer 2 protocol tunneling [23](#)
 - MAC address-table move update [12](#)
 - multicast router interfaces [11](#)
 - multi-VRF CE [14](#), [21](#), [22](#)
 - MVR [29](#)
 - object tracking [12](#)
 - REP [14](#)
 - traffic flowing among switches [1](#)
 - tunneling [23](#)
 - VLAN filters [26](#)
 - VLAN maps [26](#)
- monitoring and troubleshooting
 - BFD [17](#)
- M-record [23](#)
- MST
 - and multiple spanning trees [8](#), [22](#)
 - boundary ports [27](#)
 - BPDU s [23](#)
 - configuration parameters [26](#)
 - configuring [28](#)
 - displaying configurations [32](#)
 - edge ports [27](#)
 - enabling [29](#)
 - hop count [28](#)
 - instances
 - configuring parameters [31](#)
 - description [23](#)
 - number supported [26](#)
 - interoperability with PVST+ [23](#)

- link type [28](#)
- master [27](#)
- message age [28](#)
- regions [26](#)
- restrictions [28](#)
- to-SST interoperability [24](#)
- MSTP
 - EtherChannel guard
 - enabling [6](#)
 - M-record [23](#)
 - M-tree [23](#)
- MST-to-PVST+ Interoperability (PVST+ simulation) [35](#)
- MST-to-PVST+ Interoperability guidelines [35](#)
- M-tree [23](#)
- MTU size
 - configuring [34](#), [35](#), [44](#)
 - default [4](#)
- MTUS
 - understanding [32](#)
- Multi-authentication
 - described [23](#)
- multiauthentication mode [8](#)
- multicast
 - See IP multicast
- Multicast client aging robustness [3](#)
- multicast Ethernet loopback (ETH-LB) [29](#)
- multicast Ethernet loopback, using [31](#)
- Multicast Forwarding Information Base (MFIB) [12](#)
- multicast groups
 - static joins [7](#)
- Multicast HA [13](#)
- Multicast implementation
 - HA [13](#)
 - MFIB [12](#)
 - S/M, 224/4 [13](#)
- multicast packets
 - blocking [2](#)
- Multicast router discovery [3](#)
- multicast router interfaces, displaying [17](#)
- multicast router interfaces, monitoring [11](#)
- multicast router ports, adding [7](#)
- multicast router table
 - displaying [24](#)
- multicast routers
 - flood suppression [12](#)
- Multicast Storm Control
 - enabling [4](#)
 - disabling [6](#)
- multicast television application, using MVR [21](#)
- Multicast VLAN Registration
 - See MVR
- multichassis EtherChannel
 - see MEC [13](#)
- multidomain authentication
 - See MDA
- multidomain authentication mode [7](#)
- multioperations scheduling, IP SLAs [5](#)
- Multiple AuthorizationAuthentication
 - configuring [36](#)
- Multiple Domain Authentication [36](#)
- multiple forwarding paths [8](#), [22](#)
- Multiple Spanning Tree
 - See MST
- multiple VPN routing/forwarding
 - See multi-VRF CE
- multiple-hosts mode [7](#)
- multi-VRF CE
 - components [3](#)
 - configuration example [17](#)
 - defined [1](#)
 - displaying [14](#), [21](#), [22](#)
 - monitoring [14](#), [21](#), [22](#)
 - network components [3](#)
 - packet-forwarding process [3](#)
- MVR
 - configuration guidelines and limitations [23](#)
 - configuring global parameters [24](#)

- configuring on a trunk port [27](#)
- configuring on access ports [26](#)
- default configuration [23](#)
- displaying information [29](#)
- in a multicast television application [21](#)
- monitoring [29](#)
- setting global parameters [24](#)

N

NAC Layer 2 802.1X authentication, intro [40](#)

NAC Layer 2 IP validation, intro [40](#)

named IPv6 ACLs, configuring

- ACLs

- configuring named IPv6 ACLs [16](#)

named MAC extended ACLs

- ACLs

- configuring named MAC extended [14](#), [15](#)

native VLAN

- and 802.1Q tunneling [3](#)

- specifying [6](#)

NDAC [9](#)

- defined [9](#)

- MACsec [1](#)

NEAT

- configuring [90](#)

- overview [25](#)

neighbor offset numbers, REP [5](#)

NetFlow packet sampling

- about [2](#)

NetFlow-lite

- clear commands [9](#)

- display commands [8](#)

Network Assistant

- and VTY [12](#)

- configure

- enable communication with switch [13](#), [17](#)

- default configuration [3](#)

- overview of CLI commands [3](#)

Network Device Admission Control (NDAC) [9](#)

Network Edge Access Topology

- See NEAT

network fault tolerance [8](#), [22](#)

network management

- configuring [1](#)

- RMON [1](#)

- SNMP [1](#)

network performance, measuring with IP SLAs [3](#)

network policy TLV [2](#), [9](#)

Network Time Protocol

- See NTP

network traffic, marking [18](#), [52](#)

New Software Features in Release 7.7

- TDR [3](#)

Next Hop Resolution Protocol

- See NHRP

NHRP

- support [18](#)

non-fiber-optics interfaces

- disabling UDLD [7](#)

non-IP traffic filtering [14](#), [15](#)

non-RPF traffic

- description [10](#)

- in redundant configurations (figure) [11](#)

Nonstop Forwarding

- See NSF

nonvolatile random-access memory

- See NVRAM

normal-range VLANs

- See VLANs

NSF

- defined [1](#)

- guidelines and restrictions [9](#)

- operation [4](#)

NSF with SSO supervisor engine redundancy

- and CEF [5](#)

- overview [3](#)

- SSO operation [4](#)

- NSF-aware
 - supervisor engines [3](#)
 - support [2](#)
 - NSF-capable
 - supervisor engines [3](#)
 - support [2](#)
 - NTP
 - associations
 - authenticating [4](#)
 - defined [2](#)
 - enabling broadcast messages [7](#)
 - peer [6](#)
 - server [6](#)
 - default configuration [4](#)
 - displaying the configuration [11](#)
 - overview [2](#)
 - restricting access
 - creating an access group [9](#)
 - disabling NTP services per interface [10](#)
 - source IP address, configuring [10](#)
 - stratum [2](#)
 - synchronizing devices [6](#)
 - time
 - services [2](#)
 - synchronizing [2](#)
 - ntroduction
 - PPPoE Intermediate Agent [41](#)
 - Storm Control [42](#)
 - uRPF Strict Mode [42](#)
 - NVRAM
 - saving settings [10](#)
- O**
-
- OAM
 - client [34](#)
 - features [34](#)
 - sublayer [34](#)
 - OAM manager
 - configuring [52](#)
 - with CFM and Ethernet OAM [51](#)
 - OAM PDUs [35](#)
 - OAM protocol data units [33](#)
 - OBFL, displaying for the 9000W AC [4](#)
 - object tracking
 - monitoring [12](#)
 - OGACLs [3](#)
 - OIR
 - overview [38](#)
 - on-demand online diagnostics [1](#)
 - online diagnostic
 - troubleshooting [8](#)
 - Online Diagnostics [1](#)
 - online diagnostics
 - configuring on-demand [1](#)
 - data path, displaying test results [6](#)
 - displaying tests and test results [4](#)
 - linecard [8](#)
 - scheduling [2](#)
 - starting and stopping tests [3](#)
 - online insertion and removal
 - See OIR
 - Open Shortest Path First
 - See OSPF
 - operating system images
 - See system images
 - Option 82
 - enabling DHCP Snooping [10](#)
 - OSPF
 - area concept [19](#)
 - description [18](#)
 - for IPv6 [6](#)
 - OSPF for Routed Access, introduction [21](#)
 - OSPF, introduction [18](#)
- P**
-
- packet type filtering

- overview [14](#)
- SPAN enhancement [14](#)
- packets
 - modifying [9](#)
- PACL
 - using with access-group mode [32](#)
- PACL configuration guidelines [30](#)
- PACL with VLAN maps and router ACLs [34](#)
- PAgP
 - understanding [4](#)
- PAgP, dual-active detection [23](#)
- passwords
 - configuring enable password [14](#)
 - configuring enable secret password [14](#)
 - encrypting [22](#)
 - in clusters [8](#)
 - recovering lost enable password [25](#)
 - setting line password [14](#)
- PBR (policy-based routing)
 - configuration (example) [16](#)
 - enabling [7](#), [10](#)
 - features [2](#)
 - overview [1](#)
 - route maps [2](#)
 - route-map processing logic [3](#)
 - when to use [6](#)
- PE to CE routing, configuring [9](#)
- percentage thresholds in tracked lists [6](#)
- Permanent Right-To_Use [14](#)
- per-port and VLAN Access Control List [19](#)
- per-port per-VLAN QoS
 - enabling [36](#), [70](#)
 - overview [10](#)
- Per-User ACL and Filter-ID ACL, configure [48](#)
- Per-VLAN Rapid Spanning Tree [6](#)
 - enabling [20](#)
 - overview [6](#)
- physical layer 3 interfaces [2](#)
- Physical Layer 3 interfaces, configuring [12](#)
- PIM
 - configuring dense mode [15](#)
 - configuring sparse mode [15](#)
 - displaying information [24](#)
 - displaying statistics [28](#)
 - enabling sparse-dense mode [15](#), [16](#)
 - overview [3](#)
- PIM on an interface, enabling [15](#)
- PIM-DM [3](#)
- PIM-SM [3](#)
- PIM-SSM mapping, enabling [17](#)
- ping
 - executing [8](#)
 - overview [7](#)
- ping command [8](#), [24](#)
- PoE [7](#), [8](#)
 - configuring power consumption for single device [5](#), [16](#)
 - configuring power consumption, powered devices [5](#)
 - displaying operational status for an interface [6](#)
 - Enhanced PoE support on E-series [15](#)
 - policing and monitoring [12](#)
 - power consumption for powered devices
 - Intelligent Power Management [4](#)
 - power management modes [2](#)
 - powering down a module [22](#)
- PoE policing
 - configuring errdisable recovery [14](#)
 - configuring on an interface [13](#)
 - displaying on an interface [14](#)
 - power modes [12](#)
- point-to-point
 - in 802.1X authentication (figure) [3](#)
- policing
 - how to implement [18](#), [52](#)
 - See QoS policing
- policing IPv6 control traffic [20](#)
- policing, PoE [12](#)
- policy associations, QoS on Sup 6-E [39](#), [73](#)
- policy map marking action, configuring [23](#), [57](#)

- policy-map command [16](#), [51](#)
- port ACLs
 - and voice VLAN [5](#)
 - defined [3](#)
- Port Aggregation Protocol
 - see PAgP
- port cost (STP)
 - configuring [15](#)
- port description TLV [2](#)
- port numbering with TwinGig Convertors [13](#)
- port priority
 - configuring MST instances [31](#)
 - configuring STP [13](#)
- port security
 - aging [5](#)
 - configuring [7](#)
 - displaying [28](#)
 - guidelines and restrictions [33](#)
 - on access ports [7](#), [22](#)
 - on private VLAN [14](#)
 - host [14](#)
 - promiscuous [16](#)
 - topology [15](#), [18](#), [32](#)
 - on trunk port [17](#)
 - guidelines and restrictions [15](#), [18](#), [32](#)
 - port mode changes [22](#)
 - on voice ports [22](#)
 - sticky learning [5](#)
 - using with 802.1X [19](#)
 - violations [6](#)
 - with 802.1X Authentication [32](#)
 - with DHCP and IP Source Guard [31](#)
 - with other features [33](#)
- port states
 - description [5](#)
- port VLAN ID TLV [2](#)
- port-based authentication
 - 802.1X with voice VLAN [22](#)
 - Authentication Failed VLAN assignment [17](#)
- authentication server
 - defined [2](#)
- changing the quiet period [87](#)
- client, defined [3](#), [2](#)
- configuration guidelines [30](#), [6](#)
- configure ACL assignments and redirect URLs [40](#)
- configure switch-to-RADIUS server communication [34](#)
- configure with Authentication Failed [73](#)
- configure with Critical Authentication [65](#)
- configure with Guest-VLANs [60](#)
- configure with MAC Authentication Bypass [63](#)
- configure with VLAN User Distribution [71](#)
- configure with Voice VLAN [75](#)
- configuring
 - Multiple Domain Authentication and Multiple Authorization [36](#)
 - RADIUS server [10](#)
 - RADIUS server parameters on the switch [9](#)
- configuring Fallback Authentication [80](#)
- configuring Guest-VLAN [34](#)
- configuring manual re-authentication of a client [97](#)
- configuring with Unidirectional Controlled Port [69](#)
- controlling authorization state [5](#)
- default configuration [29](#), [6](#)
- described [1](#)
- device roles [2](#)
- displaying statistics [127](#), [14](#)
- enabling [30](#)
 - 802.1X authentication [9](#)
- enabling multiple hosts [85](#)
- enabling periodic re-authentication [84](#)
- encapsulation [3](#)
- host mode [6](#)
- how 802.1X fails on a port [27](#)
- initiation and message exchange [4](#)
- method lists [30](#)
- modes [6](#)
- multidomain authentication [23](#)

- multiple-hosts mode, described [7](#)
 - port security
 - multiple-hosts mode [7](#)
 - ports not supported [5](#)
 - pre-authentication open access [8](#)
 - resetting to default values [97](#)
 - setting retransmission number [89](#)
 - setting retransmission time [88](#)
 - switch
 - as proxy [2](#)
 - switch supplicant
 - configuring [90](#)
 - overview [25](#)
 - topologies, supported [27](#)
 - using with ACL assignments and redirect URLs [20](#)
 - using with port security [19](#)
 - voice aware 802.1x security
 - configuring [77](#)
 - described [22](#), [76](#)
 - with Critical Authentication [14](#)
 - with Guest VLANs [11](#)
 - with MAC Authentication Bypass [12](#)
 - with Unidirectional Controlled Port [15](#)
 - with VLAN assignment [10](#)
 - with VLAN User Distribution [16](#)
- port-channel
- see EtherChannel
- port-channel interfaces
- See also EtherChannel
 - creating [48](#), [8](#)
 - overview [2](#)
- port-channel load-balance
- command [14](#), [16](#)
 - command example [16](#)
- port-channel load-balance command [19](#)
- PortFast
- and MST [23](#)
 - configuring or enabling [23](#)
 - overview [7](#)
- PortFast BPDU filtering
- and MST [23](#)
 - overview [16](#)
- PortFast Edge BPDU Filtering [17](#)
- ports
- blocking [1](#)
 - checking status [2](#)
 - dynamic VLAN membership
 - example [28](#)
 - reconfirming [25](#), [26](#)
 - forwarding, resuming [3](#)
 - REP [6](#)
 - See also interfaces
- power
- inline [5](#)
- power dc input command [21](#)
- power handling for Supervisor Engine II-TS [12](#)
- power inline command [3](#)
- power inline consumption command [5](#)
- power management
- Catalyst 4500 series [7](#)
 - Catalyst 4500 Switch power supplies [14](#)
 - Catalyst 4948 series [23](#)
 - configuring combined mode [13](#)
 - configuring redundant mode [12](#)
 - overview [1](#)
 - redundancy [7](#)
- power management for Catalyst 4500 Switch
- combined mode [9](#)
 - redundant mode [9](#)
- power management limitations in Catalyst 4500 Switch [10](#)
- power management mode
- selecting [10](#)
- power management TLV [2](#), [3](#), [9](#)
- power negotiation
- through LLDP [11](#)
- power policing, displaying on an interface [14](#)
- power redundancy-mode command [13](#)
- power supplies

- available power for Catalyst 4500 Switch **14**
- fixed **8**
- variable **8, 23**
- powered devices, configuring power consumption **5**
- Power-On-Self-Test diagnostics **10, 19**
- Power-On-Self-Test for Supervisor Engine V-10GE **12**
- pre-authentication open access **8**
- pre-authentication open access. See port-based authentication.
- preempt delay time, REP **5**
- primary edge port, REP **4**
- primary VLANs **2, 4**
 - associating with secondary VLANs **16**
 - configuring as a PVLAN **15**
- priority
 - overriding CoS of incoming frames **4**
- priority queuing, QoS on Sup 6-E **30, 64**
- private VLAN
 - configure port security **14, 15**
 - enabling DHCP Snooping **12**
- private VLANs
 - across multiple switches **5**
 - and SVIs **10**
 - benefits of **2**
 - community ports **3**
 - community VLANs **2, 3**
 - default configuration **12**
 - end station access to **3**
 - isolated port **4**
 - isolated VLANs **2, 3, 4**
 - ports
 - community **3**
 - isolated **4**
 - promiscuous **4**
 - primary VLANs **2, 4**
 - promiscuous ports **4**
 - secondary VLANs **2**
 - subdomains **2**
 - traffic in **9**
- privileged EXEC mode **5**
- privileges
 - changing default **23**
 - configuring levels **23**
 - exiting **24**
 - logging in **24**
- promiscuous ports
 - configuring PVLAN **17**
 - defined **4**
 - setting mode **24**
- protocol timers **4**
- provider edge devices **2**
- PRTU, managing software licenses **14**
- pruning, VTP
 - See VTP pruning
- pseudobridges
 - description **25**
- PVACL **19**
- PVID (port VLAN ID)
 - and 802.1X with voice VLAN ports **22**
- PVLAN promiscuous trunk port
 - configuring **11, 17, 21**
- PVLANS
 - 802.1q support **14**
 - across multiple switches **5**
 - configuration guidelines **12**
 - configure port security **14, 16, 18**
 - configure port security in a wireless setting **32**
 - configuring **11**
 - configuring a VLAN **15**
 - configuring promiscuous ports **17**
 - host ports
 - configuring a Layer 2 interface **18**
 - setting **24**
 - overview **1**
 - permitting routing, example **23**
 - promiscuous mode
 - setting **24**
 - setting

interface mode [24](#)
 PVST+ simulation [36](#)

Q

- QoS
- classification [6–??](#)
 - definitions [3](#)
 - enabling per-port per-VLAN [36, 70](#)
 - overview [1](#)
 - overview of per-port per-VLAN [10](#)
 - packet modification [9](#)
 - traffic shaping [9](#)
 - See also COS; DSCP values; transmit queues
- QoS active queue management
- tracking queue length [9](#)
- QoS labels
- definition [3](#)
- QoS marking
- description [5](#)
- QoS on Sup 6-E
- Active Queue management via DBL [34, 68](#)
 - active queue management via DBL [27, 34, 61, 68](#)
 - classification [16, 50](#)
 - configuring [13, 47](#)
 - configuring CoS mutation [45, 79](#)
 - configuring the policy map marking action [23, 57](#)
 - hardware capabilities for marking [23, 57](#)
 - how to implement policing [18, 52](#)
 - marking action drivers [21, 55](#)
 - marking network traffic [18, 52](#)
 - MQC-based QoS configuration [13, 48](#)
 - multi-attribute marking support [22, 56](#)
 - platform hardware capabilities [15, 49](#)
 - platform restrictions [18, 52](#)
 - platform-supported classification criteria and QoS features [13, 14, 48](#)
 - policing [17, 51](#)
 - policy associations [39, 73](#)
 - prerequisites for applying a service policy [15, 49](#)
 - priority queuing [30, 64](#)
 - queue-limiting [31, 65](#)
 - restrictions for applying a service policy [15, 50](#)
 - shaping [25, 59](#)
 - sharing(bandwidth) [27, 61](#)
 - sharing(bandwidth), shapring, and priority queuing [25, 59](#)
 - software QoS [40, 74](#)
 - traffic marking procedure flowchart [21, 55](#)
- QoS policing
- definition [5](#)
 - described [8](#)
- QoS policy
- attaching to interfaces [8](#)
- QoS service policy
- prerequisites [15, 49](#)
 - restrictions for applying [15, 50](#)
- QoS transmit queues
- burst [9](#)
 - maximum rate [9](#)
 - sharing link bandwidth [9](#)
- quad-supervisor
- uplink forwarding [6](#)
- Quality of service
- See QoS
- queueing [8](#)
- queue-limiting, QoS on Sup 6-E [31, 65](#)

R

- RA Guard
- configuring [38](#)
 - deployment [38](#)
 - examples [39](#)
 - introduction [37](#)
 - usage guidelines [40](#)
- RADIUS
- attributes

- vendor-proprietary [116](#)
 - vendor-specific [114](#)
 - change of authorization [100](#)
 - configuring
 - accounting [113](#)
 - authentication [108](#)
 - authorization [112](#)
 - communication, global [106](#), [114](#)
 - communication, per-server [105](#), [106](#)
 - multiple UDP ports [106](#)
 - default configuration [105](#)
 - defining AAA server groups [110](#)
 - displaying the configuration [118](#)
 - identifying the server [105](#)
 - limiting the services to the user [112](#)
 - method list, defined [105](#)
 - operation of [99](#)
 - server load balancing [118](#)
 - suggested network environments [98](#)
 - tracking services accessed by user [113](#)
 - understanding [98](#)
- RADIUS Change of Authorization** [100](#)
- RADIUS server**
- configure to-Switch communication [34](#)
 - configuring settings [36](#)
 - parameters on the switch [34](#)
- RADIUS, controlling switch access with** [98](#)
- range command** [4](#)
- range macros**
- defining [11](#)
- ranges of interfaces**
- configuring [4](#)
- Rapid Spanning Tree**
- See RSTP
- rcommand command** [13](#)
- reachability, tracking IP SLAs IP host** [9](#)
- re-authentication of a client**
- configuring manual [97](#)
 - enabling periodic [84](#)
- redirect URLs, port-based authentication** [20](#)
- reduced MAC address** [2](#)
- redundancy**
- configuring [7](#)
 - guidelines and restrictions [5](#)
 - changes made through SNMP [11](#)
 - NSF-aware support [2](#)
 - NSF-capable support [2](#)
 - overview [2](#)
 - redundancy command [8](#), [7](#)
 - understanding synchronization [4](#), [5](#)
- redundancy (NSF)** [1](#)
- configuring
 - BGP [11](#)
 - CEF [11](#)
 - EIGRP [16](#)
 - IS-IS [14](#)
 - OSPF [13](#)
 - routing protocols [5](#)
- redundancy (RPR)**
- route processor redundancy [2](#), [3](#)
 - synchronization [4](#), [5](#)
- redundancy (SSO)**
- redundancy command [10](#)
 - route processor redundancy [3](#)
 - synchronization [5](#)
- reload command** [28](#), [29](#)
- Remote Authentication Dial-In User Service**
- See RADIUS
- remote failure indications** [34](#)
- remote loopback, Ethernet OAM** [34](#), [37](#)
- Remote Network Monitoring**
- See RMON
- rendezvous point, configuring** [17](#)
- rendezvous point, configuring single static** [21](#)
- REP**
- administrative VLAN [8](#)
 - administrative VLAN, configuring [9](#)
 - and STP [6](#)

- configuration guidelines [7](#)
- configuring interfaces [10](#)
- convergence [4](#)
- default configuration [7](#)
- manual preemption, configuring [13](#)
- monitoring [14](#)
- neighbor offset numbers [5](#)
- open segment [2](#)
- ports [6](#)
- preempt delay time [5](#)
- primary edge port [4](#)
- ring segment [2](#)
- secondary edge port [4](#)
- segments [1](#)
 - characteristics [2](#)
- SNMP traps, configuring [14](#)
- supported interfaces [1](#)
- triggering VLAN load balancing [6](#)
- verifying link integrity [4](#)
- VLAN blocking [13](#)
- VLAN load balancing [4](#)
- replication
 - description [9](#)
- report suppression, IGMP
 - disabling [10](#)
- reserved-range VLANs
 - See VLANs
- reset command [3](#)
- resetting a switch to defaults [33](#)
- resetting an interface to default configuration [45](#)
- Resilient Ethernet ProtocolSee REP
- responder, IP SLAs
 - described [4](#)
 - enabling [7](#)
- response time, measuring with IP SLAs [4](#)
- restricting access
 - NTP services [8](#)
 - RADIUS [98](#)
 - TACACS+ [15](#)
- retransmission number
 - setting in 802.1X authentication [89](#)
- retransmission time
 - changing in 802.1X authentication [88](#)
- RFC
 - 1157, SNMPv1 [2](#)
 - 1305, NTP [2](#)
 - 1757, RMON [2](#)
 - 1901, SNMPv2C [2](#)
 - 1902 to 1907, SNMPv2 [2](#)
 - 2273-2275, SNMPv3 [2](#)
- RFC 5176 Compliance [100](#)
- RIP
 - description [19](#)
 - for IPv6 [6](#)
- RIP, introduction [19](#)
- RMON
 - default configuration [3](#)
 - displaying status [6](#)
 - enabling alarms and events [3](#)
 - groups supported [2](#)
 - overview [1](#)
- ROM monitor
 - boot process and [26](#)
 - CLI [7](#)
 - commands [2–3](#)
 - debug commands [5–6](#)
 - entering [1](#)
 - exiting [6](#)
 - overview [1](#)
- root bridge
 - configuring [9](#)
 - selecting in MST [22](#)
- root guard
 - and MST [23](#)
 - enabling [2](#)
 - overview [2](#)
- route maps
 - defining [8, 10, 12](#)

- PBR [2](#)
- route targets
 - VPN [3](#)
- routed packets
 - ACLs [28](#)
- route-map (IP) command [8](#), [10](#), [12](#)
- router ACLs
 - description [41](#), [3](#)
 - using with VLAN maps [27](#)
- router ACLs, using PACL with VLAN maps [34](#)
- Routing Information Protocol
 - See RIP
- RPF
 - See Unicast RPF
- RSPAN
 - configuration guidelines [16](#)
 - destination ports [5](#)
 - IDS [2](#)
 - monitored ports [4](#)
 - monitoring ports [5](#)
 - received traffic [3](#)
 - sessions
 - creating [17](#)
 - defined [3](#)
 - limiting source traffic to specific VLANs [23](#)
 - monitoring VLANs [21](#)
 - removing source (monitored) ports [20](#)
 - specifying monitored ports [17](#)
 - source ports [4](#)
 - transmitted traffic [4](#)
 - VLAN-based [5](#)
- RSTP
 - compatibility [23](#)
 - description [22](#)
 - port roles [24](#)
 - port states [24](#)

S

- S/M, 224/4 [13](#)
- SAID
 - See 802.10 SAID
- SAP
 - defined [9](#)
 - negotiation [9](#)
 - support [1](#)
- scheduling [8](#)
- scheduling, IP SLAs operations [5](#)
- secondary edge port, REP [4](#)
- secondary root switch [12](#)
- secondary VLANs [2](#)
 - associating with primary [16](#)
 - permitting routing [23](#)
- security
 - configuring [1](#)
- Security Association Identifier
 - See 802.10 SAID
- Security Exchange Protocol
 - See SAP
- selecting a power management mode [10](#)
- selecting X2/TwinGig Convertor Mode [14](#)
- sequence numbers in log messages [7](#)
- server IDs
 - description [23](#)
- service policy, configure class-level queue-limit [31](#), [65](#)
- service-policy input command [2](#)
- service-provider networks
 - and customer VLANs [2](#)
- session keys, MKA [2](#)
- set default interface command [9](#), [11](#)
- set interface command [8](#), [10](#)
- set ip default next-hop command [9](#), [11](#)
- set ip next-hop command [8](#), [10](#), [16](#)
- set-request operation [4](#)
- severity levels, defining in system messages [8](#)
- shaping, QoS on Sup 6-E [25](#), [59](#)

- sharing(bandwidth), QoS on Sup 6-E [27](#), [61](#)
- Shell functions
 - See Auto SmartPorts macros
 - See Auto Smartports macros
- Shell triggers
 - See Auto SmartPorts macros
 - See Auto Smartports macros
- show adjacency command [10](#)
- show boot command [32](#)
- show catalyst4000 chassis-mac-address command [3](#)
- show cdp command [2](#), [3](#)
- show cdp entry command [4](#)
- show cdp interface command [3](#)
- show cdp neighbors command [4](#)
- show cdp traffic command [4](#)
- show ciscoview package command [48](#)
- show ciscoview version command [48](#)
- show cluster members command [13](#)
- show configuration command [29](#)
- show debugging command [4](#)
- show environment command [2](#)
- show history command [4](#)
- show interfaces command [34](#), [35](#), [42](#), [44](#)
- show interfaces status command [2](#)
- show ip cef command [8](#)
- show ip eigrp interfaces command [20](#)
- show ip eigrp neighbors command [20](#)
- show ip eigrp topology command [20](#)
- show ip eigrp traffic command [20](#)
- show ip interface command [24](#)
- show ip local policy command [12](#)
- show ip mroute command [24](#)
- show ip pim interface command [24](#)
- show l2protocol command [18](#)
- show lldp traffic command [15](#)
- show mac-address-table address command [3](#)
- show mac-address-table interface command [3](#)
- show mls entry command [8](#)
- show module command [1](#), [6](#)
- show PoE consumed [8](#)
- show power inline command [6](#)
- show power supplies command [13](#)
- show protocols command [42](#)
- show running-config command
 - adding description for an interface [29](#)
 - checking your settings [9](#)
 - displaying ACLs [21](#), [23](#), [32](#), [33](#)
- show startup-config command [10](#)
- show users command [6](#)
- show version command [29](#)
- shutdown threshold for Layer 2 protocol packets [16](#)
- shutdown, command [43](#)
- shutting down
 - interfaces [42](#)
- Simple Network Management Protocol
 - See SNMP
- single spanning tree
 - See SST
- single static RP, configuring [21](#)
- single-host mode [7](#)
- slot numbers, description [2](#)
- Slow timer, configuring BFD [16](#)
- smart call home [1](#)
 - description [2](#)
 - destination profile (note) [5](#)
 - registration requirements [3](#)
 - service contract requirements [3](#)
 - Transport Gateway (TG) aggregation point [2](#)
- SMARTnet
 - smart call home registration [3](#)
- Smartports macros
 - applying global parameter values [8](#), [14](#)
 - applying macros [8](#)
 - applying parameter values [8](#)
 - configuration guidelines [6](#), [13](#)
 - configuring [2](#)
 - creating [7](#)
 - default configuration [3](#), [13](#)

- defined [10, 1](#)
- displaying [12](#)
- tracing [6, 13](#)
- SNMP
 - accessing MIB variables with [4](#)
 - agent
 - described [4](#)
 - disabling [7](#)
 - and IP SLAs [2](#)
 - authentication level [10](#)
 - community strings
 - configuring [7](#)
 - overview [4](#)
 - configuration examples [15](#)
 - configuration guidelines [6](#)
 - default configuration [5](#)
 - enabling [4, 5](#)
 - engine ID [6](#)
 - groups [6, 9](#)
 - host [6](#)
 - informs
 - and trap keyword [11](#)
 - described [5](#)
 - differences from traps [5](#)
 - enabling [14](#)
 - limiting access by TFTP servers [15](#)
 - limiting system log messages to NMS [9](#)
 - manager functions [3](#)
 - notifications [5](#)
 - overview [1, 4](#)
 - status, displaying [16](#)
 - system contact and location [14](#)
 - trap manager, configuring [13](#)
 - traps
 - described [3, 5](#)
 - differences from informs [5](#)
 - enabling [11](#)
 - enabling MAC address notification [31](#)
 - enabling MAC move notification [33](#)
 - enabling MAC threshold notification [35](#)
 - overview [1, 4](#)
 - types of [11](#)
 - users [6, 9](#)
 - versions supported [2](#)
- SNMP commands [4](#)
- SNMP traps
 - REP [14](#)
- SNMPv1 [2](#)
- SNMPv2C [2](#)
- SNMPv3 [2](#)
- software
 - upgrading [13, 12](#)
- software configuration register [26](#)
- software QoS, on Sup 6-E [40, 74](#)
- software switching
 - description [5](#)
 - interfaces [6](#)
 - key data structures used [8](#)
- source group tag [4, 10](#)
- source IDs
 - call home event format [22](#)
- SPAN
 - and ACLs [5](#)
 - configuration guidelines [7](#)
 - configuring [7–10](#)
 - destination ports [5](#)
 - IDS [2](#)
 - monitored port, defined [4](#)
 - monitoring port, defined [5](#)
 - received traffic [3](#)
 - sessions
 - defined [3](#)
 - source ports [4](#)
 - transmitted traffic [4](#)
 - VLAN-based [5](#)
- SPAN and RSPAN
 - concepts and terminology [3](#)
 - default configuration [6](#)

- displaying status [24](#)
- overview [1](#)
- session limits [6](#)
- SPAN enhancements
 - access list filtering [13](#)
 - configuration example [15](#)
 - CPU port sniffing [10](#)
 - encapsulation configuration [12](#)
 - ingress packets [12](#)
 - packet type filtering [14](#)
- spanning-tree backbonefast command [24](#)
- spanning-tree cost command [15](#)
- spanning-tree guard root command [2](#)
- spanning-tree port-priority command [13](#)
- spanning-tree uplinkfast command [20](#)
- spanning-tree vlan
 - command [9](#)
 - command example [9](#)
- spanning-tree vlan command [8](#)
- spanning-tree vlan cost command [16](#)
- spanning-tree vlan forward-time command [19](#)
- spanning-tree vlan hello-time command [18](#)
- spanning-tree vlan max-age command [18](#)
- spanning-tree vlan port-priority command [13](#)
- spanning-tree vlan priority command [17](#)
- spanning-tree vlan root primary command [10](#)
- spanning-tree vlan root secondary command [12](#)
- speed
 - configuring interface [24](#)
- speed command [25](#), [26](#), [27](#)
- SSO
 - configuring [10](#)
- SSO operation [4](#)
- SST
 - description [22](#)
 - interoperability [24](#)
- static ACL, removing the requirement [30](#)
- static addresses
 - See addresses
- static routes
 - configuring [11](#)
 - verifying [12](#)
- statistics
 - 802.1X [14](#)
 - displaying 802.1X [127](#)
 - displaying PIM [28](#)
 - LLDP [14](#)
 - LLDP-MED [14](#)
 - MKA [4](#)
 - SNMP input and output [16](#)
- sticky learning
 - configuration file [6](#)
 - defined [5](#)
 - disabling [6](#)
 - enabling [5](#)
 - saving addresses [6](#)
- sticky MAC addresses
 - configuring [7](#)
 - defined [4](#)
- storing captured packets to a .pcap file, Wireshark [8](#)
- Storm Control
 - displaying [6](#)
 - enabling Broadcast [3](#)
 - enabling Multicast [4](#)
 - hardware-based, implementing [2](#)
 - overview [1](#)
 - software-based, implementing [2](#)
- STP
 - and REP [6](#)
 - bridge ID [2](#)
 - configuring [7–20](#)
 - creating topology [5](#)
 - defaults [7](#)
 - disabling [20](#)
 - enabling [8](#)
 - enabling extended system ID [9](#)
 - enabling Per-VLAN Rapid Spanning Tree [20](#)
 - EtherChannel guard

- disabling [7](#)
 - forward-delay time [19](#)
 - hello time [17](#)
 - Layer 2 protocol tunneling [13](#)
 - maximum aging time [18](#)
 - overview [1, 3](#)
 - per-VLAN rapid spanning tree [6](#)
 - port cost [15](#)
 - port priority [13](#)
 - root bridge [9](#)
- stratum, NTP [2](#)
- stub routing (EIGRP)
 - benefits [18](#)
 - configuration tasks [18](#)
 - configuring [14](#)
 - overview [13, 14](#)
 - restrictions [18](#)
 - verifying [19](#)
- subdomains, private VLAN [2](#)
- summer time [13](#)
- supervisor engine
 - accessing the redundant [14](#)
 - configuring [8–13](#)
 - copying files to standby [14](#)
 - default configuration [1](#)
 - default gateways [11](#)
 - environmental monitoring [1](#)
 - redundancy [1](#)
 - ROM monitor [26](#)
 - startup configuration [25](#)
 - static routes [11](#)
 - synchronizing configurations [11, 10](#)
- Supervisor Engine 7L-E, selecting the uplink port [22](#)
- Supervisor Engine II-TS
 - insufficient inline power handling [22, 12](#)
- Smartports macros
 - See also Auto Smartports macros
- SVI Autostate Exclude
 - understanding [3](#)
- SVI Autostate exclude
 - configuring [8](#)
- S-VLAN [2, 7](#)
- switch [2](#)
- switch access with RADIUS, controlling [98](#)
- switch ports
 - See access ports
- switched packets
 - and ACLs [27](#)
- Switched Port Analyzer
 - See SPAN
- switchport
 - show interfaces [34, 35, 44](#)
- switchport access vlan command [5, 7](#)
- switchport block multicast command [2](#)
- switchport block unicast command [2](#)
- switchport mode access command [7](#)
- switchport mode dot1q-tunnel command [6](#)
- switchport mode dynamic command [5](#)
- switchport mode trunk command [5](#)
- switchport trunk allowed vlan command [6](#)
- switchport trunk encapsulation command [5](#)
- switchport trunk native vlan command [6](#)
- switchport trunk pruning vlan command [6](#)
- switch-to-RADIUS server communication
 - configuring [34](#)
- sysret command [5](#)
- system
 - reviewing configuration [10](#)
 - settings at startup [27](#)
- system alarms
 - overview [6](#)
- system and network statistics, displaying [24](#)
- system capabilities TLV [2](#)
- system clock
 - configuring
 - daylight saving time [13](#)
 - manually [11](#)
 - summer time [13](#)

- time zones [12](#)
- displaying the time and date [12](#)
- overview [2](#)
- See also NTP
- system description TLV [2](#)
- system images
 - loading from Flash memory [30](#)
 - modifying boot field [27](#)
 - specifying [30](#)
- system message logging
 - default configuration [3](#)
 - defining error message severity levels [8](#)
 - disabling [3](#)
 - displaying the configuration [12](#)
 - enabling [4](#)
 - facility keywords, described [12](#)
 - level keywords, described [8](#)
 - limiting messages [9](#)
 - message format [2](#)
 - overview [1](#)
 - sequence numbers, enabling and disabling [7](#)
 - setting the display destination device [4](#)
 - synchronizing log messages [5](#)
 - timestamps, enabling and disabling [6](#)
 - UNIX syslog servers
 - configuring the daemon [10](#)
 - configuring the logging facility [11](#)
 - facilities supported [12](#)
- system MTU
 - 802.1Q tunneling [5](#)
 - maximums [5](#)
- system name
 - manual configuration [22](#)
 - See also DNS
- system name TLV [2](#)
- system prompt, default setting [21](#)

T

- TACACS+ [1](#)
 - accounting, defined [16](#)
 - authentication, defined [16](#)
 - authorization, defined [16](#)
 - configuring
 - accounting [21](#)
 - authentication key [18](#)
 - authorization [21](#)
 - login authentication [19](#)
 - default configuration [18](#)
 - displaying the configuration [22](#)
 - identifying the server [18](#)
 - limiting the services to the user [21](#)
 - operation of [17](#)
 - overview [15](#)
 - tracking services accessed by user [21](#)
- tagged packets
 - 802.1Q [3](#)
 - Layer 2 protocol [13](#)
- TCAM programming and ACLs [7](#)
 - for Sup II-Plust thru V-10GE [7](#)
- TCAM programming and ACLs for Sup 6-E [10](#)
- TDR
 - checking cable connectivity [3](#)
 - enabling and disabling test [3](#)
 - guidelines [3](#)
- Telnet
 - accessing CLI [2](#)
 - disconnecting user sessions [7](#)
 - executing [5](#)
 - monitoring user sessions [6](#)
- telnet command [6](#)
- templates, Ethernet OAM [45](#)
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- TFTP
 - configuration files in base directory [5](#)

- configuring for autoconfiguration [4](#)
 - limiting access by servers [15](#)
- TFTP download
 - See also console download
- threshold monitoring, IP SLAs [6](#)
- time
 - See NTP and system clock
- Time Domain Reflectometer
 - See TDR
- time exceeded messages [9](#)
- time zones [12](#)
- timer
 - See login timer
- timestamps in log messages [6](#)
- TLV
 - host presence detection [8](#)
- TLVs
 - defined [7, 2](#)
 - LLDP-MED [2](#)
- Token Ring
 - media not supported (note) [5, 9](#)
- Topology change notification processing
 - MLD Snooping
 - Topology change notification processing [4](#)
- TOS
 - description [4](#)
- trace command [9](#)
- traceroute
 - See IP traceroute
 - See Layer 2 Traceroute
- traceroute mac command [11](#)
- traceroute mac ip command [11](#)
- track state, tracking IP SLAs [9](#)
- tracked lists
 - configuring [3](#)
 - types [3](#)
- tracked objects
 - by Boolean expression [4](#)
 - by threshold percentage [6](#)
 - by threshold weight [5](#)
- tracking interface line-protocol state [2](#)
- tracking IP routing state [2](#)
- tracking objects [1](#)
- tracking process [1](#)
- traffic
 - blocking flooded [2](#)
- traffic control
 - using ACLs (figure) [4](#)
 - using VLAN maps (figure) [6](#)
- traffic marking procedure flowchart [21, 55](#)
- traffic shaping [9](#)
- translational bridge numbers (defaults) [5](#)
- traps
 - configuring MAC address notification [31](#)
 - configuring MAC move notification [33](#)
 - configuring MAC threshold notification [35](#)
 - configuring managers [11](#)
 - defined [3](#)
 - enabling [31, 33, 35, 11](#)
 - notification types [11](#)
 - overview [1, 4](#)
- troubleshooting
 - with CiscoWorks [4](#)
 - with system message logging [1](#)
 - with traceroute [8](#)
- troubleshooting high CPU due to ACLs [7](#)
- trunk failover
 - See link-state tracking
- trunk ports
 - configure port security [17](#)
 - configuring PVLAN [19–21](#)
- trunks
 - 802.1Q restrictions [4](#)
 - configuring [5](#)
 - configuring access VLANs [5](#)
 - configuring allowed VLANs [6](#)
 - default interface configuration [5](#)
 - enabling to non-DTP device [4](#)

- specifying native VLAN [6](#)
 - understanding [3](#)
 - trustpoint [3](#)
 - tunnel ports
 - 802.1Q, configuring [5](#)
 - described [2](#)
 - incompatibilities with other features [5](#)
 - tunneling
 - defined [1](#)
 - TwinGig Convertors
 - limitations on using [14](#)
 - port numbering [13](#)
 - selecting X2/TwinGig Convertor mode [14](#)
 - type length value
 - See TLV
 - type of service
 - See TOS
-
- ## U
- UDLD
 - configuring probe message interval per-interface [8](#)
 - default configuration [3](#)
 - disabling on fiber-optic interfaces [7](#)
 - disabling on non-fiber-optic interfaces [7](#)
 - displaying link status [9](#)
 - enabling globally [5](#)
 - enabling per-interface [6](#)
 - modes of operation [3](#)
 - resetting disabled LAN interfaces [8](#)
 - use case [2](#)
 - UDLD, overview [1](#)
 - UDP jitter operation, IP SLAs [8](#)
 - UDP jitter, configuring [9](#)
 - unauthorized ports with 802.1X [5](#)
 - unicast
 - See IP unicast
 - unicast flood blocking
 - configuring [1](#)
 - unicast MAC address filtering
 - and adding static addresses [38](#)
 - and broadcast MAC addresses [37](#)
 - and CPU packets [37](#)
 - and multicast addresses [37](#)
 - and router MAC addresses [37](#)
 - configuration guidelines [37](#)
 - described [37](#)
 - unicast MAC address filtering, configuring
 - ACLs
 - configuring unicast MAC address filtering [14](#)
 - Unicast RPF (Unicast Reverse Path Forwarding)
 - applying [5](#)
 - BGP attributes
 - caution [4](#)
 - CEF
 - requirement [2](#)
 - tables [7](#)
 - configuring [9](#)
 - (examples) ??–[12](#)
 - BOOTP [8](#)
 - DHCP [8](#)
 - enterprise network (figure) [6](#)
 - prerequisites [9](#)
 - routing table requirements [7](#)
 - tasks [9](#)
 - verifying [10](#)
 - deploying [5](#)
 - description [22](#), [1](#)
 - disabling [11](#)
 - enterprise network (figure) [6](#)
 - FIB [2](#)
 - implementing [4](#)
 - packets, dropping (figure) [4](#)
 - prerequisites [9](#)
 - restrictions
 - basic [8](#)
 - routing asymmetry [7](#)
 - routing asymmetry (figure) [8](#)

- routing table requirements **7**
- security policy
 - applying **5**
 - attacks, mitigating **5**
 - deploying **5**
 - tunneling **5**
- source addresses, validating **3**
 - (figure) **3, 4**
 - failure **3**
- traffic filtering **5**
- tunneling **5**
- validation
 - failure **3, 4**
 - packets, dropping **3**
 - source addresses **3**
- verifying **10**
- unicast traffic
 - blocking **2**
- Unidirectional Controlled Port, configuring 802.1X **69**
- unidirectional ethernet
 - enabling **2**
 - example of setting **2**
 - overview **1**
- UniDirectional Link Detection Protocol
 - See UDLD
- Universal PoE, configuring **16**
- UNIX syslog servers
 - daemon configuration **10**
 - facilities supported **12**
 - message logging configuration **11**
- uplink forwarding
 - quad-supervisor **6**
- uplink mode, selecting on supervisor engine 6-E **17**
- uplink port, selecting on a supervisor engine 7L-E **22**
- UplinkFast
 - and MST **23**
 - enabling **23**
 - MST and **23**
 - overview **19**

- usage examples, Wireshark **18**
- user EXEC mode **5**
- user sessions
 - disconnecting **7**
 - monitoring **6**
- user-defined event triggers
 - configuring, 802.1X-based **8**
 - configuring, MAC address-based **9**
- User-defined triggers and built-in macros, configuring mapping **9**

V

- VACLs
 - Layer 4 port operations **10**
- virtual configuration register **3**
- virtual LANs
 - See VLANs
- virtual ports, MKA **3**
- Virtual Router Redundancy Protocol, introduction **23**
- Virtual Switch System(VSS), displaying EtherChannel to **20**
- VLAN ACLs
 - See VLAN maps
- VLAN blocking, REP **13**
- vlan command **6**
- vlan dot1q tag native command **4**
- VLAN ID
 - service provider **8**
- VLAN ID translation
 - See VLAN mapping
- VLAN ID, discovering **44**
- VLAN load balancing
 - REP **4**
- VLAN load balancing on flex links **2**
 - configuration guidelines **5**
- VLAN load balancing, triggering **6**
- VLAN Management Policy Server
 - See VMPS

VLAN mapping

- 1-to-1 [7](#)
- 1-to-1, configuring [10](#)
- configuration guidelines [9](#)
- configuring [10](#)
- configuring on a trunk port [10](#)
- default [9](#)
- described [2](#), [7](#)
- selective QinQ [8](#)
- selective Q-in-Q, configuring [12](#)
- traditional QinQ [8](#)
- traditional Q-in-Q, configuring [11](#)
- types of [7](#)

VLAN maps

- applying to a VLAN [23](#)
- configuration example [24](#)
- configuration guidelines [20](#)
- configuring [19](#)
- creating and deleting entries [20](#)
- defined [41](#)
- denying access example [25](#)
- denying packets [21](#)
- displaying [26](#)
- order of entries [20](#)
- permitting packets [21](#)
- router ACLs and [27](#)
- using (figure) [5](#)
- using in your network [23](#)

VLAN maps, PACL and Router ACLs [34](#)

VLAN Trunking Protocol

See VTP

VLAN trunks

- overview [3](#)

VLAN User Distribution, configuring 802.1X [71](#)

VLANs

- allowed on trunk [6](#)
- configuration guidelines [3](#)
- configuring [5](#)
- configuring as Layer 3 interfaces [8](#)

customer numbering in service-provider networks [3](#)

default configuration [4](#)

description [11](#)

extended range [3](#)

IDs (default) [4](#)

interface assignment [7](#)

limiting source traffic with RSPAN [23](#)

monitoring with RSPAN [21](#)

name (default) [4](#)

normal range [3](#)

overview [1](#)

reserved range [3](#)

See also PVLANS

VMPS

- configuration file example [31](#)
- configuring dynamic access ports on client [24](#)
- configuring retry interval [26](#)
- database configuration file [31](#)
- dynamic port membership
 - example [28](#)
 - reconfirming [25](#), [26](#)
- reconfirming assignments [25](#)
- reconfirming membership interval [26](#)
- server overview [20](#)

VMPS client

- administering and monitoring [27](#)
- configure switch
 - configure reconfirmation interval [26](#)
 - dynamic ports [24](#)
 - entering IP VMPS address [24](#)
 - reconfirm VLAM membership [25](#)
 - reconfirmation interval [26](#)
- default configuration [23](#)
- dynamic VLAN membership overview [23](#)
- troubleshooting dynamic port VLAN membership [28](#)

VMPS server

- fall-back VLAN [22](#)
- illegal VMPS client requests [22](#)
- overview [20](#)

- security modes
 - multiple [22](#)
 - open [21](#)
 - secure [21](#)
- voice aware 802.1x security
 - port-based authentication
 - configuring [77](#)
 - described [22](#), [76](#)
- voice interfaces
 - configuring [1](#)
- Voice over IP
 - configuring [1](#)
- voice ports
 - configuring VVID [3](#)
- voice traffic [2](#), [5](#)
- voice VLAN
 - IP phone data traffic, described [2](#)
 - IP phone voice traffic, described [2](#)
- voice VLAN ports
 - using 802.1X [22](#)
- Voice VLAN, configure 802.1X [75](#)
- VPN
 - configuring routing in [8](#)
 - forwarding [3](#)
 - routes [2](#)
 - routing and forwarding table
 - See VRF
- VRF
 - defining [3](#)
 - tables [1](#)
- VRF-aware services
 - ARP [6](#), [15](#), [17](#)
 - configuring [6](#), [15](#)
 - ftp [16](#)
 - ping [15](#)
 - tftp [16](#)
 - traceroute [16](#)
 - uRPF [16](#)
- VRF-lite
 - description [22](#)
- VSS
 - dual-active detection
 - displaying [54](#)
 - Enhanced PAgP, advantages [23](#)
 - enhanced PAgP, configuring [52](#)
 - Enhanced PAgP, description [23](#)
 - fast-hello, configuring [53](#)
- VTP
 - client, configuring [16](#)
 - configuration guidelines [12](#)
 - default configuration [13](#)
 - disabling [16](#)
 - Layer 2 protocol tunneling [13](#)
 - monitoring [19](#)
 - overview [7](#)
 - pruning
 - configuring [15](#)
 - See also VTP version 2
 - server, configuring [16](#)
 - statistics [19](#)
 - transparent mode, configuring [16](#)
 - version 2
 - enabling [15](#)
- VTP advertisements
 - description [9](#)
- VTP domains
 - description [8](#)
- VTP modes [8](#)
- VTP pruning
 - overview [10](#)
- VTP versions 2 and 3
 - overview [9](#)
 - See also VTP
- VTY and Network Assistant [12](#)
- VVID (voice VLAN ID)
 - and 802.1X authentication [22](#)
 - configuring [3](#)

W

WCCP

- configuration examples [9](#)
- configuring on a router [2](#), [13](#)
- features [3](#)
- restrictions [5](#)
- service groups [5](#)

Web Cache Communication Protocol

See [WCCP 1](#)

web cache services

description [4](#)

web caches

See [cache engines](#)

web caching

See [web cache services](#)

See also [WCCP](#)

web-based authentication

authentication proxy web pages [4](#)

description [43](#), [14](#), [1](#)

web-based authentication, interactions with other features

[4](#)

weight thresholds in tracked lists [5](#)

Wireshark

- activating and deactivating, capture points, conceptual [10](#)
- attachment points [6](#)
- capture filter [7](#)
- capture points [6](#)
- core system filter [7](#)
- decoding and displaying packets [9](#)
- display filter [7](#)
- feature interactions [10](#)
- filters [6](#)
- storing captured packets to a .pcap filter [8](#)
- usage examples [18](#)

Wireshark, about [5](#)Wireshark, activating and deactivating a capture point [14](#)Wireshark, defining/modifying/deleting a capture point [12](#)Wireshark, displaying information [14](#)WS-X46490-CSFP-E, support on a 10-slot chassis [17](#)**X**

X.509v3 Certificates for SSH Authentication

Overview [2](#)

Y

Y.1731

default configuration [29](#)

described [27](#)

ETH-AIS

Ethernet Alarm Signal function (ETH-AIS)

[28](#)

ETH-RDI [28](#)

multicast Ethernet loopback [31](#)

multicast ETH-LB [29](#)

terminology [27](#)