



Release Notes for Cisco Jabber 14.0

First Published: 2021-03-25

Last Modified: 2022-02-25

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883



CONTENTS

CHAPTER 1

What's New in Release 14.0 1

- Jabber End-User Content on Cisco Webex Help Center 1
- Build Numbers 1
- New and Updated Features 3
- EMM Clients 7
 - Jabber for Intune 14.0(3) 7
 - Jabber for BlackBerry 14.0(3) 7

CHAPTER 2

Limitations 9

- Cisco Jabber for Windows 9
 - Limitations for All Deployments 9
 - Limitations for On-Premise Deployments 15
 - Limitations for Cloud Deployments 16
- Cisco Jabber for Mac 17
 - Limitations for All Deployments 17
 - Limitations for On-Premise Deployments 19
- Cisco Jabber for Android 20
 - Limitations for All Deployments 20
 - Limitations for Cloud Deployments 23
- Cisco Jabber for iPhone and iPad 23
 - Limitations for All Deployments 23
 - Limitations for Cloud Deployments 29

CHAPTER 3

Search for Bugs 31

- Bug Severity Levels 31
- Cisco Jabber for Windows 32

Cisco Jabber for Mac 35

Cisco Jabber for Android 36

Cisco Jabber for iPhone and iPad 37

Cisco Jabber for Intune 38

Cisco Jabber for BlackBerry 38



CHAPTER 1

What's New in Release 14.0

- [Jabber End-User Content on Cisco Webex Help Center](#), on page 1
- [Build Numbers](#), on page 1
- [New and Updated Features](#), on page 3
- [EMM Clients](#), on page 7

Jabber End-User Content on Cisco Webex Help Center

You can find information on the Jabber client at <https://help.webex.com/ld-n1uv5wq-CiscoJabber/Jabber>. The Help Center contains articles on using Jabber features. You can provide feedback on individual articles or request new articles through the Help Center.

The Help Center search includes a set of filters to narrow your results by product, release, activities, operating system, and other categories.

Build Numbers

Jabber for Windows

Version	Build Number
14.0.5	14.0.5.57306 Build 307306
14.0.4	14.0.4.56553 Build 306553
14.0.3	14.0.3.56354 Build 306354
14.0.2	14.0.2.56216 Build 306216
14.0.1	14.0.1.55914 Build 305914
14.0	14.0.0.55563 Build 305563
12.9.6	12.9.6.55898 Build 305898
12.8.6	12.8.6.55855 Build 305855

Version	Build Number
12.7.5	12.7.5.55797 Build 305797

Jabber for Mac

Version	Build Number
14.0.5	14.0.5.307306
14.0.4	14.0.4.306555
14.0.3	14.0.3.306210
14.0.2	14.0.2.305994
14.0.1	14.0.1.305914
14.0	14.0.0.305556
12.9.7	12.9.7.305996

DownloadURL

The DownloadURL file element in the XML file for automatic updates is:

Release	File Name
14.0.5	Install_Cisco-Jabber-Mac-14.0.5.307306-120915339-MCwCFBOR1QnEv2SE_OS&aPKM+Y62RwQ_AhQY0dU2ZnmWCzDvtvVFOL662zMZw!! zip
14.0.4	Install_Cisco-Jabber-Mac-14.0.4.306555-120920848-MC0CFQCHRgC8RejyGHszOgJlpdNixANigIUyoiUnZVYrczd5NE4Oe+Jji58Ves! zip
14.0.3	Install_Cisco-Jabber-Mac-14.0.3.306210-121263735-MC0CFQCMp4sMg84kwXClsAAOWT8fx0iyOAIUF7AbGK4A82BqzV+Fs8K0tOAgz! zip
14.0.2	Install_Cisco-Jabber-Mac-14.0.2.305994-120356597-MCwCFGciEbl3_l56IVjoGu9AW4YVBzKAhQcXqP1DqzqTCzYXG8jxfZ4abe3bQ!! zip
14.0.1	Install_Cisco-Jabber-Mac-14.0.1.305914-121132537-MCwCFB_ggNA9BHeeV5ddU3pdaMWmoVWuAhQ4ig+Z+3TFGgRYH91FrfUSN+QcnA!! zip
14.0	Install_Cisco-Jabber-Mac-14.0.0.305556-120486118-MCwCFAY4Fp12hyYxYCICCrNfNyA9c3Fm0AhRV57Rfc5glleofu3bQ5aU2j2FbGA!! zip
12.9.7	Install_Cisco-Jabber-Mac-12.9.7.305996-118774040-MC0CFEvHBdogP+Qc90_haf4CNWE9q+hTAhUAl1uRvTqfpDLS43sSw3gdkr8Cto! zip

The DownloadURL file element refers to the Cisco Jabber for Mac installation file. The installation file on the update server must be renamed to match this DownloadURL file element name.

You can also download the manual installation file, if your users install the client manually.



Note To ensure the DSA signature succeeds, configure Web servers to escape special characters. For example, on Microsoft IIS the option is: **Allow double spacing**.

New and Updated Features

Android OS 12 Support

Released in 14.0.3

Windows	Mac	iPhone and iPad	Android
No	No	No	Yes

Jabber now supports Android OS 12.

Auto Upgrade Support on Mobile and Remote Access (MRA)

Released in 14.0

Windows	Mac	iPhone and iPad	Android
—	Yes	—	—

Jabber for Mac now supports auto upgrade on MRA.

CMS: Lobby Control

Released in 14.0

Windows	Mac	iPhone and iPad	Android
Yes	Yes	Yes	Yes

Locked CMS conference call users can select participants from the lobby and admit them to the meeting. The meeting doesn't need to be unlocked.

ChromeOS support without MRA

Released in 14.0.1

Windows	Mac	iPhone and iPad	Android
No	No	No	Yes

Jabber for Android now supports ChromeOS without MRA.

Disable First Time Experience

Released in 14.0

Windows	Mac	iPhone and iPad	Android
Yes	—	—	Yes

You can now disable the first time experience dialog after a reset or clear cache. For details, see the *EnableFTE* parameter in the *Parameters Reference Guide for Cisco Jabber 14.0*, <https://www.cisco.com/c/en/us/support/unified-communications/jabber-windows/products-installation-guides-list.html>.

iOS 15 Support

Released in 14.0.3

Windows	Mac	iPhone and iPad	Android
No	No	Yes	No

Jabber now supports iOS 15.

iOS Dark Mode

Released in 14.0

Windows	Mac	iPhone and iPad	Android
No	No	Yes	No

iOS and iPad users can now set Jabber themes, including dark mode.

IPv6 support for Mobile and Remote Access

Released in 14.0(4)

Windows	Mac	iPhone and iPad	Android
Yes	Yes	Yes	Yes

Starting in Release 14.0.4, we now support IPv6 connections from Jabber clients over MRA.

While the Video Communication Server Edge (VCSE) connection to the client supports IPv6, the Video Communication Server Core (VCSC) connection to Unified Communication Manager (UCM) is still IPv4. This mismatch causes some limitations when on-premise clients that register with UCM over IPv6 connect to clients over MRA:

- Calls only support audio. Video is not available.
- Hold/Resume is not available.

Other advanced calling features might not work between on-premise IPv6 clients and IPv6 MRA clients.

macOS Big Sur Support

Released in 14.0

Windows	Mac	iPhone and iPad	Android
No	Yes	No	No

Jabber now supports macOS Big Sur.

macOS Monterey Support**Released in 14.0.3**

Windows	Mac	iPhone and iPad	Android
No	Yes	No	No

Jabber now supports macOS Monterey.

Mobile and Remote Access (MRA) Failover**Released in 14.0**

Windows	Mac	iPhone and iPad	Android
Yes	Yes	Yes	Yes

Jabber now supports Expressway-E, Expressway-C, and Cisco Unified Communication Manager (Cisco Unified CM) node failover to keep phone services connected.

Out of Office**Released in 14.0**

Windows	Mac	iPhone and iPad	Android
Yes	Yes	Yes	Yes

Your account profile status shows out of office when your exchange account is set to automatic replies (out of office). This feature requires Cisco Unified Communications Manager IM & Presence Service, Release 14.0.

Save Detailed Logs to Local Device

Windows	Mac	iPhone and iPad	Android
—	—	Yes	Yes

You can enable detailed logs, define the number of logs, clear logs, and control reporting options.

Set the UserEnabledDetailedLogging parameter to true to enable detailed log mode. Default is false.

There are two parameters to control which options your user sees on Jabber mobile:

- EnablesSendLogsViaEmail - set to false if you want to hide "Send via email" button. The default is true.
- SaveLogToLocal - set to false if you want to hide "Save logs to" button. The default is true.

Use the MaxNumberOfFilesMobile parameter to increase the number of log files. The maximum is 20, default is 5.

Users use the new **Clear logs** option to clear logs saved on the local device.

Security improvement while joining a Webex meeting**Released in 14.0.1, 14.0(2)**

Windows	Mac	iPhone and iPad	Android
Yes, 14.0(1)	Yes, 14.0(2)	No	No

Jabber now launches the meetings client when joining a Webex meeting.

Supported Android Devices**Released in 14.0.3, 14.0.4**

Windows	Mac	iPhone and iPad	Android
No	No	No	Yes

In Release 14.0.3, Jabber adds support for Google Pixel 5 and Ascom Myco 3.

In Release 14.0.4, Jabber adds support for ASUS Chromebook Flip C434 and Dell Latitude 5400 Chromebook Enterprise.

Windows 11 Support**Released in 14.0.4**

Windows	Mac	iPhone and iPad	Android
Yes	No	No	No

Jabber now supports Windows 11.

Zero Down Time**Released in 14.0**

Windows	Mac	iPhone and iPad	Android
Yes	Yes	Yes	Yes

Jabber now supports one active connection to the primary node, and one inactive connection to the backup node. When a failover or upgrade occurs, your users will not experience an interruption.

For details, see the following:

- *EnableDualConnections* and *Inactive_Connection_Activation_Timer* parameters in the *Parameters Reference Guide for Cisco Jabber 14.0*, <https://www.cisco.com/c/en/us/support/unified-communications/jabber-windows/products-installation-guides-list.html>.
- This feature requires Cisco Unified Communications Manager IM & Presence Service, Release 14.0 with high availability enabled. See <https://www.cisco.com/c/en/us/support/unified-communications/unified-presence/series.html>.

EMM Clients

These clients follow a delayed release cycle. The clients release later than the corresponding releases of Jabber for Android and Jabber for iPhone and iPad.

Jabber for Intune 14.0(3)

Jabber for Intune on iOS

This release includes these features:

- We now support iOS 15.
- We now support Apple Push Notification (APN) for IMs. Previously, Jabber for Intune only supported APN for voice calls.

Jabber for BlackBerry 14.0(3)

Jabber for BlackBerry on iOS

This release includes these features:

- We now support iOS 15.
- We now support Apple Push Notification (APN) for IMs. Previously, Jabber for BlackBerry only supported APN for voice calls.

Limitations



Important You can't install Jabber for BlackBerry iOS 14.0(3) on an iOS device with a previous version of Jabber for BlackBerry installed. First, uninstall any previous version of Jabber for BlackBerry. Jabber for BlackBerry iOS 14.0(3) won't activate if you try to upgrade from a previous version.

If you set `MAMAccountBinding = 1`, Jabber for BlackBerry 14.0(3) doesn't support the use of `ServicesDomain` and `VoiceServicesDomain` in the `jabber.config` file.



CHAPTER 2

Limitations

- [Cisco Jabber for Windows, on page 9](#)
- [Cisco Jabber for Mac, on page 17](#)
- [Cisco Jabber for Android, on page 20](#)
- [Cisco Jabber for iPhone and iPad, on page 23](#)

Cisco Jabber for Windows

These are the limitations that apply to the Jabber for Windows client.

Limitations for All Deployments

These limitations apply to all Jabber for Windows deployments.

Allow Paste Operations via Script

Jabber versions 11.8.5 and later may have issues with Copy/Paste when the policy **Allow paste operations via script** is enabled for Internet Explorer at **Windows Components > Internet Explorer > Internet Control Panel > Security Page > Internet zone**.

Automatic Detection of Proxy Settings (WPAD)

Cisco Jabber doesn't support Web Proxy Auto-Discovery (WPAD) proxy discovery. For information about how to configure proxy settings for Cisco Jabber, see *Configure Proxy Settings* in the *On-Premises Deployment for Cisco Jabber* guide.

Bluetooth Connectivity Unsupported with Cisco Headset 56x

Cisco Jabber doesn't support the use of Bluetooth with Model 56x Cisco headsets. You can use these headsets with a USB-C to USB connector cable.

Call Transfers

When you're transferring a call to a third party, the third party must respond to the call before you can complete the transfer. You can't currently dial the third party and connect the first party while waiting for the call to connect (also known as a blind transfer).

Prior to Release 12.7(1), Cisco Jabber doesn't correctly inform Unified Communications Manager that a call being transferred is on hold. This behavior results in incorrect reporting when you use Jabber with Cisco Finesse.

Cannot Copy Image

You can't right-click over an image in a conversation in Jabber and select copy. Instead, highlight the image and then right-click to copy it.

Chat Reply and No Voicemail Profile

If the user has no voicemail profile configured, the chat reply feature doesn't work. If the user selects **Chat reply** in an incoming call, the call continues to ring and the **Chat reply** and **Answer** options are grayed out. CSCux75667 documents this limitation.

Chat Behavior During Transition to MRA

Jabber loses chat messages that are sent while the Jabber client is transitioning from an on-premises network connection to an MRA network connection, or vice versa. Users receive an error message when they try to send chat messages during this transition period.

Cisco AnyConnect Secure Mobility Client

Cisco Jabber for Windows supports Cisco AnyConnect Secure Mobility Client version 4.0 and later. CSCuy14721 documents this limitation.

Cisco IP Communicator

Cisco IP Communicator isn't supported as a controlled device on Jabber when users choose to use their desk phone for calls.

Cisco Unity Connection Dispatch Messages

In Cisco Unity Connection, a dispatch message is sent to a distribution list with the message configured in such a way that only one user responds to that message. A user can accept, decline, or postpone the dispatch message. Cisco Jabber for Windows doesn't support Cisco Unity Connection dispatch messages. CSCuw31908 documents this limitation..

Contact Resolution for Enterprise Groups

Jabber resolves contacts in enterprise groups individually rather than all at once. As a result, when you add an enterprise group to your users' contact lists—or if they clear their local cache—they'll only see the username and domain for each person until they hover over or interact with them.

Emails to a Group of Contacts

There's a limit of 2083 characters in the **To** field when sending an email to a group of contacts. With long email addresses or many recipients, not all contacts may be added to the email. For more information about the 2083 character limitation, see <https://support.microsoft.com/en-ie/kb/208427>.

Extension Mobility

Jabber doesn't support the Cisco Extension Mobility Cross Cluster (EMCC) feature.

Device Name with Extension Mobility

When Extension Mobility is enabled, the controlled devices menu in Jabber displays the phone type only, instead of the phone type and user name.

Do Not Disturb (DND)

If Jabber is controlling the Deskphone and if Do Not Disturb (DND) is set on the Deskphone, the presence status of the Jabber client does not change.

This behavior indicates that the Jabber client is functioning as designed. No action is required from the user.

HTML Sanitization Code

The Jabber HTML sanitization code has been modified to disallow 'masked' links in XMPP message payloads due to its potential abuse in phishing attacks. These links are no longer allowed for security reasons.

It is recommended that Jabber Administrators educate potential users who may be affected by this feature enhancement.

IBM Notes Contact Search

When searching for an IBM Notes contact, entering either " or \ as the first character in the search string won't find the correct contact.

Jabber Config Change Detected Loop Scenario

A Jabber "Config Change Detected" loop can occur if you assign the Jabber Config Profile (jabber-config.xml) on UC service and in the Group Config file for Phone page/common phone profile, and then you remove the Jabber Config Profile from the UC Service while Fast Login is enabled. In this scenario, once you remove the Config Profile from UC Service, the config change detected loop is triggered.

Workaround: Disable Fast Login, see *Planning Guide for Cisco Jabber*.

Jabber to Jabber Calls and Symantec Host IDS (HIDS)

Jabber to Jabber calls can trigger errors in Symantec HIDS.

Symantec HIDS has a rule that disables connections from internet-based servers if it receives 5 connection requests from the same internet-based server within 200 seconds. For example, 3 Jabber to Jabber calls within 200 seconds will trigger Symantec HIDS. When this happens, ongoing Jabber to Jabber calls are dropped and Jabber to Jabber calls are disabled for 600 seconds.

To avoid this scenario, you must add Cisco Jabber to the Symantec exception list. This behavior is documented in CSCu32007.

Joining Meetings by Meeting Number

In deployments that use a Cisco Webex Meeting Server, you cannot use the meeting number when joining by Webex. Use the meeting URL instead.

Joining Webex Meetings from Jabber

Webex site disclaimers don't appear when you join Webex meetings from Jabber. This limitation applies whether joining from the meeting reminder popup, or by selecting **Join in Webex** in Jabber.

LDAP Credential Delivery with Unified Communications Manager 12.5(1) SU2

In Unified Communications Manager Release 12.5(1) SU2, Unified CM added support for securely passing encrypted LDAP credentials in the Service Profile. This update secures access to your directory by ensuring that the password is always stored and sent in an encrypted format. This change includes encryption during directory access authentication, client configuration file downloads, BAT imports/exports, and upgrades.

In Jabber 12.8 with this Unified CM release or later, we take advantage of this capability by downloading the LDAP credentials as part of User Profile after end-user authentication.

In Jabber 12.7 and earlier with this Unified CM release or later, we can't use these credentials from the Service Profile as we did before. They pass an encrypted password to Active Directory which causes a connection failure. For these Jabber releases with the upgraded Unified CM, provide the LDAP credentials through the jabber-config.xml file.

For more details, see the *Release Notes for Cisco Unified Communications Manager and the IM and Presence Service, Release 12.5(1) SU2* and the section on LDAP Service Accounts in the *Planning Guide for Cisco Jabber*.

Limit of 450 Participants in a CMS Meeting

You can have a maximum of 450 people in a single CMS meeting.

Location Feature and Multiple Domain Support

Consider the following deployment scenario:

When you deployed your Cisco Unified Communications Manager IM and Presence Service node, all users were imported with single domain support. You later changed the address scheme to Directory URI (multiple domain support).

The location feature now doesn't work for newly added domain users. Users in the initial domain are unaffected. CSCuu63734 documents this limitation.

Logitech Keyboard Display Changes

The built-in display for Logitech UC keyboard K725-C doesn't display caller or device information on incoming calls. Instead, the Cisco logo is displayed.

Meeting Reminders

Cisco Jabber displays pop-up reminders for Cisco Webex meetings only. Reminders for non-Cisco Webex meetings are not displayed.

If the URL for a Webex meeting is changed (for example, by URL filter software), attempts to join the meeting from the meeting reminder or from the Meetings tab fail. This behavior is documented in CSCux03658.

Microsoft Outlook Local Contacts and Presence

Users' presence is unknown when the contact is manually added to contacts in Microsoft Outlook 2010 and 2013, when the contact is added to local (custom) contacts with an email address type of SMTP. To resolve this issue, delete the contact and add it again manually, ensuring the email address type is Exchange (EX). CSCuo57172 documents this limitation.

Microsoft Outlook OST File

Intermittently Cisco Jabber for Windows is unable to access the Microsoft Outlook OST file. To resolve this issue, restart Jabber and restart Outlook.

Multiline

Cisco Jabber can't make calls from any line, while there's an incoming call ringing on another line. While another line is ringing, the green **Call** button is dimmed and not available. Users can wait for the ringing to stop, or decline the incoming call.

168 Byte Limit for Transferred Filenames

When transferring a file, the filename cannot exceed 168 bytes (including extension). If you attempt to send a file with a longer name, you are notified that you have exceeded 168 bytes.

Phone Mode Deployments with Microsoft Lync

Disable Click-to-x functionality if you want to deploy Cisco Jabber for Windows in phone mode on the same computer as Microsoft Lync. See the *Common Installation Arguments* section of the *Deployment Guide* for more information about the CLICK2X installer switch.

Plantronics Accessories and Software

If you use Plantronics accessories for Cisco Jabber call management, and if you have Plantronics Hub installed, ensure that at least version 3.5 is installed. Download Plantronics Hub 3.5 from the Plantronics website.

Presence indicators on Sharepoint 2016

When you sign-out of Jabber, the presence indicator bubbles are grayed out and do not refresh after signing back into Jabber.

You can resolve this behavior by refreshing the webpage. This will ensure that accurate presence information is displayed.

Real-Time Transport Control Protocol (RTCP)

Jabber sends RTCP packets even when disabled. RTCP is an integral component of Jabber Telephony services.

Remote Desktop Control over Mobile and Remote Access

Remote desktop control over Mobile and Remote Access isn't supported. This limitation is documented in CSCuz19139.

Removing Participants During Conference Calls

Users can only remove participants from a conference call when using a softphone (CSF) device for calls in a non-VDI deployment. Users can't remove participants from conference calls in desk phone control mode or using extend and connect.

SAML Single Sign-On Limitations

When configuring SAML SSO on Cisco Unified Communications Manager servers, use a fully qualified domain name (FQDN) instead of an IP Address to define the server name. If you use an IP Address, the client displays a warning message that the certificate isn't valid. The requirement to use an FQDN is because the

embedded Internet Explorer browser isn't able to validate IP addresses in the **Subject Alternate Name (SAN)** certificate.

For the same reason, when you configure SAML SSO on Cisco Unity Connection servers, use a fully qualified domain name (FQDN) in Cisco Unified Communications Manager Service Profile instead of an IP Address to define the server name. If you use an IP Address, the client displays a warning message that the certificate isn't valid.

Schedule Meeting Button Disabled on Phone-Only Mode

When Outlook is installed, and the MacCalendarIntegrationType parameter is set to Outlook, the **Schedule Meeting** button is displayed. However in phone-only mode, the button is not shown.

Single Number Reach

For Cisco TelePresence Video Communication Server Control (VCS) versions earlier than 8.10.X, configure the editable inbound rules to enable the single number reach for users who are using Cisco Jabber over Mobile and Remote Access. For more information, see *Limitations in Enable Single Number Reach* section from the *Feature Configuration Guide for Cisco Jabber 12.0*.

Space Characters in Credentials

The following rules apply to space characters and credentials:

- Usernames can contain spaces in on-premises deployments.
The first and last characters of usernames in on-premises deployments can't be spaces. This rule is also true for usernames synchronized from a directory source.
- Usernames can't contain spaces in cloud-based deployments.
- Passwords can't contain spaces in any deployment scenario.

Standard CTI Secure Connection User Group

Cisco Jabber for Windows doesn't currently support CTI connections over transport layer security (TLS). As a result, Cisco Jabber for Windows users can't switch from using a CSF device to using a desk phone device if they belong to the Standard CTI Secure Connection user group. This limitation is documented in CSCux83786.

Supported Characters in a Cisco Jabber User ID/E-mail Address

The following characters are supported in a Cisco Jabber user ID/E-mail Address:

- Uppercase (A to Z) and lowercase (a to z) characters
- Numbers (0-9)
- Period (.)
- Hyphen (-)
- Underscore (_)
- Tilde (~)

TIFF Images Not Supported

In this release, if users have a .tiff image as their avatar, then Jabber displays the default icon image instead. To use a personal avatar, users must upload an image in a supported format, such as jpg, bmp, or png.

Using Click-To-X Feature with Contacts in Microsoft Outlook

If you use UDS as a directory source, users can only use Click-To-X capabilities, such as Click-To-Call and Click-To-IM, to contact Microsoft Outlook users if they are already in the cache file. A cache file is created for someone if they are in the users' Cisco Jabber contacts list, or have a Cisco Jabber history created by the user previously searching, IMing, or calling them, or by leaving a voice message.

Video Calls

The **Start My Video** button doesn't work immediately after a call connects. Users must wait approximately 6 seconds after the call starts before clicking the **Start My Video** button. This behavior is documented in CSCuz06415.

Voicemail Credential Popup during Sign-in

In a hybrid deployment, if Webex messenger, Call Manager and Unity connection are all SSO enabled, and voicemail credentials have been previously saved to cloud, users may see the **Update Credentials** popup for voicemail during the sign-in process. The workaround is not to configure voicemail server address on the cloud server but only configure it in the service profile or the `jabber-config.xml` file.

Windows 10 Crash Using Cisco 700 Series Headsets

If you use Cisco 700 Series headsets, you might experience Windows OS crashes (Blue screen). This occurs on Windows 10 version 1803 and earlier versions. Update to a later version of Windows 10 to correct the problem.

Limitations for On-Premise Deployments

These limitations apply to Jabber for Windows on-premises deployments.

Adding Federated Contacts

When adding federated contacts, Cisco recommends that users add the federated contacts as company contacts (**File > New > Contact**), rather than as custom contacts. Adding federated contacts as custom contacts can cause intermittent presence issues. This issue is documented in CSCuz59060.

Creating and Configuring Devices for Users in Cisco Unified Communications Manager 11.0

If you are creating devices for users in Cisco Unified Communications Manager 11.0, you can now specify a key order as **RSA Only**, **EC Only** or **EC Preferred, RSA Backup**. However, the **EC Only** option is not currently supported by Cisco Jabber, and if you select it, the client will fail to connect to the server.

Multiple Resource Login

When a user signs in to multiple instances of the client at the same time, the chat feature behaves as follows in on-premises deployments (more on multiple resource login in Common Deployment Scenarios):

- Signing in on one client changes custom availability states to 'Available' on other clients.

- If you set the availability state from 'On a call' to another state while on a call, the availability state does not automatically change to 'On a call' for subsequent calls.

SIP Trunk for Phone Presence

From Release 11.5(3), you must configure a SIP trunk between Cisco Unified Communications Manager and IM and Presence Service if you want Cisco Jabber users to see phone presence. In previous releases, a SIP trunk was not required for phone presence. This limitation is documented in CSCuz85578.

Port Contention Disrupts Sennheiser Plug-In

Call control with the Sennheiser plug-in uses port 8001 by default. If another application uses this port, it can cause issues.

As a workaround, you can change the EPOS SDK's PortNumber parameter to another port in the appropriate file:

- Windows—%LOCALAPPDATA%\Sennheiser\SDKCore\PDS\config.dat
- Mac—/Library/Application Support/Sennheiser/SenncomSDK/secomSFSDK.dat



Note Consult Sennheiser for more information about these files.

Shut down Jabber before changing the port in the SDK. Then, restart Jabber after you change the port.

Limitations for Cloud Deployments

These limitations apply to Jabber for Windows on Webex Messenger and Team Messaging Mode deployments.

Blocking Users in Enterprise Groups

Blocking users does not prevent a blocked user's status from being displayed if the blocked users are in a contact list as part of an enterprise group. For example, User A blocks User B. However, User A is in User B's contact list as part of an enterprise group. As a result, User B can view User A's availability status.

Invitees to Instant Webex Meetings

Invitees to instant Webex meetings must be provisioned with Webex accounts before they can join an instant Webex meeting. For example, User A has a Webex account and starts an instant Webex meeting from Cisco Jabber. User A then invites User B, who does not have a Webex account, to the meeting. When User B clicks on the meeting link in Cisco Jabber, an error message is displayed and the user can't join the meeting. User B must be provisioned with a Webex account before attempting to join any instant Webex meetings. This limitation is documented in CSCux52068.

Jabber to Jabber Calls

We recommend running Internet Explorer 10 or greater while using the Jabber to Jabber calling feature. Using this feature with previous versions of Internet Explorer or with Internet Explorer in Compatibility Mode can cause issues with Cisco Jabber client login (non-SSO setup) or Jabber to Jabber calling capability (SSO setup).

Users in Common Identity

There is a known issue with signing into Cisco Jabber for some users who have migrated to Common Identity. If users receive an *Incorrect user name or password* error message when entering their credentials, see the following article, <https://help.webex.com/en-us/yhq7pw/Reset-Forgotten-Password-in-Cisco-Jabber>.

Cisco Jabber for Mac

These are the limitations that apply to the Jabber for Mac client.

Limitations for All Deployments

These limitations apply to all Jabber for Mac deployments.

Chat Behavior During Transition to MRA

Jabber loses chat messages that are sent while the Jabber client is transitioning from an on-premises network connection to an MRA network connection, or vice versa. Users receive an error message when they try to send chat messages during this transition period.

Limit of 450 Participants in a CMS Meeting

You can have a maximum of 450 people in a single CMS meeting.

New Certificate Requirements for macOS 10.15

Apple has new requirements for trusted certificates in macOS 10.15 (see <https://support.apple.com/en-us/HT210176>). Ensure that the certificates on the Unified Communications Manager, IM & Presence, and Expressway servers meet these requirements. If your certificates don't meet these requirements, users are prompted to accept the certificates for each session.

Webex Site Disclaimers

Webex site disclaimers don't appear when you join Webex meetings from Jabber. This limitation applies whether joining from the meeting reminder popup, or by selecting **Join in Webex** in Jabber.

Single Number Reach

For Cisco TelePresence Video Communication Server Control (VCS) versions earlier than 8.10.X, configure the editable inbound rules to enable the single number reach for users who are using Cisco Jabber over Mobile and Remote Access. For more information, see *Limitations in Enable Single Number Reach* section from the *Feature Configuration Guide for Cisco Jabber 12.0*.

Save Chats to Outlook

When you use Outlook 2016, Outlook won't save images that are sent in chats. However, Outlook does save any emoji in the chats.

Audio Device Setting After Upgrade

When users upgrade the client, it can intermittently result in a reset of their selected audio devices. To resolve this issue, set the audio devices in the **Audio/Video Preferences** window. CSCva48136 documents this limitation.

Antivirus

When the client connects to Cisco Unity Connection on a device that has antivirus software, users can have issues with voicemail connections. To resolve this issue, add the Cisco Unity Connection server information to the exceptions list for the antivirus software.

Users in Common Identity

There's a known issue signing into Cisco Jabber for some users who have migrated to Common Identity. If users receive an *Incorrect username or password* error message when entering their username and password, see the following knowledge base article https://cisco-support.webex.com/guest/articles/en_US/Troubleshooting/WBX000019555/myr=false.

Creating and Configuring Devices for Users in Cisco Unified Communications Manager 11.0

If you're creating devices for users in Cisco Unified Communications Manager 11.0, you can now specify a key order as either:

- **RSA Only**
- **EC Only**
- **EC Preferred, RSA Backup**

However, Cisco Jabber doesn't support the **EC Only** option. If you select it, the client fails to connect to the server.

Certificate Validation for CTI Connections

Cisco Jabber uses certificate validation for CTI connections. We recommend using either Public CA or Private CA to sign certificates.

Connecting to Cisco Unified Communications Manager using a self-signed certificate, results in a certificate validation failure, to resolve this issue do one of the following:

- The user accepts the invalid Cisco Unified Communications Manager self-signed certificate on first certificate validation failure and Cisco Jabber saves this certificate to the trust store.
- Deploy the certificates using a certificate deployment management application.

Expressway for Mobile and Remote Access Deployment

For an Expressway for Mobile and Remote Access deployment, when using an online certificate status protocol (OCSP) or online certificate revocation lists (CRL) to verify certificate status, Cisco Jabber expects a response time of less than 5 seconds. Connections fail if the response time is greater than the 5 seconds.

Network Disconnection When Using Cisco Jabber on Audio or Video Call

There's a known issue in the Mac OS where network interfaces drop intermittently when DSCP is enabled.

If you encounter this issue, do the following:

1. Select **Preferences > Calls > Advanced**.
2. Uncheck **Enable Differentiated Service for Calls**.

Standard CTI Secure Connection User Group

Cisco Jabber for Mac doesn't currently support CTI connections over transport layer security (TLS). As a result, Cisco Jabber for Mac users can't switch from using a CSF device to using a desk phone device if they belong to the Standard CTI Secure Connection user group.

Contact Resolution for Enterprise Groups

Jabber resolves contacts in enterprise groups individually rather than all at once. When you add an enterprise group to your users' contact lists or they clear their local cache, they originally only see each person's username and domain. More information appears when they next hover over or interact with a person.

Bluetooth Connectivity Unsupported with Cisco Headset 56x

Cisco Jabber doesn't support the use of Bluetooth with Model 56x Cisco headsets. You can use these headsets with a USB-C to USB connector cable.

Poly Headset Plug-in Removed

Cisco Jabber for Mac 12.8 removed the Poly headset plug-in. The plug-in caused a monitor keyboard input alert on macOS 10.15. Without the plug-in, we can't support call controls (answer, decline, hold, and resume) on the headsets.

When there's a fix for the plug-in, we'll add it back into Jabber.

Windows 10 Crash Using Cisco 700 Series Headsets

If you use Cisco 700 Series headsets, you might experience Windows OS crashes (Blue screen). This occurs on Windows 10 version 1803 and earlier versions. Update to a later version of Windows 10 to correct the problem.

Joining Meetings by Meeting Number

In deployments that use a Cisco Webex Meeting Server, you cannot use the meeting number when joining by Webex. Use the meeting URL instead.

168 Byte Limit for Transferred Filenames

When transferring a file, the filename cannot exceed 168 bytes (including extension). If you attempt to send a file with a longer name, you are notified that you have exceeded 168 bytes.

Limitations for On-Premise Deployments

These limitations apply to Jabber for Mac on-premises deployments.

Port Contention Disrupts Sennheiser Plug-In

Call control with the Sennheiser plug-in uses port 8001 by default. If another application uses this port, it can cause issues.

As a workaround, you can change the EPOS SDK's PortNumber parameter to another port in the appropriate file:

- Windows—%LOCALAPPDATA%\Sennheiser\SDKCore\PDS\config.dat
- Mac—/Library/Application Support/Sennheiser/SenncomSDK/secomSFSDK.dat



Note Consult Sennheiser for more information about these files.

Shut down Jabber before changing the port in the SDK. Then, restart Jabber after you change the port.

Cisco Jabber for Android

These are the limitations that apply to the Jabber for Android client.

Limitations for All Deployments

These limitations apply to all Jabber for Android deployments.

Jabber for Android does not Receive Location Information

Device location information is not shared while the application is running in background.

Chat Behavior During Transition to MRA

Jabber loses chat messages that are sent while the Jabber client is transitioning from an on-premises network connection to an MRA network connection, or vice versa. Users receive an error message when they try to send chat messages during this transition period.

Limit of 450 Participants in a CMS Meeting

You can have a maximum of 450 people in a single CMS meeting.

Jabber for Android Doesn't Start with the OS

As of Release 12.7, Jabber for Android doesn't support automatically starting with the OS.

Webex Site Disclaimers Don't Appear When Joining Meetings

Webex site disclaimers don't appear when you join Webex meetings from Jabber. This limitation applies whether joining from the meeting reminder popup, or by selecting **Join in Webex** in Jabber.

Video Calls Don't Start if Chromebook Camera Is Already in Use

If another app is using the camera, Jabber for Android can't start video calls from your Chromebook.

Voicemail Server Might Not Display URI of Missed Call

Because of a limitation of Cisco Unity Connection, the voicemail server can't display the URI for a missed call. This issue occurs when you decline an incoming Cisco Jabber call from a URI and the call diverts to voicemail. If the contact information for the caller contains only a URI, the voicemail server displays the caller as Unknown. If the contact information contains a URI and a directory number, the voicemail server displays the directory number for that contact.

Music Apps Keep Playing When You Start Video Call

When you play music with a third-party application, the music doesn't automatically pause when you make or receive a Cisco Jabber for Android video call. To work around this issue, you can open the third-party application to pause and resume the music.

Audio Issues on Calls over MRA

If you make a Cisco Jabber for Android call using Expressway for Mobile and Remote Access over a 2G, 3G, or 4G network, you may experience audio quality issues from network instability.

Conflicts with Cisco AnyConnect and SafeNet MobilePASS

If you use Cisco AnyConnect Secure Mobility Client, MobilePASS one-time password generator from SafeNet, and Cisco Jabber for Android on the same device, you may experience problems due to compatibility issues between these applications. For example, during a Cisco Jabber for Android call, you may hear no audio or one-way audio, or you may experience delays if you transfer the call.

Contact Resolution for Enterprise Groups

Jabber resolves contacts in enterprise groups individually, not all at once. So, when you add an enterprise group to your users' contact lists—or if they clear their local cache—they see only the username and domain for each person until they hover over or interact with that contact.

Creating and Configuring Devices for Users in Cisco Unified Communications Manager 11.0

If you're creating devices for users in Cisco Unified Communications Manager 11.0, you can specify a key order:

- RSA Only
- EC Only
- EC Preferred
- RSA Backup

However, Jabber doesn't support the EC Only option, and if you select it, the client fails to connect to the server.

Network Reconnection in a MRA Non-SSO Environment

In a Mobile and Remote Access non-SSO environment, when Jabber loses its connection to the Cisco VCS Expressway server, there's an interval of 120 seconds between sending connection requests. This interval prevents multiple requests to the server from multiple clients. During this 120-seconds interval, even if your network connection is active, Jabber remains inactive.

Samsung Unmonitored App List

When you install Jabber for the first time, Samsung devices automatically put Jabber in the unmonitored apps list. The device doesn't put unmonitored apps to sleep while they run in the background. However, if you upgrade your Samsung OS from a version without unmonitored apps list, you have to add Jabber to the unmonitored apps list manually.

Cisco TelePresence Video Communication Server Control Earlier than 8.10

For Cisco TelePresence Video Communication Server Control (VCS) versions earlier than 8.10.X, configure the editable inbound rules to enable the single number reach for users who are using Cisco Jabber over Mobile and Remote Access. For more information, see the limitations in the "Enable Single Number Reach" section of the *Feature Configuration Guide for Cisco Jabber*.

Sign-In Issues with Jabber in SSO Mode

If your users have issues with signing into Cisco Jabber in SSO mode, they can upgrade Android System WebView and Chrome browser to resolve the issue. Users can upgrade Android System WebView and Chrome browser from Google Play Store.

HTTP Basic SAML SSO Authentication

Sign in might fail when switching users with the **Reset Jabber** option. Reset Cisco Jabber, quit the application fully in the Android OS, and try again.

Issues with tel:// URI Feature

Because of the large number of third-party applications that support the tel:// URI feature, we can't guarantee interoperability of this feature on all third-party applications. In some third-party applications, this feature allows you to click a tel:// link and select Cisco Jabber for Android to call.

168 Byte Limit for Transferred Filenames

When transferring a file, the filename cannot exceed 168 bytes (including extension). If you attempt to send a file with a longer name, you are notified that you have exceeded 168 bytes.

SRST Not Supported From Release 10.6

Security Survivable Remote Site Telephony (SRST) is not supported in Cisco Jabber for Android Release 10.6 or later.

Connection Issues With Invalid Certificates

With the Cisco Unified Communications Manager 11.0 and later, not accepting invalid certificates quickly can cause issues with your server connections. If you don't accept an invalid certificate when prompted in 10 seconds, for some HTTPS connections, you might have issues, such as, inability to download some configuration or inability to connect to the phone service or the voicemail.

Android Webview Impact on Jabber in SSO Mode

For users with an SSO account, Jabber stops working if the Android Webview is reset, upgraded, or restarted.

Compression of Transferred Files

During file transfer, only files with JPEG file format are compressed.

MRA and WebEx Meetings with siteType "Orion"

If the meeting siteType is "ORION", then Jabber mobile clients can't start WebEx Meeting over Expressway for Mobile and Remote Access network.

Auto Authentication Not Supported from 12.7

Auto authentication at startup is no longer supported from Release 12.7.

Wi-Fi Turned Off When Answering Call

Jabber turns off Wi-Fi when you answer a call on cellular network to avoid call drops.

Limitations for Cloud Deployments

These limitations apply to all Jabber for Android on Webex Messenger and Team Messaging Mode deployments.

Team Messaging Mode Doesn't Support Android Wear Devices

Jabber team messaging mode doesn't support notifications on Android Wear devices.

Cisco Jabber for iPhone and iPad

These are the limitations that apply to the Jabber for iPhone and iPad client.

Limitations for All Deployments

These limitations apply to all Jabber for iPhone and iPad deployments.

Chat Behavior During Transition to MRA

Jabber loses chat messages that are sent while the Jabber client is transitioning from an on-premises network connection to an MRA network connection, or vice versa. Users receive an error message when they try to send chat messages during this transition period.

Limit of 450 Participants in a CMS Meeting

You can have a maximum of 450 people in a single CMS meeting.

New Apple Certificate Requirements for iOS 13

Apple has new requirements for trusted certificates in iOS 13 (see <https://support.apple.com/en-us/HT210176>). Ensure that the certificates on the Unified Communications Manager (Unified CM), IM & Presence, and Expressway servers meet these requirements. If your certificates don't meet these requirements, Jabber prompts users to accept the certificates for each session.

Webex Site Disclaimers Don't Show When Joining From Jabber

Webex site disclaimers don't appear when you join Webex meetings from Jabber. This limitation applies whether joining from the meeting reminder popup, or by selecting **Join in Webex** in Jabber.

Audio Issues with MRA over 2G, 3G, and 4G Networks

If you make a Cisco Jabber for iPhone and iPad call using Expressway for Mobile and Remote Access over a 2G, 3G, or 4G network, you may experience audio quality issues from network instability.

Single Number Reach with MRA on TelePresence Video Communication Server Control

Applies to Cisco TelePresence Video Communication Server Control (VCS) versions earlier than 8.10.X.

Configure the editable inbound rules to enable single number reach for users who use Cisco Jabber over Mobile and Remote Access. For more information, see *Limitations* in *Enable Single Number Reach* section from the *Feature Configuration Guide for Cisco Jabber 12.0*.

Favorite Icon Doesn't Show with Phone-Only Accounts

Cisco Jabber for mobile clients don't show the **Favorite** icon for users with Phone Only account.

Apple Push Notifications Required with Jabber

Without Apple Push Notifications (APNs), iOS doesn't wake Cisco Jabber when Jabber receives an incoming call or chat. The call or instant message appears on the device after several minutes or when you bring Cisco Jabber the foreground. As a workaround, reset the network settings for your iOS device by going to **Settings > General > Reset > Reset Network Settings**.

Editing Phone Services Servers

Users can no longer edit their Phone Services servers manually, except when they are in hybrid cloud mode. In hybrid deployments, administrators can configure the Phone Services servers to be editable.

Certificate Installation for Secure Phone Feature

To enable the Secure Phone functionality properly, use it first on your corporate network or VPN to ensure proper certificate installation.

Voice Recognition of Voicemail PIN

Voice recognition for voicemail PIN is highly sensitive to background noise. The system may interpret background noise as user input, even when the user doesn't input anything. See *System Administration Guide for Cisco Unity Connection* to disable this function:

<https://www.cisco.com/c/en/us/support/unified-communications/unity-connection/products-maintenance-guides-list.html>

Don't Use Intermediate Certificate Authorities with Unified CM

Certificate validation windows you use a certificate from an intermediate certificate authority on Unified CM. Use a certificate that is signed with the root, rather than an intermediate certificate authority.

Jabber Account-Related Files Aren't Backed Up on iCloud and iTunes

From Release 10.5 onward, all the Cisco Jabber account-related files aren't backed up on the iCloud and iTunes due to privacy reasons. This restriction includes files such as the Configuration, Contacts, Credentials, History, Logs, and Photo.

Don't Use "EC Only" Key Order when Configuring Devices in Unified CM

When you create devices for users in Unified CM 11.0, you can specify a key order as RSA Only, EC Only, EC Preferred, or RSA Backup. However, Jabber doesn't support the EC Only option. If you select it, the client fails to connect to the server.

Jabber Might Reconnect Slowly When a Device Moves Between Networks

When you move between networks, for example, from WiFi to 3G, with Jabber in the background, the client disconnects from the servers. The client might not reconnect for several minutes which can lead to missed calls. To avoid missed calls, enable the Apple Push Notification service.

CallKit Unavailable in China

CallKit functionality is deactivated in China due to government regulations.

MRA and WebEx Meetings with siteType "Orion"

If the meeting siteType is "ORION", then Jabber mobile clients can't start WebEx Meeting over Expressway for Mobile and Remote Access network.

Use Single Number Reach on iOS for Maximum Reliability

If your users require 100% reliability in call notifications, enable the Single Number Reach (SNR) feature for Cisco Jabber running on iOS. SNR mitigates these limitations:

- iOS may shut down Cisco Jabber and other applications that are running in the background to preserve resources. While the client attempts to relaunch, you might miss calls. To minimize the impact, enable Apple Push Notification service.
- Without Apple Push Notifications (APNs), the device sometimes switches connection from the Wi-Fi data network to the mobile voice network while the device is in Sleep mode. You might miss incoming calls due to this issue. To prevent this issue, go to the iPhone Settings and turn off **Cellular Data** or alternatively turn on **SNR**.
- The VPN can disconnect when Connect-On-Demand is enabled and the user changes networks. Cisco Jabber for iPhone and iPad may take up to 11 minutes to reconnect through the VPN. This issue can lead to missing incoming calls. This occurs when the Wi-Fi signal is not stable or sometimes the mobile network takes priority and it switches between Wi-Fi and mobile network, while Jabber is unable to quickly connect to phone services during the handover. After the client reconnects, users who have voicemail enabled receive voicemail notifications for any missed calls that went to voicemail. To minimize the time to reconnect, users can bring the app to the foreground after changing connection environments. To minimize the impact, enable Apple Push Notification service.

Dial via Office - Reverse (DVO-R) on iOS

If you are setting up Dial via Office - Reverse (DVO-R) on Unified CM consider the following:

- The feature only applies to iPhone; it is not supported on iPad or iPod Touch devices because it requires that the device can access a mobile network.
- The feature requires Unified CM Release 8.6.2 SU4, 9.1.2, or 10.x.
- You can make DvO-R calls over Expressway for Mobile and Remote Access when you are outside corporate network. DVO-R is supported over Cisco Expressway X8.7 and Unified CM 11.0(1a)SU1.
- DVO enabled devices may encounter issues registering with Unified CM 8.6 and above. Resetting the device from the Unified CM administrative interface fixes this issue.
- You can't use the feature with the Secure Call feature. Secure calls can't be established if DVO-R is enabled.
- If the user places a DVO-R call to an invalid phone number over a SIP trunk, a Unified CM limitation causes the user to hear several seconds of silence, instead of an audio message that the number was invalid.

iPhone—CM Node Failover Issue with Packet Loss

If Cisco Jabber on iPhone is unable to reach the primary subscriber due to packet loss, it does not failover to secondary CM node. For more information, see [CSCux83785](#).

iPhone—Incoming Mobile Call Places Unified CM Call on Hold

If the user is on a Unified CM call and receives an incoming mobile call, iPhone starts ringing and prompts the user to answer or decline the mobile call. At the same time, the Unified CM call on Cisco Jabber goes on hold automatically.

When you receive an incoming call on your iPhone, the iPhone automatically disables the microphone for all other applications. There is no time to inform your current caller that you need to take another call. If you accept the new incoming call, your Unified CM call in Jabber is automatically placed on hold, and you can't return to it until you end the iPhone call. To work around this issue, decline the call and then tap **Resume** so that your current caller can hear you again. If your device is locked, quickly press the **On/Off Sleep/Wake** button twice to decline the call, and then tap **Resume**.

iPhone—Turn on Jabber Sound Settings

To ensure that you do not miss incoming Cisco Jabber chats and calls, go to **iOS Settings > Notification Center** and check that the Cisco Jabber sound setting is turned on.

iPhone—Incoming Unified CM Calls Sent to Voicemail While on VoIP Call

If you receive a Unified CM call, while placing a VoIP call, the client sends the incoming call to voicemail. If you do not have voicemail, Jabber ignores the call.

iPhone—Maximum Participants for Ad-hoc Conference

The maximum number of participants for ad-hoc conferences is limited to three; this is the maximum number of calls for TCT devices. You can configure the maximum participants for ad-hoc conference on Unified CM in **Service Parameter Configuration > Clusterwide Parameters > Maximum Ad Hoc Conference Required**.

iPhone—Quality Issues on Some Connections

Voice and video quality over non-corporate Wi-Fi or mobile data networks can't be guaranteed.

The quality of video calls varies depending on the network connection. Cisco Technical Assistance Center (TAC) can't troubleshoot video quality when you use 3G or 4G networks to connect Cisco Jabber for iPhone and iPad with Cisco AnyConnect Secure Mobility Client or another VPN client.

iPhone—SIP Digest Authentication

SIP Digest Authentication is not supported.

iPhone—Device Capacity of Unified CM as a Directory Source

Unified CM as a directory source is capable of scaling to 50% of the device capacity that a Unified CM node can handle.

iPhone—Call Notification When Device Is Locked

When the device is in Do Not Disturb (DND) mode and locked, it vibrates upon receiving a Cisco Jabber call.

iPhone—Jabber Relaunches After Hours in Background

When in the background for a few hours, Jabber relaunches without notification.

Apple Watch—No Call Notifications

With iOS versions 10 and 11 with Cisco Jabber 12.0, you can't receive call notifications on Apple Watch because CallKit can't work with Apple Watch. This is an Apple iOS limitation.

iPad—Inaccurate Status During Network Transitions

When users transition between networks, their availability status may not be accurate.

Jabber With Cisco TelePresence System

Cisco Jabber for iPhone and iPad supports interoperability and optimal video quality with Cisco TelePresence System (CTS) devices if you use a TelePresence or video bridge to connect the devices. The number of devices that you can use for joining a video call will be determined by the Multipoint Control Unit (MCU) and settings defined for the conference bridge.

Required versions and settings for CTS interoperability
VCS call control environment: All CTS devices must be using 1.9.1(68) or a later firmware version.
Unified CM call control environment: <ul style="list-style-type: none"> • All CTS devices must be using 1.9.1(68) or a later firmware version. • Create Media Regions for iPad and CTS by following these steps: <ol style="list-style-type: none"> 1. Provision two media regions with the first region for CTS using a maximum video call bit rate of 32000 Kbps and second region for iPad using a maximum video call bit rate of 768 Kbps. 2. Create a region relationship from the CTS region to the iPad region, described in step 1, using a maximum video call bit rate of 512 Kbps.

- All CTS devices must be using 1.9.1(68) or a later firmware version.

- Create Media Regions for iPad and CTS by following these steps:

1. Provision two media regions with the first region for CTS using a maximum video call bit rate of 32000 Kbps and second region for iPad using a maximum video call bit rate of 768 Kbps.
2. Create a region relationship from the CTS region to the iPad region, described in step 1, using a maximum video call bit rate of 512 Kbps.

Required versions and settings for CTS interoperability

To verify your VCS firmware and hardware codec versions, check the Device information screen in the Cisco TelePresence System Administration.

Consult the Unified CM Administration documentation for details about setup.

iPad—Blocking and Deleting Contacts

You cannot block contacts who are within your own organization.

If you delete a group of contacts on a device other than an iPad, you might not see the change immediately in Cisco Jabber for iPhone and iPad. Sign out and then sign in again for the changes to take effect.

iPad—Don't Send Jabber to the Background Before the Current Operation Completes

If you start an action, such as signing in or tapping **Webex Meeting** to start a meeting, and then bring Cisco Jabber for iPhone and iPad to the background before the action completes, you can't successfully complete the action.

iPad—Starting Webex Meetings

If you tap **Webex Meeting** to start a meeting, the system sends a meeting invitation when either the meeting starts or 60 seconds has elapsed.

iPad—Recording Indicator Mistakenly Comes On When Jabber Put In the Background

When on a Cisco Jabber call and you put Cisco Jabber to the background, sometimes the call indicator shows Cisco Jabber recording, depending on the iOS versions.

Multiple Resource Login

When a user signs in to multiple instances of the client at the same time, the chat feature behaves as follows:

- The first incoming chat message is sent to all the clients.
- The first client to reply to the incoming chat message gets all the subsequent messages. The other clients do not get these subsequent incoming messages.
- If the client does not use the chat feature for 5 minutes, the next incoming message is sent to all the clients again.

Contact Resolution for Enterprise Groups

Jabber resolves contacts in enterprise groups individually rather than all at once. As a result, when you add an enterprise group to your users' contact lists—or if they clear their local cache—they'll only see the username and domain for each person until they hover over or interact with them.

168 Byte Limit for Transferred Filenames

When transferring a file, the filename cannot exceed 168 bytes (including extension). If you attempt to send a file with a longer name, you are notified that you have exceeded 168 bytes.

Limitations for Cloud Deployments

These limitations apply to all Jabber for iPhone and iPad on Webex Messenger and Team Messaging Mode deployments.

Apple Watch—Notifications Aren't Supported in TMM

Notifications aren't supported on Apple Watch in Jabber Team Messaging Mode (TMM).



CHAPTER 3

Search for Bugs

To search for bugs not listed here, use the Bug Search Tool.

Procedure

- Step 1** To access the Bug Search Tool, go to <https://tools.cisco.com/bugsearch/search>.
- Step 2** Sign in with your Cisco.com user ID and password.
- Step 3** To look for information about a specific problem, enter the bug ID number in the **Search for** field, then press **Enter**. Alternatively, you can search by product and release.
- For more information, select **Help** at the top right of the Bug Search page.
-

- [Bug Severity Levels, on page 31](#)
- [Cisco Jabber for Windows, on page 32](#)
- [Cisco Jabber for Mac, on page 35](#)
- [Cisco Jabber for Android, on page 36](#)
- [Cisco Jabber for iPhone and iPad, on page 37](#)
- [Cisco Jabber for Intune, on page 38](#)
- [Cisco Jabber for BlackBerry, on page 38](#)

Bug Severity Levels

Known defects, or bugs, have a severity level that indicates the priority of the defect. These release notes include the following bug types:

- All severity level 1 or 2 bugs
- Significant severity level 3 bugs
- All customer-found bugs except severity level 6 enhancement requests

Severity Level	Description
1 Catastrophic	Reasonably common circumstances cause the entire system to fail, or a major subsystem to stop working, or disrupts other devices on the network. No workarounds exist.

Severity Level	Description
2 Severe	Important functions are unusable and workarounds don't exist. Other functions and the rest of the network is operating normally.
3 Moderate	Failures occur in unusual circumstances, or minor features don't work at all, or failures have low-impact workarounds. This severity is the highest level for documentation bugs.
4 Minor	Failures occur under unusual circumstances, but operation essentially recovers without intervention. Users don't need to install any workarounds and performance impact is tolerable.
5 Cosmetic	Defects don't cause any detrimental effect on system functionality.
6 Enhancement	Requests for new functionality or feature improvements.

Cisco Jabber for Windows

Resolved Caveats in Release 14.0(5)

Identifier	Severity	Headline
CSCwc24382	3	Cisco Jabber Security Vulnerability: XMPP Stanza Smuggling with stream:stream tag

Resolved Caveats in Release 14.0(4)

Identifier	Severity	Headline
CSCvy40988	2	Audiostream stops all of a sudden on Jabber
CSCvz15243	3	Jabber Privacy setting Issue
CSCvz83356	3	Jabber Client sends same client type value for both Desktop and Android tab devices
CSCwa41980	3	Unable to select "Start Video" button during Jabber deskphone video call with 88xx phones
CSCvw43701	5	Jabber 12.9(2) typo on German under Settings > Audio

Resolved Caveats in Release 14.0(3)

Identifier	Severity	Headline
CSCvy68527	3	Jabber crashes when call is answered invalid Class Pointer Read for JabraJabberPlugin.dll.
CSCvz36316	3	Call recording is failing causing the call to drop

Identifier	Severity	Headline
CSCvz63831	3	J4W: Jabber client dumps JSON string to chat window upon submitting interactive form in Jabber bot

Resolved Caveats in Release 14.0(2)

Identifier	Severity	Headline
CSCvy76326	2	Jabber one way audio issue on JFW
CSCvy32909	3	Jabber still creates Proximity thread when Proximity Feature is disabled
CSCvy55728	3	Jabber Crash on initial login after a PC reboot
CSCvy58598	3	Jabber 14 for Windows Randomly Crashes Multiple Times
CSCvy60179	3	Jabber is not resolving calling numbers to names if the number contains \"(\", \"\" and \"\")\" characters
CSCvy60911	3	Jabber 14.0.1 crashes when going to mentions in persistent chat
CSCvy83728	3	UCM Calling - TFTP list is not randomized
CSCvy87870	3	Green Call Button not working on directory search
CSCvy88202	3	Jabber \"Unavailable\" status
CSCvy95249	3	Jabber incorrectly perceive calling number as URI in CTI deskphone mode
CSCvz32450	3	Jabber for Windows requests CTL from CUCM in SIPOAuth mode
CSCvy71604	6	Improve Jabber Contact Search behavior to prevent CUCM CPU spikes
CSCvy83854	6	Jabber - reduce the number of /cucm-uds/version request
CSCvy83911	6	Jabber should randomly sort for tftp servers for load balancing

Open Caveats in Release 14.0(1)

Identifier	Severity	Headline
CSCvy43582	3	UI/UX: Emoji breaks output formatting
CSCvy30570	3	Phone numbers for a chat contact in Jabber are displayed for only two seconds
CSCvy20781	3	Jabber Windows does not retain font changes or change is not reflected in Chat Window
CSCvy15830	3	Jabber should support sessionTicket longer than 512 for Meetings API
CSCvy09500	3	Click \"Organize Meeting\" opens Outlook to organize the meeting, but the contact's email is not copied

Resolved Caveats in Release 14.0(1)

Identifier	Severity	Headline
CSCvx77840	3	Jabber for Windows 12.9.4 crashing on libglib_2_0_0
CSCvx84014	3	Jabber disable CMR meeting control feature by default
CSCvx93726	3	Custom tabs not loading after upgrade to 14.0.0
CSCvx94284	3	Jabber cannot activate session if TLS connection to IM&P server is disabled
CSCvy06023	3	Call Control buttons on Headset not working for jabber 12.9.x or 14.0
CSCvy07190	3	J4W does not wait for credentials input in SSO flow over expressway
CSCvy07349	3	Jabber For Window Fails Encryption for SRTP when FIPS is Enabled
CSCvy14385	3	Jabber BFCP Screen sharing not working during a CMS conference.
CSCvy15265	3	Protocol handlers in custom tab not working when link includes target="_blank". Worked in 12.9
CSCvy27366	3	Jabber 14.0 takes 35+ seconds to reconnect to IM&P after exiting the application
CSCvy30645	3	Jabber4W 14.0.0 cannot answer or disconnect the call by Head set button

Open Caveats in Release 14.0

Identifier	Severity	Headline
CSCvv92950	3	Directory contact search - name displays on the wrong side when using Arabic language
CSCvw16499	3	J4W 12.9 add members to the room now - does not notify invitee
CSCvx30016	3	A Pop-up for directory credential update doesn't show after switching to ldap
CSCvx44185	3	Setting call forward all in softphone mode to unregistered DN results in interface stuck in spinning
CSCvx56203	3	Jabber fails to send 200 OK for INVITES during Call Recording feature
CSCvw25486	4	Contact search for 'Add mention' goes beyond screen

Resolved Caveats in Release 14.0

Identifier	Severity	Headline
CSCvu89112	2	ext/fts3/fts3_snippet.c in SQLite before 3.32.0 has a NULL pointer dereference via a crafted matchinfo() query.

Identifier	Severity	Headline
CSCvu89115	2	In SQLite before 3.32.3 select.c mishandles query-flattener optimization, leading to a multiSelectOrderBy heap overflow because of misuse of transitive properties for constant propagation.
CSCvw16215	2	Bad voice quality when recording is enabled
CSCvw80168	2	Cisco Jabber for Windows Authentication Token Exposure Issue
CSCvs57616	3	[Headset] Mute indicator not appear on Jabber call window when pressing mute button on Jabra Evolve
CSCvu96763	3	Jabber contact photo refresh for all group chat members
CSCvv48257	3	J4W over MRA: both local ringback and remote media are heard if SIP 183 is followed by 180
CSCvv80521	3	Jabber for Windows crashes randomly when minimized
CSCvv85622	3	When uninstalling Jabber it will sometimes not clear its registry keys
CSCvw06691	3	Jabber doesn't clean up registries for C2x when uninstalled
CSCvw22276	3	Cisco Jabber changes Stream ID during small network disconnect
CSCvx23169	3	Jabber not perfectly processing SIP fragment packets
CSCvx29176	3	Jabber is sending queries for SRV records every 60 seconds when it's connected over MRA
CSCvx74361	3	Jabber 12.9.3 cannot start group chat in CMS conference
CSCvx75594	3	Disable Locus CMR Meeting while meeting site is FedRAMP
CSCvv25846	6	Jabber for windows : Recording icon is presented,even if the record-invoker is set to "silent"

Cisco Jabber for Mac

Resolved Caveats in Release 14.0(5)

Identifier	Severity	Headline
CSCwc24382	3	Cisco Jabber Security Vulnerability: XMPP Stanza Smuggling with stream:stream tag

Resolved Caveats in Release 14.0(4)

Identifier	Severity	Headline
CSCvz23903	3	Jabber for Mac/iOS crashes on restarting phone service
CSCvz69778	3	Duplicate characters are detected in the search box from the Jabber chats window with Classic view

Identifier	Severity	Headline
CSCwa11447	3	Jabber for Mac is not showing accurate presence status for users in Outlook
CSCwa56887	3	Jabber MAC 12.9/14 seeing popup "macOS wants to use the "System" keychain" repeatedly via MRA

Caveats in Release 14.0(3)

There are no caveats to report.

Resolved Caveats in Release 14.0(2)

Identifier	Severity	Headline
CSCvy64007	2	One way audio

Resolved Caveats in Release 14.0(1)

Identifier	Severity	Headline
CSCvx76442	3	Jabber for Mac not resolving properly conference participants

Resolved Caveats in Release 14.0

Identifier	Severity	Headline
CSCvr42540	3	"Join in Jabber" does not dial the SIP URI, if the meeting was created in iCal
CSCvt74277	3	ENH: Voicemail credential should be locked in Jabber when Service Profile is set to use IM&P creds
CSCvv82236	4	Unable to read meeting contents in Jabber dark mode appearance setting

Cisco Jabber for Android

Resolved Caveats in Release 14.0(4)

Identifier	Severity	Headline
CSCwa54406	3	Jabber Client sends same client type value for both Desktop and Android tab devices

Resolved Caveats in Release 14.0(3)

Identifier	Severity	Headline
CSCvz49733	3	Jabber for Android has inconsistency in the time format between the contact list and the chat room
CSCvz50553	3	Does not honor "Allow cut & paste in instant messages" setting

Resolved Caveats in Release 14.0(2)

Identifier	Severity	Headline
CSCvy51585	3	Cisco Jabber Android 14 - Loosing Microphone

Resolved Caveats in Release 14.0(1)

Identifier	Severity	Headline
CSCvx97173	3	Jabber Android does not allow for double @ in login page

Resolved Caveats in Release 14.0

Identifier	Severity	Headline
CSCvy47403	2	Multiple Vulnerabilities in expat
CSCvy47418	2	Multiple Vulnerabilities in glib
CSCvv92601	3	Hint message notification is displaying on chat window even after reading the message
CSCvw07298	3	"New Messages" hint notification is displaying even after reading new messages in chat window
CSCvw79638	3	Certificate based SSO login failing when connected internally
CSCvx32298	3	J4A [Jabber for Android] not having the Recording Tone Feature working
CSCvx45600	3	Bad voice quality when recording is enabled (Android)
CSCvy47420	3	Multiple Vulnerabilities in openldap

Cisco Jabber for iPhone and iPad

Resolved Caveats in Release 14.0(4)

There are no public resolved caveats for this release.

Resolved Caveats in Release 14.0(3)

Identifier	Severity	Headline
CSCvy78286	2	Jabber send the 486 Busy here, because the Timer sipLocalExp expired

Resolved Caveats in Release 14.0(2)

Identifier	Severity	Headline
CSCvy63998	2	One way audio
CSCvy60665	3	Jabber for iPhone TCT unregisters after 15 minutes over MRA

Resolved Caveats in Release 14.0(1)

Identifier	Severity	Headline
CSCvy14201	3	Jabber For iOS Fails Encryption for SRTP when FIPS is Enabled

Resolved Caveats in Release 14.0

Identifier	Severity	Headline
CSCvu43878	3	Custom tabs over MRA does not properly work
CSCvu47711	3	5~6 seconds audio delay after call pickup on Jabber for iPhone
CSCvv74385	3	[Jabber iOS] Phone service disconnects immediately over MRA
CSCvw72876	3	J4iPhone uses same contact for Primary and Secondary REGISTER message and send it to single EXP-E
CSCvx02708	3	Jabber for iOS - Failed to connect to phone service
CSCvx76643	4	Jabber IOS audio intermittently is muted after hold/resume operation

Cisco Jabber for Intune

There are no defects to report.

Cisco Jabber for BlackBerry

Resolved Caveats in Release 14.0(3)

Identifier	Severity	Headline
CSCvz21043	2	Jabber 12.9 IOS for BB client not able to complete consult transfer call

Identifier	Severity	Headline
CSCvz31973	2	Jabber for blacberry login issue

