

Release Notes for Cisco Aironet 1800s Active Sensor, Cisco Wireless Release 8.8.259.0

First Published: 2018-12-20

Introduction

This release notes document describes features, enhancements, and caveats for the Cisco Aironet 1800s Active Sensor using the Cisco Wireless Release 8.8.259.0. These release notes are updated as needed to provide information about new features, caveats, potential software deferrals, and related documents.



Note Explore the [Content Hub](#), the all new portal that offers an enhanced product documentation experience.

- Use faceted search to locate content that is most relevant to you.
- Create customized PDFs for ready reference.
- Benefit from context-based recommendations.

Get started with the Content Hub at content.cisco.com to craft a personalized documentation experience.

Do provide feedback about your experience with the Content Hub.

We recommend that you view the field notices for this release to check whether your software or hardware platforms are affected. If you have an account on Cisco.com, you can find the field notices at: http://www.cisco.com/en/US/customer/support/tsd_products_field_notice_summary.html.

However, if you do not have a Cisco.com account, you can find the field notices at: http://www.cisco.com/en/US/support/tsd_products_field_notice_summary.html.

Overview of Cisco Aironet 1800s Active Sensor

The Cisco Aironet 1800s Active Sensor is a part of Cisco's Wireless Service Assurance solution. The Wireless Service Assurance platform has three components, namely, Wireless Performance Analytics, Real-time Client Troubleshooting, and Proactive Health Assessment.

The Cisco Aironet 1800s Active Sensor is referred to as the Network Sensor, or sensor in this document.

The Cisco Aironet 1800s Active Sensor is an 802.11 a/b/g/n/ac (Wave 2) sensor, with internal antennas and an Ethernet backhaul. The sensor can be mounted, in a vertical orientation, on a wall or a desk and supports 2x2:2 SS MU-MIMO applications. The sensor is capable of joining an infrastructure access point as a client. The sensor can be used to monitor, measure, and troubleshoot overall wireless network performance.

What's New in Cisco Wireless Release 8.8.259.0

This release is to address the caveats listed in the [Resolved Caveats, on page 3](#) and [Open Caveats, on page 3](#) sections.

Caveats

Caveats describe unexpected behavior in the Cisco Wireless Network Sensor software. Severity 1 caveats are the most serious while Severity 2 caveats are less serious.

The and sections list the caveats in the Cisco Wireless Release . The following information is provided for each caveat:

- Identifier—Each caveat is assigned a unique identifier (ID) with a pattern of CSCxxNNNNN, where x is any letter (a-z) and N is any number (0-9). These IDs are frequently referenced in Cisco documentation, such as Security Advisories, Field Notices and other Cisco support documents. Technical Assistance Center (TAC) engineers or other Cisco staff can also provide you with the ID for a specific caveat.
- Description—A description of what is observed when the caveat occurs.

Cisco Bug Search Tool

The [Cisco Bug Search Tool](#) (BST), which is the online successor to the Bug Toolkit, is designed to improve the effectiveness in network risk management and device troubleshooting. The BST allows partners and customers to search for software bugs based on product, release, and keyword, and aggregates key data, such as bug details, product, and version. The tool has a provision to filter bugs based on credentials to provide external and internal bug views for the search input.

For more information about how to use the [Cisco Bug Search Tool](#) effectively, including how to set email alerts for bugs, filter bugs, and save bugs and searches, see the [Bug Search Tool Help & FAQ](#) page.

You can access the listed bugs through the BST. This web-based tool provides you access to the Cisco bug tracking system, which maintains information about bugs and vulnerabilities in the Cisco Wireless Network Sensor software and other Cisco hardware and software products.

Click the Caveat Identifier number in the table. The corresponding BST page is displayed with details of the bug.



Note

If you are not logged in, you will be redirected to a **Log In** page where you need to enter your registered Cisco.com username and password to log In. If you do not have a Cisco.com account, you can [register](#) for one.

If the defect that you have selected cannot be displayed, this may be due to one or more of the following reasons:

- The defect number does not exist
- The defect does not have a customer-visible description yet
- The defect has been marked Cisco Confidential

Open Caveats

This section lists the open caveats in Cisco Wireless Release 8.8.259.0. These caveats apply to the current release and may apply to previous releases. A caveat that is open for a prior release and is still unresolved applies to all future releases until it is resolved.

Table 1: Cisco Aironet Network Sensor: Open Caveats in Cisco Wireless Release 8.8.259.0

Caveat Identifier	Caveat Description
CSCvm75439	Cisco Aironet 1800s may reboot to OOM on running all tests
CSCvm79133	Sensor does not recover from HEARTBEAT FAILURE after upgrade from 1.2.4 to 1.2.5
CSCvn14831	Cisco DNA Center 1.2.6: Sensor EAP-FAST test reports slow-onboarding
CSCvn68270	Web-server test fails for web-authentication-enabled SSID

Resolved Caveats

This section lists the caveats that have been resolved in Cisco Wireless Release 8.8.259.0.

Table 2: Cisco Aironet Network Sensor: Resolved Caveats in Cisco Wireless Release 8.8.259.0

Caveat Identifier	Caveat Description
CSCvm55730	Inconsistent test results in the Sensor dashboard
CSCvn04116	IOS AP needs to be avoided for running IPSLA tests
CSCvn12673	Sensor "test results" for all tests has missing test results.
CSCvn21729	SSH-Credential and Traceback fix
CSCvn28996	Logs are not rolled over to backup file after wsa.log file is full.
CSCvn48155	Wireless sensor fails display 50% of result when 2.4Ghz and 5Ghz testsuit is enabled

Service and Support

For all support-related information, see <http://www.cisco.com/c/en/us/support/index.html>.

Related Documentation

- [Cisco Aironet 1800s Active Sensor Getting Started Guide](#)
- [Cisco Aironet Sensor Deployment Guide](#)

Communications, Services, and Additional Information

- To receive timely, relevant information from Cisco, sign up at [Cisco Profile Manager](#).
- To get the business impact you're looking for with the technologies that matter, visit [Cisco Services](#).

- To submit a service request, visit [Cisco Support](#).
- To discover and browse secure, validated enterprise-class apps, products, solutions and services, visit [Cisco Marketplace](#).
- To obtain general networking, training, and certification titles, visit [Cisco Press](#).
- To find warranty information for a specific product or product family, access [Cisco Warranty Finder](#).

Cisco Bug Search Tool

[Cisco Bug Search Tool](#) (BST) is a web-based tool that acts as a gateway to the Cisco bug tracking system that maintains a comprehensive list of defects and vulnerabilities in Cisco products and software. BST provides you with detailed defect information about your products and software.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: [www.cisco.com go trademarks](http://www.cisco.com/go/trademarks). Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2018 Cisco Systems, Inc. All rights reserved.