



N : M Redundancy

- [Revision History, on page 1](#)
- [Feature Description, on page 1](#)
- [Configuring Ignore SSH IP Installation, on page 2](#)

Revision History



Note Revision history details are not provided for features introduced before release 21.24.

Revision Details	Release
With this release support is provided for a new CLI to ignore the SSH IP installation in UP.	21.26.7
First introduced.	Pre 21.24

Feature Description

The CUPS User Plane (UP) is an all-important network component in the core network that carries and anchors the data traffic of subscribers. To ensure a smooth quality of experience (QoE), it is necessary to preserve data traffic and continue with minimal interruption. This is feasible only when there is a provision of a robust redundancy mechanism for all the data sessions that are hosted and anchored on UPs.

Every UP should have a redundant UP on standby (warm, hot, or active). However, this model mandates significant resource requirement for the service providers and is not a preferred model because of the number of UPs that can keep scaling horizontally. The preferred model is to have an N:M model with multiple UPs acting as standby-UPs for every active UPs. The N:M Redundancy feature provides this redundancy model.

On the UP, there is a new Cisco proprietary node called the Redundancy and Configuration Manager (RCM) which handles the configuration management of the UPs and the redundancy functionality.

For details on N:M redundancy and RCM, refer the *Redundancy and Configuration Manager Configuration and Administration Guide*.

Configuring Ignore SSH IP Installation

Use the configuration given below to ignore the SSH IP installation in UP:

```
configure
  context context_name
    redundancy-configuration-module module_name
      ignore-ssh-ip
    end
```



Note By default, when this CLI is not configured, the NSO SSH IP is configured on UP as usual.
