

Configuración de SVTI con reconocimiento de VRF IKEv2

Contenido

[Introducción](#)

[Prerequisites](#)

[Requirements](#)

[Componentes Utilizados](#)

[Configurar](#)

[Diagrama de la red](#)

[Antecedentes](#)

[Configuración](#)

[Verificación](#)

[Troubleshoot](#)

[Comandos para resolución de problemas](#)

[Ejemplo de resultado del comando debug](#)

[Referencias](#)

Introducción

Este documento proporciona un ejemplo de configuración para configurar interfaces de túnel virtual estático (SVTI) con reconocimiento de routing y reenvío virtual (VRF) entre dos peers de red privada virtual (VPN) mediante el protocolo Internet Key Exchange versión 2 (IKEv2). Esta configuración incluye una IVRF de la que forma parte la subred local y un VRF de puerta delantera (FVRF) donde se produce el establecimiento del túnel.

Prerequisites

Requirements

Cisco recomienda que tenga conocimiento sobre estos temas:

- Conocimiento básico de la configuración IOS CLI
- Conocimiento fundamental de IKEv2 e IPSEC

Componentes Utilizados


La información de este documento se basa en un Cisco IOS 2900 Series Router con Cisco IOS® Software Release 15.7.

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. Si su red está en producción, asegúrese de comprender el impacto potencial de cualquier comando.

Configurar

En esta sección encontrará la información para configurar las funciones descritas en este documento.

Diagrama de la red



Antecedentes

Los túneles que reconocen VRF se utilizan para conectar las redes de los clientes separadas por otras redes centrales no fiables o redes centrales con diferentes infraestructuras. Con esta configuración, cualquier origen y destino de un túnel se puede configurar para que pertenezca a cualquier tabla VRF.

En una interfaz de túnel, el comando "vrf forwarding" se utiliza para colocar la interfaz de túnel en esa tabla de ruteo determinada. Con el comando "tunnel vrf", se indica al router que utilice la tabla de ruteo de VRF especificada para las direcciones IP de origen y destino del túnel.

En el ejemplo utilizado para este documento, la interfaz de loopback VRF es como un VRF de segmento LAN. Los paquetes que ingresan a través de esta interfaz se rutean usando este VRF. Los paquetes que salen del túnel se reenvían a este VRF.

El VRF configurado en el túnel mediante el comando "tunnel vrf" es el VRF de transporte. Es el VRF que se aplica a la carga útil encapsulada y se utiliza para buscar los puntos finales del túnel. Este VRF es el mismo que el VRF asociado con la interfaz física sobre la cual el túnel envía paquetes.

Configuración

Paso 1. Defina los VRF. En este ejemplo, se definen dos VRF con el nombre "local" e "internet" respectivamente para las interfaces LAN y WAN.

SiteA :

! — Defining vrf

```
vrf definition internet
rd 2:2
address-family ipv4
exit-address-family
```

```
vrf definition local
rd 1:1
address-family ipv4
exit-address-family
```

SiteB :

! — Defining vrf

```
vrf definition internet
 rd 2:2
 address-family ipv4
 exit-address-family
```

```
vrf definition local
 rd 1:1
 address-family ipv4
 exit-address-family
```

Paso 2. Configure los parámetros necesarios para activar un túnel IKEv2, comenzando con la creación de la propuesta IKEv2 y el llaneo de claves. Luego, el perfil IKEv2 se configura donde se llama al anillo de claves criptográficas y para concluir con la configuración de criptografía, configure el perfil IPSEC incluye el conjunto de transformación IPSEC y el perfil IKEv2.

SiteA :

! — IKEv2 Proposal

```
crypto ikev2 proposal prop-1
 encryption aes-cbc-256
 integrity sha512
 group 5
```

! --- IKEv2 Policy

```
crypto ikev2 policy policy-1
 match fvrf internet
 match address local 192.168.1.1
 proposal prop-1
```

! — IKEv2 Keyring

```
crypto ikev2 keyring keyring-1
 peer ANY
 address 0.0.0.0 0.0.0.0
 pre-shared-key cisco123
```

! — IKEv2 Profile

```
crypto ikev2 profile IKEv2-Profile-1
 match fvrf internet
 match identity remote address 0.0.0.0
 authentication remote pre-share
 authentication local pre-share
 keyring local keyring-1
```

! — IPSEC Transform set

```
crypto ipsec transform-set transform-1 esp-aes 256 esp-sha-hmac
 mode transport
```

! — IPSEC Profile

```
crypto ipsec profile IPSEC-Profile-1
 set transform-set transform-1
```

```
set ikev2-profile IKEv2-Profile-1
```

SiteB :

! — IKEv2 Proposal

```
crypto ikev2 proposal prop-1
  encryption aes-cbc-256
  integrity sha512
  group 5
```

! -- IKEv2 Policy

```
crypto ikev2 policy policy-1
match fvrfl internet
match address local 192.168.2.1
proposal prop-1 ! — IKEv2 Keyring
```

```
crypto ikev2 keyring keyring-1
  peer ANY
  address 0.0.0.0 0.0.0.0
  pre-shared-key cisco123
```

! — IKEv2 Profile

```
crypto ikev2 profile IKEv2-Profile-1
  match fvrfl internet
  match identity remote address 0.0.0.0
  authentication remote pre-share
  authentication local pre-share
  keyring local keyring-1
```

! — IPSEC Transform set

```
crypto ipsec transform-set transform-1 esp-aes 256 esp-sha-hmac
mode transport
```

! — IPSEC Profile

```
crypto ipsec profile IPSEC-Profile-1
  set transform-set transform-1
  set ikev2-profile IKEv2-Profile-1
```

Paso 3. Configure las interfaces necesarias. En este ejemplo, la interfaz de loopback es parte del VRF "local" y actúa como tráfico interesante. La interfaz física, que forma parte del VRF de "Internet", es la interfaz WAN conectada al ISP. La interfaz de túnel se utiliza para activar la encapsulación GRE cifrada con IPSEC.

SiteA :

! — Interface Configuration

```
interface Loopback1
  vrf forwarding local
  ip address 10.1.1.1 255.255.255.0

interface Tunnel1
  vrf forwarding local
  ip address 10.10.10.1 255.255.255.0
  tunnel source 192.168.1.1
  tunnel destination 192.168.2.1
```

```
tunnel key 777
tunnel vrf internet
tunnel protection ipsec profile IPSEC-Profile-1
```

```
interface GigabitEthernet0/0
vrf forwarding internet
ip address 192.168.1.1 255.255.255.0
```

SiteB :

! — Interface Configuration

```
interface Loopback1
vrf forwarding local
ip address 10.2.2.2 255.255.255.0
```

```
interface Tunnell
vrf forwarding local
ip address 10.10.10.2 255.255.255.0
tunnel source 192.168.2.1
tunnel destination 192.168.1.1
tunnel key 777
tunnel vrf internet
tunnel protection ipsec profile IPSEC-Profile-1
```

```
interface GigabitEthernet0/0
vrf forwarding internet
ip address 192.168.2.1 255.255.255.0
```

Paso 4: Configure las rutas específicas de VRF. En esta configuración, una ruta en VRF "Internet" se configura como una ruta predeterminada que apunta al salto siguiente de la interfaz física (o ISP en entornos reales). La segunda ruta en el VRF "local" es para la subred VPN remota que apunta a la interfaz de túnel, lo que finalmente hace que el tráfico pase a través de la interfaz de túnel y active la VPN.

SiteA :

! — VRF specific routes

```
ip route vrf internet 0.0.0.0 0.0.0.0 192.168.1.2
ip route vrf local 10.2.2.0 255.255.255.0 Tunnell
```

SiteB :

! — VRF specific routes

```
ip route vrf internet 0.0.0.0 0.0.0.0 192.168.2.2
ip route vrf local 10.1.1.0 255.255.255.0 tunnel 1
```

Verificación

En esta sección encontrará información que puede utilizar para confirmar que su configuración esté funcionando correctamente.

[Cisco CLI Analyzer](#) admite ciertos comandos show. Utilice el Analizador de Cisco CLI para ver un análisis de los resultados del comando show.

SiteA :

SiteA#show crypto ikev2 sa

IPv4 Crypto IKEv2 SA

	Tunnel-id	Local	Remote	fvrfr/ivrf	Status
1	192.168.1.1/500	192.168.2.1/500	internet/local	READY	

Encr: AES-CBC, keysize: 256, PRF: SHA512, Hash: SHA512, DH Grp:5, Auth sign: PSK, Auth verify: PSK
Life/Active Time: 86400/128 sec

SiteA#show crypto ipsec sa detail

interface: Tunnell

Crypto map tag: Tunnell-head-0, local addr 192.168.1.1

protected vrf: local

local ident (addr/mask/prot/port): (192.168.1.1/255.255.255.255/47/0)

remote ident (addr/mask/prot/port): (192.168.2.1/255.255.255.255/47/0)

current_peer 192.168.2.1 port 500

PERMIT, flags={origin_is_acl,}

#pkts encaps: 25, #pkts encrypt: 25, #pkts digest: 25

#pkts decaps: 25, #pkts decrypt: 25, #pkts verify: 25

#pkts compressed: 0, #pkts decompressed: 0

#pkts not compressed: 0, #pkts compr. failed: 0

#pkts not decompressed: 0, #pkts decompress failed: 0

#pkts no sa (send) 0, #pkts invalid sa (rcv) 0

#pkts encaps failed (send) 0, #pkts decaps failed (rcv) 0

#pkts invalid prot (rcv) 0, #pkts verify failed: 0

#pkts invalid identity (rcv) 0, #pkts invalid len (rcv) 0

#pkts replay rollover (send): 0, #pkts replay rollover (rcv) 0

##pkts replay failed (rcv): 0

#pkts tagged (send): 0, #pkts untagged (rcv): 0

#pkts not tagged (send): 0, #pkts not untagged (rcv): 0

#pkts internal err (send): 0, #pkts internal err (rcv) 0

local crypto endpt.: 192.168.1.1, remote crypto endpt.: 192.168.2.1

plaintext mtu 1458, path mtu 1500, ip mtu 1500, ip mtu idb GigabitEthernet0/0

current outbound spi: 0xE0B1BF6B(3769745259)

PFS (Y/N): N, DH group: none

inbound esp sas:

spi: 0xCA8E7D53(3398335827)

transform: esp-256-aes esp-sha-hmac ,

in use settings ={Transport, }

conn id: 2010, flow_id: Onboard VPN:10, sibling_flags 80000000, crypto map: Tunnell-

head-0

sa timing: remaining key lifetime (k/sec): (4368363/3461)

IV size: 16 bytes

replay detection support: Y

Status: ACTIVE(ACTIVE)

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0xE0B1BF6B(3769745259)

transform: esp-256-aes esp-sha-hmac ,

in use settings ={Transport, }

conn id: 2009, flow_id: Onboard VPN:9, sibling_flags 80000000, crypto map: Tunnell-head-

0

sa timing: remaining key lifetime (k/sec): (4368363/3461)

IV size: 16 bytes

replay detection support: Y
Status: ACTIVE(ACTIVE)

outbound ah sas:

outbound pcp sas:

SiteA#show crypto session remote 192.168.2.1 detail

Crypto session current status

Code: C - IKE Configuration mode, D - Dead Peer Detection
K - Keepalives, N - NAT-traversal, T - cTCP encapsulation
X - IKE Extended Authentication, F - IKE Fragmentation
R - IKE Auto Reconnect, U - IKE Dynamic Route Update
S - SIP VPN

Interface: Tunnell

Profile: IKEv2-Profile-1

Uptime: 00:02:35

Session status: **UP-ACTIVE**

Peer: 192.168.2.1 port 500 fvrf: internet ivrf: local

Phase1_id: 192.168.2.1

Desc: (none)

Session ID: 3

IKEv2 SA: local 192.168.1.1/500 remote 192.168.2.1/500 Active

Capabilities:(none) connid:1 lifetime:23:57:25

IPSEC FLOW: permit 47 host 192.168.1.1 host 192.168.2.1

Active SAs: 2, origin: crypto map

Inbound: #pkts dec'ed 25 drop 0 life (KB/Sec) 4368363/3444

Outbound: #pkts enc'ed 25 drop 0 life (KB/Sec) 4368363/3444

SiteB :

SiteB#show crypto ikev2 sa

IPv4 Crypto IKEv2 SA

	Tunnel-id	Local	Remote	fvrf/ivrf	Status
1	192.168.2.1/500	192.168.1.1/500	internet/local	READY	

Encr: AES-CBC, keysize: 256, PRF: SHA512, Hash: SHA512, DH Grp:5, Auth sign: PSK, Auth verify: PSK
Life/Active Time: 86400/90 sec

SiteB#show crypto ipsec sa detail

interface: Tunnell

Crypto map tag: Tunnell-head-0, local addr 192.168.2.1

protected vrf: local

local ident (addr/mask/prot/port): (192.168.2.1/255.255.255.255/47/0)

remote ident (addr/mask/prot/port): (192.168.1.1/255.255.255.255/47/0)

current_peer 192.168.1.1 port 500

PERMIT, flags={origin_is_acl,}

#pkts encaps: 25, #pkts encrypt: 25, #pkts digest: 25

#pkts decaps: 25, #pkts decrypt: 25, #pkts verify: 25

#pkts compressed: 0, #pkts decompressed: 0

#pkts not compressed: 0, #pkts compr. failed: 0

#pkts not decompressed: 0, #pkts decompress failed: 0

#pkts no sa (send) 0, #pkts invalid sa (rcv) 0

#pkts encaps failed (send) 0, #pkts decaps failed (rcv) 0

#pkts invalid prot (rcv) 0, #pkts verify failed: 0

#pkts invalid identity (rcv) 0, #pkts invalid len (rcv) 0

#pkts replay rollover (send): 0, #pkts replay rollover (rcv) 0

##pkts replay failed (rcv): 0
#pkts tagged (send): 0, #pkts untagged (rcv): 0
#pkts not tagged (send): 0, #pkts not untagged (rcv): 0
#pkts internal err (send): 0, #pkts internal err (recv) 0

local crypto endpt.: 192.168.2.1, remote crypto endpt.: 192.168.1.1

plaintext mtu 1458, path mtu 1500, ip mtu 1500, ip mtu idb GigabitEthernet0/0
current outbound spi: 0xCA8E7D53(3398335827)
PFS (Y/N): N, DH group: none

inbound esp sas:

spi: 0xE0B1BF6B(3769745259)

transform: esp-256-aes esp-sha-hmac ,
in use settings ={Transport, }

conn id: 2009, flow_id: Onboard VPN:9, sibling_flags 80000000, crypto map: Tunnell-head-

0

sa timing: remaining key lifetime (k/sec): (4251213/3468)

IV size: 16 bytes

replay detection support: Y

Status: ACTIVE(ACTIVE)

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0xCA8E7D53(3398335827)

transform: esp-256-aes esp-sha-hmac ,
in use settings ={Transport, }

conn id: 2010, flow_id: Onboard VPN:10, sibling_flags 80000000, crypto map: Tunnell-

head-0

sa timing: remaining key lifetime (k/sec): (4251213/3468)

IV size: 16 bytes

replay detection support: Y

Status: ACTIVE(ACTIVE)

outbound ah sas:

outbound pcp sas:

SiteB#**show crypto session remote 192.168.1.1 detail**

Crypto session current status

Code: C - IKE Configuration mode, D - Dead Peer Detection
K - Keepalives, N - NAT-traversal, T - cTCP encapsulation
X - IKE Extended Authentication, F - IKE Fragmentation
R - IKE Auto Reconnect

Interface: Tunnell

Profile: IKEv2-Profile-1

Uptime: 00:02:33

Session status: **UP-ACTIVE**

Peer: 192.168.1.1 port 500 fvrf: internet ivrf: local

Phase1_id: 192.168.1.1

Desc: (none)

Session ID: 4

IKEv2 SA: local 192.168.2.1/500 remote 192.168.1.1/500 Active

Capabilities:(none) connid:1 lifetime:23:57:27

IPSEC FLOW: permit 47 host 192.168.2.1 host 192.168.1.1

Active SAs: 2, origin: crypto map

Inbound: #pkts dec'ed 25 drop 0 life (KB/Sec) 4251213/3447

Outbound: #pkts enc'ed 25 drop 0 life (KB/Sec) 4251213/3447

Troubleshoot

En esta sección encontrará información que puede utilizar para solucionar problemas de configuración. También se muestra un ejemplo de salida del debug .

Comandos para resolución de problemas

Nota: Consulte Información Importante sobre Comandos Debug antes de utilizar los comandos debug. Si hay varios túneles configurados en el router, puede utilizar la siguiente condición:

- **Debug crypto ikev2 internal**
- **Depurar paquete crypto ikev2**

Ejemplo de resultado del comando debug

SiteA Debugs :

```
*Jul 16 05:30:50.731: IKEv2: Got a packet from dispatcher
*Jul 16 05:30:50.731: IKEv2: Processing an item off the pak queue
*Jul 16 05:30:50.731: IKEv2-INTERNAL:% Getting preshared key by address 192.168.2.1
*Jul 16 05:30:50.731: IKEv2-INTERNAL:Adding Proposal default to toolkit policy
*Jul 16 05:30:50.731: IKEv2-INTERNAL:(1): Choosing IKE profile IKEv2-Profile-1
*Jul 16 05:30:50.731: IKEv2-INTERNAL:New ikev2 sa request admitted
*Jul 16 05:30:50.731: IKEv2-INTERNAL:Incrementing outgoing negotiating sa count by one

*Jul 16 05:30:50.731: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: IDLE Event: EV_INIT_SA
*Jul 16 05:30:50.731: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_GET_IKE_POLICY
*Jul 16 05:30:50.731: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_SET_POLICY
*Jul 16 05:30:50.731: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Setting configured policies
*Jul 16 05:30:50.731: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_CHK_AUTH4PKI
*Jul 16 05:30:50.731: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_GEN_DH_KEY
*Jul 16 05:30:50.791: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_NO_EVENT
*Jul 16 05:30:50.791: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_OK_REC'D_DH_PUBKEY_RESP
*Jul 16 05:30:50.791: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Action: Action_Null
*Jul 16 05:30:50.791: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_GET_CONFIG_MODE
*Jul 16 05:30:50.791: IKEv2-INTERNAL:No config data to send to toolkit:
*Jul 16 05:30:50.791: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=0000000000000000 (I) MsgID = 0 CurState: I_BLD_INIT Event:
EV_BLD_MSG
*Jul 16 05:30:50.791: IKEv2-INTERNAL:Construct Vendor Specific Payload: DELETE-REASON
*Jul 16 05:30:50.791: IKEv2-INTERNAL:Construct Vendor Specific Payload: CISCOVPN-REV-02
*Jul 16 05:30:50.791: IKEv2-INTERNAL:Sending DRU Handshake
*Jul 16 05:30:50.791: IKEv2-INTERNAL:(1): Sending custom vendor id : CISCO-DYNAMIC-ROUTE
```

*Jul 16 05:30:50.791: IKEv2-INTERNAL:Construct Vendor Specific Payload: (CUSTOM)
*Jul 16 05:30:50.791: IKEv2-INTERNAL:Construct Vendor Specific Payload: (CUSTOM)
*Jul 16 05:30:50.791: IKEv2-INTERNAL:Construct Notify Payload: NAT_DETECTION_SOURCE_IP
*Jul 16 05:30:50.791: IKEv2-INTERNAL:Construct Notify Payload: NAT_DETECTION_DESTINATION_IP

*Jul 16 05:30:50.795: **IKEv2-PAK:(SESSION ID = 3,SA ID = 1):Next payload: SA, version: 2.0**
Exchange type: IKE_SA_INIT, flags: INITIATOR Message id: 0, length: 550

Payload contents:

SA Next payload: KE, reserved: 0x0, length: 144
last proposal: 0x0, reserved: 0x0, length: 140
Proposal: 1, Protocol id: IKE, SPI size: 0, #trans: 15 last transform: 0x3, reserved: 0x0:
length: 12

type: 1, reserved: 0x0, id: AES-CBC
last transform: 0x3, reserved: 0x0: length: 12
type: 1, reserved: 0x0, id: AES-CBC
last transform: 0x3, reserved: 0x0: length: 12
type: 1, reserved: 0x0, id: AES-CBC
last transform: 0x3, reserved: 0x0: length: 8
type: 2, reserved: 0x0, id: SHA512
last transform: 0x3, reserved: 0x0: length: 8
type: 2, reserved: 0x0, id: SHA384
last transform: 0x3, reserved: 0x0: length: 8
type: 2, reserved: 0x0, id: SHA256
last transform: 0x3, reserved: 0x0: length: 8
type: 2, reserved: 0x0, id: SHA1
last transform: 0x3, reserved: 0x0: length: 8
type: 2, reserved: 0x0, id: MD5
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA512
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA384
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA256
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA96
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: MD596
last transform: 0x3, reserved: 0x0: length: 8
type: 4, reserved: 0x0, id: DH_GROUP_1536_MODP/Group 5
last transform: 0x0, reserved: 0x0: length: 8
type: 4, reserved: 0x0, id: DH_GROUP_1024_MODP/Group 2

KE Next payload: N, reserved: 0x0, length: 200
DH group: 5, Reserved: 0x0

N Next payload: VID, reserved: 0x0, length: 36
VID Next payload: VID, reserved: 0x0, length: 23
VID Next payload: VID, reserved: 0x0, length: 19
VID Next payload: VID, reserved: 0x0, length: 23
VID Next payload: NOTIFY, reserved: 0x0, length: 21

NOTIFY(NAT_DETECTION_SOURCE_IP) Next payload: NOTIFY, reserved: 0x0, length: 28
Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_SOURCE_IP
NOTIFY(NAT_DETECTION_DESTINATION_IP) Next payload: NONE, reserved: 0x0, length: 28
Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_DESTINATION_IP

*Jul 16 05:30:50.931: **IKEv2-INTERNAL:Got a packet from dispatcher**
*Jul 16 05:30:50.931: **IKEv2-INTERNAL:Processing an item off the pak queue**

*Jul 16 05:30:50.939: **IKEv2-PAK:(SESSION ID = 3,SA ID = 1):Next payload: SA, version: 2.0**
Exchange type: IKE_SA_INIT, flags: RESPONDER MSG-RESPONSE Message id: 0, length: 431

Payload contents:

SA Next payload: KE, reserved: 0x0, length: 48
last proposal: 0x0, reserved: 0x0, length: 44
Proposal: 1, Protocol id: IKE, SPI size: 0, #trans: 4 last transform: 0x3, reserved: 0x0:
length: 12

type: 1, reserved: 0x0, id: AES-CBC
last transform: 0x3, reserved: 0x0: length: 8
type: 2, reserved: 0x0, id: SHA512
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA512
last transform: 0x0, reserved: 0x0: length: 8
type: 4, reserved: 0x0, id: DH_GROUP_1536_MODP/Group 5
KE Next payload: N, reserved: 0x0, length: 200
DH group: 5, Reserved: 0x0
N Next payload: VID, reserved: 0x0, length: 36

*Jul 16 05:30:50.939: IKEv2-INTERNAL:Parse Vendor Specific Payload: CISCO-DELETE-REASON
VID Next payload: VID, reserved: 0x0, length: 23

*Jul 16 05:30:50.939: IKEv2-INTERNAL:Parse Vendor Specific Payload: CISCOVPN-REV VID Next
payload: VID, reserved: 0x0, length: 19

*Jul 16 05:30:50.939: IKEv2-INTERNAL:Parse Vendor Specific Payload: (CUSTOM) VID Next payload:
NOTIFY, reserved: 0x0, length: 21

*Jul 16 05:30:50.939: IKEv2-INTERNAL:Parse Notify Payload: NAT_DETECTION_SOURCE_IP
NOTIFY(NAT_DETECTION_SOURCE_IP) Next payload: NOTIFY, reserved: 0x0, length: 28
Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_SOURCE_IP

*Jul 16 05:30:50.939: IKEv2-INTERNAL:Parse Notify Payload: NAT_DETECTION_DESTINATION_IP
NOTIFY(NAT_DETECTION_DESTINATION_IP) Next payload: NONE, reserved: 0x0, length: 28
Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_DESTINATION_IP

*Jul 16 05:30:50.939: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_WAIT_INIT Event:
EV_RECV_INIT

*Jul 16 05:30:50.939: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Processing IKE_SA_INIT message

*Jul 16 05:30:50.939: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_PROC_INIT Event:
EV_CHK4_NOTIFY

*Jul 16 05:30:50.939: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_PROC_INIT Event:
EV_VERIFY_MSG

*Jul 16 05:30:50.939: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_PROC_INIT Event:
EV_PROC_MSG

*Jul 16 05:30:50.939: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_PROC_INIT Event:
EV_DETECT_NAT

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Process NAT discovery notify

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Processing nat detect src notify

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Remote address matched

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Processing nat detect dst notify

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Local address matched

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):No NAT found

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_PROC_INIT Event:
EV_CHK_NAT_T

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_PROC_INIT Event:
EV_CHK_CONFIG_MODE

*Jul 16 05:30:50.943: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: INIT_DONE Event:
EV_GEN_DH_SECRET

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: INIT_DONE Event:
EV_NO_EVENT

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: INIT_DONE Event:

EV_OK_REC'D_DH_SECRET_RESP

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Action: Action_Null

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: INIT_DONE Event:

EV_GEN_SKEYID

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):**Generate skeyid**

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: INIT_DONE Event: EV_DONE

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Cisco DeleteReason Notify is enabled

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: INIT_DONE Event:

EV_CHK4_ROLE

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_BLD_AUTH Event:

EV_GET_CONFIG_MODE

*Jul 16 05:30:51.019: IKEv2-INTERNAL:Sending config data to toolkit

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_BLD_AUTH Event:

EV_CHK_EAP

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_BLD_AUTH Event:

EV_GEN_AUTH

*Jul 16 05:30:51.019: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_BLD_AUTH Event:

EV_CHK_AUTH_TYPE

*Jul 16 05:30:51.023: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_BLD_AUTH Event:

EV_OK_AUTH_GEN

*Jul 16 05:30:51.023: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 0 CurState: I_BLD_AUTH Event:

EV_SEND_AUTH

*Jul 16 05:30:51.023: IKEv2-INTERNAL:Construct Vendor Specific Payload: CISCO-GRANITE

*Jul 16 05:30:51.023: IKEv2-INTERNAL:Construct Notify Payload: INITIAL_CONTACT

*Jul 16 05:30:51.023: IKEv2-INTERNAL:Construct Notify Payload: USE_TRANSPORT_MODE

*Jul 16 05:30:51.023: IKEv2-INTERNAL:Construct Notify Payload: SET_WINDOW_SIZE

*Jul 16 05:30:51.023: IKEv2-INTERNAL:Construct Notify Payload: ESP_TFC_NO_SUPPORT

*Jul 16 05:30:51.023: IKEv2-INTERNAL:Construct Notify Payload: NON_FIRST_FRAGS

Payload contents:

VID Next payload: IDi, reserved: 0x0, length: 20

IDi Next payload: AUTH, reserved: 0x0, length: 12

Id type: IPv4 address, Reserved: 0x0 0x0

AUTH Next payload: CFG, reserved: 0x0, length: 72

Auth method PSK, reserved: 0x0, reserved 0x0

CFG Next payload: SA, reserved: 0x0, length: 304

cfg type: CFG_REQUEST, reserved: 0x0, reserved: 0x0

*Jul 16 05:30:51.023: SA Next payload: TSi, reserved: 0x0, length: 44

last proposal: 0x0, reserved: 0x0, length: 40

Proposal: 1, Protocol id: ESP, SPI size: 4, #trans: 3 last transform: 0x3, reserved: 0x0: length: 12

type: 1, reserved: 0x0, id: AES-CBC

last transform: 0x3, reserved: 0x0: length: 8

type: 3, reserved: 0x0, id: SHA96

last transform: 0x0, reserved: 0x0: length: 8

type: 5, reserved: 0x0, id: Don't use ESN

TSi Next payload: TSr, reserved: 0x0, length: 24

Num of TSs: 1, reserved 0x0, reserved 0x0

TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16

start port: 0, end port: 65535

start addr: 192.168.1.1, end addr: 192.168.1.1

TSr Next payload: NOTIFY, reserved: 0x0, length: 24

Num of TSs: 1, reserved 0x0, reserved 0x0

TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16

start port: 0, end port: 65535

start addr: 192.168.2.1, end addr: 192.168.2.1
NOTIFY(INITIAL_CONTACT) Next payload: NOTIFY, reserved: 0x0, length: 8
Security protocol id: Unknown - 0, spi size: 0, type: INITIAL_CONTACT
NOTIFY(USE_TRANSPORT_MODE) Next payload: NOTIFY, reserved: 0x0, length: 8
Security protocol id: Unknown - 0, spi size: 0, type: USE_TRANSPORT_MODE
NOTIFY(SET_WINDOW_SIZE) Next payload: NOTIFY, reserved: 0x0, length: 12
Security protocol id: Unknown - 0, spi size: 0, type: SET_WINDOW_SIZE
NOTIFY(ESP_TFC_NO_SUPPORT) Next payload: NOTIFY, reserved: 0x0, length: 8
Security protocol id: Unknown - 0, spi size: 0, type: ESP_TFC_NO_SUPPORT
NOTIFY(NON_FIRST_FRAGS) Next payload: NONE, reserved: 0x0, length: 8
Security protocol id: Unknown - 0, spi size: 0, type: NON_FIRST_FRAGS

*Jul 16 05:30:51.023: **IKEv2-PAK:(SESSION ID = 3,SA ID = 1):Next payload: ENCR, version: 2.0**
Exchange type: IKE_AUTH, flags: INITIATOR Message id: 1, length: 640
Payload contents:
ENCR Next payload: VID, reserved: 0x0, length: 612

*Jul 16 05:30:51.023: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 1 CurState: I_WAIT_AUTH Event:
EV_NO_EVENT

*Jul 16 05:30:51.023: **IKEv2-INTERNAL:Got a packet from dispatcher**
*Jul 16 05:30:51.023: **IKEv2-INTERNAL:Processing an item off the pak queue**

*Jul 16 05:30:51.107: **IKEv2-PAK:(SESSION ID = 3,SA ID = 1):Next payload: ENCR, version: 2.0**
Exchange type: IKE_AUTH, flags: RESPONDER MSG-RESPONSE Message id: 1, length: 320
Payload contents:

*Jul 16 05:30:51.111: IKEv2-INTERNAL:Parse Vendor Specific Payload: (CUSTOM) VID Next payload:
IDr, reserved: 0x0, length: 20
IDr Next payload: AUTH, reserved: 0x0, length: 12
Id type: IPv4 address, Reserved: 0x0 0x0
AUTH Next payload: SA, reserved: 0x0, length: 72
Auth method PSK, reserved: 0x0, reserved 0x0
SA Next payload: TSi, reserved: 0x0, length: 44
last proposal: 0x0, reserved: 0x0, length: 40
Proposal: 1, Protocol id: ESP, SPI size: 4, #trans: 3 last transform: 0x3, reserved: 0x0:
length: 12
type: 1, reserved: 0x0, id: AES-CBC
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA96
last transform: 0x0, reserved: 0x0: length: 8
type: 5, reserved: 0x0, id: Don't use ESN
TSi Next payload: TSr, reserved: 0x0, length: 24
Num of TSs: 1, reserved 0x0, reserved 0x0
TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16
start port: 0, end port: 65535
start addr: 192.168.1.1, end addr: 192.168.1.1
TSr Next payload: NOTIFY, reserved: 0x0, length: 24
Num of TSs: 1, reserved 0x0, reserved 0x0
TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16
start port: 0, end port: 65535
start addr: 192.168.2.1, end addr: 192.168.2.1

*Jul 16 05:30:51.111: IKEv2-INTERNAL:Parse Notify Payload: USE_TRANSPORT_MODE
NOTIFY(USE_TRANSPORT_MODE) Next payload: NOTIFY, reserved: 0x0, length: 8
Security protocol id: Unknown - 0, spi size: 0, type: USE_TRANSPORT_MODE

*Jul 16 05:30:51.111: IKEv2-INTERNAL:Parse Notify Payload: SET_WINDOW_SIZE
NOTIFY(SET_WINDOW_SIZE) Next payload: NOTIFY, reserved: 0x0, length: 12
Security protocol id: Unknown - 0, spi size: 0, type: SET_WINDOW_SIZE

*Jul 16 05:30:51.111: IKEv2-INTERNAL:Parse Notify Payload: ESP_TFC_NO_SUPPORT
NOTIFY(ESP_TFC_NO_SUPPORT) Next payload: NOTIFY, reserved: 0x0, length: 8

Security protocol id: Unknown - 0, spi size: 0, type: ESP_TFC_NO_SUPPORT

*Jul 16 05:30:51.111: IKEv2-INTERNAL:Parse Notify Payload: NON_FIRST_FRAGS
NOTIFY(NON_FIRST_FRAGS) Next payload: NONE, reserved: 0x0, length: 8

Security protocol id: Unknown - 0, spi size: 0, type: NON_FIRST_FRAGS

*Jul 16 05:30:51.111: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 1 CurState: I_WAIT_AUTH Event:

EV_RECV_AUTH

*Jul 16 05:30:51.111: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):Action: Action_Null

*Jul 16 05:30:51.123: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 1 CurState: READY Event:
EV_CHK_IKE_ONLY

*Jul 16 05:30:51.123: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (I) MsgID = 1 CurState: READY Event: EV_I_OK

*Jul 16 05:30:52.011: SM Trace-> SA: I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1
CurState: AUTH_DONE Event: EV_CHK4_ROLE

*Jul 16 05:30:52.027: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1 CurState: READY Event: EV_R_OK

*Jul 16 05:30:52.027: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1 CurState: READY Event: EV_NO_E

*Jul 16 05:30:52.027: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1 CurState:I_PROC_AUTH: **EV_VERIFY_AUTH**

*Jul 16 05:30:52.027: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1 CurState:I_PROC_AUTH

EVENT:EV_NOTIFY_AUTH_DONE

*Jul 16 05:30:52.027: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1 CurState:**AUTH_DONE** Event
EV_CHK4_ROLE

*Jul 16 05:30:52.027: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1 CurState: **READY**Event:
EV_CHK_IKE_ONLY

*Jul 16 05:30:52.027: IKEv2-INTERNAL:(SESSION ID = 3,SA ID = 1):SM Trace-> SA:
I_SPI=34CDD54C620910B0 R_SPI=F1A0F4AB68B75F00 (R) MsgID = 1 CurState: **READY**Event: **EV_I_OK**

SiteB Debugs:

*Jul 16 06:01:45.231: **IKEv2-INTERNAL:Got a packet from dispatcher**

*Jul 16 06:01:45.231: **IKEv2-INTERNAL:Processing an item off the pak queue**

*Jul 16 06:01:45.231: **IKEv2-INTERNAL:New ikev2 sa request admitted**

*Jul 16 06:01:45.231: **IKEv2-INTERNAL:Incrementing incoming negotiating sa count by one**

*Jul 16 06:01:45.231: **IKEv2-PAK:Next payload: SA, version: 2.0 Exchange type: IKE_SA_INIT, flags: INITIATOR** Message id: 0, length: 550

Payload contents:

SA Next payload: KE, reserved: 0x0, length: 144

last proposal: 0x0, reserved: 0x0, length: 140

Proposal: 1, Protocol id: IKE, SPI size: 0, #trans: 15 last transform: 0x3, reserved: 0x0:
length: 12

type: 1, reserved: 0x0, id: AES-CBC

last transform: 0x3, reserved: 0x0: length: 12

type: 1, reserved: 0x0, id: AES-CBC

last transform: 0x3, reserved: 0x0: length: 8

type: 2, reserved: 0x0, id: SHA1

last transform: 0x3, reserved: 0x0: length: 12

type: 1, reserved: 0x0, id: AES-CBC

last transform: 0x3, reserved: 0x0: 1 last transform: 0x3, reserved: 0x0: length: 8

type: 2, reserved: 0x0, id: MD5

last transform: 0x3, reserved: 0x0: length: 8

type: 3, reserved: 0x0, id: SHA512

last transform: 0x3, reserved: 0x0: length: 8

type: 3, reserved: 0x0, id: SHA384
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA256
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA96
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: MD596
last transform: 0x3, reserved: 0x0: length: 8
type: 4, reserved: 0x0, id: DH_GROUP_1536_MODP/Group 5
type: 2, reserved: 0x0, id: SHA512
last trans0x0, length: 23
KE Next payload: N, reserved: 0x0, length: 200
DH group: 5, Reserved: 0x0
N Next payload: VID, reserved: 0x0, length: 36

*Jul 16 06:01:45.231: IKEv2-INTERNAL:Parse Vendor Specific Payload: CISCOVPN-REV VID Next payload: VID, reserved: 0x0, length: 19

*Jul 16 06:01:45.231: IKEv2-INTERNAL:Parse Vendor Specific Payload: (CUSTOM) VID Next payload: VID, reserved: 0x0, length: 23

*Jul 16 06:01:45.231: IKEv2-INTERNAL:form: 0x3, reserved: 0x0: length: 8

*Jul 16 06:01:45.231: IKEv2-INTERNAL:Parse Vendor Specific Payload: CISCO-DELETE-REASON VID Next payload: VID, reserved:

*Jul 16 06:01:45.231: IKEv2-INTERNAL:Parse Notify Payload: NAT_DETECTION_SOURCE_IP NOTIFY(NAT_DETECTION_SOURCE_IP) Next payload: NOTIFY, reserved: 0x0, length: 28
Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_SOURCE_IP

*Jul 16 06:01:45.231: IKEv2-INTERNAL:Parse Notify Payload: NAT_DETECTION_DESTINATION_IP NOTIFY(NAT_DETECTION_DESTINATION_IP) Next payload: NONE, reserved: 0x0, length: 28
Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_DESTINATION_IP

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: IDLE Event: **EV_RECV_INIT**

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_INIT Event:

EV_VERIFY_MSG

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_INIT Event: **EV_INSERT_SA**

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_INIT Event:

EV_GET_IKE_POLICY

*Jul 16 06:01:45.231: IKEv2-INTERNAL:Adding Proposal default to toolkit policy

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_INIT Event: **EV_PROC_MSG**

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_INIT Event:

EV_DETECT_NAT

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Process NAT discovery notify

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Processing nat detect src notify

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Remote address matched

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Processing nat detect dst notify

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Local address matched

*Jul 16 06:01:45.231: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):No NAT found

*Jul 16 06:01:45.235: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_INIT Event:

EV_CHK_CONFIG_MODE

*Jul 16 06:01:45.235: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:

EV_SET_POLICY

*Jul 16 06:01:45.235: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):**Setting configured policies**

*Jul 16 06:01:45.235: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:

EV_CHK_AUTH4PKI

```

*Jul 16 06:01:45.235: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_GEN_DH_KEY
*Jul 16 06:01:45.295: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_NO_EVENT
*Jul 16 06:01:45.295: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_OK_REC'D_DH_PUBKEY_RESP
*Jul 16 06:01:45.295: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Action: Action_Null
*Jul 16 06:01:45.295: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_GEN_DH_SECRET
*Jul 16 06:01:45.371: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_NO_EVENT
*Jul 16 06:01:45.371: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_OK_REC'D_DH_SECRET_RESP
*Jul 16 06:01:45.371: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Action: Action_Null
*Jul 16 06:01:45.371: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_GEN_SKEYID
*Jul 16 06:01:45.371: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Generate skeyid
*Jul 16 06:01:45.371: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_GET_CONFIG_MODE
*Jul 16 06:01:45.371: IKEv2-INTERNAL:No config data to send to toolkit:
*Jul 16 06:01:45.371: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_BLD_INIT Event:
EV_BLD_MSG
*Jul 16 06:01:45.371: IKEv2-INTERNAL:Construct Vendor Specific Payload: DELETE-REASON
*Jul 16 06:01:45.371: IKEv2-INTERNAL:Construct Vendor Specific Payload: CISCOVPN-REV-02
*Jul 16 06:01:45.371: IKEv2-INTERNAL:Construct Vendor Specific Payload: (CUSTOM)
*Jul 16 06:01:45.371: IKEv2-INTERNAL:Construct Notify Payload: NAT_DETECTION_SOURCE_IP
*Jul 16 06:01:45.371: IKEv2-INTERNAL:Construct Notify Payload: NAT_DETECTION_DESTINATION_IP

*Jul 16 06:01:45.371: IKEv2-PAK:(SESSION ID = 4,SA ID = 1):Next payload: SA, version: 2.0
Exchange type: IKE_SA_INIT, flags: RESPONDER MSG-RESPONSE Message id: 0, length: 431
Payload contents:
SA Next payload: KE, reserved: 0x0, length: 48
  last proposal: 0x0, reserved: 0x0, length: 44
  Proposal: 1, Protocol id: IKE, SPI size: 0, #trans: 4    last transform: 0x3, reserved: 0x0:
length: 12
  type: 1, reserved: 0x0, id: AES-CBC
  last transform: 0x3, reserved: 0x0: length: 8
  type: 2, reserved: 0x0, id: SHA512
  last transform: 0x3, reserved: 0x0: length: 8
  type: 3, reserved: 0x0, id: SHA512
  last transform: 0x0, reserved: 0x0: length: 8
  type: 4, reserved: 0x0, id: DH_GROUP_1536_MODP/Group 5
KE Next payload: N, reserved: 0x0, length: 200
  DH group: 5, Reserved: 0x0
N Next payload: VID, reserved: 0x0, length: 36
VID Next payload: VID, reserved: 0x0, length: 23
VID Next payload: VID, reserved: 0x0, length: 19
VID Next payload: NOTIFY, reserved: 0x0, length: 21
NOTIFY(NAT_DETECTION_SOURCE_IP) Next payload: NOTIFY, reserved: 0x0, length: 28
  Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_SOURCE_IP
NOTIFY(NAT_DETECTION_DESTINATION_IP) Next payload: NONE, reserved: 0x0, length: 28
  Security protocol id: Unknown - 0, spi size: 0, type: NAT_DETECTION_DESTINATION_IP

*Jul 16 06:01:45.375: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: INIT_DONE Event: EV_DONE

```

*Jul 16 06:01:45.375: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Cisco DeleteReason Notify is enabled

*Jul 16 06:01:45.375: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA: I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: INIT_DONE Event: EV_CHK4_ROLE

*Jul 16 06:01:45.375: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA: I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: INIT_DONE Event: EV_START_TMR

*Jul 16 06:01:45.375: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA: I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 0 CurState: R_WAIT_AUTH Event: EV_NO_EVENT

*Jul 16 06:01:45.375: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):New ikev2 sa request admitted

*Jul 16 06:01:45.375: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Incrementing outgoing negotiating sa count by one

*Jul 16 06:01:45.390: **IKEv2-INTERNAL:Got a packet from dispatcher**

*Jul 16 06:01:45.390: **IKEv2-INTERNAL:Processing an item off the pak queue**

*Jul 16 06:01:45.375: **IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Next payload: ENCR, version: 2.0 Exchange type: IKE_AUTH, flags: INITIATOR** Message id: 1, length: 556

Payload contents:

*Jul 16 06:01:45.375: IKEv2-INTERNAL:Parse Vendor Specific Payload: (CUSTOM) VID Next payload: IDi, reserved: 0x0, length: 20

Payload contents:

IDi Next payload: AUTH, reserved: 0x0, length: 12
Id type: IPv4 address, Reserved: 0x0 0x0

AUTH Next payload: CFG, reserved: 0x0, length: 72
Auth method PSK, reserved: 0x0, reserved 0x0

CFG Next payload: SA, reserved: 0x0, length: 304
cfg type: CFG_REQUEST, reserved: 0x0, reserved: 0x0

SA Next payload: TSi, reserved: 0x0, length: 44
last proposal: 0x0, reserved: 0x0, length: 40

Proposal: 1, Protocol id: ESP, SPI size: 4, #trans: 3 last transform: 0x3, reserved: 0x0: length: 12
type: 1, reserved: 0x0, id: AES-CBC
last transform: 0x3, reserved: 0x0: length: 8
type: 3, reserved: 0x0, id: SHA96
last transform: 0x0, reserved: 0x0: length: 8
type: 5, reserved: 0x0, id: Don't use ESN

TSi Next payload: TSr, reserved: 0x0, length: 24
Num of TSs: 1, reserved 0x0, reserved 0x0
TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16
start port: 0, end port: 65535
start addr: 192.168.1.1, end addr: 192.168.1.1

TSr Next payload: NOTIFY, reserved: 0x0, length: 24
Num of TSs: 1, reserved 0x0, reserved 0x0
TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16
start port: 0, end port: 65535
start addr: 192.168.2.1, end addr: 192.168.2.1

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA: I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event: **EV_RECV_AUTH**

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA: I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event: EV_CHK_NAT_T

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA: I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event: EV_PROC_ID

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Received valid parameteres in process id

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA: I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event: EV_CHK_IF_PEER_CERT_NEEDS_TO_BE_FETCHED_FOR_PROF_SEL

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event:
EV_GET_POLICY_BY_PEERID

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event:
EV_SET_POLICY

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Setting configured policies

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event:
EV_VERIFY_POLICY_BY_PEERID

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event:
EV_CHK_AUTH4EAP

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_WAIT_AUTH Event:
EV_CHK_POLREQEAP

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_CHK_AUTH_TYPE

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_GET_PRESHR_KEY

*Jul 16 06:01:45.463: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_VERIFY_AUTH

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_CHK4_IC

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_CHK_REDIRECT

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Redirect check is not needed,
skipping it

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_NOTIFY_AUTH_DONE

*Jul 16 06:01:45.467: IKEv2-INTERNAL:AAA group authorization is not configured

*Jul 16 06:01:45.467: IKEv2-INTERNAL:AAA user authorization is not configured

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_CHK_CONFIG_MODE

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_SET_RECDCONFIG_MODE

*Jul 16 06:01:45.467: IKEv2-INTERNAL:Received config data from toolkit:

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_CHK_GKM

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_CHK_DIKE

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_PROC_SA_TS

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_NO_EVENT

*Jul 16 06:01:45.467: IPSEC(ipsec_get_crypto_session_id): Invalid Payload Id

*Jul 16 06:01:45.467: IKEv2-INTERNAL:IPSEC accepted group 0

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_POLICY_NEGOTIATED

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):Action: Action_Null

*Jul 16 06:01:45.467: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_VERIFY_AUTH Event:
EV_GET_CONFIG_MODE

*Jul 16 06:01:45.471: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_BLD_AUTH Event:
EV_MY_AUTH_METHOD

*Jul 16 06:01:45.471: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_BLD_AUTH Event:
EV_GET_PRESHR_KEY

*Jul 16 06:01:45.471: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_BLD_AUTH Event:

EV_GEN_AUTH

*Jul 16 06:01:45.471: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_BLD_AUTH Event:
EV_CHK4_SIGN

*Jul 16 06:01:45.471: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_BLD_AUTH Event:
EV_OK_AUTH_GEN

*Jul 16 06:01:45.471: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: R_BLD_AUTH Event:
EV_SEND_AUTH

*Jul 16 06:01:45.471: IKEv2-INTERNAL:Construct Vendor Specific Payload: CISCO-GRANITE

*Jul 16 06:01:45.471: IKEv2-INTERNAL:Construct Notify Payload: USE_TRANSPORT_MODE

*Jul 16 06:01:45.471: IKEv2-INTERNAL:Construct Notify Payload: SET_WINDOW_SIZE

*Jul 16 06:01:45.471: IKEv2-INTERNAL:Construct Notify Payload: ESP_TFC_NO_SUPPORT

*Jul 16 06:01:45.471: IKEv2-INTERNAL:Construct Notify Payload: NON_FIRST_FRAGS

*Jul 16 06:01:45.471: **IKEv2-PAK:(SESSION ID = 4,SA ID = 1):Next payload: ENCR, version: 2.0**
Exchange type: IKE_AUTH, flags: RESPONDER MSG-RESPONSE Message id: 1, length: 320

Payload contents:

VID Next payload: IDr, reserved: 0x0, length: 20

IDr Next payload: AUTH, reserved: 0x0, length: 12

Id type: IPv4 address, Reserved: 0x0 0x0

AUTH Next payload: SA, reserved: 0x0, length: 72

Auth method PSK, reserved: 0x0, reserved 0x0

SA Next payload: TSi, reserved: 0x0, length: 44

last proposal: 0x0, reserved: 0x0, length: 40

Proposal: 1, Protocol id: ESP, SPI size: 4, #trans: 3 last transform: 0x3, reserved: 0x0:
length: 12

type: 1, reserved: 0x0, id: AES-CBC

last transform: 0x3, reserved: 0x0: length: 8

type: 3, reserved: 0x0, id: SHA96

last transform: 0x0, reserved: 0x0: length: 8

type: 5, reserved: 0x0, id: Don't use ESN

TSi Next payload: TSr, reserved: 0x0, length: 24

Num of TSs: 1, reserved 0x0, reserved 0x0

TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16

start port: 0, end port: 65535

start addr: 192.168.1.1, end addr: 192.168.1.1

TSr Next payload: NOTIFY, reserved: 0x0, length: 24

Num of TSs: 1, reserved 0x0, reserved 0x0

TS type: TS_IPV4_ADDR_RANGE, proto id: 47, length: 16

start port: 0, end port: 65535

start addr: 192.168.2.1, end addr: 192.168.2.1

NOTIFY(USE_TRANSPORT_MODE) Next payload: NOTIFY, reserved: 0x0, length: 8

Security protocol id: Unknown - 0, spi size: 0, type: USE_TRANSPORT_MODE

NOTIFY(SET_WINDOW_SIZE) Next payload: NOTIFY, reserved: 0x0, length: 12

Security protocol id: Unknown - 0, spi size: 0, type: SET_WINDOW_SIZE

NOTIFY(ESP_TFC_NO_SUPPORT) Next payload: NOTIFY, reserved: 0x0, length: 8

Security protocol id: Unknown - 0, spi size: 0, type: ESP_TFC_NO_SUPPORT

NOTIFY(NON_FIRST_FRAGS) Next payload: NONE, reserved: 0x0, length: 8

Security protocol id: Unknown - 0, spi size: 0, type: NON_FIRST_FRAGS

ENCR Next payload: VID, reserved: 0x0, length: 292

*Jul 16 06:01:45.479: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:

I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: **AUTH_DONE** Event:
EV_CHECK_DUPE
*Jul 16 06:01:45.479: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: AUTH_DONE Event:
EV_CHK4_ROLE
*Jul 16 06:01:45.479: IKEv2-INTERNAL:(SESSION ID = 4,SA ID = 1):SM Trace-> SA:
I_SPI=AA81AF8C052B480F R_SPI=53457A4ACA42FD10 (R) MsgID = 1 CurState: **READY** Event: **EV_R_OK**

Referencias

<https://community.cisco.com/t5/security-documents/vrf-aware-ipsec-cheat-sheet/ta-p/3109449>
https://www.cisco.com/c/en/us/td/docs/ios/sec_secure_connectivity/configuration/guide/convert/sec_ike_for_ipsec_vpns_15_1_book/sec_vrf_aware_ipsec.html
https://www.cisco.com/c/en/us/td/docs/ios/sec_secure_connectivity/configuration/guide/convert/sec_ike_for_ipsec_vpns_15_1_book/sec_cfg_ikev2.html
[https://www.cisco.com/en/US/docs/ios-xml/ios/sec_conn_ikevpn/configuration/15-1mt/Configuring Internet Key Exchange Version 2.html](https://www.cisco.com/en/US/docs/ios-xml/ios/sec_conn_ikevpn/configuration/15-1mt/Configuring%20Internet%20Key%20Exchange%20Version%202.html)