

IOS# show ip ips configuration

- 12.3T(af af%ã,ãfšã³12.3(2)Tã€12.3(4)Tã€ãŠã,^ã³12.3(7)Tã,é™ãã)
- 12.3XQã€12.3XRã€12.3XSã€12.3XWã€12.3XXã€12.3XY
- 12.3YAã€12.3YDã€12.3YGã€12.3YHã€12.3YIã€12.3YJã€12.3YKã€12.3YMã€1
- 12.4
- 12.4MR
- 12.4T
- 12.4XAã€12.4XB

IOS# show ip ips configuration

ip ips

configurationã,³ãfžãf³ãf%ã, 'ã½ç"ã—ã¼ã™ã€ã"ã®ã,³ãfžãf³ãf%ã™ã€IPSã,ããf³ã,¹ãfš

<#root>

router#

show ip ips configuration

```

Configured Config Locations: -none-
Last signature default load time: 18:46:50 UTC Jan 5 2007
Last signature delta load time: -none-
Last event action (SEAP) load time: -none-
IPS Auto Update is not currently configured
IPS fail closed is disabled
Fastpath ips is enabled
Quick run mode is enabled
Event notification through syslog is enabled
Event notification through SDEE is enabled
Total Active Signatures: 85
Total Inactive Signatures: 61
IPS Rule Configuration
  IPS name test
IPS Category CLI is not configured
Interface Configuration
  Interface FastEthernet0/0
    Inbound IPS rule is test
    Outgoing IPS rule is not set

```

router#

show ip interface FastEthernet0/0

FastEthernet0/0 is up, line protocol is up

ã,Šã®ã¼ãšã™ã€ã,ããf³ã,ããf¼ãfã,šã,ãã,¹FastEthernet0/0ã€IPSã,'ã½ç"ã™ã€ã,^ãããã

è,†ã¼±ã€šã,'ã«ã,"ãšã,,ããã,,ã"ã"ãçç°èãã•ã,ãã€Yè£½ã"

ã»-ã

CSCsg15598(ç™»éŒ²ãfiãf¼ã,¶ã°,ç™):DYIDS:Fragmentation

CSCsg15598ã®ç°ãçfã,¹ã,³ã,çã,è™^ç

CVSS åŸ°æœ-ã,¹ã,³ã,ç - 4.7

æ”»æ’fã...fãŒ°ã†	æ”»æ’fæã»¶ã®èæ†é’ã•	[Authentication]	æ©Ÿã†æ-€šã,ã®ã½±éŸ¿	ã®Œã.
Remote	ã½žã,,	ã,è	éf^ã†çš,,	éf^ã†çš

CVSS ç¾¾çš¶ã,¹ã,³ã,ç - 3.9

æ”»æ’fã•ã,Œã,ãè½æ€š	ã©ç™ãèf½ãª¾ç-ã®ãf-ãf™ãf«	Report
æ©Ÿèf½ã™ã,<	æfã¼	çç°èª

CSCsa5334(ç™»éŒ²ãfiãf¼ã,¶ã°,ç™):bus error i

CSCsa5334ã®ç°ãçfã,¹ã,³ã,çã,è™^ç

CVSS åŸ°æœ-ã,¹ã,³ã,ç¼¾3.3

æ”»æ’fã...fãŒ°ã†	æ”»æ’fæã»¶ã®èæ†é’ã•	[Authentication]	æ©Ÿã†æ-€šã,ã®ã½±éŸ¿	ã®Œã.
Remote	ã½žã,,	ã,è	ãªã—	ãªã

CVSS ç¾¾çš¶ã,¹ã,³ã,ç - 2.7

æ”»æ’fã•ã,Œã,ãè½æ€š	ã©ç™ãèf½ãª¾ç-ã®ãf-ãf™ãf«	Report
---------------------	--------------------------	--------


```

%IPS Signature 3123:0 is marked for deletion
%IPS The signature will be deleted when signatures are reloaded or saved
router(config)#

interface FastEthernet0/0

router(config)#

no ip ips test in

router(config)#

ip ips test in

router(config)#

exit

```

```

<#root>

router#

show ip ips signature 3123

```

<#root>

router#

```
show ip ips signatures | include 3123
```

```
3123:0      N    A      MED    0      0      0    100    30 FA N    S46
```

```

<#root>

router#

show ip ips signature 3123

```

<#root>

router#

```
show ip ips signatures | include 3123
```

```
3123:0      N*   A      MED    0      0      0    100    30 FA N    S46
```

```

<#root>

router#

show ip ips signature 3123

```

<#root>

	<p>12.3(11)T10</p> <p>12.3(14)T7</p> <p>âˆ©ç””â€² èf½ãªáf—áf©ãffáf^áf•ã,©ãf¼ãfã é™ã®šã•ã,Æã</p> <p>12.4(12)ä»¥é™ã«çš»è;Æã—ã ãããããã„ã€,</p>
12.3XQ	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(12)ä»¥é™ã«çš»è;Æ</p>
12.3XR	<p>è,,†ã¼±æ€§ã,ã,Šã€,TACã«ãŠãã„ã^ã,ããããããã•ã</p>
12.3XS	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(12)ä»¥é™ã«çš»è;Æ</p>
12.3XW	<p>è,,†ã¼±æ€§ã,ã,Šã€,12.3(11)YFã»¥é™ã«çš»è;Æã—ã ãããããã</p>
12.3XX	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(12)ä»¥é™ã«çš»è;Æ</p>
12.3XY	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(12)ä»¥é™ã«çš»è;Æ</p>
12.3YA	<p>è,,†ã¼±æ€§ã,ã,Šã€,TACã«ãŠãã„ã^ã,ããããããã•ã</p>
12.3YD	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(2)T3ã»¥é™ã«çš»è;Æ</p>
12.3YG	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(2)T3ã»¥é™ã«çš»è;Æ</p>
12.3YH	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(2)T3ã»¥é™ã«çš»è;Æ</p>
12.3YI	<p>è,,†ã¼±æ€§ã,ã,Šã€ 12.4(2)T3ã»¥é™ã«çš»è;Æ</p>

12.3YJ	è,,†â¼±æ€§ã,ã,Šã€ 12.3(14)YQ8ä»¥é™ã«çš»è;Ē
12.3YK	è,,†â¼±æ€§ã,ã,Šã€ 12.4(4)Tä»¥é™ã«çš»è;Ē
12.3YM	12.3(14)YM5
12.3YQ	12.3(14)YQ8
12.3YS	è,,†â¼±æ€§ã,ã,Šã€ 12.4(4)Tä»¥é™ã«çš»è;Ē
12.3YT	è,,†â¼±æ€§ã,ã,Šã€ 12.4(4)Tä»¥é™ã«çš»è;Ē
12.3YX	12.3(14)YX3
12.3YZ	12.3(11)YZ
è©²â¼²“ã™ã,< 12.4 ãf™ãf¼ã,¹ã®ãfããfãf¼ã,¹	ãfãf“ãf«ãf%o
12.4	12.4(1c)
	12.4(3b)
	12.4(7e)i¼^2007â¹³æœ²6æ—¥ã«ã...¥æ%o<ã-èf¼i¼%o
	ã™ã¹ã ã®12.4(8)ãfããfãf¼ã,¹ã«è,,†â¼±æ€§ãĒĒã~ãœ”ã
	12.4(10b)
12.4MR	12.4(6)MR1

12.4T	12.4(2)T3
	12.4(9)T3i¼^2007â¹´4æœ^9æ—¥ã«â...¥æ%œ<â`-èf½i¼%œ
	12.4(11)T1
12.4XA	12.4(2)XA2
12.4XB	12.4(2)XB3
12.4XE	è,,†â¼±æ€§šã,,ã,šš€€,TACã«ãššã,,ã^ã,ã>ããããããã•ã

ã,æ£â^©ç”” ä°<ã¾<ã”” å...-å¼ç™°èi”

ã“ã®ã,çãf%œãfã,ãã,¶ãfããSèª-æžã•ã,CEã|ã,,ã,<è,,†â¼±æ€§šã®å...-èj”ã,,,æ,ªç””ã«é-
Cisco PSIRTã«ã`ã,,ã>ã,%œã,CEã|ã,,ã¾ãã>ã,“ã€,

ãf•ãf©ã,°ãf;ãf³ãf^ãCE-ã•ã,CEãÿãfã,±ãffãf^ãžéçã®è,,†â¼±æ€§šã-ã€ã,ã,¹ã,³ã†...éf”ãSç™°

ATOMIC.TCPã®æ£è|èj”ç¾ã«ã,^ã,<ã,µãf¼ãf”ã,¹æ<ã|ã®è,,†â¼±æ€§šã-ã€ããššã®çæš

URL

<https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20070213-iosips>

æ””¹è”,ã±¥æ´

ãf³ãf“ã,ãfšãf³ 1.0	2007â¹´2æœ^13æ—¥	ã^ã>žã...-é-<ãf³ãf³ãf¼ã,¹
-----------------------	------------------	---------------------------

ã^©ç””è!ç´,,

æœ-ã,çãf%œãfã,ãã,¶ãfããç,,ãžè”¼ã®ã,,ã®ã”ã-ã|ã”æ””ã¾ãã-ã|ãššã,šš€€

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。