

Cisco ASA

5500 Cisco ASA Firewall Services Advisory (Cisco-SA-2011-0394)



Severity: High
Published: 2011-02-23

Last Updated: 2011-02-23 16:00

Document Version: 1.0 (Final)

CVSS v3 Score: 7.8

Workarounds: None available

Cisco ASA ID:

[CVE-2011-0394](#)

[CVE-2011-0395](#)

[CVE-2011-0393](#)

[CVE-2011-0396](#)

This advisory describes a Denial of Service (DoS) vulnerability in Cisco ASA Firewall Services. This vulnerability allows an attacker to cause a denial of service on a Cisco ASA device by sending a specially crafted message to the Skinny Client Control Protocol (SCCP) port.

Affected Products

Cisco ASA

5500 Cisco ASA Firewall Services Advisory (Cisco-SA-2011-0394)

- Cisco ASA Firewall Services (ASA)
- Skinny Client Control Protocol (SCCP)
- Routing Information Protocol (RIP)
- Denial of Service (DoS)

This advisory describes a Denial of Service (DoS) vulnerability in Cisco ASA Firewall Services. This vulnerability allows an attacker to cause a denial of service on a Cisco ASA device by sending a specially crafted message to the Skinny Client Control Protocol (SCCP) port.

This advisory describes a Denial of Service (DoS) vulnerability in Cisco ASA Firewall Services. This vulnerability allows an attacker to cause a denial of service on a Cisco ASA device by sending a specially crafted message to the Skinny Client Control Protocol (SCCP) port.

This advisory describes a Denial of Service (DoS) vulnerability in Cisco ASA Firewall Services. This vulnerability allows an attacker to cause a denial of service on a Cisco ASA device by sending a specially crafted message to the Skinny Client Control Protocol (SCCP) port.

Affected Products

Module(FWSM) Cisco ASA Firewall Services Advisory (Cisco-SA-2011-0394)

This advisory describes a Denial of Service (DoS) vulnerability in Cisco ASA Firewall Services. This vulnerability allows an attacker to cause a denial of service on a Cisco ASA device by sending a specially crafted message to the Skinny Client Control Protocol (SCCP) port.

Cisco ASA Firewall Services

Cisco ASA

5500ã,·ãf^aãf^{1/4}ã,ºé♦©å¿œåž<ã,»ã,ãf¥ãf^aãftã,£ã,çãf—ãf©ã,¤ã,çãf³ã,¹ã♦~ã€♦è¤‡æ•°ã♦®è,,†å½±æ€§ã
ASAã,½ãf•ãf^ã,|ã,§ã,çã♦®ãf♦ãf^{1/4}ã,ãf§ãf³ã♦~ã€♦ç‰¹å®šã♦®è,,†å½±æ€§ã♦«ã,^ã♦£ã♦|ç•°ã♦

è,,†å½±æ€§ã♦®ã♦,ã,<èF½å”♦

å€<ã€...♦®ãf♦ãf^{1/4}ã,ãf§ãf³æf...å±ã♦«ã♦¤ã,„ã♦|ã♦~ã€♦ã♦“ã♦®ã,çãf‰ãf♦ã,¤ã,¶ãf^aã♦®ã
ãf♦ãf^{1/4}ã,ãf§ãf³ã♦šã,^ã♦³ä¿®æ£ã€♦ã,»ã,~ã,·ãf§ãf³ã,'å♦,ç...§ã♦—ã♦|ã♦?♦ã♦~ã♦•ã♦,„ã€,

ãf^ãf©ãf³ã,¹ãf§ã,çãf¬ãf³ãf^ãf•ã,¡ã,¤ã,çã,|ã,Cãf^{1/4}ãf«ãf‘ã,±ãffãf^ãf♦ãffãf•ã,¡æž~æ,‡

ãf‘ã,±ãffãf^ãf♦ãffãf•ã,¡æž~æ,‡ã♦®è,,†å½±æ€§ã♦~ã€♦ã,»ã,ãf¥ãf^aãftã,£ã,çãf—ãf©ã,¤ã,çãf³ã,¹ã
ASAã,½ãf•ãf^ã,|ã,§ã,çã♦®è¤‡æ•°ã♦®ãf♦ãf^{1/4}ã,ãf§ãf³ã♦«å½±éÝ<ã,‘ã,žã♦^ã♦?⁹ã♦™ã€,è~å®šã
transparentã♦Œå♦«ã♦³/⁹ã,Œã♦|ã♦,„ã,‘å♦~ã€♦ã,çãf—ãf©ã,¤ã,çãf³ã,¹ã♦§ãf^ãf©ãf³ã,¹ãf§ã,çã
firewallã,³ãfžãf³ãf‰ã,‘ä½ç”“ã♦—ã♦|ã€♦ãf•ã,¡ã,¤ã,çã,|ã,Cãf^{1/4}ãf«ã«å«ä½œãfçãf^{1/4}ãf‰ã,’å^¤å^¥ã♦

```
ciscoasa# show firewall
Firewall mode: Transparent
```

SCCPã,¤ãf³ã,¹ãf§ã,~ã,·ãf§ãf³ã♦«ã♦šã♦’ã,<DoSè,,†å½±æ€§

ã,¶ãf^{1/4}ãf“ã,¹æ<’å♦|ã♦®è,,†å½±æ€§ã♦~ã€♦Cisco ASA

5500ã,·ãf^aãf^{1/4}ã,ºé♦©å¿œåž<ã,»ã,ãf¥ãf^aãftã,£ã,çãf—ãf©ã,¤ã,çãf³ã,¹ã♦®SCCPã,¤ãf³ã,¹ãf§ã,~ã,·ãf§ã

ç®¡ç♦†è€...ã♦~ã€♦show service-policy | include

skinnyã,³ãfžãf³ãf‰ã,‘ä½ç”“ã♦—ã♦|ã€♦æ¬|ã♦®ä³/⁹ã♦«ç¤ºã♦™ã,~ã♦†ã♦~å‡ºåŠ›ã♦Œè¿”ã♦•ã,

```
ciscoasa# show service-policy | include skinny
Inspect: skinny, packet 0, drop 0, reset-drop 0
```

ã♦?⁹ã♦Ýã♦~ã€♦SCCPã,¤ãf³ã,¹ãf§ã,~ã,·ãf§ãf³ã♦Œæœ‰åŠ¹ã♦«ã♦~ã♦£ã♦|ã♦,„ã,·ãf‡ãf♦ã,¤ã,

```
class-map inspection_default
match default-inspection-traffic
```

!

```
policy-map global_policy
class inspection_default
```

```
...
inspect skinny
...
!
service-policy global_policy global
```

æ³·í/šã, ãf¹/4ãf“ã, ¹ãf♦ãfã, ·ãf¹/4ã♦~ã€♦å%o♦ã♦®æ³/4^oã♦«ç¤°ã♦™ã, ^ã♦†ã♦«ã€♦ã, °ãfãf¹/4ãf♦ãf»

SCCPã, ãf3ã, ¹ãfšã, ~ã, ·ãf§ãf3ã♦~ãf‡ãf•ã, ©ãf«ãf^ã♦§æœ%oåŠ¹ã♦«ã♦ã♦£ã♦!ã♦,,ã♦³/4ã♦™ã, €

RIP♦®DoSè,,†å¼±æ€§

ã, ãf¹/4ãf“ã, ¹æ<’å♦!ã♦®è,,†å¼±æ€§ã♦~ã€♦RIPã♦”Cisco Phone
Proxyæ©Ýèf½ã♦®æ-¹ã♦Œå♦Œã♦~ãf‡ãf♦ã, ã, ¹ã♦§æœ%oåŠ¹ã♦«ã♦ã♦£ã♦!ã♦,,ã, ^å ASA
5500ã, ·ãfãf¹/4ã, °é♦©å¿œåžã, »ã, ãf¥ãfãftã, £ã, çãf—ãf©ã, ã, çãf³ã, ¹ã♦®RIPå®ÝèF...ã♦«å½±éÝè
ASAã, ½ãf•ãf^ã, !ã, §ã, çãf♦ãf¹/4ã, ãf§ãf³8.0ã♦§ã, ^ã♦³8.1i/4%oã, 'ç¤°ã♦—ã♦!ã♦,,ã♦³/4ã♦™ã, €,

```
router rip
...
!
phone-proxy <instance name>
  media-termination address <IP address>
...
<Rest of phone proxy feature configuration>
```

ã♦³/4ã♦Ýã♦~i/4^Cisco ASAã, ½ãf•ãf^ã, !ã, §ã, çãf♦ãf¹/4ã, ãf§ãf³8.2ä»¥é™♦i/4%o:

```
router rip
...
!
media-termination <instance name>
  address <IP address>
...
<Rest of phone proxy feature configuration>
```

ã,»ã,ãf¥ãf^af†ã,£ã,cãf—ãf©ã,¤ã,cãf³ã,!ã—ã€◆RIPãf|ãffã,»ãf¼ã,(router rip)ã, ’å‡!ç◆†ã—ã◆|ã◆,,ã◆|ã€◆Cisco Phone

Proxyæ©Ýèf½ã◆«ã,°ãfãf¼ãf◆ãf«ã◆^ãf|ãf‡ã,£ã,¢ã,¿ãf¼ãfÝãf◆ãf¼ã,·ãf§ãf³ã,¢ãf%oãf—ã,!ã◆CE “ ASAã,½ãf•ãf^ã,|ã,§ã,¢ãf◆ãf¼ã,ãf§ãf³8.0ã◆Šã,^ã◆³8.1ã◆§ã—ã€◆ã,°ãfãf¼ãf◆ãf«ãf|ãf‡ã,£ã,¢ã ASAã,½ãf•ãf^ã,|ã,§ã,¢ãf◆ãf¼ã,ãf§ãf³8.2ä»¥é™◆ã◆§ã—ã€◆ãf|ãf‡ã,£ã,¢ã,¿ãf¼ãfÝãf◆ãf¼ã,·ãf§

<IP address> interface <interface

name>ã,’ç™oè;Œã◆™ã,<ã◆”ã◆”ã◆“ã◆«ã,^ã◆£ã◆|å®Ýè;Œã◆•ã,Œã,<ã◆”ã◆®è”å®§ã—å½±éÝ;ã,å

ãf‡ãf•ã,©ãf«ãf^ã◆§ã—ã€◆RIPã,,Cisco Phone

Proxyæ©Ýèf½ã,,æœ%oåŠ¹ã◆«ã◆^ãf|ãf‡ã,|ã◆,,ã◆³/ã◆>ã,”ã€,

ã◆æfã◆^ãf•ã,¡ã,¤ãf«ã,·ã,!ãf†ãf ã,¢ã,—ã,»ã,!ã◆®è,,†å½±æ€§ã—ã€◆ã,»ã,ãf¥ãf^af†ã,£ã,cãf—ãf© ASA

5500ã,·ãfãf¼ã,°é◆©å¿œåž•ã,»ã,ãf¥ãf^af†ã,£ã,¢ãf—ãf©ã,¤ã,cãf³ã,!ã◆«å½±éÝ;ã—ã◆³/ã◆™ã€

```
crypto ca trustpoint <trustpoint name>
  keypair <keypair name>
  crl configure
crypto ca server
crypto ca certificate chain <trustpoint name>
  certificate ca 01
  ...
!
```

http server enable

ãfãf¼ã,«ãf«CAã,ãf¼ãf◆ã—ã€◆ãf‡ãf•ã,©ãf«ãf^ã◆§ã—æœ%oåŠ¹ã◆«ã◆^ãf|ãf‡ã,|ã◆,,ã◆³/ã◆&

Cisco PIX

500ã,·ãf^aãf¼ã,ºã,»ã,ãf¥ãf^af†ã,£ã,cãf—ãf©ã,¤ã,cãf³ã,!ã◆®è,,†å½±æ€§ã,!ãf†ãf¼ã,¿

Cisco PIX

500ã,·ãf^aãf¼ã,ºã,»ã,ãf¥ãf^af†ã,£ã,cãf—ãf©ã,¤ã,cãf³ã,!ã◆—ã€◆ãf^ãf©ãf³ã,!ãf§ã,¢ãf—ãf§ãf^ãf•ã,¡ã,¤ã

Cisco PIX

500ã,·ãf^aãf¼ã,ºã,»ã,ãf¥ãf^af†ã,£ã,cãf—ãf©ã,¤ã,cãf³ã,!ã◆—ã€◆2009å¹'7æœ^28æ—¥ã◆«ã,½ãf•ãf^ã,PIX

500ã,·ãf^aãf¼ã,ºã,»ã,ãf¥ãf^af†ã,£ã,¢ãf—ãf©ã,¤ã,cãf³ã,!ã,‘ã◆”ã½¿ç”“ã◆®ã◆Šå®¢æ§~ã◆«ã◆—ã€◆ASA

5500

ASA

5500
http://www.cisco.com/en/US/prod/collateral/vpndevc/ps5708/ps5709/ps2030/end_of_life_notice_cisco_px_525_sec_app.html

ãšã, µãf ãf%4ã, °é ◊ ©å¿œåž<ã, »ã, ãf¥ãfãftã, fã, çãf—ãf©ã, ãa, çãf³ã, 1ã «çñ» è; Æã ◊™ã, <ã ◊ <ã€ ◊ã

ã, ½ãf•ãf^ã, |ã, §ã, çãf ◊ ãf%4ã, ãf§ãf³ã ◊ ®å^ ãå^ ¥æ-1æ³•

è,, †å½±æ€§ã ◊ ®ã, ã, <ãf ◊ ãf%4ã, ãf§ãf³ã ◊ ® Cisco ASA

ã, ½ãf•ãf^ã, |ã, §ã, çãf ◊ Æã, çãf—ãf©ã, ãa, çãf³ã, 1ã ◊ ãšå®ÿè; Æã ◊ |ã, „ã, <ãf<ãf ◊ ®ã, †ã ◊ <ã, 'õ

version

ã, ³ãfžãf³ãf%oã, 'ç™oè; Æã ◊ —ã ◊ ¾ã ◊™ã€, æ¬|ã ◊ ®ã¾ã ◊ —ã €◊ã, ½ãf•ãf^ã, |ã, §ã, çãf ◊ ãf%4ã, ãf§ãf³ã

ASA

5500
ASA#show version | include Version

Cisco Adaptive Security Appliance Software Version 8.3(1)

Device Manager Version 6.3(1)

Cisco Adaptive Security Device

Manager(ASDM)ã, 'ä½ç”ã—ã ◊ |ãftãf ◊ ã, ãa, 1ã, 'ç®jç ◊ †ã ◊ —ã ◊ |ã, „ã, <ãf®çæs~ã ◊ —ã€◊ã, ãf§ãf³ã

ASDMã, |ã, ãf§ãf³ãf%oã, |ã ◊ ®ã, |ã, Šéš...ã ◊ «è| „ç¤ºã ◊ •ã, Æã, <è| „ã, ½ãf•ãf^ã, |ã, §ã, çãf ◊ ãf%4ã, ãf§ã

è,, †å½±æ€§ã, 'ã ◊ «ã, "ã ◊ ãšã ◊ „ã ◊ a ã ◊ "ã ◊ "ã ◊ Æççºè a ã ◊ •ã, Æã ◊ Ÿèf½å" ◊

Cisco PIX 500ã, ·ãfãf%4ã, °ã, »ã, ãf¥ãfãftã, fã, çãf—ãf©ã, ãa, çãf³ã, 1ã ◊ —ã€◊ã, »ã, ãf¥ãfãftã, fã, Æã ◊

Module(FWSM)ã, 'é™¤ã ◊ ã€◊ã ä»—ã ◊ ®ã, ·ã, 1ã, ³èf½å" ◊ ã ◊ «ã, Šã, „ã, ã ◊ |ã, „ã, Æã, %oã ◊ ®è,, †å½±æ€§ã

è®³ç`°

Cisco ASA

5500
ASA#show version | include Version

Cisco ASA

5500
ASA#show version | include Version

ãf^ãf©ãf³ã, 1ãfšã, çãf¬ãf³ãf^ãf•ã, |ã, ãa, çã, |ã, ©ãf¹ãf«ãf‘ã, ±ãffãf^ãf ◊ ãffãf•ã, |æž—æ, †ã

ãf^ãf©ãf³ã, 1ãfšã, çãf¬ãf³ãf^ãf•ã, |ã, ãa, çã, |ã, ©ãf¹ãf«ãfçãf¹ãf%oã ◊ «è „å®šã ◊ •ã, Æã ◊ |ã, „ã, <Cisco

ASA

5500ã,·ãf^aãf^{1/4}ã,ºé♦©å¿œåž<ã,»ã,ãf¥ãf^aãftã,£ã,çãf—ãf©ã,¤ã,çãf³ã,¹ã♦~ã€♦ãf'ã,±ãffãf^ãf♦ãffãf•ã,

ç®¡ç♦†è€...ã♦~ã€♦show

blocksã,³ãfžãf³ãf%oã, ’çTMøèjŒã♦—ã♦| å‡ºåŠ>ã,'è^a;ã♦1ã€♦ä½ç”“å♦~èf½ã♦a1,550ãf♦ã,¤ãf^ãf-ãfãfj

ciscoasa# show blocks

SIZE	MAX	LOW	CNT
0	400	360	400
4	200	199	199
80	400	358	400
256	1412	1381	1412
1550	6274	0	0
...			

ã♦“ã♦®è,,†å½±æ€§ã♦~ã€♦Cisco Bug ID [CSCtj04707](#)

([çTMøèjŒ](#)ãf^{1/4}ã,¶å°,ç”“)ã♦~ã♦—ã♦| æ-‡æ>,åŒ-ã♦•ã,Œã€♦Common Vulnerabilities and Exposures(CVE)IDã♦~ã♦—ã♦| CVE-2011-

0393ã♦Œå‰²ã,Šå½“ã♦| ã,‰oã,Œã♦| ã♦,,ã♦¾ã♦™ã€,

SCCPã,¤ãf³ã,¹ãfšã,¬ã,·ãf§ãf³ã«ã♦Šã♦’ã,<DoSè,,†å½±æ€§

Cisco ASA

5500ã,·ãf^aãf^{1/4}ã,ºé♦©å¿œåž<ã,»ã,ãf¥ãf^aãftã,£ã,çãf—ãf©ã,¤ã,çãf³ã,¹ã♦~ã€♦ã,♦æ£ã♦aSCCPãf;ãffã,»

ã♦“ã♦®è,,†å½±æ€§ã♦~é€šé♦Žãf^ãf©ãf•ã,£ãffã,¬ã♦«ã,^ã♦fã♦| ã♦®ã♦çå½•ã♦~ã♦èµ·ã♦“ã♦•ã,C

ã♦“ã♦®è,,†å½±æ€§ã♦~ã€♦Cisco Bug ID [CSCtg69457](#)

([çTMøèjŒ](#)ãf^{1/4}ã,¶å°,ç”“)ã♦~ã♦—ã♦| æ-‡æ>,åŒ-ã♦•ã,Œã€♦Common Vulnerabilities and Exposures(CVE)IDã♦~ã♦—ã♦| CVE-2011-

0394ã♦Œå‰²ã,Šå½“ã♦| ã,‰oã,Œã♦| ã♦,,ã♦¾ã♦™ã€,

RIPã♦®DoSè,,†å½±æ€§

Cisco ASA

5500ã,·ãf^aãf^{1/4}ã,ºé♦©å¿œåž<ã,»ã,ãf¥ãf^aãftã,£ã,çãf—ãf©ã,¤ã,çãf³ã,¹ã♦~ã€♦æœ‰oåŠ¹ã♦aRIPã,çãffã,

Phone

Proxyæ©Ýèf½ã♦®ã,¡æ-¹ã♦Œæœ‰oåŠ¹ã♦«ã♦~ã♦fã♦| ã♦,,ã,å`å♦~ã♦«ã♦®ã♦çè,,†å½±ã♦§ã♦

æ³”i½å½±eÝ;ã,’å♦—ã♦’ã,«è`å®šã♦§ã♦~ã€♦ã,ºãfãf½ã♦ãf«ãf|ãf‡ã,£ã,çã,çãf½ãfÝãf♦ãf½ã,·ãf§ãf ASAã,½ãf•ãf^ã,|ã,§ã,çãf♦ãf½ã,ãf§ãf³8.0ã♦Šã,^ã♦³8.1ã♦§ã”“ã,€å♦~èf½ã♦~è`å®šã,ºãf—ã,·ãf§ãf ASAã,½ãf•ãf^ã,|ã,§ã,çãf♦ãf½ã,ãf§ãf³8.2ã»¥é™♦ã♦§ã♦~ã€♦ãf|ãf‡ã,£ã,çã,çãf½ãfÝãf♦ãf½ã,·ãf§ãf

ã“ã®è,,†å½±æ€§ã“ã€Cisco Bug ID [CSCtg66583](#)

([CVE-2011-0395](#)) IDã“ã—ã|æ-‡æ›,åŒ-ã•ã,Œæ€Common Vulnerabilities and Exposures(CVE)IDã“ã—ã|CVE-2011-0395ãŒå‰²ã,Šå½“ã|ã,‰oã,Œã|ã„ã¾ã™ã€,

ã“æ£ã“ãƒ•ã,¡ã,¤ãf«ã,·ã,¹ãƒtãf ã,çã,“ã,»ã,¹ã®è,,†å½±æ€§

Cisco ASA

5500ã·ãfãf1/4ã,ºéŒå¿œåž<ã,»ã,ãƒ¥ãfãf†ã,£ã,çãf—ãf@ã,¤ã,çãf³ã,¹ã“ã€ã,»ã,ãƒ¥ãfãf†ã,£ã,çãf—ã

ASAã½ãf•ãf•ã,|ã,§ã,çã,¤ãf|ãf1/4ã,ã€ãf‡ã,ã,çãf«è”¼æ~Žæ,ã“ãœŒã“ãœ©Yå¬†æf...å±ãŒå“ã“ã®è,,†å½±æ€§

ã“ã®è,,†å½±æ€§ã“ã€Cisco Bug ID [CSCtk12352](#)

([CVE-2011-0396](#)) IDã“ã—ã|CVE-2011-0396ãŒå‰²ã,Šå½“ã|ã,‰oã,Œã|ã„ã¾ã™ã€,

å›žé?¿ç-

ã“ã®Ciscoã»ã,ãƒ¥ãfãf†ã,£ã,çãf‰oãfã,¤ã,¶ãfãšã“ã€è¤‡æ°ºã“ã®å€[å^¥ã](#)ã®è,,†å½±æ€§

ãf^ãf©ãf³ã,¹ãfšã,çãf¬ãf³ãf^ãf•ã,¡ã,¤ã,çã,|ã,©ãf1/4ãf«ãf‘ã,±ãffãf^ãfãffãf•ã,¡æž¬æ,‡ã

ã“ã®è,,†å½±æ€§ã“ã¬å¾ã™ã,å›žé?¿ç-ã,ã,Šã¾ã»ã,“ã€,

SCCPã,¤ãf³ã,¹ãfšã,“ã,·ãf§ãf³ã“ã“ã“Šã“ã,«DoSè,,†å½±æ€§

SCCPã,¤ãf³ã,¹ãfšã,“ã,·ãf§ãf³ãŒä,?è|?ã“å‘å?“ã€?ç,,jåŠ¹ã“ã“ã“ã“šã€?ã?“ã“ã“inspect

skinnyã,³ãfžãf³ãf‰oã,’çTM“è;Œã—ã|ã€SCCPã,¤ãf³ã,¹ãfšã,“ã,·ãf§ãf³ã,’ç,jåŠ¹ã“ã“ã“šã?ã“ã¾ã“ã

RIPã®DoSè,,†å½±æ€§

Cisco

ASAã½ãf•ãf^ã,¡ã,§ã,çãfãf1/4ã,ãf§ãf³8.0ã“Šã,“ã“8.1ã“ã¬å¾ã™ã,å›žé?¿ç-ã,ã,Šã¾ã“ã“ã“

ASAã½ãf•ãf^ã,¡ã,§ã,çãfãf1/4ã,ãf§ãf³8.2ã“¥é™ã“ã“§ã“ã€?ç®jç“tè€...ã“ç‰¹å®šã“ã,¤ãf³ã

router rip

...

!

```
media-termination <instance name>
address <IP address> interface <interface name>
```

!

<Rest of phone proxy feature configuration>

ä,♦æ£ä♦¤äf•ä,¡ä,¤äf«ä,·ä,¹äftäf ä,çä,¬ä,»ä,¹ä♦®è,,†å¼±æ€§

ä♦“ä♦®è,,†å¼±æ€§ä♦«å¬¾ä♦™ä,<å>žé♦¿ç–ä♦¬ä♦,ä,šä♦¾ä♦>ä,”ä€,

ä;®æ£æ,^ä♦¿ä,½äf•äf^ä,|ä,sä,c

ä,çäffäf—ä,°äf¬äf¹/₄äf%oä,’æ¤œè„žä♦™ä,<å ’å♦^ä♦¬ä€♦<http://www.cisco.com/go/psirt>

ä♦”å¾Œç¶šä♦®ä,çäf%oäf♦ä,¤ä,¶äf¤ä,,å♦,ç...§ä♦—ä♦|ä€♦å•♦é;Œä♦®è§fæ±°çŠ¶æ³♦ä♦”å®ä,½äf¤äf¥äf¹/₄ä,·äf§äf³ä,’ç¢°è^ä♦—ä♦|ä♦¤ä♦ã♦¤ä♦,ã♦¤ä♦„ä€,

ä♦,,ä♦šä,Œä♦®å ’å♦^ä,,ä€♦ä,çäffäf—ä,°äf¬äf¹/₄äf%oä♦™ä,<æ©ÿå™”ä♦«å♦¤ä^tä♦¤äfjäfçäf¤ä¤

Technical Assistance

Centerï¼^TACï¼‰oä♦¾ä♦ÿä♦¬å¥'ç’„ä,’çµ♦ä,“ä♦§ä♦,,ä,<äfjäf³äftäf§äf³ä,¹äf—äf¤äf♦ä,¤äf¤äf¹/₄ä♦«ä♦šå•♦ä♦„ä♦^ä♦>ä♦¤ä♦ã♦¤ä♦„ä♦¤ä♦„ä€,

è,,†å¼±æ€§

äf^äf©äf³ä,¹äfšä,çäf¬äf³äf^äf•ä,¡ä,¤ä,çä,|ä,©äf¹/₄äf«äf‘ä,±äffäf^äf♦äffäf•ä,jæž¬æ,‡ä♦®è,,†å¼±æ€§([SCtj04707](#))

SCCPã,¤ãf³ã,¹ãfšã,¬ã,·ãf§ãf³ã♦®DoSè,,†å¼±æ€§([CSCtg69457](#))

RIPã♦®DoSè,,†å¼±æ€§([CSCtg66583](#))

æZ·å¥·äf^aäf^{1/4}ä,¹
æ¬jä®è¡”ä«ää€ä®™ä¹ä®!ä®æZ·å¥·äf^aäf^{1/4}ä,¹ä,’ç¤°ä®—ä®³/4ä®™ä€,ä®”ä,Œä,%oä®

æZ·å¥·äf^aäf^{1/4}ä,¹

æ¬jä®è¡”ä«ää€ä®™ä¹ä®!ä®æZ·å¥·äf^aäf^{1/4}ä,¹ä,’ç¤°ä®—ä®³/4ä®™ä€,ä®”ä,Œä,%oä®

äf;ä, äffäf ^{1/4} äf ^a äf ^a äf ^{1/4} ä,¹	æZ·å¥·äf ^a äf ^{1/4} ä,¹
7.0	7.0(8.12)í¹/4^2011å¹’2æœ^ä,æ—¬ä®«å...¥æ‰o<ä®—èf½í¹/4‰o

7.1	7.2(5.2)» ®ç§»è;Œ
7.2	7.2i ^{1/4} ^5.2i ^{1/4} %o
8.0	8.0i ^{1/4} ^5.23i ^{1/4} %o
8.1	8.1(2.49)i ^{1/4} ^2011å¹³æœ^å^æ—¬æ«æææææé—<å§ <i>i</i> 1/4%o
8.2	8.2i ^{1/4} ^4.1i ^{1/4} %o
8.3	8.3i ^{1/4} ^2.13i ^{1/4} %o
8.4	8.4(1)

Cisco ASA Firewall Software

Cisco ASA Firewall Software

Center » Cisco.com Software Navigator.html » [Products] > [Cisco ASA Firewall Appliances] > [Cisco ASA Firewall Series] > [Cisco ASA Software] > [Cisco ASA Firewall Software]

5500 Series Adaptive Security Appliances] > <Cisco ASA Firewall Software>

[Cisco ASA Software] > [Cisco ASA Firewall Software]

Cisco ASA Firewall Software

Cisco ASA Firewall Software is a comprehensive security solution for enterprise networks. It provides advanced threat protection, including intrusion prevention, antivirus, and anti-spam features. Cisco ASA Firewall Software is designed to be easy to install and manage, with a user-friendly interface and a range of configuration options.

The Cisco ASA Firewall Software is available for download from the Cisco website. It is compatible with most major operating systems and can be easily integrated into existing network infrastructure.

If you have any questions or need further assistance, please contact Cisco Support. We are here to help you get the most out of your Cisco ASA Firewall Software.

URL

<https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20110223-asa>

æ”’è”,å±¥æ‘

ãf ^a f“ã, „ãf§ãf ³ 1.0	2011å¹`2æœ^23æ—¥	å^?å›žå...¬é—<ãf ^a ãf ^a f¼ã, ¹
---	------------------	---

å^©ç”’è!?ç‘,

æœ¬ã,¢ãf‰oãf♦ã,¤ã,¶ãf^aã?“ç„¡ä¿?è”¼ã?®ã,,ã?®ã?“ã?—ã?|ã?“æ?♦?ä¾?ã?—ã?|ã?|ã?Šã,Šã€æœ¬ã,Cãf‰oãf♦ã,¤ã,¶ãf^aã?®æf...å±ã?Šã,^ã?³ãf^af³ã,¬ã?®ä½?ç”“ã?«é-Cã?™ã,<è²¬ä»»ã?®ä,€ã?¾ã?Ýã€?ã,·ã,¹ã,³ã?“æœ¬ãf‰oã,ãf¥ãf|ãf³ã?®å†...å®¹ã,’ä°^å’Šã?“ã?—ã?«å¤‰oæ>ã?—ã?æœ¬ã,¢ãf‰oãf♦ã,¤ã,¶ãf^aã?®è”~è?°å†...å®¹ã?«é-Cã?—ã?|æf...å±é...?ä¿jã?® URL
ã,’çœ?ç•¥ã?—ã€?å?~ç<-ã?®è»Cè¼‰oã,,æ,,?è”³ã,’æ-½ã?—ã?Ýå’å?^ã€?å½?ç¤¾ã?Œç®¡ç?ã?“ã?®ãf‰oã,ãf¥ãf|ãf³ã?®æf...å±ã?~ã€?ã,·ã,¹ã,³è£½å“?ã?®ã,“ãf³ãf‰oãf!ãf¼ã,¶ã,’å?¾è±ã?

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。