

Typhoon™ af1/4ã, 1ã @ãf©ã, ðãf³ã, «ãf¼ãf%ã, 'æ è¼%ã —ã ĘCisco ASR

9000ã, ·ãfªãf¼ã, °ãf«ãf¼ã, çã ¯ã€ãã"ã®è,, †ã¼±æ€šã®ã½±éÿçã, 'ã —ã'ã¾ã™ã€,ã"ã

ã"ã®è,, †ã¼±æ€šã®ã, æfã^©ç"ã Çã ¯èf¼ãªãã®ãã ¯ã€ã BVIã, 'ã»ã —ã |ã·ã,%

Cisco IOS

XRã, ½ãf·ãf^ã, |ã, §ã, çã šã ¯ã€ããfãf·ã, ©ãf«ãf^ã šBVIã€ã uRPFã€ã PBRã€ã QoSã€ãã šã, ^ã€ã

BVIã Çããfãfãã, ðã, 1ã šè ¯ã®šã·ã, Çã |ã,,ã, <ã<ã©ã†ã<ã, 'çç°èªã™ã, <ã«ã ¯ã€ã

show running-config | include bviç%ª¹æ"©EXECã, ³ãfžãf³ãf%ã, 'ã½çç"ã —ã¾ã™ã€,

interface bviã Ç show running-config | include

bviã ¯ã€ã BVIã Çè ¯ã®šã·ã, Çã |ã,,ã, <ã"ã ¯ã, 'ççªã —ã¾ã™ã€,

ã»ã, <ã«ã show running-config | include

bviã, ³ãfžãf³ãf%ã, 'ã€ã BVIã Çè ¯ã®šã·ã, Çã ĘCisco IOS

XRã, ½ãf·ãf^ã, |ã, §ã, çã, 'ã®ÿè; Çã —ã |ã,,ã, <ãfãfãã, ðã, 1ã šã®ÿè; Çã —ã¾ã™ã€,

```
RP/0/RSP0/CPU0:router(admin)# show running-config | include bvi
interface bvi 50
```

ã, ðãf³ã, çãf¼ãf·ã, §ã, ðã, 1ã š uRPFã Çææ%ãš¹ã «ãªã£ã |ã,,ã, <ã<ã©ã†ã<ã, 'çç°èªã™ã

show running-config | include verifyç%ª¹æ"©EXECã, ³ãfžãf³ãf%ã, 'ã½çç"ã —ã¾ã™ã€, ipv4

verify unicast source reachable-via rxã Ç show running-config | include

verifyã ¯ã€ã uRPFã Çææ%ãš¹ã šãã,ã, <ã"ã ¯ã, 'ççªã —ã¾ã™ã€,

ã»ã, <ã«ã show running-config | include "verify

source"ã, ³ãfžãf³ãf%ã, 'ã€ã uRPFæ©ÿèf¼ã Çææ%ãš¹ã «ãªã£ã |ã,,ã, <ãCisco IOS

XRã, ½ãf·ãf^ã, |ã, §ã, çã, 'ã®ÿè; Çã —ã |ã,,ã, <ãfãfãã, ðã, 1ã šã®ÿè; Çã —ã¾ã™ã€,

ã, ðãf³ã, çãf¼ãf•ã, §ã, ðã, ¹ã S QoSã Cæœ%ããš¹ã «ãªã£ã |ã,,ã,ã<ã©ãtä<ã,çç°èã

show running-config | include service-

policyç%ã¹æ©EXECã,³ãfžãf³ãf%ãã, 'ã½ç'ã—ã¾ã™ã€, service-policy inputã¾ãÿã

service-policy outputã C show running-config | include service-

policyã-ã€QoSã Cèã@šã•ã, Cã |ã,,ã,ã"ãã,çç°ã—ã¾ã™ã€,

ã»ÿã,ã<ã«ã€ **show running-config | include service-**

policyã,³ãfžãf³ãf%ãã, 'ã€QoSæ©ÿèf½ã Cèã@šã•ã, CãÿCisco IOS

XRã,½ãf•ãfã, |ã,šã,çã,'ã@ÿè; Cã—ã |ã,,ã,ãfžãfã, ðã, ¹ã Sã@ÿè; Cã—ã¾ã™ã€,

```
RP/0/RSP0/CPU0:router(admin)# show running-config | include service-policy
service-policy input test_in
service-policy output test_out
```

Cisco ASR

9000ã,ãfªãf¼ã,°ã,ðãf¼ã,ðfãffãfãf©ã,ðãf³ã,«ãf¼ãf%ãã Rç¬2ã,-ã»£ã-ã€Typhoonãf™ãf¼ã,

ãf—ãfã,»ãffã,µi¼^NPi¼%ã«ç"±æÿã—ã¾ã™ã€,

æ¬ã Rãf©ã,ðãf³ã,«ãf¼ãf%ãã Typhoonãf™ãf¼ã,¹ã Sã™ã€,

- A9K-MOD80-SE
- A9K-MOD80-TR
- A9K-MOD160-SE
- A9K-MOD160-TR
- A9K-24X10GE-SE
- A9K-24X10GE-TR
- A9K-36X10GE-SE
- A9K-36X10GE-TR
- A9K-2X100GE-SE
- A9K-2X100GE-TR
- A9K-1X100GE-SE
- A9K-1X100GE-TR

ASR

9000ã,·ãfãf1/4ã,°ãf«ãf1/4ã,¿ã®ãf©ã,ªãf³ã,«ãf1/4ãf%ããⓂTyphoonãf™ãf1/4ã,1ã«ã©ãtã«ã,çç°

show

diagã,³ãfžãf³ãf%ãã,²ã1/2ç”ã—ã³/4ã™ã€è²ã1/2”ã™ã,ãf†ãfã,ªã,1ã«ã-ã€ã’ããããã

24X10GE-

SEã,«ãf1/4ãf%ããⓂEã,çã,ãf†ã,£ãf-ã«ããã£ã|ã,,ã,ãf†ãfã,ªã,1ã,çç°ã—ã|ã,,ã³/4ã

RP/0/RSP0/CPU0:router(admin)# show diag

Mon Jun 22 12:55:10.554 PST

NODE module 0/RSP0/CPU0 :

MAIN: board type 0x100302

!--- output truncated

NODE module 0/1/CPU0 :

MAIN: board type 0x20207

S/N: FOC123081J6

Top Assy. Number: 68-3182-03

PID: A9K-24X10GE-SE

UDI_VID: V1D

HwRev: V0.0

New Deviation Number: 0

CLEI:

Board State : IOS XR RUN

PLD: Motherboard: N/A, Processor: 0x8004 (rev: 2.2), Power: N/A

ROMMON: Version 1.0(20081208:174521) [ASR9K ROMMON]

!--- output truncated

æ³1/4š4 .3.1ã,^ã,šã%ãã®Cisco IOS

XRã,1/2ãf·ãf^ã,1ã,šã,çã®ãfããfãf1/4ã,1ã-ã€ãã”ã®è,,†ã1/4±æ€šã®ã1/2±éÿã,ã—ã’ã³/4ã

è,,†ã1/4±æ€šã,²ã«ã,“ãšã,,ããã,,ã”ã”ãⓂçç°èããã,ⓂEãÿè1/2ã”

ã

“ã®è,,tå¼±æ€šã®å½±éÿ¿ã,å—ã’ã,ã®ã¯€Typhoonãf™ãf¼ã,¹ã®ãf©ã,ãã³ã,«ã
ASR 9000ã,·ãªãf¼ã,°ãf«ãf¼ã,¿ãã’ãšã™ã€,
Cisco ASR 9001ãšã,^ã³Cisco ASR 9001-
Sãf«ãf¼ã,¿ã¯€ã’ã®è,,tå¼±æ€šã®å½±éÿ¿ã,å—ã’ã¾ã™ã€,

æ³’i¼š4 .3.1ã,^ã,šã%ã®Cisco IOS
XRã,½ãf·ãf^ã,|ã,šã,çã®ãfªãfªãf¼ã,¹ã¯€ãã’ã®è,,tå¼±æ€šã®å½±éÿ¿ã,å—ã’ã¾ã™ã€

Tridentãf™ãf¼ã,¹ã®ãf©ã,ãã³ã,«ãf¼ãf%ãã,æè¼%ã—ãÿCisco ASR
9000ã,·ãªãf¼ã,°ãf«ãf¼ã,¿ã¯€ãã’ã®è,,tå¼±æ€šã®å½±éÿ¿ã,å—ã’ã¾ã™ã>ã,“ã€,ASF
9000ã,·ãªãf¼ã,°ã,ããf¼ã,µãfãffãf^ãf©ã,ãã³ã,«ãf¼ãf%ãã®ç¬¬1ã,-ã»£ã¯€ãTridentãf™ãf¼ã

æ¬¡ã®ãf©ã,ãã³ã,«ãf¼ãf%ãã¯€Tridentãf™ãf¼ã,¹ãšã™ã€,

- A9K-40GE-L
- A9K-40GE-B
- A9K-40GE-E
- A9K-4T-L
- A9K-4T-B
- A9K-4T-E
- A9K-8T/4-L
- A9K-8T/4-B
- A9K-8T/4-E
- A9K-2T20GE-L
- A9K-2T20GE-B
- A9K-2T20GE-E
- A9K-8T-L
- A9K-8T-B
- A9K-8T-E
- A9K-16T/8-B

ã»ã®ã,·ã,¹ã,³è£½ã”ã«ãšã,,ã|ã€ãã’ã®ã,çãf%ããfã,ãã,¶ãããã®å½±éÿ¿ã,å—ã

è©³ç’°

Cisco ASR 9000ã,·ãªãf¼ã,°ã,çã,°ãfªã,²ãf¼ã,·ãfšãf³ã,µãf¼ãf“ã,¹ãf«ãf¼ã,¿(ASR)ç”ã®Cisco IOS

ã"ã®è,,t¼±æ€šã-ã€æ-ã®Cisco IOS

XRã,½ãf•ãf^ã,|ã,sã,çãfãf³ãfãf³ãf³ã,¹ã,çãffãf—ãfãf¼ãf^(SMU)ãšà®æ£ã•ã,£ã|ã,,ã¾ã

- asr9k-px-4.3.4.CSCur62957.pie¼^ãfãf¼ã,ãfšãf³4.3.4ç"i¼%o
- asr9k-px-5.1.2.CSCur62957.pie¼^ãfãf¼ã,ãfšãf³5.1.2ç"i¼%o
- asr9k-px-5.1.3.CSCur62957.pie¼^ãfãf¼ã,ãfšãf³5.1.3ç"i¼%o
- asr9k-px-5.2.2.CSCur62957.pie¼^ãfãf¼ã,ãfšãf³5.2.2ç"i¼%o
- asr9k-px-5.3.0.CSCur62957.pie¼^ãfãf¼ã,ãfšãf³5.3.0i¼%o

æ³i¼š 4.3.1ã,^ã,šã%ã®Cisco IOS

XRã,½ãf•ãf^ã,|ã,sã,çã®ãfãfãf¼ã,¹ã-ã€ã"ã®è,,t¼±æ€šã®ã½±éÿã,ã—ãã¾ã

æ³i¼šè;½ãšãfãf¼ã,ãfšãf³ç"ã®Cisco IOS

XRã,½ãf•ãf^ã,|ã,sã,çSMUã-ã€ã©ç"ã-èf½ã«ãã£ãÿæ™,ç,¹ãšã...-é-ãã,£ã¾ã

ä,æ£ã^©ç"ã°ã¾ã"ã...-ã¼ç™è;''

Cisco Product Security Incident Response

Team¼^PSIRTi¼%ã-ã€æœ-ã,çãf%ãfã,ã,¶ã,¶ãfãã«è"~è¼%ã•ã,£ã|ã,,ã,è,,t¼±æ€šã

ã"ã®è,,t¼±æ€šã-ã€ããšã®çæš~ã®ã,±ãf¼ã,¹ã®èªæÿ»ãã«Cisco

TACã«ã,^ã£ã|ç™è|ãã,£ã¾ã—ãÿã€,

URL

<https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-20150415-iosxr>

æ"¹è,,ã±¥æ'

ãfãf"ã,ãfšãf³ 1.1	2015 å¹´ 4 æœˆ 17 æ—¥	ã%ã>´ãã,£ãÿè©²ã½"ãfããfãf¼ã,¹
ãfããf"ã,ãfšãf³ 1.0	2015å¹´4æœˆ15æ—¥	ã^ç%ã^ãfããfãf¼ã,¹

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。