

af#af a,ma,1a «a1/2±eY;a,a Sã 1/4a —ã 3/4a™ã€€HTTP

a,mãf1/4ãf æ©Y`èf1/2ã @ãf#ãfãã,©ãf«ãf^ã @çS¶æ...ã ¯ã€ãfãf1/4ã,ãfSãf³ã «ã,^ã £ã |ç•

è,,†ã1/4±æ€§ã CEã~ãœ¨ã™ã, Cisco IOS XE a,1/2ãfãf^ã,|ã,šã,ç

ãfãfãfãf1/4ã,1ã «ã ¢ã,,ã |ã ¯ã€ãã “ã @ã,çãf%ããfãã,ãã,¶ã,¶ãfãã @ã€CEã¿@æ£æ,^ã ¿ã,1/2ã

HTTP a,mãf1/4ãf è¨ã@šã @çç°èª

HTTP

a,mãf1/4ãf æ©Y`èf1/2ã CEãf#ãfãã,ma,1ã Sæœ%ããš1ã ¤ã ©ã ¤ã ¤ã ¤ã,çç°èªã™ã,ã «ã ¯ã€ã

CLI a S show running-config | include ip http server|secure-

serverã,ãfžãf³ãf%ãã,ã1/2¿ç¨ã —ã |ã€ãã,ããfãf1/4ãfãfãã,ãf³ãfãã,£ã,@ãf¥ãfããfãã,ãfSãf³ã «ip

http serverã,ãfžãf³ãf%ãã 3/4ã Yã ¯ ip http secure-

serverã,ãfžãf³ãf%ãã CEã~ãœ¨ã™ã,ã ¤ã ¤ã ©ã ¤ã ¤ã ¤ã,çç°èªã —ã 3/4ã™ã€ãã ©ã |ã,ãã

a,mãf1/4ãf æ©Y`èf1/2ã CEæœ%ããš1ã Sã™ã€€,

ã»¥ã,ã «ã€ show running-config | include ip http server|secure-

serverã,ãfžãf³ãf%ãã,çç°èª;CEã —ã 3/4ã™ã€€,

<#root>

Router#

show running-config | include ip http server|secure-server

ip http server
ip http secure-server

af#af a,ma,1e¨ã@šã «ã ©ã;ã,%ãã ¤ã @ã,ãfžãf³ãf%ãã CEã «ã 3/4ã,CEã |ã,,ã,ãã ¤ã^ã

a,mãf1/4ãf æ©Y`èf1/2ã CEæœ%ããš1ã «ãªã £ã |ã,,ã 3/4ã™ã€€,

ã%è¿ããã,ãfžãf³ãf%ãã @ã†ããšãã «æ-|ãã @ãt...ãã1ã,,ãã «ã 3/4ã,CEã |ã,,ãã ¤ã^ã

ip http active-session-modules none
ip http secure-active-session-modules none

ã “ã @ãf#ãfãã,ma,1ã ¯ã€ãã “ã @ã,çãf%ããfãã,ãã,¶ã,¶ãfãã «è¨è1/4%ãããã,CEã Y`è,,†ã1/4±æ€§ã

Cisco IOS XE a,1/2ãfãf^ã,|ã,šã,çãfããfããf1/4ã,1ã @ã^ãã^¥

af#af a,ma,1ã,šã Sã@Y`è;CEããã,CEã |ã,,ã, Cisco IOS XE a,1/2ãfãf^ã,|ã,šã,ç

afafaf1a,1a~a€ç@çtè€...ã€æf#afã,ã,1ã«afã,ã,ãfãã—ã|ã€CLIãS
show version a,3ãfzãfãf%ã,'ã®ÿè;CEã—ã€è;ç°ãã,CEã,ã,ã,1ãftãf
ãfãfSãf1ã,'ã,ç...Sã™ã,ãã“ã”ã«ã,^ã,Šçç°èããããããã™ã€ã,ãfãfã,ã,ã,1ã
Cisco IOS XEã,½ãfãf^ã,|ã,šã,çã,'ã®ÿè;CEã—ã|ã,ã,ã,ã'ã^ã€ã,ã,1ãftãf
ãfãfSãf1ã«ã€CECisco IOS Softwareã€ã€ã€CECisco IOS XE
Softwareã€ã€ã€ã€©ã€®ãftã,ã,1ãfã€CE;ç°ãã,ã,CEã¾ã™ã€,

æ¬ã«ã€Cisco IOS XRã,½ãfãf^ã,|ã,šã,çããfãfãf1ã,16.2.1
ã€ã®ÿè;CEãã,CEã|ã,ã|ã€ã,ããfã,1ãfãfãfãfããã,CEã|ã,ã,ã,ããfãfãfã,ããã
CAT3K_CAA-UNIVERSALK9-M
ããšã,ã,ãfãfãã,ã,1ãšã®ã,3ãfzãfãf%ã®ã†°ãŠ>ã¾ã,'ç°ã—ã¾ã™ã€,

```
<#root>  
  
ios-xe-device#  
  
show version
```

Cisco IOS Software, Catalyst L3 Switch Software (CAT3K_CAA-UNIVERSALK9-M), Version Denali 16.2.1, REL
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2016 by Cisco Systems, Inc.
Compiled Sun 27-Mar-16 21:47 by mcpre
.
.
.

Cisco IOS XEã,½ãfãf^ã,|ã,šã,çã
ãfãfãf1ã,1ã®ã'½ããã”ã”ã°ãã»ããã®è|ã%ããã«è-ãã™ã,èç°ãã—ã€ã€ãŽCisco
[IOS and NX-OS Software Reference Guide](#)ã€ã,'ã,ç...Sã—ã|ãããããããã,ã€,

è,†ã¼±æ€šã,'ã«ã,“ããšã,,ãããã,,ãã“ã”ã€çç°èããã,CEãÿè½ã”ã
ããã®ã,çãf%ãããã,ã,ã,ãfããã®è,†ã¼±æ€šãã®ãã,ã,è½ã”ãã,»ã,ã,ãfSãfãã«è”è¼%ãããã

ã,ã,1ã,3ã~ã€ãã“ã®è,,†ã¼±æ€šãã€CE Cisco IOSã,½ãfãf^ã,|ã,šã,çã€Cisco IOS XR
ã,½ãfãf^ã,|ã,šã,çããããšã,^ã³ Cisco NX-OS
ã,½ãfãf^ã,|ã,šã,çãããã”ã½±éÿã,ã,Žã^ãããã,,ãã“ã”ã,'çç°èãã—ã¾ã™ã—ãÿã€,

ãžéç-

ããã®è,,†ã¼±æ€šãã«ã¾ã†|ã™ãã,ãžéç-ããã,ã,šã¾ãããã,ã€,

HTTP
ã,ãfãfãf

© 2014 Cisco and/or its affiliates. All rights reserved. Cisco Confidential
no ip http server
secure-Server

no ip http server
secure-Server

no ip http server
secure-Server

end-user-license-agreement.html

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

Technical Assistance

Technical Assistance

Technical Assistance

<https://www.cisco.com/c/en/us/support/web/tsd-cisco-worldwide-contacts.html>

<https://www.cisco.com/c/en/us/support/web/tsd-cisco-worldwide-contacts.html>

Cisco IOS Software Checker

Check Cisco IOS Software Version

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Cisco IOS Software Checker

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

- **show version** command output (e.g., 15.1(4)M2) and device model (e.g., 3845) to check the software version.
- **show version** command output (e.g., 15.1(4)M2) and device model (e.g., 3845) to check the software version.
- **show version** command output (e.g., 15.1(4)M2) and device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

[IOS Software Checker](#) - Check the software version of your Cisco IOS device.

IOS Software Checker

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Check Cisco IOS Software Version

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

(e.g., 3845)

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Cisco IOS XE Software Version Checker

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

Enter the IOS version string (e.g., 15.1(4)M2) and the device model (e.g., 3845) to check the software version.

[Notes](#) - Check the software version of your Cisco IOS XE device.

ãf◆ãf¼ã,ãfšãf³	èª-æ~Ž	ã,»ã,ã,ãfšãf³	ã,¹ã,
1.0	å^◆å>žå...-é-<ãfªãfªãf¼ã,¹	-	Final

å^©ç””è!◆ç´,,

æœ-ã,çãf%ãf◆ã,ãã,¶ãfªã◆ç,,jäç◆è”¼ã◆@ã,,ã◆@ã◆”ã◆—ã◆|ã◆”æ◆◆ã¼ã◆—ã◆|ã◆šã,šã€
æœœ-ã,çãf%ããf◆ã,ãã,¶ãfªã◆@æf...å±ã◆šã,^ã◆³ãfªãf³ã,ã◆@ã½ç””ã◆«é-çã◆™ã,<è²-ã»ã◆@ã,€
ã◆¾ã◆ÿã€◆ã,ã,¹ã,³ã◆æœœ-ãf%ãã,ãfãf;ãf³ãf^ã◆@å†...å®¹ã,’ã°^ãšã◆ªã◆—ã◆«ã¼ãœ’ã◆—ã◆
æœœ-ã,çãf%ããf◆ã,ãã,¶ãfªã◆@è”~èç°å†...å®¹ã◆«é-çã◆—ã◆|æf...å±é...◆äjã◆@ URL
ã,’çœ◆ç•¥ã◆—ã€◆å◆~ç<-ã◆@è»çè¼%ãã,,æ,,◆è”³ã,’æ-½ã◆—ã◆ÿã’ã◆^ã€◆å½”ç¾¾ã◆€ç@çç◆
ã◆”ã◆@ãf%ãã,ãfãf;ãf³ãf^ã◆@æf...å±ã◆æœœ-ã,ã,¹ã,³è£½ã”◆ã◆@ã,“ãf³ãf%ããf¼ã,¶ã,ã”¾è±jã

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。