

Cisco NX-OS

ã,½ãf•ãf^ã,|ã,§ã,çã «ã Šã 'ã, <èª è ¨¼ã •ã,Œ



ã,çãf%ãfã,ã,¶ã,¶ãfããf¼ID : cisco-sa-

[CVE-2021-](#)

3000-9000-fileaction-QtLzDRy2

[1361](#)

â^â...-é-<æ—¥ : 2021-02-24 16:00

æœ€gæ>´æ-°æ—¥ : 2021-03-08 20:56

ãfãf¼ã,ãfšãf³ 1.2 : Final

CVSSã,¹ã,³ã,ç : [9.8](#)

â>žéç- : Yes

Cisco ãfã,° ID : [CSCvw89875](#)

æ—¥æœ-èªžã «ã, ^ã, <æf...â ±ã -ã€ è<±èªžã «ã, ^ã, <ãŽYæ-#ã ®é çã...-ã¼ã

æ!,è!?

Cisco NX-OS ã,½ãf•ãf^ã,|ã,§ã,çã,¹ã@ÿè;Œæ—ã |ã,ã,ã,ã,½ã,çãfãf%ã,çãfãf³ NX-OS

ãfçãf¼ãf%ã® Cisco Nexus 3000 ã,ãfãf¼ã,°ã,¹ã,¶ãffãfã Šã, ^ã³ Cisco Nexus 9000

ã,ãfãf¼ã,°

ã,¹ã,¶ãffãfã®ãt...éfãfã,ã,¶ãf«ç®çtã,µãf¼ãf"ã,¹ã®ã®ÿè£...ã®è,,tã¼±æ€šã «ã, ^ã, Šã€

ã"ã®è,,tã¼±æ€šã -ã€ TCP ãfãf¼ãf^ 9075

ãŒæå-éfãæŽ¥ç¶šè! æ±,ã,¹ãfãffã,¹ãf³ã—ã |ãçœç"ã™ã,ã, ^ãtã «èªã£ã |èã®šã •ã

ãfãf¼ãf^ 9075ã®ãfãf¼ã,«ãf«ã,¶ãf³ã,çãf¼ãfã,šã,¶ã,¹ã «èã®šã •ã,Œæ |ã,ã, < IP

ã,çãf%ãf-ã,¹ã «ã€ç°ã¥ã •ã,Œæãÿ TCP

ãfã,±ãffãfã,é€ãçãã™ã,ã"ã"ã «ã, ^ã, Šã€ã"ã®è,,tã¼±æ€šã,¹ã,ã,ã,¹ãf-ãfã,¶ãfã™

ã,ã,¹ã,³ã -ã"ã®è,,tã¼±æ€šã «ã³ã¶!ã™ã,ã,½ãfãf^ã, |ã,šã,çã,çãffãf-ãfãf¼ãf^ã,¹ãfãfãf¼ã

ã"ã®ã,çãf%ãfã,ã,¶ã,¶ãfãã -ã€æ-ã®ãfããfã,ã, ^ã,Šçç°èªãšããã³ãã™ã€,

<https://sec.cloudapps.cisco.com/security/center/content/CiscoSecurityAdvisory/cisco-sa-3000-9000-fileaction-QtLzDRy2>

ã"ã®ã,çãf%ãfã,ã,¶ã,¶ãfãã -ã€ 2021 ã¹ 2 æœ^ã «ã...-é-<ã •ã,Œæÿ Cisco FXOS

ã Šã, ^ã³ NX-OS ã,½ãfãf^ã, |ã,šã,çã®ã,»ã,ãfãfãfãfã,£ã,çãf%ãfã,ã,¶ã,¶ãfã

ãfãfãf%ãf«ã®ã,€éfãšã™ã€,ã,çãf%ãfã,ã,¶ã,¶ãfãã®ã®Œæ...ãªãfãã,¹ãfã"ã"ããã

[Event Response: February 2021 Cisco FXOS and NX-OS Software Security Advisory Bundled](#)

[Publication](#)ã€ã,ã,ç...šã—ã |ãããããããã,ã€,

è©²å½“è£½å“?

è,†å¼±æ€§ã®ã,ã,«è£½å”

æœ¬èè,†å¼±æ€§ã¬ã€Cisco NX-OS ã½ãfãfã,|ã,sã,çãfãfãfã,¹ 9.3(5)

ã¼ãÿã¬ãfãfãfã,¹ 9.3(6)

ã,å®Yè;Cã—ã|ã,,ã,«æ¬ã®ã,ã,¹ã,³è£½å”ã«å½±éÿã,ä,Žã^ã¼ã™ã€,

- Nexus 3000 ã.ãfãfã,°ã,¹ã,¬ãfãfã
- ã,¹ã,¼ãfãf%ã,çãfãf³ NX-OS ãfçãf¼ãf%ã® Nexus 9000 ã.ãfãfã,°ã,¹ã,¬ãfãfã

ã”ã,Cã,%ã®ãfãfã,¬ã,¹ã¬ãfãfã,©ãf«ãf^ã§èè,†å¼±ã§ã™ã€,

ãfãfã,¬ã,¹ã,ççèªã™ã,ã«ã¬ã€show sockets connection | include 9075

CLIã,³ãfžãfãf%ã,¹ã½ç”ã—ã¼ã™ã€ã,³ãfžãfãf%ã<ã,%ãå†°ãš>ãCè:”ã•ã,Cããã,,ã

<#root>

nexus#

show sockets connection | include 9075

tcp LISTEN 0 32 * :

9075

:

ã,³ãfžãfãf%ã<ã,%ãæ¬ã«ã,€è†ã™ã,ãå†°ãš>ãCè:”ã•ã,Cããÿã’ã¬ã€ãç®ã€ã€©

<#root>

nexus#

show sockets connection | include 9075

tcp LISTEN 0 32 *%v

eobc:9075

:

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

`bash guestshell`

`ssh -i ipsec@nx-os`

Guides and Articles

[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

`ssh -i ipsec@nx-os`

`ssh -i ipsec@nx-os`

<https://www.cisco.com/c/en/us/products/end-user-license-agreement.html>

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

`ssh -i ipsec@nx-os`

`ssh -i ipsec@nx-os`

`ssh -i ipsec@nx-os`

`ssh -i ipsec@nx-os`

`ssh -i ipsec@nx-os`

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

`ssh -i ipsec@nx-os`

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

`ssh -i ipsec@nx-os`

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

Technical Assistance

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

[cisco-worldwide-](#)

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting

»[Cisco NX-OS Software Devices - Use Authentication, Authorization, and Accounting](#)

3000 S, ^ 39000, .afaf, a, 1a, mafaf S Cisco NX-

OS, 1/2af^a, |a, sa, cafafaf, 19.3(5) S, ^ 39.3(6) SSMU, 'a1/2c' a S a 3/4 TM ae-

SMU a, Cisco.com a R Software Center a a, %afca, |afafafaf%a S a 3/4 TM a,

- nxos.CSCvw89875-n9k_ALL-1.0.0-9.3.5.lib32_n9000.rpm
- nxos.CSCvw89875-n9k_ALL-1.0.0-9.3.6.lib32_n9000.rpm

a "a, Ca, %a R Cisco Nexus a, 1a, mafaf a a' Cisco NX-OS

a, 1/2af^a, |a, sa, ca « S a, < SMU

a @afca, |afafafaf%a a a, maf^a, 1af^afaf« R e^3c' a «a ma, a | a a e^2a1/2" a TM a,

NX-OS a, .a, 1aftaf c@; c t a, 3afaf.a, Ea, R afafaf-af/4a, .afsf a, -a, maf% [e±e^z]

a @a CE Performing Software Maintenance

Upgrades a a, a, c... sa — a | a a a a .a, a,

- [Cisco Nexus 3000 Series Switches](#)
- [Cisco Nexus 9000 Series Switches](#)

a a R a — a R af a, 1/2af/4a, 1

Cisco Nexus a, 1a, mafaf a a «aeae e^ a a Cisco NX-OS

a, 1/2af^a, |a, sa, cafafafaf, 1a R ae± a R sa «es>a — a | a, maf af/4af^a Ca...e | a a a 'a ^a

a, caf%af a, ma, |af a S, ^a, Sa — a — a, afafafaf/4a, 1a Ca Z' a ¥ a a, Ca | a, a, a ^a

[Cisco MDS a, .afaf/4a, a, 1a, mafaf](#)

[Vmware a, 1a, mafaf a a' Cisco Nexus 1000V](#)

[Cisco Nexus 3000 Series Switches](#)

[Cisco Nexus 5500 af — af @afaf^af.a, Caf/4af a, 1a, mafaf](#)

[Cisco Nexus 5600 af — af @afaf^af.a, Caf/4af a, 1a, mafaf](#)

[Cisco Nexus 6000 Series Switches](#)

[Cisco Nexus 7000 Series Switches](#)

[Cisco Nexus 9000 Series Switches](#)

[ACI afcaf/4af%a R Cisco Nexus 9000 a, .afaf/4a, a, 1a, mafaf](#)

Cisco UCS

a, 1/2af^a, |a, sa, ca «aeae e^ a a afafafaf/4a, 1a, 'c^e^a a TM a, a «a a — a afaf a, ma, 1a R afaf

a, ae fa ^ c' a a < a 3/4 a a a ... - a 1/4 c TM e i

Cisco Product Security Incident Response

Team 1/4 ^ PSIRT 1/4 %a a ae - a, caf%af a, ma, |af a «e ~ e 1/4 %a a, Ca | a, a, e, t a 1/4 ± ae S a

a ^ a ... ,

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。