

自分の ESA がオープン リレーとして使用されることを防ぐにはどうしますか。

目次

[質問](#)

質問

自分の ESA がオープン リレーとして使用されることを防ぐにはどうしますか。

公共リスナーの受信者のアクセス表 (RATS) の受信者のドメインを規定したこと、そして「すべての」エントリが拒否するために「設定されることを開いたリレーが、確かめるので使用からの ESA を保護するために。 RATS エントリは Mail Policies タブの GUI によって、追加することができます。示す例は CLI によって RATS にドメインを、「example.com」追加する方法を下記にあります。

```
mail.example.com> listenerconfig
```

```
Currently configured listeners:
```

1. InboundMail (on PublicNet, 172.19.1.80) SMTP TCP Port 25 Public
2. OutboundMail (on PrivateNet, 172.19.2.80) SMTP TCP Port 25 Private

```
Choose the operation you want to perform:
```

- NEW - Create a new listener.
- EDIT - Modify a listener.
- DELETE - Remove a listener.
- SETUP - Change global settings.

```
[ ]> edit
```

```
Enter the name or number of the listener you wish to edit.
```

```
[ ]> 1
```

```
Name: InboundMail
```

```
Type: Public
```

```
Interface: PublicNet (172.19.1.80/24) TCP Port 25
```

```
Protocol: SMTP
```

```
Default Domain:
```

```
Max Concurrency: 1000 (TCP Queue: 50)
```

```
Domain Map: Disabled
```

```
TLS: No
```

```
SMTP Authentication: Disabled
```

```
Bounce Profile: Default
```

```
Use SenderBase For Reputation Filters and IP Profiling: Yes
```

```
Footer: None
```

```
LDAP: Off
```

```
Choose the operation you want to perform:
```

- NAME - Change the name of the listener.
- INTERFACE - Change the interface.
- LIMITS - Change the injection limits.
- SETUP - Configure general options.
- HOSTACCESS - Modify the Host Access Table.
- RCPTACCESS - Modify the Recipient Access Table.
- BOUNCECONFIG - Choose the bounce profile to use for messages injected on

this listener.

- MASQUERADE - Configure the Domain Masquerading Table.
- DOMAINMAP - Configure domain mappings.

[> **rcptaccess**

Recipient Access Table

There are currently 1 recipients.

Default Access: REJECT<

Choose the operation you want to perform:

- NEW - Create a new entry.
- EDIT - Modify an entry.
- IMPORT - Import a table from a file.
- EXPORT - Export the table to a file.

[> **new**

Enter the recipient address for this entry.

Hostnames such as "example.com" and "[1.2.3.4]" are allowed.

Partial hostnames such as ".example.com" are allowed.

Usernames such as "postmaster@" are allowed.

Full email addresses such as "joe@example.com" or "joe@[1.2.3.4]" are allowed.

Separate multiple addresses with commas.

[> **example.com**

Select the action to apply to this address:

1. Accept
2. Reject

[1]>

Would you like to specify a custom SMTP response? [N]>

Would you like to bypass receiving control for this entry? [N]>

Recipient Access Table

There are currently 2 recipients.

Default Access: REJECT

Choose the operation you want to perform:

- NEW - Create a new entry.
- EDIT - Modify an entry.
- DELETE - Remove an entry.
- PRINT - Display all entries.
- IMPORT - Import a table from a file.
- EXPORT - Export the table to a file.
- CLEAR - Remove all entries.

[> **print**

ironport.com ACCEPT

ALL REJECT

「すべての」エントリが拒否するために「設定されることに注意して下さい。明確に受け入れられるために設定されないこのエントリによりシステムはあらゆるホストからのメッセージを拒否します。