

200/300, ·āf^aāf^{1/4}, °āfžāf ♦āf^{1/4}ā, āf%oā, 'ā, ☒āffāf◀

© Rcs, ,

Remote Authorization Dial-In User

Service(RADIUS) – å...fåŒ-•ã,Œã?Ýã,»ã,ãƒ¥ãƒªãƒ†ã,£ã,çãƒ¼ã,ãƒ†ã,–ãf?ãƒ£ã,'æŒ?ã?¤ã

é♦©ç”“å♦¬èƒ½ã♦ªãƒ‡ãƒ♦ã,¤ã,¹ | ã,½ãƒ•ãƒ^ã,|ã,§ã,¢ãƒ♦ãƒ¼ã,ãƒ§ãƒ³

- SF/SG 200° 1.2.9.x
 - SF/SG 300° 1.2.9.x

RADIUS® ©

æ‰œé † 1

Web浏览器的安全性 >

RADIUS®é †ã«é®, æŠžã—ã³/4™ã€, RADIUSfšäf¹/ã, ãŒé-<ã?ã?ã³/4™ã€,

RADIUS

RADIUS Accounting: Port Based Access Control (802.1X, MAC Based)
 Management Access
 Both Port Based Access Control and Management Access
 None

Use Default Parameters

IP Version: Version 6 Version 4

Retries: (Range: 1 - 10, Default: 3)

Timeout for Reply: sec. (Range: 1 - 30, Default: 3)

Dead Time: min. (Range: 0 - 2000, Default: 0)

Key String: Encrypted
 Plaintext (0/128 Characters Used)

Buttons: Apply | Cancel

	Server	Priority	Key String(Encrypted)	Timeout for Reply	Authentication Port	Accounting Port	Retries	Dead Time	Usage Type
0 results found.									

Action Buttons: Add... | Edit... | Delete

Display Sensitive Data As Plaintext

ã?“ã?®è”~äº[ã?®ç»åf](#)ã?~ã€[SG300](#)ãfçäf‡ãf«ã?®ã,¹ã,¤ãffãf^{ã?}[®ã,,ã?](#)[®ã](#)?§ã?™ã€,

æ‰œé † 2

RADIUS

Accounting $f \bullet \tilde{a}, \tilde{f}^1 / 4 \tilde{f} \ll \tilde{f} \% \tilde{a}$ $\diamond \tilde{\tilde{s}} \tilde{a} \tilde{\tilde{\epsilon}}$ $\diamond \tilde{\tilde{a}} \tilde{\tilde{-}} \tilde{\tilde{j}}$ $\tilde{\tilde{a}}$ $\diamond \tilde{\tilde{R}}$ $\tilde{\tilde{a}}$ „ $\tilde{\tilde{a}}$ $\tilde{\tilde{\diamond}}$ $\tilde{\tilde{s}}$ $\tilde{\tilde{a}}$, $\tilde{\tilde{E}}$ $\tilde{\tilde{a}}$ $\tilde{\tilde{\diamond}}$ $\tilde{\tilde{a}}, \tilde{\tilde{'}}$ $\tilde{\tilde{a}}$, $\tilde{\tilde{-}}$ $\tilde{\tilde{a}}$ $\tilde{\tilde{f}}$ $\tilde{\tilde{a}}$ $\tilde{\tilde{f}}$ $\tilde{\tilde{f}}$, $\tilde{\tilde{-}}$ $\tilde{\tilde{a}}$ $\tilde{\tilde{\diamond}}$ $\tilde{\tilde{-}}$ $\tilde{\tilde{a}}$ $\tilde{\tilde{\diamond}}$ $\tilde{\tilde{3}}$ $\tilde{\tilde{/}}$ $\tilde{\tilde{a}}$ $\tilde{\tilde{\diamond}}$ $\tilde{\tilde{T}}$ $\tilde{\tilde{a}}$ $\tilde{\tilde{\epsilon}}$,

æ‰œé † 3

Use Default

Parameters: Retries, Radius, μ

æ‰é † 4

Timeout for

Reply-Address: f14af<af%o@RADIUS,μf14af@³™,å„è„è™@ejCE®æ™,é-”l¼

æ‰é † 5

Dead

Time•f•ã,f•f^{1/4}•f«•f%oã◆«ã€◆ã,¹ã,¤ãffãf◆ã◆Œå¿œç"ã◆—ã◆ã◆„RADIUSã,µãf^{1/4}f◆ã,'deadã◆"ã◆

æ‰œé † 6

Key

- Encrypteddi¹/4šā¹¥ā²®āf‡āf²ā,¤ā,¹ā²<ā,%oæš—å²·åŒ-ä²•ä,Œä²¥ā,äf¹4ä²Œä²,ä,<å²·å²^ä²—
 - äf—äf—äf¹4äf³äf†ä,¤,¹äf^i¹/4šå¹¥ā²®äf‡äf²ä,¤ä,¹ä²<ä,%oæš—å²·åŒ-ä²•ä,Œä²¥ā,äf¹4ä²Œä²

ā, ¹āf†āffāf—7

Apply, $\text{aff}^{\text{RADIUS}}$, $\mu\text{af}^{\frac{1}{4}}$

RADIUS, πr^2 / $\frac{1}{4}\pi d^2$ $\diamond \diamond \diamond$ $\circ \circ \circ$ $\times \times \times$

„ã“ „ã® „» „ã· „ãƒ§ „ãƒ“ „ã€“ 200/300 „ã· „ãƒ„ „ãƒ¼ „ãƒž „ãƒ“ „ãƒ¼ „ãƒ‰ „ã· „ãƒff „ã“ «RADIUS»

æ‰œé † 1

Web浏览器的安全性 >

RADIUS®é †ã?«é ?, æŠžã?—ã?¾ã?™ã€, RADIUSfšãf¼ã?, ã?Œé-ã?ã?¾ã?™ã€,

RADIUS Table									
	Server	Priority	Key String(Encrypted)	Timeout for Reply	Authentication Port	Accounting Port	Retries	Dead Time	Usage Type
0 results found.									
Add...	Edit...	Delete							

æ‰œé † 2

RADIUS Table, »ä, -ä, -äf§äf³ä, §ä€, Add, 'ä, -äf^aäffä, -ä —ä, ¾ä, TMä€, Add Radius Server, |ä, fäf³äf%ä, |ä, Eèj „ç¤°ä, •ä, Eä, ¾ä, TMä€,

ç ¾åce „ ã ® RADIUS, µäf¼äf ã, 'ç .. é>†ã ?™ã, <ã ?«ã ?-ã € Editã, 'ã, -ã fªffã, -ã ?—ã ? | ã € ? RADIUS

Server Definition:	<input checked="" type="radio"/> By IP address <input type="radio"/> By name
IP Version:	<input type="radio"/> Version 6 <input checked="" type="radio"/> Version 4
IPv6 Address Type:	<input type="radio"/> Link Local <input checked="" type="radio"/> Global
Link Local Interface:	<input type="button" value="None"/>
Server IP Address/Name:	<input type="text" value="192.168.1.20"/>
Priority:	<input type="text" value="1"/> (Range: 0 - 65535)
Key String:	<input checked="" type="radio"/> Use Default <input type="radio"/> User Defined (Encrypted) <input type="password"/> <input type="radio"/> User Defined (Plaintext) <input type="text" value=""/> (0/128 Characters Used)
Timeout for Reply:	<input checked="" type="radio"/> Use Default <input type="radio"/> User Defined <input type="text" value="Default"/> sec. (Range: 1 - 30, Default: 10)
Authentication Port:	<input type="text" value="1812"/> (Range: 0 - 65535, Default: 1812)
Accounting Port:	<input type="text" value="1813"/> (Range: 0 - 65535, Default: 1813)
Retries:	<input checked="" type="radio"/> Use Default <input type="radio"/> User Defined <input type="text" value="Default"/> (Range: 1 - 10, Default: 5)
Dead Time:	<input checked="" type="radio"/> Use Default <input type="radio"/> User Defined <input type="text" value="Default"/> min. (Range: 0 - 2000, Default: 5)
Usage Type:	<input checked="" type="radio"/> Login <input type="radio"/> 802.1x <input type="radio"/> All

æ‰œé † 3

Server

Definition $f(x) = x^{1/4}$ für $x \geq 0$ ist eine Funktion, die die Wurzel aus x liefert.

- By Name: RADIUS, πr^2 , $\frac{4}{3}\pi r^3$, πd^2 , $\pi \times 3.14 \times r^2$, $\pi \times 3.14 \times d^2$, $\pi \times 3.14 \times \frac{d}{2}^2$, $\pi \times 3.14 \times \frac{d}{2} \times \frac{d}{2}$, $\pi \times 3.14 \times \frac{d}{2} \times \frac{d}{2} \times \frac{d}{2}$

- By IP

Address: RADIUS, <http://192.168.1.1>, <http://192.168.1.1>

æ‰é † 4

IP

Version 4.0 - Afffah - Version 4.0 - TM

æ‰é † 5

IPv6, cf%oaf-¹, ; af—² ®IP³, cf%oaf-¹, ; af—² | af² af¹/4, af³ af⁶ | Cfé, æSžæ•, D

- äf^af³ä, -äf^af^{1/4}ä, «äf^af^{1/4}ä» ä, €ä, ®äf^af^{1/4}ä, -äf^af³ä, -ä, Šä, ®äf^a, ¹äf^a ä, ®ä, ¿ä, 'è~ä~ä'
 - ä, °äf^af^{1/4}äf^af^{1/4}ä» -ä, ®äf^af^{1/4}ä, -ä, ä, %oå~°é, "å, èf^{1/2}ä, ^IPv6ä, çäf%oäf-ä, ¹ä€

æ‰œé † 6

IPv6 %f%o f- , 1 , ; f— ♦ .. ♦ — ♦ | Link

Local Ä Æ é œ Š ž ä • å Æ ä | ä „ ä , ä , ä å ä ^ ä — ä € ä Link Local

ā, āf†āffāf—7

Server IP

Address/Name: RADIUS, IP: 192.168.1.1, Port: 1645, Shared Secret: 123456

æ‰é † 8

Priority f , $\text{f}^1 \text{f}^2 \text{f}^3 \text{f}^4 \text{f}^5 \text{f}^6 \text{f}^7 \text{f}^8 \text{f}^9 \text{f}^{10}$, f^{RADIUS} , f^{Radius} — f^{C} , f^{G}

æ‰œé † 9

[ä,ääf¹/₄æ-‡å—å^—]ääf•ää,ääf¹/₄äf<äf%oä♦§ä€♦æ¬jä♦®ä♦„ä♦šä,Œä♦<ä,'ä,—äf^aäffä,—ä♦—ä♦¾ä♦™ä€,

- Use Default (Encrypted) — $\text{æ} \rightarrow \text{æ}$, $\text{æ} \rightarrow \text{æ}$, $\text{æ} \rightarrow \text{æ}$
 - User Defined — $\text{æ} \rightarrow \text{æ}$, $\text{æ} \rightarrow \text{æ}$, $\text{æ} \rightarrow \text{æ}$

æ‰œé † 10

[è;”ä;]ä♦®ä,¿ä,¤äf ä,çä,|äf^]äf•ä,£äf%äf«äf‰ä♦§ä€♦æ¬ä♦®ä♦,,ä♦šä,Œä♦<ä,'ä,—äf¤äffä,—ä♦—ä

- Use Default — RADIUS , User Defined

æ‰œé † 11

Authentication

Portã•ã,£ãf¹/₄ãf«ãf‰oã «ã€♦ RADIUSã,µãf¹/₄ãf♦ã♦Œèª♦è „½ã «ã½ç”“ã♦™ã,«UDPãf♦ãf¹/₄ãf^ã,’ã...»

æ‰œé † 12

Accounting

Portã•ã,£ãf¹/₄ãf«ãf‰oã «ã€♦ RADIUSã,µãf¹/₄ãf♦ã♦Œã,çã,«ã,¡ã³ãftã,£ãf³ã,ºã «ã½ç”“ã♦™ã,«UDPãf»

æ‰œé † 13

[ã†♦è© ¡èŒ]ãf•ã,£ãf¹/₄ãf«ãf‰oã «ã€♦ æ¬jã♦®ã „ã♦šã,Œã♦<ã,'ã,¬ãf³ãffã,¬ã♦—ã♦¾ã♦™ã€,

- Use Defaulti¹/₄šãf‡ãf•ã,©ãf«ãf^ã€¤ã, ’ã½ç”“ã♦—ã♦¾ã♦™ã€,
- ãf|ãf¹/₄ã,¶ãf¹/₄ã®šç³/4©i¹/₄šç•ºã♦ºã,«ã€¤ã, ’ã½ç”“ã♦—ã♦¾ã♦™ã€,RADIUSã,µãf¹/₄ãf♦ã♦,ã♦®æŽ¥

æ‰œé † 14

Dead Timeãf•ã,£ãf¹/₄ãf«ãf‰oã «ã€♦ æ¬jã♦®ã „ã♦šã,Œã♦<ã,'ã,¬ãf³ãffã,¬ã♦—ã♦¾ã♦™ã€,

- Use Defaulti¹/₄šãf‡ãf•ã,©ãf«ãf^ã€¤ã, ’ã½ç”“ã♦—ã♦¾ã♦™ã€,
- ãf|ãf¹/₄ã,¶ãf¹/₄ã®šç³/4©i¹/₄šç•ºã♦ºã,«ã€¤ã, ’ã½ç”“ã♦—ã♦¾ã♦™ã€,ã,¹ã,¤ãffãf♦ã♦Œå¿œç”ã♦—ã♦

æ‰œé † 15

æ€Œæ½ç”“ã,çã,¤ãf—ã♦ãf•ã,£ãf¹/₄ãf«ãf‰oã «ã€♦ æ¬jã♦®ã „ã♦šã,Œã♦<ã,'ã,¬ãf³ãffã,¬ã♦—ã♦¾ã♦™ã€,

- ãfã,ºã,¤ãf³i¹/₄šã,¹ã,¤ãffãf♦ã♦®ç®jç♦†è€...ã,’èª♦è „½ã «ã½ç”“ã♦—ã♦¾ã♦™ã€,
- 802.1x:RADIUSã,µãf¹/₄ãf♦ã♦—ã€♦802.1xãf♦ãf¹/₄ãf^ãf™ãf¹/₄ã,¹ã♦®ãf♦ãffãf^ãf^ãf¹/₄ã,¬ã,çã,¬ã,»ã
- Alli¹/₄šã,¡æ—¹ã♦®ã,çã,¤ãf—ã♦®èª♦è „½ã «ã½ç”“ã♦—ã♦¾ã♦™ã€,

æ‰œé † 16

[APPLY] ã,’ã,¬ãf³ãffã,¬ã♦—ã♦¾ã♦™ã€,

RADIUS

RADIUS Accounting: Port Based Access Control (802.1X, MAC Based)
 Management Access
 Both Port Based Access Control and Management Access
 None

Use Default Parameters

IP Version:	Version 6 Version 4
<input checked="" type="radio"/> Retries:	<input type="text" value="5"/> (Range: 1 - 10, Default: 3)
<input checked="" type="radio"/> Timeout for Reply:	<input type="text" value="10"/> sec. (Range: 1 - 30, Default: 3)
<input checked="" type="radio"/> Dead Time:	<input type="text" value="5"/> min. (Range: 0 - 2000, Default: 0)
Key String:	<input checked="" type="radio"/> Encrypted <input type="text" value="mslIBwBuYnGQnhHOZ"/> <input type="radio"/> Plaintext <input type="text" value=""/> <small>(0/128 Characters Used)</small>

RADIUS Table

<input checked="" type="checkbox"/>	Server	Priority	Key String(Encrypted)	Timeout for Reply	Authentication Port	Accounting Port	Retries	Dead Time	Usage Type
<input checked="" type="checkbox"/>	192.168.1.20	1	mslIBwBuYnGQnh...	10	1812	1813	5	5	Login

Buttons: Add... Edit... Delete

Display Sensitive Data As Plaintext

æ‰é † 17

í¼^ã, ^f—ã, ·f§ãf³í¼‰RADIUSã, þf¼ãf♦ã,'å‰Šé™¤ã♦™ã, <ã♦«ã♦—ã€♦RADIUS Table, »ã, —ã, ·ãf§ãf³ã♦§ã€♦å‰Šé™¤ã♦™ã, <RADIUSã, þf¼ãf♦ã♦®ãf♦ã, §ãffã, —ãfœãffã, —ã, ^ã, 'ã, ^ã,

RADIUS è♦è ° ¼

RADIUSã, þf¼ãf♦ã,'é♦©å^‡ã♦«è ° å®šã♦—ã♦Ýã, %oã€♦ã, ^ã, §ãffãf♦ã♦§ã♦§ã♦®ã, þf¼ãf♦ã,'è

æ‰é † 1

Webè°å®šãf|äf¼ãf†ã, fãf^äf†ã, fã♦«ãfã, °ã, §ãf³ã♦—ã€♦**Security > Management Access**

Authentication♦®é †ã♦«é♦, æŠžã♦—ã♦¾ã♦™ã€, *Management Access*

Authenticationãf¼ã, , ã♦Œé—ã♦ã♦ã♦¾ã♦™ã€,

Management Access Authentication

Application: Console

Optional Methods: Selected Methods:

RADIUS	Local
TACACS+	
None	

Apply Cancel

The screenshot shows the 'Management Access Authentication' dialog box. In the 'Optional Methods' list, 'RADIUS' is highlighted with a red oval. Below it are 'TACACS+' and 'None'. To the right, under 'Selected Methods', is a single item 'Local'. At the bottom are 'Apply' and 'Cancel' buttons.

æ‰œé † 2

Optional Methodså‘, å‘f^ä§ä€♦RADIUSä‘, æŠžä♦—ä♦¾ä♦™ä€,

Management Access Authentication

Application: Console

Optional Methods: Selected Methods:

RADIUS	Local
TACACS+	
None	

Apply Cancel

The screenshot shows the 'Management Access Authentication' dialog box. In the 'Optional Methods' list, 'RADIUS' is highlighted with a blue dotted selection. To its right, a red circle highlights the 'Move to Selected' button (a right-pointing arrow). Below it are 'TACACS+' and 'None'. Under 'Selected Methods', there is one item 'Local'. At the bottom are 'Apply' and 'Cancel' buttons.

æ‰œé † 3

>äƒœä¿äƒ³ä¿, ’ä¿äƒªäffa, —ä♦¾ä♦™ä€,

Management Access Authentication

Application: Console

Optional Methods: Selected Methods:

TACACS+	Local
None	RADIUS

Apply Cancel

The screenshot shows the 'Management Access Authentication' dialog box. In the 'Optional Methods' list, 'TACACS+' and 'None' are listed. To its right, a red circle highlights the 'Move to Selected' button. Below it is 'Local'. Under 'Selected Methods', 'RADIUS' is listed. At the bottom are 'Apply' and 'Cancel' buttons.

æ‰œé†4

[APPLY] ,’äf“äffa,—ä♦—ä♦¾ä♦™ä€,

翻訳について

シスコは世界中のユーザにそれぞれの言語でサポート コンテンツを提供するために、機械と人による翻訳を組み合わせて、本ドキュメントを翻訳しています。ただし、最高度の機械翻訳であっても、専門家による翻訳のような正確性は確保されません。シスコは、これら翻訳の正確性について法的責任を負いません。原典である英語版（リンクからアクセス可能）もあわせて参照することを推奨します。