

Perguntas frequentes sobre o serviço Cloudcenter Manager-4.8.2 e a localização dos arquivos alterados

Contents

[Introduction](#)

[Como verificar se o servidor de gerenciamento está funcionando corretamente?](#)

[Como reiniciar o Management Server?](#)

[Como reiniciar o servidor de difusão?](#)

[Como reiniciar o servidor de configuração no CCM?](#)

[Como reiniciar o servidor de notificações no CCM?](#)

[Como reiniciar o serviço cliente-administrador no CCM?](#)

[Onde estão localizados os arquivos de log do CloudCenter?](#)

[Onde está o local do assistente de configuração do CCM CloudCenter?](#)

[Onde as configurações do CCM são salvas após a execução do Assistente de configuração?](#)

[Onde a configuração de log-stash do ELK é salva no CCM ?](#)

Introduction

Este documento descreve a localização dos arquivos que foram alterados.

Como verificar se o servidor de gerenciamento está funcionando corretamente?

1. Faça login no CloudCenter Manager com SSH.
2. Verifique se o servidor de gerenciamento é executado usando o comando.

```
[root@ip-172-31-78-238 sysconfig]# systemctl status mgmtserver.service
mgmtserver.service - Management Server
   Loaded: loaded (/etc/systemd/system/mgmtserver.service; enabled; vendor preset: disabled)
   Active: inactive (dead) since Fri 2017-11-10 16:55:31 UTC; 15s ago
   Process: 2732 ExecStart=/bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/mgmtserver.war
   (code=killed, signal=TERM)
   Main PID: 2732 (code=killed, signal=TERM)
```

```
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: / ____| | | |
____| | | | | \ / |
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: | | | | ____ _ _ _ | | | |
_ | | _ _ _ | \ / | _ _ _ _ _ _ _ _ _ _
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: | | | | / _ \| | | | / _` | | | / _ \
'_ \ | __/ _ \ '___| | | \ / | / _ \| ' _ \| / _ \| / _ \|
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: | |____| | ( ) | | ( | |____| _/
```

```

| | | | | _/ | | | | ( | | | | ( | | ( | | _/ |
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: \____|_| \____/ \_,_| \_,_| \____\____|_|
|_| \____\____|_| |_| |_| \____, |_| |_| \____, |_| \____|_|
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: _/ |
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: |____/
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: packager : (v4.8.2-SNAPSHOT), Powered by
Spring Boot : 1.5.8.RELEASE
Nov 10 16:55:31 ip-172-31-78-238.ec2.internal systemd[1]: Stopping Management Server...
Nov 10 16:55:31 ip-172-31-78-238.ec2.internal systemd[1]: Stopped Management Server.
[root@ip-172-31-78-238 sysconfig]#

```

Como reiniciar o Management Server?

Todos os serviços foram alterados para systemctl, portanto é necessário executar o comando systemctl para reiniciar o servidor de gerenciamento.

```

[root@ip-172-31-78-238 sysconfig]# systemctl restart mgmtserver.service
[root@ip-172-31-78-238 sysconfig]#

```

```

-----

[root@ip-172-31-78-238 sysconfig]# systemctl status mgmtserver
mgmtserver.service - Management Server
   Loaded: loaded (/etc/systemd/system/mgmtserver.service; enabled; vendor preset: disabled)
   Active: active (running) since Fri 2017-11-10 15:19:20 UTC; 1h 27min ago
   Main PID: 601 (sh)
   CGroup: /system.slice/mgmtserver.service
           601 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/mgmtserver.war
           611 /bin/bash /usr/local/cliqr/apps/mgmtserver.war
           667 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true -
Xms2048m -Xmx4096m -Djava.security.egd=file:/dev/./urandom -jar
/usr/local/cliqr/apps/mgmtserver.war

```

```

Nov 10 15:19:20 ip-172-31-78-238.ec2.internal sh[601]: logger: Executing configuration set by
user
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: _____
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: / _____ | | | | /
_____| | | | | \ / |
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: | | | | _____ - - _| | | _____ -
- | | _____ - - | \ / | _____ - - - - - - - - - -
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: | | | | / _ \ | | | | / _ ` | | | | / _ \
'_ \ | _/ _ \ ' _| | | \ | | / _ ` | ' _ \ / _ ` | / _ ` | / _ \ ' _|
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: | | _____ | ( | | ( | | _____ _/ |
| | | | _/ | | | | | ( | | | | ( | | ( | | _/ |
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: \____|_| \____/ \_,_| \_,_| \____\____|_|
|_| \____\____|_| |_| |_| \____, |_| |_| \____, |_| \____|_|
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: _/ |
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: |____/
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: packager : (v4.8.2-SNAPSHOT), Powered by
Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#

```

Como reiniciar o servidor de difusão?

```

[root@ip-172-31-78-238 sysconfig]# systemctl restart hazelcast-server
[root@ip-172-31-78-238 sysconfig]#
[root@ip-172-31-78-238 sysconfig]# systemctl status hazelcast-server
hazelcast-server.service - Hazelcast Server

```

```
Loaded: loaded (/etc/systemd/system/hazelcast-server.service; enabled; vendor preset: disabled)
```

```
Active: active (running) since Fri 2017-11-10 16:54:37 UTC; 14s ago
```

```
Main PID: 2731 (sh)
```

```
CGroup: /system.slice/hazelcast-server.service
```

```
2731 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/hazelcast-server.jar
```

```
2735 /bin/bash /usr/local/cliqr/apps/hazelcast-server.jar
```

```
2760 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
```

```
-Xms256m -Xmx256m -Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/hazelcast-server.jar
```

```
Nov 10 16:54:37 ip-172-31-78-238.ec2.internal systemd[1]: Started Hazelcast Server.
```

```
Nov 10 16:54:37 ip-172-31-78-238.ec2.internal systemd[1]: Starting Hazelcast Server...
```

```
Nov 10 16:54:39 ip-172-31-78-238.ec2.internal sh[2731]: 16:54:39.116 [main] INFO
```

```
com.cisco.cloudcenter.hazelcast.HazelcastServer - Starting Hazelcast Server..
```

```
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: _ _ _
```

```
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | | | | | | | | | | | |
```

```
| / | ( )
```

```
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | | | | | | | | | | | |
```

```
| | ( | | | | | | | | | | | |
```

```
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | _ | / _ ` | _ / _ \ | / _ / _ ` / _ |
```

```
_ | \ _ \ / _ \ ' _ \ \ / / | / _ / _ \
```

```
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | | | | ( | | / / _ / | ( | ( | \ _ \
```

```
| _ _ ) | _ / | \ v / | | ( | _ /
```

```
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | _ |
```

```
| _ | \ _ / _ / \ _ | _ | \ _ \ _ / \ _ | | _ / \ _ | _ | \ _ / | _ | \ _ \ _ |
```

```
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: CliQr Hazelcast Server : (v4.8.2-
```

```
SNAPSHOT), Powered by Spring Boot : 1.5.8.RELEASE
```

```
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
```

```
[root@ip-172-31-78-238 sysconfig]# ps -ef | grep hazelcast
```

```
cliqrus+ 2731 1 0 16:54 ? 00:00:00 /bin/sh -c .
```

```
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/hazelcast-server.jar
```

```
cliqrus+ 2735 2731 0 16:54 ? 00:00:00 /bin/bash /usr/local/cliqr/apps/hazelcast-
```

```
server.jar
```

```
cliqrus+ 2760 2735 6 16:54 ? 00:00:14 /usr/lib/jvm/java-8-sun/bin/java -
```

```
Dsun.misc.URLClassPath.disableJarChecking=true -Xms256m -Xmx256m -
```

```
Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/hazelcast-server.jar
```

```
root 3024 1854 0 16:58 pts/0 00:00:00 grep --color=auto hazelcast
```

```
[root@ip-172-31-78-238 sysconfig]#
```

Como reiniciar o servidor de configuração no CCM?

```
[root@ip-172-31-78-238 sysconfig]# systemctl restart config-server
```

```
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
```

```
[root@ip-172-31-78-238 sysconfig]# ps -ef | grep config-server
```

```
cliqrus+ 3096 1 0 17:00 ? 00:00:00 /bin/sh -c .
```

```
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/config-server.jar
```

```
cliqrus+ 3100 3096 0 17:00 ? 00:00:00 /bin/bash /usr/local/cliqr/apps/config-
```

```
server.jar
```

```
cliqrus+ 3177 3100 48 17:00 ? 00:00:16 /usr/lib/jvm/java-8-sun/bin/java -
```

```
Dsun.misc.URLClassPath.disableJarChecking=true -Xmx256m -jar /usr/local/cliqr/apps/config-
```

```
server.jar
```

```
root 3300 1854 0 17:00 pts/0 00:00:00 grep --color=auto config-server
```

```
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
```

```

[root@ip-172-31-78-238 sysconfig]# systemctl status config-server
config-server.service - Config Server
  Loaded: loaded (/etc/systemd/system/config-server.service; enabled; vendor preset: disabled)
  Active: active (running) since Fri 2017-11-10 17:00:14 UTC; 1min 12s ago
  Main PID: 3096 (sh)
  CGroup: /system.slice/config-server.service
          3096 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/config-server.jar
          3100 /bin/bash /usr/local/cliqr/apps/config-server.jar
          3177 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
          -Xmx256m -jar /usr/local/cliqr/apps/config-server.jar

Nov 10 17:00:14 ip-172-31-78-238.ec2.internal systemd[1]: Starting Config Server...
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: _____
_
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: / ____|          /
_(_)          | | (_)          / ____|
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: | |      ___ _ __ | |__ _ __ _ __
__ _ _| |__ _ __ _ __ | (___ _ __ _ __ _ __
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: | |      / _ \| ' _ \| | / _ \| | | |
'_/_ \| ' _ \| | / _ \| ' _ \| | / _ \| | / _ \| | | |
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: | |____| (| | | | | | (| | | | | |
| (| | | | | (| | | | ____| | __/ | \ v / __/ |
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: \____\___/|_| |_| | |_\__, | \__,_|_|
\__,_| \__,_| \__,_|_| |_| |____/ \___|_| \___\___|_|
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: __/ |
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: |____/
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: CliQr Configuration Server : (v4.8.2-
SNAPSHOT) , Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#

```

Como reiniciar o servidor de notificações no CCM?

```

[root@ip-172-31-78-238 sysconfig]# systemctl restart notification
[root@ip-172-31-78-238 sysconfig]#

-----
[root@ip-172-31-78-238 sysconfig]# ps -ef | grep notification
cliqrus+ 3572 1 0 17:02 ? 00:00:00 /bin/sh -c .
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/notification-server.jar
cliqrus+ 3574 3572 0 17:02 ? 00:00:00 /bin/bash /usr/local/cliqr/apps/notification-
server.jar
cliqrus+ 3587 3574 68 17:02 ? 00:00:31 /usr/lib/jvm/java-8-sun/bin/java -
Dsun.misc.URLClassPath.disableJarChecking=true -Xms256m -Xmx256m -
Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/notification-server.jar
root 3704 1854 0 17:03 pts/0 00:00:00 grep --color=auto notification
[root@ip-172-31-78-238 sysconfig]#

-----

[root@ip-172-31-78-238 sysconfig]#
[root@ip-172-31-78-238 sysconfig]# systemctl status notification
notification.service - Notification Server
  Loaded: loaded (/etc/systemd/system/notification.service; enabled; vendor preset: disabled)
  Active: active (running) since Fri 2017-11-10 17:02:57 UTC; 1min 16s ago
  Main PID: 3572 (sh)
  CGroup: /system.slice/notification.service
          3572 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/notification-server.jar
          3574 /bin/bash /usr/local/cliqr/apps/notification-server.jar
          3587 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
          -Xms256m -Xmx256m -Djava.security.egd=file:/dev/./urandom -jar
          /usr/local/cliqr/apps/notification-server.jar

```

```

Nov 10 17:02:57 ip-172-31-78-238.ec2.internal systemd[1]: Started Notification Server.
Nov 10 17:02:57 ip-172-31-78-238.ec2.internal systemd[1]: Starting Notification Server...
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: _ _ _ _ _
_
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | \ | | | | ( ) / _ ( ) | |
( ) / _ |
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | \ | | _ _ | | _ _ | _ _ _ _ | | _
_ _ _ _ | ( _ _ _ _ _ _ _ _ _ _
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | . ` | / _ \ | _ | | _ | / _ / _ ` | _ |
| / _ \ | ' _ \ \ _ _ \ / _ \ ' _ \ \ / / _ \ ' _ |
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | | \ | ( ) | | _ | | | | ( _ | ( _ | | | _
| ( _ ) | | | | _ _ ) | _ / | \ v / _ / |
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | _ | \ _ | \ _ / \ _ | _ | _ |
| _ | \ _ \ _ , _ | \ _ | _ | \ _ / | _ | | _ _ / \ _ | _ | \ / \ _ | _ |
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: osmosix-notification : (v4.8.2-
SNAPSHOT), Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#

```

Como reiniciar o serviço cliente-administrador no CCM?

```

[root@ip-172-31-78-238 sysconfig]# systemctl restart cliqr-admin
[root@ip-172-31-78-238 sysconfig]#

```

```

-----

[root@ip-172-31-78-238 sysconfig]# ps -ef | grep cliqr-admin
cliqrus+ 3736      1  0 17:05 ?          00:00:00 /bin/sh -c .
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/cliqr-admin.jar
cliqrus+ 3737    3736  0 17:05 ?          00:00:00 /bin/bash /usr/local/cliqr/apps/cliqr-admin.jar
cliqrus+ 3750    3737 69 17:05 ?          00:00:22 /usr/lib/jvm/java-8-sun/bin/java -
Dsun.misc.URLClassPath.disableJarChecking=true -Xms256m -Xmx256m -
Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/cliqr-admin.jar
root      3779    1854  0 17:05 pts/0    00:00:00 grep --color=auto cliqr-admin
[root@ip-172-31-78-238 sysconfig]#

```

```

-----

[root@ip-172-31-78-238 sysconfig]# systemctl status cliqr-admin
cliqr-admin.service - Cliqr Admin
  Loaded: loaded (/etc/systemd/system/cliqr-admin.service; enabled; vendor preset: disabled)
  Active: active (running) since Fri 2017-11-10 17:05:28 UTC; 1min 2s ago
  Main PID: 3736 (sh)
  CGroup: /system.slice/cliqr-admin.service
          3736 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/cliqr-admin.jar
          3737 /bin/bash /usr/local/cliqr/apps/cliqr-admin.jar
          3750 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
-Xms256m -Xmx256m -Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/cliqr-
admin.jar

```

```

Nov 10 17:05:28 ip-172-31-78-238.ec2.internal systemd[1]: Started Cliqr Admin.
Nov 10 17:05:28 ip-172-31-78-238.ec2.internal systemd[1]: Starting Cliqr Admin...
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: i _ _ _ _ _
_
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: / _ _ | | | | |
| | | | | \ | | | | ( )
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | | | | | _ _ _ _ _ | | _ _ _ _ _
_ _ | | _ _ _ _ _ / \ _ _ | | _ _ _ _ _
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | | | | | / _ \ | | | | / _ ` | / _ / _ \ '
\ | _ / _ \ ' _ | / \ \ / _ ` | ' _ ` _ \ | | ' _ \
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | | _ _ | | ( ) | | _ | | ( _ | ( _ _ / |
| | | | _ / | | | | / _ _ \ ( _ | | | | | | | | | | |

```

```
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: \____|_|\___/ \__,_|\__,_|\___\___|_|
|_|\___\___|_| /_/ \_\_,_|\_| |_| |_|_|_| |_|
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#
```

Onde estão localizados os arquivos de log do CloudCenter?

Houve uma mudança nos locais de registro do gerenciador do CloudCenter na versão 4.8.2. Atualmente, os registros estão localizados em

diretório /usr/local/cliqr/logs

O arquivo inclui **Capacity-manager.log**, **config-server.log**, **mgmtserver.log**, **notification-server.log**, **cliqr-admin.log**, **hazelcast-server.log**

```
[root@ip-172-31-78-238 logs]# ls -l
total 109472
-rw-r--r--. 1 cliqruser cliqruser 250936 Nov 10 17:01 capacity-manager.log
-rw-r--r--. 1 cliqruser cliqruser 161563 Nov 10 17:05 cliqr-admin.log
-rw-r--r--. 1 cliqruser cliqruser 124466 Nov 10 17:05 config-server.log
-rw-r--r--. 1 cliqruser cliqruser 92667 Nov 10 17:03 hazelcast-server.log
-rw-r--r--. 1 cliqruser cliqruser 10485969 Nov 10 16:55 mgmtserver-1.log
-rw-r--r--. 1 cliqruser cliqruser 10705871 Nov 10 16:57 mgmtserver-2.log
-rw-r--r--. 1 cliqruser cliqruser 10485969 Nov 10 16:57 mgmtserver-3.log
-rw-r--r--. 1 cliqruser cliqruser 10485802 Nov 10 16:57 mgmtserver-4.log
-rw-r--r--. 1 cliqruser cliqruser 10485988 Nov 10 16:58 mgmtserver-5.log
-rw-r--r--. 1 cliqruser cliqruser 10485953 Nov 10 17:01 mgmtserver-6.log
-rw-r--r--. 1 cliqruser cliqruser 10485791 Nov 10 17:01 mgmtserver-7.log
-rw-r--r--. 1 cliqruser cliqruser 10485825 Nov 10 17:02 mgmtserver-8.log
-rw-r--r--. 1 cliqruser cliqruser 10485876 Nov 10 17:02 mgmtserver-9.log
-rw-r--r--. 1 cliqruser cliqruser 8147705 Nov 10 17:13 mgmtserver.log
-rw-r--r--. 1 cliqruser cliqruser 383964 Nov 10 17:09 notification-server.log
```

Onde está o local do assistente de configuração do CCM CloudCenter?

Todos os arquivos de configuração estão localizados no diretório **/usr/local/cliqr/bin**

Onde as configurações do CCM são salvas após a execução do Assistente de configuração?

Todas as configurações serão salvas no arquivo **mgmtserver.conf**, localizado no diretório **/etc/sysconfig**.

Onde a configuração de log-stash do ELK é salva no CCM ?

O arquivo de configuração de log-stash do ELK está localizado em **/etc/sysconfig/** directory com o nome do arquivo **filebeat**.

Versão do aplicativo: 4.8.2 / 4.8.2.x