

# Como coletar registros da controladora de RAID UCSC-PSAS12GHBA?

## Contents

[Introduction](#)

[Prerequisites](#)

[Requirements](#)

[Componentes Utilizados](#)

[Informações de Apoio](#)

[Como visualizar registros](#)

[Solução](#)

[Informações Relacionadas](#)

## Introduction

Este documento descreve como coletar registros da controladora de RAID UCSC-PSAS12GHBA?

## Prerequisites

## Requirements

Não existem requisitos específicos para este documento.

## Componentes Utilizados

- PID do controlador: UCSC-PSAS12GHBA
- Fornecedor: PMC-Sierra (Microsemi)
- Driver: acraid

The information in this document was created from the devices in a specific lab environment. All of the devices used in this document started with a cleared (default) configuration. Se a rede estiver ativa, certifique-se de que você entenda o impacto potencial de qualquer comando.

## Informações de Apoio

UCSC-PSAS12GHBA (MicrosemipMC-Sierra HBA) é o único controlador HBA NON-LSI usado no servidor C240 M4; diferentemente das controladoras RAID LSI, o Storage Deamon "storaged" (armazenado) no CIMC não armazena os registros desta placa HBA.

## Como visualizar registros

Exemplos de registros do servidor UCS: mensagens/

"Event log fetch is not valid for this controller type"

```
723: 6:2017 Dec 20 00:50:14 EST:BMC:storaged:1628: handy_utils.c:46:==>>> ctrl 2 pd_list device_IDs:
0x0000000000000000 0x0000000000000000 0x0000000000000000 0x000000000000007f00
 749: 6:2017 Dec 20 00:50:50 EST:BMC:storaged:1628: handy_utils.c:46:==>>> ctrl 2 occupied slots according to
pd_list: 0x0000000000000000 0x0000000000000000 0x0000000000000000 0x00000000000000fe
 893: 5:2017 Dec 20 01:29:11 EST:BMC:storaged:1628: service.c:283:CMD: 'controller-type: ALL;controller: SLOT-
HBA;log: ;command: get-newest-entries;starting-entry: 1;entry-count: 500 '
 894: 5:2017 Dec 20 01:29:11 EST:BMC:storaged:1628: service.c:333:Accepted request 'controller-type:
ALL;controller: SLOT-HBA;log: ;command: get-newest-entries;starting-entry: 1;entry-count: 500 '
 895: 4:2017 Dec 20 01:29:11 EST:BMC:storaged:1628: service.c:169:CMD: write-status: Event log fetch is not valid
for this controller type
 896: 5:2017 Dec 20 01:29:11 EST:BMC:storaged:1628: service.c:283:CMD: 'controller-type: RAID;controller: SLOT-
HBA;operation: get-tty-log;mode: compressed '
 897: 5:2017 Dec 20 01:29:11 EST:BMC:storaged:1628: service.c:333:Accepted request 'controller-type:
RAID;controller: SLOT-HBA;operation: get-tty-log;mode: compressed '
 898: 5:2017 Dec 20 01:29:11 EST:BMC:storaged:1628: service.c:283:CMD: 'controller-type: RAID;controller: SLOT-
HBA;operation: get-phy-errors '
 899: 5:2017 Dec 20 01:29:11 EST:BMC:storaged:1628: service.c:333:Accepted request 'controller-type:
RAID;controller: SLOT-HBA;operation: get-phy-errors '
 900: 4:2017 Dec 20 01:29:12 EST:BMC:storaged:1628: service.c:169:CMD: write-status: Invalid controller operation
```

## Solução

Há uma ferramenta CLI para este controlador HBA (assim como o storcli para controladores LSI), Adaptec ARCCONF Command Line Utility v2.01.22270

[https://storage.microsemi.com/en-us/speed/raid/storage\\_manager/arconf\\_v2\\_01\\_22270\\_zip.php](https://storage.microsemi.com/en-us/speed/raid/storage_manager/arconf_v2_01_22270_zip.php)

Guia do usuário:

[http://download.adaptec.com/pdfs/user\\_guides/cli\\_arc\\_v2\\_01\\_22270\\_users\\_guide.pdf](http://download.adaptec.com/pdfs/user_guides/cli_arc_v2_01_22270_users_guide.pdf)

## Informações Relacionadas

Para obter detalhes do driver para esta controladora:

Linux:

```
$ modinfo aacraid
filename:      /lib/modules/2.6.32-696.6.3.el6.x86_64/kernel/drivers/scsi/aacraid/aacraid.ko
version:      1.2-0[30300]-ms
license:      GPL
description:  Dell PERC2, 2/Si, 3/Si, 3/Di, Adaptec Advanced Raid Products, HP NetRAID-4M, IBM ServeRAID & ICP
SCSI driver
author:       Red Hat Inc and Adaptec
VMWare:
```

```
vmkload_mod -s aacraid | grep Version
```