

ASR9000以太网环回测试

目录

[使用环回接口测试以太网接口](#)

[内部环回](#)

[配置环回](#)

[clear counters](#)

[Ping本地IP](#)

[检查接口计数器](#)

[检查控制器计数器](#)

[外部环回](#)

[配置环回](#)

[clear counters](#)

[Ping本地IP](#)

[检查接口计数器](#)

[检查控制器计数器](#)

[参考](#)

使用环回接口测试以太网接口

如有必要，可以使用环回查找线卡、交换矩阵、网络处理器(NP)、收发器或光纤传输路径的问题。

有两种主要的环回类型：内部环回和外部环回。

*内部*环路可以远程执行，但提供的信息并不多。

*外部*环路必须在现场执行，但应提供最大量的信息。

以下示例使用此接口：

```
RP/0/RSP0/CPU0:ASR9001-F# show run int tenGigE 0/0/1/1
interface TenGigE0/0/1/1
  ipv4 address 10.100.101.1 255.255.255.0
!
```

内部环回

这是一项基本测试，无需访问远程站点即可执行。它可以发现CPU、交换矩阵路径、NP和收发器问题，但无法发现光纤或传输问题。

配置环回

这会影响流量

```
RP/0/RSP0/CPU0:ASR9001-F# configure
RP/0/RSP0/CPU0:ASR9001-F(config)# int tenGigE 0/0/1/1
RP/0/RSP0/CPU0:ASR9001-F(config-if)# loopback internal
RP/0/RSP0/CPU0:ASR9001-F(config-if)# commit
RP/0/RSP0/CPU0:ASR9001-F(config-if)# end
```

clear counters

这将清除接口和控制器上的计数器。

```
RP/0/RSP0/CPU0:ASR9001-F# clear counters tenGigE 0/0/1/1
Clear "show interface" counters on this interface [confirm]
```

Ping本地IP

```
RP/0/RSP0/CPU0:ASR9001-F# ping 10.100.101.1 count 10000 size 1500 timeout 0
pings with timeout=0 may result in system instability and
control protocol flaps resulting in traffic impact.
DO you really want to continue[confirm with only 'y' or 'n'] [y/n] :y
Type escape sequence to abort.
Sending 10000, 1500-byte ICMP Echos to 10.100.101.1, timeout is 0 seconds:
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

[output omitted]

```
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
Success rate is 100 percent (10000/10000), round-trip min/avg/max = 1/1/5 ms
```

检查接口计数器

```
RP/0/RSP0/CPU0:ASR9001-F# show interfaces tenGigE 0/0/1/1
TenGigE0/0/1/1 is up, line protocol is up
  Interface state transitions: 3
  Hardware is TenGigE, address is 70e4.2217.ba65 (bia 70e4.2217.ba65)
  Layer 1 Transport Mode is LAN
  Internet address is 10.100.101.1/24
  MTU 1514 bytes, BW 10000000 Kbit (Max: 10000000 Kbit)
    reliability 255/255, txload 0/255, rxload 0/255
  Encapsulation ARPA,
  Full-duplex, 10000Mb/s, link type is force-up
  output flow control is off, input flow control is off
  loopback set (External),
  ARP type ARPA, ARP timeout 04:00:00
  Last input 00:00:00, output 00:00:00
  Last clearing of "show interface" counters 00:02:40
  5 minute input rate 685000 bits/sec, 126 packets/sec
  5 minute output rate 685000 bits/sec, 126 packets/sec
    10003 packets input, 15140657 bytes, 0 total input drops 0 drops for unrecognized upper-
level protocol Received 0 broadcast packets, 3 multicast packets 0 runts, 0 giants, 0 throttles,
0 parity 0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort 10003 packets output,
15140657 bytes, 0 total output drops Output 0 broadcast packets, 3 multicast packets 0 output
errors, 0 underruns, 0 applique, 0 resets 0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
```

检查控制器计数器

```
RP/0/RSP0/CPU0:ASR9001-F# show controllers tenGigE 0/0/1/1 stats
Statistics for interface TenGigE0/0/1/1 (cached values):
```

Ingress:

```
Input total bytes          = 15140657
Input good bytes           = 15140657
```

```
Input total packets = 10003 Input 802.1Q frames = 0 Input pause frames = 0 Input pkts 64
bytes = 0 Input pkts 65-127 bytes = 0 Input pkts 128-255 bytes = 3 Input pkts 256-511 bytes = 0
Input pkts 512-1023 bytes = 0 Input pkts 1024-1518 bytes = 10000 Input pkts 1519-Max bytes = 0
Input good pkts = 10003 Input unicast pkts = 10000 Input multicast pkts = 3 Input broadcast pkts
= 0 Input drop overrun = 0 Input drop abort = 0 Input drop invalid VLAN = 0 Input drop invalid
DMAC = 0 Input drop invalid encap = 0 Input drop other = 0 Input error giant = 0 Input error
runt = 0 Input error jabbers = 0 Input error fragments = 0 Input error CRC = 0 Input error
collisions = 0 Input error symbol = 0 Input error other = 0 Input MIB giant = 0 Input MIB jabber
= 0 Input MIB CRC = 0 Egress: Output total bytes = 15140657 Output good bytes = 15140657 Output
total packets = 10003 Output 802.1Q frames = 0 Output pause frames = 0 Output pkts 64 bytes = 0
Output pkts 65-127 bytes = 0 Output pkts 128-255 bytes = 3 Output pkts 256-511 bytes = 0 Output
pkts 512-1023 bytes = 0 Output pkts 1024-1518 bytes = 10000 Output pkts 1519-Max bytes = 0
Output good pkts = 10003 Output unicast pkts = 10000 Output multicast pkts = 3 Output broadcast
pkts = 0 Output drop underrun = 0 Output drop abort = 0 Output drop other = 0 Output error other
= 0
```

外部环回

此测试验证线卡中央处理器(CPU)、交换矩阵路径、NP、收发器和光纤。

此测试需要一段光缆，以便将发送(Tx)信号物理地环接到接收(Rx)端口。

配置环回

这会影影响流量

```
RP/0/RSP0/CPU0:ASR9001-F# configure
RP/0/RSP0/CPU0:ASR9001-F(config)# interface tenGigE 0/0/1/1
RP/0/RSP0/CPU0:ASR9001-F(config-if)# loopback external
RP/0/RSP0/CPU0:ASR9001-F(config-if)# commit
RP/0/RSP0/CPU0:ASR9001-F(config-if)# end
```

clear counters

这将清除接口和控制器上的计数器。

```
RP/0/RSP0/CPU0:ASR9001-F# clear counters
Clear "show interface" counters on all interfaces [confirm]
```

Ping本地IP

```
RP/0/RSP0/CPU0:ASR9001-F# ping 10.100.101.1 count 10000 size 1500 timeout 0
pings with timeout=0 may result in system instability and
control protocol flaps resulting in traffic impact.
DO you really want to continue[confirm with only 'y' or 'n'] [y/n] :y
Type escape sequence to abort.
```

Sending 10000, 1500-byte ICMP Echos to 10.100.101.1, timeout is 0 seconds:
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!

[output omitted]

!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
Success rate is 100 percent (10000/10000), round-trip min/avg/max = 1/1/5 ms

检查接口计数器

```
RP/0/RSP0/CPU0:ASR9001-F# show interfaces tenGigE 0/0/1/1
TenGigE0/0/1/1 is up, line protocol is up
  Interface state transitions: 7
  Hardware is TenGigE, address is 70e4.2217.ba65 (bia 70e4.2217.ba65)
  Layer 1 Transport Mode is LAN
  Internet address is 10.100.101.1/24
  MTU 1514 bytes, BW 10000000 Kbit (Max: 10000000 Kbit)
    reliability 255/255, txload 0/255, rxload 0/255
  Encapsulation ARPA,
  Full-duplex, 10000Mb/s, link type is force-up
  output flow control is off, input flow control is off
  loopback set (Internal),
  ARP type ARPA, ARP timeout 04:00:00
  Last input 00:00:00, output 00:00:00
  Last clearing of "show interface" counters 00:00:32
  5 minute input rate 504000 bits/sec, 52 packets/sec
  5 minute output rate 504000 bits/sec, 52 packets/sec
    10001 packets input, 15140219 bytes, 0 total input drops 0 drops for unrecognized upper-
level protocol Received 0 broadcast packets, 1 multicast packets 0 runts, 0 giants, 0 throttles,
0 parity 0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort 10001 packets output,
15140219 bytes, 0 total output drops Output 0 broadcast packets, 1 multicast packets 0 output
errors, 0 underruns, 0 applique, 0 resets 0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
```

检查控制器计数器

```
RP/0/RSP0/CPU0:ASR9001-F# show controllers tenGigE 0/0/1/1 stats
Statistics for interface TenGigE0/0/1/1 (cached values):

Ingress:
  Input total bytes          = 15140219
  Input good bytes          = 15140219

  Input total packets = 10001 Input 802.1Q frames = 0 Input pause frames = 0 Input pkts 64
bytes = 0 Input pkts 65-127 bytes = 0 Input pkts 128-255 bytes = 1 Input pkts 256-511 bytes = 0
Input pkts 512-1023 bytes = 0 Input pkts 1024-1518 bytes = 10000 Input pkts 1519-Max bytes = 0
Input good pkts = 10001 Input unicast pkts = 10000 Input multicast pkts = 1 Input broadcast pkts
= 0 Input drop overrun = 0 Input drop abort = 0 Input drop invalid VLAN = 0 Input drop invalid
DMAC = 0 Input drop invalid encap = 0 Input drop other = 0 Input error giant = 0 Input error
runt = 0 Input error jabbers = 0 Input error fragments = 0 Input error CRC = 0 Input error
collisions = 0 Input error symbol = 0 Input error other = 0 Input MIB giant = 0 Input MIB jabber
= 0 Input MIB CRC = 0 Egress: Output total bytes = 15140219 Output good bytes = 15140219 Output
total packets = 10001 Output 802.1Q frames = 0 Output pause frames = 0 Output pkts 64 bytes = 0
Output pkts 65-127 bytes = 0 Output pkts 128-255 bytes = 1 Output pkts 256-511 bytes = 0 Output
pkts 512-1023 bytes = 0 Output pkts 1024-1518 bytes = 10000 Output pkts 1519-Max bytes = 0
Output good pkts = 10001 Output unicast pkts = 10000 Output multicast pkts = 1 Output broadcast
pkts = 0 Output drop underrun = 0 Output drop abort = 0 Output drop other = 0 Output error other
= 0
```

参考

[Cisco ASR 9000系列聚合服务路由器接口和硬件组件命令参考，版本4.3.x章节：Cisco ASR 9000系列路由器上的以太网接口命令](#)

关于此翻译

思科采用人工翻译与机器翻译相结合的方式将此文档翻译成不同语言，希望全球的用户都能通过各自的语言得到支持性的内容。

请注意：即使是最好的机器翻译，其准确度也不及专业翻译人员的水平。

Cisco Systems, Inc. 对于翻译的准确性不承担任何责任，并建议您总是参考英文原始文档（已提供链接）。