

Nexus 5500 CoPP类

目录

[简介](#)

[背景信息](#)

[Nexus 5500 CoPP类及其流量类型](#)

[CoPP类](#)

简介

本文档介绍Nexus 5500控制平面保护(CoPP)类以及与每个类匹配的流量类型。

背景信息

CoPP是通过NX-OS版本5.1(3)在Nexus 5500上引入的。CoPP仅在Nexus 55xx上实施。Nexus 50x0上不提供此功能。

Nexus 5500 CoPP类及其流量类型

与Nexus 7000相比，Nexus 5500对CoPP的控制非常有限。无法完全删除Nexus 5500 CoPP策略。用户可以在三个预定义策略之间进行选择，或者可以创建自定义策略，因为CoPP类无法从策略映射中删除。只能编辑承诺信息速率(CIR)速率/突发大小。也无法定义新的CoPP类映射。

可能的CoPP策略映射包括：

- copp-system-policy-default
- copp-system-policy-scaled-l2
- copp-system-policy-scaled-l3
- copp-system-policy-customize

策略映射名称不言自明。只能一次应用四个策略中的一个。删除任何策略会自动应用默认策略。

只能编辑copp-system-policy-customized。如果尝试编辑前三个策略，则返回错误：

```
Switch(config)# policy-map type control-plane copp-system-policy-scaled-l2  
ERROR: Only copp-system-policy-customized can be modified  
Switch(config)#
```

CoPP类

所有类映射都使用Match Protocol语句。

运行配置中不显示类映射。运行配置中显示的唯一与CoPP相关的配置是非默认自定义策略映射配置。例如：

```
Switch# sh run copp
!Command: show running-config copp
!Time: Tue Apr 30 20:20:00 2013

version 5.2(1)N1(2)
logging level copp 4
policy-map type control-plane copp-system-policy-customized
  class copp-system-class-arp
    police cir 5000 kbps bc 3600000 bytes
  class copp-system-class-default
    police cir 2048 kbps bc 6400000 bytes
control-plane
  service-policy input copp-system-policy-customized
```

Switch#

可以使用show class-map type control-plane或show policy-map interface control-plane来检查CoPP类映射。每个match语句旁边都提供了说明：

```
Switch# show policy-map interface control-plane | i class-map|match      class-map copp-system-
class-igmp (match-any)
  match protocol igmp --> Matches on IGMP IP protocol number (2)
class-map copp-system-class-pim-hello (match-any)
  match protocol pim --> Matches on PIM IP protocol number (103)
class-map copp-system-class-bridging (match-any)
  match protocol bridging --> Matches on STP BPDUs
class-map copp-system-class-arp (match-any)
  match protocol arp --> Matches on ARP Ethertype (0x806)
class-map copp-system-class-dhcp (match-any)
  match protocol dhcp --> Matches on DHCP UDP port number (67, 68)
class-map copp-system-class-mgmt (match-any)
  match protocol mgmt. --> Matches on Telnet, SSH, HTTP, SNMP, FTP,
  NTP using their well-known ports
class-map copp-system-class-lacp (match-any)
  match protocol lacp --> Matches LACP BPDUs address and Ethertype
  (01-80-C2-00-00-02, 0?8809)
class-map copp-system-class-lldp (match-any)
  match protocol lldp_dcx --> Matches on LLDP ethertype (0x88CC)
class-map copp-system-class-udld (match-any)
  match protocol udld --> Matches on UDLD destination address
class-map copp-system-class-isis (match-any)
  match protocol isis_dce --> Matches on ISIS Ethertype
class-map copp-system-class-msdp (match-any)
  match protocol msdp --> Matches on MSDP TCP port (639)
class-map copp-system-class-cdp (match-any)
  match protocol cdp --> Matches on CDP destination address 0100.0ccc.cccc
class-map copp-system-class-fip (match-any)
  match protocol fip --> Matches on FIP ethertype (0x8914)
class-map copp-system-class-bgp (match-any)
  match protocol bgp --> Matches on BGP TCP port number (179)
class-map copp-system-class-eigrp (match-any)
  match protocol eigrp --> Matches on EIGRP IP Protocol number (88)
class-map copp-system-class-exception (match-any)
  match protocol exception --> IP options, Martian packets (same src and dst addresses)
class-map copp-system-class-glean (match-any)
  match protocol glean --> Matches on Adjacency lookup miss
```

```
class-map copp-system-class-hsrp-vrrp (match-any)
  match protocol hsrp_vrrp --> Matches on HSRP & VRRP Destination IP
class-map copp-system-class-icmp-echo (match-any)
  match protocol icmp_echo --> Matches on ICMP type for echo
class-map copp-system-class-ospf (match-any)
  match protocol ospf --> Matches on OSPF IP Protocol number (89)
class-map copp-system-class-pim-register (match-any)
  match protocol reg --> Matches on PIM register packets
class-map copp-system-class-rip (match-any)
  match protocol rip --> Matches on RIP UDP Port (520)
class-map copp-system-class-l3dest-miss (match-any)
  match protocol unicast --> Miss in UFIB Lookup
class-map copp-system-class-mcast-miss (match-any)
  match protocol multicast --> Miss in MFIB Lookup
class-map copp-system-class-excp-ip-frag (match-any)
  match protocol ip_frag --> Matches on MTU-exceeded traffic
class-map copp-system-class-excp-same-if (match-any)
  match protocol same-if --> Matches traffic to be sent via same ingress interface
class-map copp-system-class-excp-ttl (match-any)
  match protocol ttl --> Matches on TTL=0/1
class-map copp-system-class-default (match-any)
  match protocol default --> Matches packets not matched by previous classes
```

Switch#

版本5.2中增强了CoPP类映射，以匹配IPv6控制数据包对应项：

```
class-map type control-plane match-any copp-system-class-arp
  match protocol nd
class-map type control-plane match-any copp-system-class-eigrp
  match protocol eigrp6
class-map type control-plane match-any copp-system-class-hsrp-vrrp
  match protocol hsrp6
class-map type control-plane match-any copp-system-class-ospf
  match protocol ospf3
```