

如何配置ESA以將傳入電子郵件路由到我的公司電子郵件伺服器？

目錄

[問題：](#)

問題：

如何配置ESA以將傳入電子郵件路由到我的公司電子郵件伺服器？

為了讓ESA將電子郵件傳送到企業電子郵件伺服器，您必須配置ESA以使用該主機作為傳送目的地。這可通過使用 `smtproutes` 命令列介面(CLI)中的命令。

其 `smtproutes` 命令可將特定域的所有電子郵件重定向到不同的郵件交換(MX)主機。

```
mail3.example.com> smtproutes
```

```
There are no routes configured.
```

```
Choose the operation you want to perform:
```

- NEW - Create a new route.
- IMPORT - Import new routes from a file.

```
[> new
```

```
Enter the hostname for which you want to set up a permanent route.
```

```
Partial hostnames such as ".example.com" are allowed.
```

```
Use "ALL" for the default route.
```

```
[> example.com
```

```
Enter the destination hosts, separated by commas, which you want mail for domain.com to be delivered.
```

```
Enter /dev/null by itself if you wish to discard the mail.
```

```
[> 10.1.1.10
```

```
Mapping for example.com to 10.1.1.10 created.
```

```
There are currently 1 routes configured.
```

```
Choose the operation you want to perform:
```

- NEW - Create a new route.
- DELETE - Remove a route.
- PRINT - Display all routes.
- IMPORT - Import new routes from a file.
- EXPORT - Export all routes to a file.
- CLEAR - Remove all routes.

在本例中，我們將example.com的郵件配置為傳送到電子郵件伺服器主機10.1.1.10。

您需要提交更改才能啟用新配置的smtproutes。

提示：您也可以在GUI上的「網路」(Network)>「SMTP路由」(SMTP Routes)下配置SMTP路由